---------- Limit all lines to a maximum of 79 cha
e to have several files open side by side, and works wel
The limite are chosen to avoid wrapping in editors with th
refer a longer line length. For code maintained exclusively o
racters. The Python standard library is conservative and req
and braces. Long lines can be broken over multiple lines by w
ltiple ``with``-statements could not use implicit continuation
e/being/written', 'w') as file_2: file_2.write(file_1.read()) (See the
. Make sure to indent the continued line appropriately. .. _`pep8-o
erators. But this can hurt readability in two ways: the operators te
which items are added and subtracted: .. code-block:: :c
To solve this readability pro maticians and their publishe
ations and relations, display always break before binary
oss_wages + taxable_intere s - qualified_dividends) - ira
uggested. Blank Lines -------- op-level function and class d
lines may be omitted betwe r related one-liners (e.g. a s
s treat these characters as tors, so you may use them t
ace. Source File Encoding --- --- Code in the core Python d
CII characters sparingly, pre to denote places and human
rs, and SHOULD use English words wherever feasible (in many cas
s should usually be on separate lines: .. code-block:: :class: goo
nen, PIPE - Imports are always put at the top of the file, just after
mports. 3. Local application/library specific imports. You should
ages) If the import system is incorrectly configured (such as w
licit relative imports are an acceptable alternative to absolu
port example Standard library code should avoid complex
ass from foo.bar.yourclass import YourClass If this s
ourClass``. - Wildcard imports (``from <module> impo
is to republish an internal interface as part of a p
hen republishing names this
or_``, ``__version__``, etc.
ock:: :class: good """This is
strings and double-quoted s
dability. For triple-quoted st
ous whitespace in the follow
g close parenthesis: .. code-
d # Wrong: if x == 4 : print(x
spacing applied. Exception:
er+offset] ham[: upper_fn(x) : st

blocks of text with fewer structural restrictions (docstrings
view tools that present the two versions in adjacent colu
set to 80, even if the tool places a marker glyph in the final
a team that can reach agreement on this issue, it is okay
lines to 79 characters (and docstrings/comments to 72)
pressions in parentheses. These should be used in prefer
ython 3.10, so backslashes were acceptable for that cas
s discussion on `multiline if-statements`_ for further tho
r-linebreak`: Should a Line Break Before or After a Binary
get scattered across different columns on the screen, and
bad # Wrong: # operators sit far away from their operands
low the opposite conventio
ations" [3]_. Following the t
uction - student_loan_inter
tions with two blank lines. Method definitions inside a class
dummy implementations). Use blank lines in function
parate pages of related sections of your file. Note, so
ution should always use UTF-8, and should not have
s. If using non-ASCII characters as data, avoid noisy U
breviations and technical terms are used which are
rect: import os import sys .. code-block:: :class: bad
dule comments and docstrings, and before module gl
nk line between each group of imports. - Absolute imp
ctory inside a package ends up on ``sys.path``): .. co
specially when dealing wit
ts and always use absolut
cal name clashes, then s
ded, as they make it uncle
iting a pure Python implementation of an interface with the d
interfaces still apply. Module Level Dunder Names ----------
re any import statements *except* ``from __future__`` imp
m __future__ import barry_as_FLUFL __all__ = ['a', 'b', 'c'] __
mendation for this. Pick a rule and stick to it. When a strin
sistent with the docstring convention in :pep:`257`. - White
ets or braces: .. code-block:: :class: good # Correct: spam
k:: :class: bad # Wrong: bar = (0,) - Immediately before a
a binary operator, and should have equal amounts on eith
mitted: .. code-block:: :class: good # Correct: ham[1:9],
+ offset] .. code-block:: :class: bad # Wrong: ham[lower + offset

omments), the line length should be limited to 72 chara
The default wrapping in most tools disrupts the visual s
mn when wrapping lines. Some web based tools may not o
rease the line length limit up to 99 characters, provided that
preferred way of wrapping long lines is by using Python's im
to using a backslash for line continuation. Backslashes may s
code-block:: :class: maybe with open('/path/to/some/file/you/
s on the indentation of such multiline ``with``-statements.) An
ator? ---------- For decades the re
h operator is moved away from its operand and onto the previous
me = (gross_wages + taxab + (dividends - qualified_divide
n his *Computers and Type es: "Although formulas withi
more readable code: .. code- : good # Correct: # easy to m
before or after a binary ope as the convention is consis
nded by a single blank line. s may be used (sparingly) t
, to indicate logical sections epts the control-L (i.e. ^L) fo
and web-based code view ecognize control-L as a form
ng declaration. In the stand on-UTF-8 encodings should b
aracters like zalgo and byte s. All identifiers in the Python
. Open source projects with a global audience are encouraged to
import sys, os it's okay to say this though: .. code-block:: :class
constants. Imports should be grouped in the following order: 1.
commended, as they are usually more readable and tend to be b
:class: good import mypkg.sibling from mypkg import sibling
olute imports would be unnecessarily verbose: .. code-block:
class-containing module, it's usually okay to spell this: .. c
: good import myclass import foo.bar.yourclass and
, confusing both readers and many automated tools.
itions from an optional accelerator module and ex
--------- Module level "dund
s. Python mandates that fut
on__ = '0.1' __author__ = 'Ca
ontains single or double quo
ce in Expressions and State
m[1], {eggs: 2}) .. code-block:
mma, semicolon, or colon: ..
ide (treating it as the operat
m[1:9:3], ham[:9:3], ham[1::3
er + offset] ham[1: 9], ham[1 :9]

.) .. code-block::
ld be complete sentences. The fir
riod. You should use one or two spaces a
peaking countries: please write your comment
he same level as that code. Each line of a block com
paringly. An inline comment is a comment on the same
vious. Don't do this: .. code-block:: :class: bad x = x + 1
") are immortalized in :pep:`257`. - Write docstrings for al
line. - :pep:`257` describes good docstring conventions. No
please keep the closing ``"""`` on the same line: .. code-bloc
currently recommended na andards. New modules and
ble to the user as public par API should follow conventio
from what they are used f lowing naming styles are
edWords`` (or CapWords Case -- so named because
mixedCase`` (differs from edWords by initial lowerca
. For example, the ``os.s unction returns a tuple w
ith that.) The X11 library u a leading X for all its public
ding or trailing underscores are recognized (these ca
underscore``; used by convention to avoid c
`` becomes ``_FooBar__boo``; see below).
ptive: Naming Conventions ----------
m the numerals one and zero. When tempted to use 'l',
odule Names ~~~~~~~~~~~~~~~~~~~~~~~~~~~~ Modules shou
n an extension module written in C or C++ has an accompan
pWords convention. The na vention for functions may b
ith the CapWords conventi nly for exception names an
mmended to add suffixes `` _contra`` to the variables
rue) Exception Names ~~~~~ ~~~ Because exceptions sho
~ (Let's hope that these varia eant for use inside one mod
der convention of prefixing ls with an underscore (whic
derscores as necessary to im adability. Variable names fol
~~~~~~~~~~~~~~~~~~~~~~~~~~~ Always use ``self`` for the firs
ather than use an abbreviation or spelling corruption. Thus ``c
rcase with words separated by underscores as necessary t
angles these names with the class name: If class Foo has a
h attributes in classes designed to be subclassed. Note
``MAX_OVERFLOW`` and ``TOTAL``. Designing for
than to make a public attribute non-public. Publ
ees that non-public attributes won't chan
in other languages). Some class
ur base class. W

gn exce ed
pep:`315 for th
othe rms f si
o s
tails a ansferred e new eption
le inste d of us ng are ``e cept:`` c
interru a p gra wi h Contro-C, an
cla s to wo es: 1. the exception
y... y`` an bette way o h le
minimum mou f co nec ssary. A
return e_va col n[k excep
ne. "
with
me

hat code e e s is
ned for th tion hy)
ex on c pr ais
as p vin the ribu e na when c verting
: .. e de-blo k:: : ss: oo try: impo platform
n dis uise o her oblems. If yo ant to catch a
ler e p ntin out r loggin he t aceback;
se. - en atc g operating s em rro pr
s avoids masking b gs: code-blo k:: :clas
Will catc Ke rro ised by h dle_val

r tha
ention
d b
ror to ribute E r, or em
cifie_module ex ept Im
ptio s th ign pro
st th us ill be aw
exp cit e ption hi
d # rrect: tr val
n k ot_fou key)

e excepti o an
ou should "Er " to
plac ent g th rig
ding e text o e original exception he new ception
ror: platform_ ecific_module = Non A bare ` except:``
rors, use `ex ept cep n:`` are exc is qui ent
an erro occur . 2. the de ee o do so cle
ntro ython S ov intr pec ion ``er no valu
ctio ept K ror: retur ey_ ot_found ey se:
res al to ticul r se on o de, us w ``
elea
exit__
es

ce
" progra n o
n is an erro ons
cin nne `ra
e). en c ching e tions, m ion sp
se w SystemEx and Keyb ardInter
exce xce n:``). A od ule of hum
wo ut then the ex tion propagat
Additi ally, for ry/xce clauses it
andle_va e(value) code-blo ::: :class
to en is cles up promp and re
~~~~~~~~~~~~~~~~~~~~~~~~~~~