marise this". - S ing-notes file the a ites its plan, findings and d cisions to, an eads at the start of each turn. It survives ompaction an a restart. It is the
d structured. - . Allocate the window urpose: instructions, the t sk, retrieved f tool results, room for the answer. Measu e what fills it runs; tool results are u
- Persist or reco ist what is expensive or im ssible to recreate: decisio s, user input, t esult of an i reversible action. Recompute what is cheap may have changed: the cu
A cached fact ab nging world is a stale fact. # 8. Control structure and liability The or stration is oftware. Make its control str cture explicit code and its failures recove
rite the control flow med states and transitions (n es and edges). The mode hooses within a ode; the graph decides between nodes. "Where are we lways has an swer. Failure
s ("when you are do DONE") that de can insp t or test. - C me. Persist the s ate after ev tool call: wh hat was prod ed, what is p g. A crash, a
from the last checkpo stead of start er. The task b rd in section 7 is the coars rm of this; a per-step checkp ne one. - Dete d replay. The ame inputs sh give the sam
pin the model version he sampling tings, log every rompt, tool call and res ith an id, and seed what can . Replay a log ith the tools ubbed to repr e a bad run. T
imeouts, ev rywhere. Pe ll, per step, p task. - Circuit b eakers and fallbacks. A or model that keeps failing i a while, not r er, and a fallb ck takes over:
human. Nam the fallback each step be re you need it. Concurrency limits. Bou he parallel calls to each mod queue the re without a lim s an outage w to happen. -
eam output as it is produced and persist pa al results so a opped run still yields its fi ed parts. Failure mode: a stre wer reaches t ore it can be f y checked. St the draft; ga
mit, a send — on the full chec ## 9. Model oice and routin The model i t. Choose it o the task, not th e model. - Sta smallest, che est model tha ses your eva
one call to a capable model. - scalate only w e it breaks: a stronger model for the one h rd step, a c eaper one for th eps. Mixed-m es are normal When quality bjective (a d
dels on the same task in isolat n, a sandbox each, and let a human or a judge pick the best. Differe models have d ngths; trying choosing bea rguing about which is best.
re quality, tokens, and calls ac ss models on your test job before you commit. ### he model r er One compon he choice of each call: by type (classify, extract, dr
bility (long co use, images y cost and latency budge and by data policy (what may leave yo emises). Chan ng in one pla ine does not which model it got. Failu
by cost alon d cases to a that fails them quie te by measured pass rate er task cla d let a failed c ate. ### Esc escalation pa explicit and both log
nfidence when th

ro ds s ( uest , t en com ul a ou (m igh y j
flo d ule eu heck nts d p know ea ch em n mo . Th a
and repeats unti d e, boun d by a t rn limit. - A g l that splits into sub-goals ( ild a feature un a campaign lan-based. A lead p ans and hands out, hen c ck nd re es; gua d i s single poin of failure. - A rge job w
e l d ca not hold er rc ic te ms. Keep the e hallow pass brie s, re urn e enc - A in of specialist ntake, t en b ling the technica : ha doff. Ea t pick w o s ext; gu rd agai t goi g in es. - Ma
vo ing pict re an est gatio a diagnos s) backb rd, with owned en ri s and o c ntro s hat cal s i do - Several cand date to choose among (de gn , draf opy, propose options): pa allel an t t sev
here ro ge h brief,