graphics-art.org/docs/typogram-ileumd); why a mode should prefer the data layer, and the prompt-injection answ
racter of the message, one position in that text where the same character stands, chosen at r
s reveal work.pdf --key tg1...` it plints the message `"..."`. The examples work with any text that c
ur message. Details: [docs/hidden-messages.md](https://typographics-art.org/docs/hidden
-it-protects-and-what-it-does-not)). Characters that do not occur in the public text cannot be
of plain, whitespace-preserved text (`TGD1[ … ]TGD1`) that goes through a work unchanged, sur
behind it and its limits are in [docs/structured-data.md](https://typographics-art.org/docs/st
achine view) shows the data as a table with its checksum, downloads it as `.xlsx`, `.csv`, `.j
ured-data-ui.md](https://typographics-art.org/docs/structured-data-ui.md), [docs/encrypted
s; keys and passwords are passed by file, standard input or environment, never as an argume
wing a secret, hidden work between it (`tgc2.`), key splitting (K0fR, Shamir) and a vault (the see
docs/cipher-review.md](https://typographics-art.org/docs/cipher-review.md) (why a differen
) (German: [docs/passwords-and-keys.de.md](https://typographics-art.org/docs/passwords
today's typography is known", not "nobody can ever get at it"): a lost key loss
ed media and the adapter.** A picture or a video can be sealed so it only opens with the key,
e plaintext ever touching the disk and without anything being uploaded. Large media is a see
t…md](https://typographics-art.org/docs/encrypted-media-adapter.md). An internal a
ersion review of t
graphics-art.org/docs/security-review-inte
acting it yields the source text, with one
nk demand per area] M --> S[Set the glyph b
per area: darkness on light paper, bright
xactly. 5. **Colour.** In colour mode
drop a photo. Presets: "High legibility" (
such a file contacts typographics-art.or
h). ### As a library No build step, dep
h | medium | free color: 'phiote', // photo |
as characters toSvg(sheet); // SVG, tex
de 22× (the CLI uses the global `WebSoc
photo.jpg --text poem.txt --fill 12000 -o
send, paid with a DigiByte transaction
ile - Hokusai |
La Hocenda - Wa
omain ([sources](https://typographics-a
t an artwork](https://github.com/typ
n gallery`. ## Where this is useful - **Ar
rt.org/docs/technique.md), rule 2), not y
AQ **Is this a calligram?** Calligrams (
he filter always comes after your text. *
main/NOTICE.md)). Mind the rights to the
ce of conduct](https://github.com/typogr
4 minutes, 522 files), then the site and
ntation builders | | `gallery/` | the 15 wo
nd](https://typographics-art.org/docs/ai
https://github.com/typographics-art/typ
unterpart of ASCII art. ASCII art chooses *
- Whitespace may be normalised: runs of
ext stays identical. - An ordinary word (u
allowed only when it is declared: it follo
measured (2026-10-01)** In Ch
text from assistive technology (`aria-hi
work itself. ### 3. Only typography var
ages. A single uniform paper colour is al
key that selects characters of its public
t work*, *a TG Art piece*. - German: *Ty
% and 128 % widths of the chosen varia
40`), so advances scale linearly with fon
r). Contrast, brightness and an unsharp m
s/ai-readability.md`). Afterwards the PDF i
ow well the title of a one-pager can be read: t
ages too. - **Fidelity**: `isFaithful(sheet)` com
tay readable for machines. This page shows ho
e it forms the picture. A **machine** should re
, byte for byte (also .html, .pdf) tg extract work.sv
s the source text with all of the tex
say the same thing. **The prompt-injection objecti
before trusting** the data layer, and fall back to the
ors. The filler contains **Cyrillic**, which
t>` content, whitespace normalised). The test suite sep
mage only | `tesseract` on a PNG rendered at 2× | share o
-|---|---| | high · char | exact | exact | 99.9 % | 99.9 % |
el (first sample) Classic OCR knows only letter shapes. A vi
order cannot be known in advance. Medium and free were r
00 % | free | 94 | 100 % | This is a small sample with one medium
hrome set "fi" in *office* as one ligature glyph, and its PDF tex
`pdftotext`'s layout mode moved the very first words of the text
The demonstrator in `demo/molly-brown/` sets 1.2 million char
visible character. The cause is a deliberate Poppler limit (see belo
r knows the PDF text compares visible characters and
ager completely Measured on the on core examples (the first ten of th
ading order | | pdfminer.six | 10 of | | | pypdf | 10 of 10 | reads at most 2
charset`) one-pagers above the 1 font mean of their text (30–50 % rea
ne type size (no glyphs below the e size), this holds even for the EU Al
le characters are identical; the b orts such a page as not exact. The a
** The text is exactly sett is exact for white-space runs stored ord
h Poppler, pass a high resolution xt -r 600` or more) for pages with m
thousands of characters, where a few pixels high). Contributions wi
e the bytes go, what was removed ible change, and which settings cha
outline per character used. It mak font for every **weight × width × ty
n 18 measured pages: ``` Chrome * outlines * 7.2 B * runs * 6.9 B * le
f letters only: no image is embedd d without visible change | Step | Sav
ion), ~16 % (Basic Law) | they were nStruct` element per style run under
the picture It was the (title or no) exactly, both burned in. 1.5 mm, in brightness and in c
full | |---|---|---|---|---| all weights, widths and sizes, colour step 6, tagged PDF | 4.53 MB
42 / 0.927 | 1.38 % | | 2 weights, one width | 1.52 MB | 20 | 0.945 / 0.930 | 1.23 % | | 1 weigh
931 / 0.918 | 1.39 % | | 2 weights, 1 size, one width | 1.13 MB | 8 | 0.946 / 0.939 | 1.82 % | | 1 we
s and sizes, colour step 6, tagged PDF | 0.73 MB | 22 | 0.995 / 0.995 | 0.00 % | | as published so
MB | 12 | 0.977 / 0.977 | 0.77 % | | 1 weight, one width (a single font) | 0.68 MB | 6 | 0.982 / 0.982
4 MB | 4 | 0.994 / 0.994 | 0.92 % | | 1 weight, 2 sizes, one width | 0.60 MB | 3 | 0.979 / 0.979 | 2.72 %
of the full version. On the title card it makes no difference. - **Weight carries the brightness.** T
ser colours hardly save.** Colour steps of 48 or 96 instead of 24 save 4 %; step 48 looks the sam
s made as art (gallery, posters) keep their sizes there the texture of mixed sizes is a choice. ## H
n messages A Typographics Art work can carry a message that only the holder of a key can read.
espace normalised, invisible format characters (soft hyphens, direction marks) removed, split into
crypto, without modulo bias). The key is the list of chosen positions. 3. **Fingerprint.** the key stor
by base64url of: 8 bytes text fingerprint, then the positions as variable-length integers (about 3 bytes per cha
140. ## Use ``` sh node cli/tg-secret. the harbour. 6 pm." # prints the key sh
standard input (`--key-stdin`) or fr CRET_KEY`. The CLI reads PDF (via M
What it protects, and what it does not - ut the key it is an ordinary work; ther
key every times, and repeated letters o e key does not show which letters re
n the public text cannot be hidden; the rare symbols may be absent from sho
er drawn from a fallback font (for k's PDF text then differs from its s
md); the work contains its deskfarest text a ver he is used to hide anything inside a wo
s/ai-readability.md`). Afterwards the PDF i
ow well the title of a one-pager can be read: t
ages too. - **Fidelity**: `isFaithful(sheet)` com
tay readable for machines. This page shows ho
e it forms the picture. A **machine** should re
, byte for byte (also .html, .pdf) tg extract work.sv
s the source text with all of the tex
say the same thing. **The prompt-injection objecti
before trusting** the data layer, and fall back to the
ors. The filler contains **Cyrillic**, which
t>` content, whitespace normalised). The test suite sep
mage only | `tesseract` on a PNG rendered at 2× | share o
-|---|---| | high · char | exact | exact | 99.9 % | 99.9 % |
el (first sample) Classic OCR knows only letter shapes. A vi
order cannot be known in advance. Medium and free were r
00 % | free | 94 | 100 % | This is a small sample with one medium
hrome set "fi" in *office* as one ligature glyph, and its PDF tex
`pdftotext`'s layout mode moved the very first words of the text
The demonstrator in `demo/molly-brown/` sets 1.2 million char
visible character. The cause is a deliberate Poppler limit (see belo
r knows the PDF text compares visible characters and
ager completely Measured on the on core examples (the first ten of th
ading order | | pdfminer.six | 10 of | | | pypdf | 10 of 10 | reads at most 2
charset`) one-pagers above the 1 font mean of their text (30–50 % rea
ne type size (no glyphs below the e size), this holds even for the EU Al
le characters are identical; the b orts such a page as not exact. The a
** The text is exactly sett is exact for white-space runs stored ord
h Poppler, pass a high resolution xt -r 600` or more) for pages with m
thousands of characters, where a few pixels high). Contributions wi
e the bytes go, what was removed ible change, and which settings cha
outline per character used. It mak font for every **weight × width × ty
n 18 measured pages: ``` Chrome * outlines * 7.2 B * runs * 6.9 B * le
f letters only: no image is embedd d without visible change | Step | Sav
ion), ~16 % (Basic Law) | they were nStruct` element per style run under
the picture It was the (title or no) exactly, both burned in. 1.5 mm, in brightness and in c
full | |---|---|---|---|---| all weights, widths and sizes, colour step 6, tagged PDF | 4.53 MB
42 / 0.927 | 1.38 % | | 2 weights, one width | 1.52 MB | 20 | 0.945 / 0.930 | 1.23 % | | 1 weigh
931 / 0.918 | 1.39 % | | 2 weights, 1 size, one width | 1.13 MB | 8 | 0.946 / 0.939 | 1.82 % | | 1 we
s and sizes, colour step 6, tagged PDF | 0.73 MB | 22 | 0.995 / 0.995 | 0.00 % | | as published so
MB | 12 | 0.977 / 0.977 | 0.77 % | | 1 weight, one width (a single font) | 0.68 MB | 6 | 0.982 / 0.982
4 MB | 4 | 0.994 / 0.994 | 0.92 % | | 1 weight, 2 sizes, one width | 0.60 MB | 3 | 0.979 / 0.979 | 2.72 %
of the full version. On the title card it makes no difference. - **Weight carries the brightness.** T
ser colours hardly save.** Colour steps of 48 or 96 instead of 24 save 4 %; step 48 looks the sam
s made as art (gallery, posters) keep their sizes there the texture of mixed sizes is a choice. ## H
n messages A Typographics Art work can carry a message that only the holder of a key can read.
espace normalised, invisible format characters (soft hyphens, direction marks) removed, split into
crypto, without modulo bias). The key is the list of chosen positions. 3. **Fingerprint.** the key stor
by base64url of: 8 bytes text fingerprint, then the positions as variable-length integers (about 3 bytes per cha
140. ## Use ``` sh node cli/tg-secret. the harbour. 6 pm." # prints the key sh
standard input (`--key-stdin`) or fr CRET_KEY`. The CLI reads PDF (via M
What it protects, and what it does not - ut the key it is an ordinary work; ther
key every times, and repeated letters o e key does not show which letters re
n the public text cannot be hidden; the rare symbols may be absent from sho
er drawn from a fallback font (for k's PDF text then differs from its s
md); the work contains its deskfarest text a ver he is used to hide anything inside a wo
text is in the fic
s, widths, sizes an
ook cipher). With the key and the right work, t
enerator suggests sample texts when one is missing.
key like a password: with key and work, anyone can r
them. ## Structured data in a work A spreadsheet or data file c
and decodes back to the data model with a checksum. ``` sh node c
. Status: library, command line, tests and the web are done. In the brows
, and opens sealed data with a key. Everything happens in the browser, noth
ps://typographics-art.org/docs/encrypted-data.md)). ### Sealed data Data c
cs/encrypted-data.md](https://typographics-art.org/docs/encrypted-data.md) a
recover everything: a strict 2-of-3 mode exists), why an Argon2id for the extra passw
s not the answer). A plain-language page for non-experts explains the password rule,
eys.de.md)). **Is this secure?** The cipher (AES-256-GCM, random 256-bit key) is soun
data, a compromised device defeats everything, and a password alone never p
an **adapter** (`cli/tg-adapter.mjs`) ma d file readable by *any* ordinary playe
; a small image or a data file stays a `t
and tests) is in [docs/security-review
e rules 1. **Fidelity.** The text is nev
ackgrounds or images besides the g
aper r photo colour] D --> O[HTML, S
bed) whose ink best matches the area it cov
ode ≥ 22.5. ``` js import { typeset, toPng } from './s
aimer to read) stretch: true, // also vary letter w
ayout', `tone`, `color`, `render`, `typeset`) r
ulPDF (`mutool`), which checks every printed
: `.svg`, `.html`, `.pdf` (text stays text), `.p
em/typographics-art/typogram/blob/main/ap
Yamaha" - LaGodio Rivera - Hokusai (
**Th
main work, except the Universal Declaration o
to the SVG, which is the work
ory. Any reader, human or machine, gets bot
awlers index the words, not just a file name. -
normal reading layout and creates the pictur
a continuous range of ink, so tones can be im
que, like ASCII art. Ideas, scripts Rob
ncies (a few seconds) npm run dev #
The process http://typographics-art.org/main/i
e texts for the generator (made by `s
ographics-art/typogram/blob/main/i
Typographics Art: definition **Typograp
Typographics Art keeps the characters the text dictates and chooses *how each one is se
gle space, and line breaks may fall at any space. - Whitespace is layout, not text: a work
ext is so short that its largest size would not hold a word on one line, the type size is red
many characters are filler. ### 2. Text stays text - The work is published in a format th
(1,281 characters, character mode) is 1,132 text nodes, and even the
the picture carries its own short description (the SVG `<title>`, the HTML `role="fig
weight and other axes of a variable font (width, optical size, slant), - typeface, -
ery character to be legible to the eye at viewing size. Very thin (tens of
does not touch the rules above: the work still contains exactly its dec
--> ## How the setting works # How the reference implementation w
ch, measured in the DOM at 40 px: - **coverage** the al
sh it; otherwise the browser would silently measure
demand and mean colour of any rectangle an
``` cost = (dT − target)² + 0.0
L
r
ics-art.org/docs/ai-readability.m
ook cipher). With the key and the right work, t
enerator suggests sample texts when one is missing.
key like a password: with key and work, anyone can r
them. ## Structured data in a work A spreadsheet or data file c
and decodes back to the data model with a checksum. ``` sh node c
. Status: library, command line, tests and the web are done. In the brows
, and opens sealed data with a key. Everything happens in the browser, noth
ps://typographics-art.org/docs/encrypted-data.md)). ### Sealed data Data c
cs/encrypted-data.md](https://typographics-art.org/docs/encrypted-data.md) a
recover everything: a strict 2-of-3 mode exists), why an Argon2id for the extra passw
s not the answer). A plain-language page for non-experts explains the password rule,
eys.de.md)). **Is this secure?** The cipher (AES-256-GCM, random 256-bit key) is soun
data, a compromised device defeats everything, and a password alone never p
an **adapter** (`cli/tg-adapter.mjs`) ma d file readable by *any* ordinary playe
; a small image or a data file stays a `t
and tests) is in [docs/security-review
e rules 1. **Fidelity.** The text is nev
ackgrounds or images besides the g
aper r photo colour] D --> O[HTML, S
bed) whose ink best matches the area it cov
ode ≥ 22.5. ``` js import { typeset, toPng } from './s
aimer to read) stretch: true, // also vary letter w
ayout', `tone`, `color`, `render`, `typeset`) r
ulPDF (`mutool`), which checks every printed
: `.svg`, `.html`, `.pdf` (text stays text), `.p
em/typographics-art/typogram/blob/main/ap
Yamaha" - LaGodio Rivera - Hokusai (<br>**Th
main work, except the Universal Declaration o
to the SVG, which is the work
ory. Any reader, human or machine, gets bot
awlers index the words, not just a file name. -
normal reading layout and creates the pictur
a continuous range of ink, so tones can be im
que, like ASCII art. Ideas, scripts Rob
ncies (a few seconds) npm run dev #
The process http://typographics-art.org/main/i
e texts for the generator (made by `s
ographics-art/typogram/blob/main/i
Typographics Art: definition **Typograp
Typographics Art keeps the characters the text dictates and chooses *how each one is se
gle space, and line breaks may fall at any space. - Whitespace is layout, not text: a work
ext is so short that its largest size would not hold a word on one line, the type size is red
many characters are filler. ### 2. Text stays text - The work is published in a format th
(1,281 characters, character mode) is 1,132 text nodes, and even the
the picture carries its own short description (the SVG `<title>`, the HTML `role="fig
weight and other axes of a variable font (width, optical size, slant), - typeface, -
ery character to be legible to the eye at viewing size. Very thin (tens of
does not touch the rules above: the work still contains exactly its dec
--> ## How the setting works # How the reference implementation w
ch, measured in the DOM at 40 px: - **coverage** the al
sh it; otherwise the browser would silently measure
demand and mean colour of any rectangle an
``` cost = (dT − target)² + 0.0
L
r