

rowmantic: Tables row by row

A Typst package for editing tables row-by-row.

The idea is a row-oriented way to input tables, with just a little less syntactical overhead than the usual `table` function in Typst.

The `rowtable` function works like the usual `table` function but takes one markup block (`[...]`) per row, and the markup is split internally¹ on a delimiter which is `&` by default.

Input: `[A & B & C]`

Table cells (effectively): `..([A], [B], [C])`

For improved table ergonomics, the table sizes the number of columns by the longest row. All rows are effectively completed so that they are of full length. This creates a better the editing experience, as rows can be filled out gradually.

Examples

Document Result

<i>goá</i>	<i>iáu-boē</i>	<i>koat-tēng</i>	<i>tang-sî</i>	<i>boeh</i>	<i>tng-khi</i>
goa ¹	iau ¹ -boe ³	koat ² -teng ³	tang ⁷ -si ⁵	boeh ²	tng ¹ -khi ³
goa ²	iau ² -boe ⁷	koat ⁴ -teng ⁷	tang ¹ -si ⁵	boeh ⁴	tng ² -khi ³
I	not-yet	decide	when	want	return.

"I have not yet decided when I shall return."

Input

```
#{
  show regex("\\d"): super.with(size: 0.8em, typographic: false)
  show table.cell: it => { set text(size: 0.9em) if it.y >= 1; it }
  show table.cell.where(y: 0): emph
  rowtable(
    separator: ",", // configurable separator
    stroke: none, // pass through table arguments, hlines, cells et.c.
    inset: (x: 0em),
    column-gutter: 0.9em,
    // rows are filled to be equal length after collecting cells
    [goá, iáu-boē, koat-tēng, tang-sî, boeh, tng-khi ],
    [goa1, iau1-boe3, koat2-teng3, tang7-si5, boeh2, tng1-khi3 ],
    [goa2, iau2-boe7, koat4-teng7, tang1-si5, boeh4, tng2-khi3 ],
    [I, not-yet, decide, when, want, return. ],
    table.hline(),
    // cell that fills remainder of row
    expandcell["I have not yet decided when I shall return."],
  )
}
```

Example from Wikipedia²

¹But shallowly - not looking into styled or nested content

²https://en.wikipedia.org/wiki/Interlinear_gloss

Document Result

Term	Explanation	Assumptions
X	Explanatory variables	Non-random
Y	Y_1, \dots, Y_n observations	Pairwise independent
β	Model parameters	

Input

```
#{
  set table(stroke: none, inset: 0.8em)
  set table.hline(stroke: 0.5pt)
  show table.cell.where(y: 0): strong
  show table.cell.where(x: 0): x => math.bold(math.uptight(x))
  rowtable(
    table.hline(),
    table.header([Term & Explanation          & Assumptions ]),
    table.hline(),
    [$X$          & Explanatory variables          & Non-random ],
    [$Y$          & $Y_1, \dots, Y_n$ observations & *Pairwise independent*],
    [$beta$       & Model parameters              ],
    table.hline(),
  )
}
```

Trying some more difficult examples

Document Result

Literal &	Strong	X-Y
Equation $\pi = 3.1415\dots$	$\int_{\Omega} d\omega$	X&Y
π^1	π^2	π^3
<ul style="list-style-type: none">• A• B	<ol style="list-style-type: none">1. A2. B	A a B b
Figure 1: Top <div>A</div>	See Figure 1 & Figure 2	<div>B</div> Figure 2: Bot
Nested rowtable <div>A B</div>	Nested table <div>A B</div>	table.cell(rowspan: 2)
Cell with colspan=2		
Expandcell		
N/A	N/A	N/A

Input

```
#rowtable(
  align: horizon,
  stroke: 0.1pt,
  row-filler: [N/A],
  [Literal \& & *Strong* & *X*--_Y_ ],
  [Equation \ $pi = 3.1415\dots$ & $ \int_{\Omega} d \omega $ & $X \& Y$],
  $ pi^1 & pi^2 & pi^3 $,
  [
    - A
    - B
    &
    + A
    + B
    &
    / A: a
    / B: b
  ],
  [
    #{
      set figure.caption(position: top)
      [#figure(rect[A], caption: "Top")<fig1>]
    }
    &
    See @fig1 \& @fig2
    &
    [#figure(rect[B], caption: "Bot")<fig2>]
  ],
  {
    [Nested rowtable \ ]
    rowtable([A & B])
    [&]
    [Nested table \ ]
    table(columns: 2, [A], [B])
    [&]
    table.cell(stroke: 1pt + red, rowspan: 2)[`table.cell(` \ `rowspan: 2)`]
  },
  [#table.cell(fill: yellow.lighten(90%), colspan: 2)[Cell with colspan=2] ],
  [#expandcell(fill: yellow.lighten(90%))[Expandcell] & #expandcell[#none]],
  table.footer([]),
)
```

Double semicolon separator

Document Result

First	This is a literal ;; and ; and , and &
Second; Third	Equation $\pi = 3.1415\dots$

Input

```
#rowtable(  
  separator: ";;",  
  stroke: 0.5pt,  
  [First      ;; This is a literal \;\; and ; and , and & ],  
  [Second; Third ;; Equation  $\pi = 3.1415\dots$ ],  
)
```

Combine with pillar (or other table function)

Use the `table` argument to let `rowtable` pass its result to a different table function rather than the standard one, for example `pillar.table` (shown below) or `zero.ztable`.

Document Result

Isotope	Z	N	Half-life	Mass (Da)	Abundance (%)
¹⁰⁷ Ag	47	60	Stable	106.905 091 5(26)	51.839 ± 0.008
¹⁰⁹ Ag	47	62	Stable	108.904 755 8(14)	48.161 ± 0.008

Input

```
#import "@preview/pillar:0.3.2"  
#set text(font: "Libertinus Serif")  
#show table.cell.where(y: 0): strong  
#rowtable(  
  separator: ",",  
  table: pillar.table,  
  cols: "rCCCCC",  
  format: (auto, ) * 4 + ((uncertainty-mode: "compact"), auto),  
  column-gutter: (0.5em, 0pt),  
  stroke: (x, y) => if y == 0 { (bottom: 0.75pt) },  
  table.header(  
    [Isotope,      Z, N, Half-life, Mass (Da),      Abundance (%) ]),  
  [#super[107]Ag, 47, 60, Stable,      106.9050915(26), 51.839(8) ],  
  [#super[109]Ag, 47, 62, Stable,      108.9047558(14), 48.161(8) ],  
)
```

Equations

Equations as rows are split on $\&$ by default, but it is configurable. Note that $\&$ can be escaped in equations, but other separator symbols are not as easy to escape³.

Document Result

A	B	C	D	E
1	x	x^2	\sum_i^n	inline equation row
1	x	x^2	\sum_i^n	block equation row
1	x	x^2	\sum_i^n	markup with embedded equations row

Input

```
#rowtable(
  align: center + horizon,
  stroke: (x, y) => (bottom: int(y == 0) * 1pt),
  separator: ",", // regular sep
  separator-eq:  $\&$ , // equation sep
  [A, B, C, D, E],
  $1  $\&$  x  $\&$  x^2  $\&$  sum_i^n  $\&$  #[inline equation row]$,
  $ 1  $\&$  x  $\&$  x^2  $\&$  sum_i^n  $\&$  #[block equation row] $,
  [$1$, $x$, $x^2$, $ sum_i^n $, markup with embedded \ equations row],
)
```

Long Division

This example shows one way to set up long division. In this case it's polynomial division, computing the result $x^3 + x + 1 = (x^2 - x + 2)(x + 1) - 1$. For this example, the colorful annotations add the most of the complexity. rowtable contributes to the example by splitting equations on the separator and filling rows to be equal length.

Document Result

Quotient \rightarrow

x^2	$-x$	2	
-------	------	-----	--

x^3	x	1	$x + 1$
-------	-----	-----	---------

Numerator

$(-)$	x^3	x^2	
-------	-------	-------	--

	$-x^2$	x	
--	--------	-----	--

Denominator

$(-)$	$-x^2$	$-x$	
-------	--------	------	--

	$2x$	1	
--	------	-----	--

$(-)$	$2x$	2	
-------	------	-----	--

	-1		
--	------	--	--

Remainder

Input

```
#import "@preview/mannot:0.3.0": annot, markhl
```

³The escape for $\&$ is just $\&$, for other separators like for example the comma a `\box` or `"`, `"` is used to escape them.

```

/// Set up strokes and gutter for long division table
#let longdiv(..args, table: std.table) = {
  let cols = args.at("columns")
  let st = std.stroke(args.at("stroke", default: black))
  let stroke = (x, y) => (
    // Add left stroke to the last column
    left: if x == cols - 1 and y == 1 { st },
    bottom: if (
      // Add top and bottom stroke to denominator cell
      y == 1 and x == cols - 1
      // Add bottom stroke every two rows (calc.even check),
      // but for one less column each time
      or y >= 1 and x < cols - 1 and calc.even(y) and x + 1 >= y / 2
    ) {
      st
    }
  )
  table(..args,
    column-gutter: (0pt,) * (cols - 2) + (1.5em, ),
    stroke: stroke,
    std.table.hline(y: 1, stroke: st))
}

// Set up marking functions
#let markhl = markhl.with(outset: (top: 0.15em, rest: 0.30em), radius: 1pt)
#let um = math.class("unary", math.minus) // unary minus
#let mkq = markhl.with(color: luma(70%))
#let mkn = markhl.with()
#let mkdenom = markhl.with(color: blue, tag: <denom>)
#let mkrem = markhl.with(color: red, tag: <rem>)

#let leftset(x) = box(place(dx: -0.3em, right + bottom, $x$))
#let rm = math.class("unary", leftset($(-)$)) // row minus

#show: block.with(breakable: false)
#rowtable(
  align: right,
  table: longdiv.with(stroke: 1.5pt),
  inset: 0.55em,
  $mkq(x^2, tag: #<ans>) & mkq(um x) & mkq(2) & $,
  $mkn(x^3) & & mkn(x) & mkn(1, tag: #<num>) & mkdenom(x + 1)$,
  $rm x^3 & x^2$,

  $ & -x^2 & & x$,
  $ & rm -x^2 & -x$,

  $ & & 2x & 1$,
  $ & & rm 2x & 2$,

  $ & & & mkrem(um 1)$,
)
#annot(<ans>, pos: left + horizon, dx: -2em, dy: -0em, annot-text-props: (fill:
black, size: 0.75em))[Quotient]
#annot(<denom>, pos: right + bottom, dy: +2em)[Denominator]
#annot(<num>, pos: right + top, dy: -1.5em, dx: 1em)[Numerator]
#annot(<rem>, pos: right + horizon, dy: 0em, dx: 2em)[Remainder]

```

Equations with alignment

Use a different separator than & to use equations with alignment.

Document Result

Matrix Form	Equation System Form
$\begin{bmatrix} y_1 \\ y_2 \end{bmatrix} = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$	$\begin{aligned} (1st) \quad y_1 &= a_{11}x_1 + a_{12}x_2 \\ (2nd) \quad y_2 &= a_{21}x_1 + a_{22}x_2 \end{aligned}$

Input

```
#set math.mat(delim: "[")
#rowtable(
  separator: ";",
  stroke: (x, y) => (bottom: int(y == 0) * 1pt),
  [Matrix Form; Equation System Form],
$
  mat(y_1; y_2) = mat(a_11, a_12; a_21, a_22) mat(x_1; x_2)
;
  "(1st)" y_1 &= a_11 x_1 &+ a_12 x_2 \
  "(2nd)" y_2 &= a_21 x_1 &+ a_22 x_2 \
$
)
```

Table Cells, rowspan and colspan

- colspan: a cell spans multiple columns
- rowspan: a cell spans multiple rows

Table cells can be customized with the usual properties (stroke, fill, etc.) but also with colspan and rowspan. It's important to include the cells inline inside the rows, i.e like this:

Document Result

1	2	3	4
A	B	Extra Wide	

Input

```
#let cell = table.cell
#rowtable(
  separator: ",",
  column-width: 3em,
  rows: 3em,
  [1, 2, 3, #cell(fill: yellow)[4]],
  [A, B, #cell(colspan: 2, stroke: 2pt)[Extra Wide]],
)
```

where [...] is the markup for the whole row. Then automatic row length computations will continue to work correctly.

The column span is straightforward, because it's contained in the row, so support for this was available from rowmantic's first version.

However, there is also support for rowspan since version 0.2.0:

Document Result

C: 2, R: 2		1	2	R: 3	4
		Expandcell			R: 3
e	f	g	h		
Expandcell				ijk	

Input

```
#show table.cell: it => if it.colspan + it.rowspan > 2 { strong(it) } else { it }
#let cell = table.cell
#rowtable(
  separator: ",",
  column-width: 3em, rows: 3em,
  inset: 0.25em,
  [#cell(rowspan: 2, colspan: 2)[C: 2, R: 2], 1, 2, #cell(rowspan: 3)[R: 3], 4],
  [#expandcell[Expandcell], #cell(rowspan: 3)[R: 3]],
  [e, f, g, h],
  [#expandcell[Expandcell], ijk],
)
```