

ctz-euclide

Typst Port

Euclidean Geometry for Typst

A comprehensive geometry package built on CeTZ
Version 0.1.0
Nathan Scheinmann

Contents

1. Introduction	4
1.1. Features	4
1.2. Installation	4
1.3. Basic Usage	4
2. Core Concepts	5
2.1. The Point Registry	5
2.2. Figure Scaling	5
2.3. Coordinate Systems	5
3. Point Definitions	6
3.1. Basic Points — <code>ctz-def-points</code>	6
3.2. Midpoint — <code>ctz-def-midpoint</code>	6
3.3. Regular Polygons — <code>ctz-def-regular-polygon</code>	6
3.4. Named Polygons — <code>ctz-def-polygon</code> / <code>ctz-label-polygon</code>	6
3.5. Linear Combination — <code>ctz-def-linear</code>	6
4. Line Constructions	8
4.1. Perpendicular — <code>ctz-def-perp</code>	8
4.2. Parallel — <code>ctz-def-para</code>	8
4.3. Angle Bisector — <code>ctz-def-bisect</code>	8
4.4. Perpendicular Bisector — <code>ctz-def-mediator</code>	9
5. Intersections	10
5.1. Line–Line — <code>ctz-def-ll</code>	10
5.2. Line–Circle — <code>ctz-def-lc</code>	10
5.3. Circle–Circle — <code>ctz-def-cc</code>	10
6. Triangle Centers	12
6.1. Basic Centers	12
6.1.1. Centroid — <code>ctz-def-centroid</code>	12
6.1.2. Circumcenter — <code>ctz-def-circumcenter</code>	12
6.1.3. Incenter — <code>ctz-def-incenter</code>	13
6.1.4. Orthocenter — <code>ctz-def-orthocenter</code>	13
6.2. The Euler Line	13
6.3. Right Triangles via Thales’ Theorem	14
6.4. Advanced Centers	15
7. Transformations	16
7.1. Rotation — <code>rotate</code>	16
7.2. Reflection — <code>ctz-def-reflect</code>	16
7.3. Homothety (Scaling) — <code>scale</code>	16
7.4. Projection — <code>ctz-def-project</code>	17
7.5. Inversion — <code>ctz-def-inversion</code>	17
7.6. Object Duplication — <code>ctz-duplicate</code>	18
7.7. Polymorphic Rotation	18
8. Drawing & Styling	20
8.1. Points — <code>ctz-draw-points</code>	20
8.2. Unified Drawing — <code>ctz-draw</code>	20
8.2.1. Drawing Named Objects	20
8.2.2. Drawing Unnamed Constructs	20
8.2.2.1. Points with Labels	20
8.2.2.2. Paths and Polylines	20
8.2.2.3. Circles	21
8.2.2.4. Arcs and Semicircles	21
8.2.2.5. Line Segments	21
8.2.3. Complete Example	22

8.3. Labels — <code>ctz-draw-labels</code>	24
8.4. Segments — <code>ctz-draw-segment</code>	24
8.5. Segment Measurements — <code>ctz-draw-measure-segment</code>	25
8.6. Paths — <code>ctz-draw-path</code>	26
8.7. Global Styling — <code>ctz-style</code>	28
8.8. Angle Marking — <code>ctz-draw-angle</code>	28
8.9. Right Angle Mark — <code>ctz-draw-mark-right-angle</code>	29
9. Circles	30
9.1. Named Circle — <code>ctz-def-circle</code> / <code>ctz-draw-circle</code>	30
9.2. Circumcircle — <code>ctz-draw-circumcircle</code>	30
9.3. Incircle — <code>ctz-draw-incircle</code>	30
9.4. Circle Through Point — <code>ctz-draw-circle-through</code>	30
9.5. Semicircle — <code>ctz-draw-semicircle</code>	30
10. Clipping	31
10.1. Set Clip Region — <code>ctz-set-clip</code>	31
10.2. Draw Clipped Line — <code>ctz-draw-line-global-clip</code>	31
10.3. Draw Clipped Segment — <code>ctz-draw-seg-global-clip</code>	31
11. Raw Algorithms	32
12. Function Reference	33
12.1. Point Definition	33
12.2. Line Constructions	33
12.3. Intersections	33
12.4. Triangle Centers	33
12.5. Special Triangles	33
12.6. Transformations	33
12.7. Drawing	33
12.8. Clipping	34
13. Gallery Examples	35

1. Introduction

ctz-euclide is a geometry package for Typst, a port of the LaTeX package `tkz-euclide`. Built on top of CeTZ (a powerful drawing library), it provides high-level constructions for Euclidean geometry.

1.1. Features

- **Point Registry:** Define points once, reference them by name throughout your figure
- **Geometric Constructions:** Perpendiculars, parallels, bisectors, mediators
- **Intersections:** Line–line, line–circle, circle–circle with multiple solution handling
- **Triangle Centers:** Centroid, circumcenter, incenter, orthocenter, and 10+ specialized centers
- **Special Triangles:** Medial, orthic, intouch triangles
- **Transformations:** Rotation, reflection, translation, homothety, projection, inversion
- **Drawing & Styling:** Points, labels, angles, segments with tick marks
- **Grid & Axes:** Coordinate systems with customizable appearance
- **Clipping:** Mathematical line clipping for clean bounded figures

1.2. Installation

Import the package in your Typst document:

```
#import "@local/ctz-euclide:0.1.0": *
```

All figures use the `ctz-canvas` function (re-exported from CeTZ):

```
#ctz-canvas({  
  import cetz.draw: *  
  ctz-init()  
  
  // Your geometry code here  
})
```

Naming notes:

- All public functions are prefixed with `ctz-` to avoid conflicts.
- Point creation and drawing use `ctz-def-points` and `ctz-draw-points`.
- Other constructors use `ctz-def-*`, and drawing utilities use `ctz-draw-*`.


The `ctz-init()` call initializes the point registry and coordinate resolver.

1.3. Basic Usage

Code

```
#ctz-canvas(length: 0.8cm, {  
  import cetz.draw: *  
  ctz-init()  
  
  // Define points  
  ctz-def-points(A: (0, 0), B: (4, 0), C: (2, 3))  
  
  // Draw triangle  
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)  
  
  // Find circumcenter and draw circumcircle  
  ctz-def-circumcenter("O", "A", "B", "C")  
  ctz-draw(circle-through: ("O", "A"), stroke: blue)  
  
  // Draw and label points  
  ctz-draw(points: ("A", "B", "C", "O"), labels: (  
    A: "below left", B: "below right",  
    C: "above", O: "below"))  
})
```

Figure



2. Core Concepts

2.1. The Point Registry

The point registry is the heart of `ctz-euclide`. Once you define a point with a name, that name can be used directly in CeTZ drawing commands.

```
ctz-def-points(A: (0, 0), B: (3, 4)) // Register points A and B
ctz-draw(segment: ("A", "B"))      // Use them directly in CeTZ
```

Under the hood, `ctz-init()` installs a coordinate resolver that translates "A" to the stored coordinates.

2.2. Figure Scaling

Control the size of your figures using CeTZ's `length` parameter:

```
#ctz-canvas(length: 0.8cm, { ... })
```

This scales everything proportionally, including stroke widths. Typical values:

- 0.6cm – small inline figures
- 0.8cm – standard examples
- 1.0cm – large detailed figures

2.3. Coordinate Systems

Points can be defined in multiple ways:

```
// Explicit coordinates
ctz-def-points(A: (2, 3))

// Using existing CeTZ coordinates
ctz-def-points(B: (rel: (1, 1), to: "A"))

// Mixed: numbers and existing points
ctz-def-points(C: (4, 0), D: "A", E: (3, 2))
```

3. Point Definitions

3.1. Basic Points — `ctz-def-points`

Define one or more points at specific coordinates:

```
ctz-def-points(A: (0, 0), B: (4, 0), C: (2, 3))
```

3.2. Midpoint — `ctz-def-midpoint`

Find the midpoint of a segment:


Code

```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 3))
  ctz-def-midpoint("M", "A", "B")

  ctz-draw(segment: ("A", "B"), stroke: black)
  ctz-draw(points: ("A", "B", "M"), labels: (
    A: "left", B: "right", M: "above"))
})
```

Figure



3.3. Regular Polygons — `ctz-def-regular-polygon`

Generate vertices of a regular n -gon. If you pass a polygon name first, it is registered and can be drawn/ labeled by name: You can also mark all sides during drawing with `mark` and optional `mark-opts`.


Code

```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(0: (0, 0), A: (3, 0))
  // 0 is the center; A is the starting vertex that
  // fixes the radius/angle.
  ctz-def-regular-polygon("Hex", ("A", "B", "C", "D",
    "E", "F"), "0", "A")

  ctz-draw("Hex", stroke: blue)
  ctz-draw(points: ("A", "B", "C", "D", "E", "F",
    "0"), labels: (0: "below"))
})
```

Figure



3.4. Named Polygons — `ctz-def-polygon` / `ctz-label-polygon`

Define a polygon once and draw/label it by name:

```
ctz-def-points(A: (0, 0), B: (4, 0), C: (4, 2), D: (0, 2))
ctz-def-polygon("P1", "A", "B", "C", "D")
ctz-draw("P1", stroke: black)
ctz-label-polygon("P1", $P_1$, pos: "center")
```

3.5. Linear Combination — `ctz-def-linear`

Define a point along a line: $P = A + k(B - A)$

```
ctz-def-linear("P", "A", "B", 0.3) // P is 30% from A to B
ctz-def-linear("Q", "A", "B", 1.5) // Q extends beyond B
```

4. Line Constructions

4.1. Perpendicular — `ctz-def-perp`

Construct a perpendicular line through a point:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 1), C: (2, 3))
  ctz-def-perp("P1", "P2", ("A", "B"), "C")
  ctz-def-project("H", "C", "A", "B")

  ctz-draw(segment: ("A", "B"), stroke: black)
  ctz-draw(segment: ("P1", "P2"), stroke: blue)
  ctz-draw-mark-right-angle("A", "H", "C", size: 0.3)

  ctz-draw(points: ("A", "B", "C"), labels: (
    A: "left", B: "right", C: "above")
})
```

Figure



4.2. Parallel — `ctz-def-para`

Construct a parallel line through a point:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 1), C: (1, 2.5))
  ctz-def-para("P1", "P2", ("A", "B"), "C")

  ctz-set-clip(-0.5, -0.5, 5.5, 3.5)
  ctz-draw-line-global-clip("A", "B", add: (2, 2),
    stroke: black)
  ctz-draw-line-global-clip("P1", "P2", add: (2, 2),
    stroke: green)

  ctz-draw(points: ("A", "B", "C"), labels: (
    A: "below",
    B: "below",
    C: "above")
  ))
})
```

Figure



4.3. Angle Bisector — `ctz-def-bisect`

Construct the bisector of an angle:

Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 0), C: (1, 3))
  ctz-def-bisect("D1", "D2", "C", "A", "B")

  ctz-set-clip(-0.5, -0.5, 4.5, 3.5)
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw-seg-global-clip("D1", "D2", stroke: red)

  ctz-draw-angle("A", "C", "B", radius: 0.5, stroke:
gray)
  ctz-draw(points: ("A", "B", "C"), labels: (
    A: "below",
    B: "below",
    C: "above"
  ))
})
```

Figure



4.4. Perpendicular Bisector — ctz-def-mediator

Construct the perpendicular bisector of a segment:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (1, 1), B: (5, 3))
  ctz-def-mediator("M1", "M2", "A", "B")
  ctz-def-midpoint("M", "A", "B")

  ctz-draw(segment: ("A", "B"), stroke: black)
  ctz-draw(segment: ("M1", "M2"), stroke: purple)
  ctz-draw-mark-right-angle("M1", "M", "A", size:
0.25)

  ctz-draw(points: ("A", "B", "M"), labels: (
    A: "left",
    B: "right",
    M: "below"
  ))
})
```

Figure



5. Intersections

5.1. Line–Line — `ctz-def-ll`

Find the intersection of two lines:

Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 3),
                C: (4, 0), D: (0, 2.5))
  ctz-def-line("L1", "A", "B")
  ctz-def-line("L2", "C", "D")
  ctz-def-ll("I", "L1", "L2")

  ctz-draw("L1", stroke: blue)
  ctz-draw("L2", stroke: red)

  ctz-draw(points: ("A", "B", "C", "D", "I"), labels:
    (I: "above"))
})
```

Figure



5.2. Line–Circle — `ctz-def-lc`

Find intersections of a line with a circle:

Code


```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(O: (0, 0), R: (3, 0),
                A: (-2, 2), B: (4, 1))
  ctz-def-line("L1", "A", "B")
  ctz-def-circle("C1", "O", through: "R")
  ctz-def-lc(("I1", "I2"), "L1", "C1")

  ctz-draw("C1", stroke: blue)
  ctz-label-circle("C1", $C_1$, pos: "above", dist:
    0.2)
  ctz-set-clip(-4, -4, 5, 4)
  ctz-draw-line-global-clip("A", "B", add: (2, 2),
    stroke: red)

  ctz-draw(points: ("O", "I1", "I2"), labels: (
    O: "below",
    I1: "above left",
    I2: "above right"
  ))
})
```

Figure



Named line/circle form:

```
ctz-def-line("L1", "A", "B")
ctz-def-circle("C1", "O", radius: 3)
ctz-def-lc(("I1", "I2"), "L1", "C1")
```

5.3. Circle–Circle — `ctz-def-cc`

Find intersections of two circles:

Code


```
#ctz-canvas(length: 0.65cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(O1: (0, 0), O2: (3, 0),
    R1: (2.5, 0), R2: (5.5, 0))
  ctz-def-circle("C1", "O1", through: "R1")
  ctz-def-circle("C2", "O2", through: "R2")
  ctz-def-cc(("I1", "I2"), "C1", "C2")

  ctz-draw("C1", stroke: blue)
  ctz-draw("C2", stroke: red)
  ctz-label-circle("C1", $C_1$, pos: "above left",
    dist: 0.2)
  ctz-label-circle("C2", $C_2$, pos: "above right",
    dist: 0.2)

  ctz-draw(points: ("O1", "O2", "I1", "I2"), labels:
  (
    I1: "above",
    I2: "below"
  ))
})
```

Figure



Named circle form:

```
ctz-def-circle("C1", "O1", through: "R1")
ctz-def-circle("C2", "O2", through: "R2")
ctz-def-cc(("I1", "I2"), "C1", "C2")
```

6. Triangle Centers

6.1. Basic Centers

6.1.1. Centroid — `ctz-def-centroid`

The intersection of medians (center of mass):

Code

```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()


  ctz-def-points(A: (0, 0), B: (5, 0), C: (2, 3.5))
  ctz-def-centroid("G", "A", "B", "C")

  // Draw medians
  ctz-def-midpoint("Ma", "B", "C")
  ctz-def-midpoint("Mb", "A", "C")
  ctz-def-midpoint("Mc", "A", "B")

  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw(segment: ("A", "Ma"), stroke: blue +
0.5pt)
  ctz-draw(segment: ("B", "Mb"), stroke: blue +
0.5pt)
  ctz-draw(segment: ("C", "Mc"), stroke: blue +
0.5pt)

  ctz-draw(points: ("A", "B", "C", "G"), labels: (
    A: "below left",
    B: "below right",
    C: "above",
    G: "above right"
  ))
})
```

Figure



6.1.2. Circumcenter — `ctz-def-circumcenter`

Center of the circumscribed circle:

Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()


  ctz-def-points(A: (0, 0), B: (5, 0), C: (2, 3.5))
  ctz-def-circumcenter("O", "A", "B", "C")

  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw(circle-through: ("O", "A"), stroke: blue +
0.7pt)

  ctz-draw(segment: ("O", "A"), stroke: gray + 0.5pt)
  ctz-draw(segment: ("O", "B"), stroke: gray + 0.5pt)
  ctz-draw(segment: ("O", "C"), stroke: gray + 0.5pt)

  ctz-draw(points: ("A", "B", "C", "O"), labels: (
    A: "below left",
    B: "below right",
    C: "above",
    O: "below"
  ))
})
```

Figure



6.1.3. Incenter — ctz-def-incenter

Center of the inscribed circle:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 0), C: (2, 3.5))
  ctz-def-incenter("I", "A", "B", "C")

  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw(incircle: ("A", "B", "C"), stroke: green +
0.7pt)

  ctz-draw(points: ("A", "B", "C", "I"), labels: (
    A: "below left",
    B: "below right",
    C: "above",
    I: "below right"
  ))
})
```

Figure



6.1.4. Orthocenter — ctz-def-orthocenter

Intersection of altitudes:

Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()


  ctz-def-points(A: (0, 0), B: (5, 0), C: (2, 3.5))
  ctz-def-orthocenter("H", "A", "B", "C")

  // Altitudes
  ctz-def-perp("Ha1", "Ha2", ("B", "C"), "A")
  ctz-def-perp("Hb1", "Hb2", ("A", "C"), "B")
  ctz-def-perp("Hc1", "Hc2", ("A", "B"), "C")

  ctz-set-clip(-0.5, -0.5, 5.5, 4)
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw-line-global-clip("A", "Ha1", add: (2, 2),
stroke: red + 0.5pt)
  ctz-draw-line-global-clip("B", "Hb1", add: (2, 2),
stroke: red + 0.5pt)
  ctz-draw-line-global-clip("C", "Hc1", add: (2, 2),
stroke: red + 0.5pt)

  ctz-draw(points: ("A", "B", "C", "H"), labels: (
    A: "left",
    B: "right",
    C: "above right",
    H: "below right"
  ))
})
```

Figure



6.2. The Euler Line

In any non-equilateral triangle, the orthocenter H , centroid G , and circumcenter O are collinear. This line is called the **Euler line**, and remarkably, G divides HO in the ratio 2 : 1.

Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()


  ctz-def-points(A: (0, 0), B: (5, 0), C: (1.5, 3.5))

  ctz-def-orthocenter("H", "A", "B", "C")
  ctz-def-centroid("G", "A", "B", "C")
  ctz-def-circumcenter("O", "A", "B", "C")

  ctz-set-clip(-0.5, -0.5, 5.5, 4)
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw-line-add("H", "O", add: 0.5, stroke:
    (paint: red, dash: "dashed"))
  ctz-draw(circle-through: ("O", "A"), stroke: blue +
    0.6pt)

  ctz-draw(points: ("A", "B", "C", "H", "G", "O"),
    labels: (
      A: "below left",
      B: "below right",
      C: "above",
      H: "left",
      G: "below",
      O: "right"
    ))
})
```

Figure



6.3. Right Triangles via Thales' Theorem

Thales' theorem states that any triangle inscribed in a semicircle with the diameter as its base has a right angle at the opposite vertex. The `ctz-def-thales-triangle()` function creates such triangles.

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(O: (0, 0))
  ctz-def-thales-triangle("A", "B", "C", "O", 2.5,
    base-angle: 30, orientation: "left")

  ctz-draw(circle-r: (_pt("O"), 2.5), stroke: gray +
    0.5pt)
  ctz-draw-path("A--B--C--A", stroke: black + 1pt)
  ctz-draw-mark-right-angle("A", "C", "B", color:
    red)

  ctz-draw(points: ("A", "B", "C", "O"), labels: (
    A: "right",
    B: "left",
    C: "above",
    O: "below"
  ))
})
```

Figure



Parameters:

- `name-a`, `name-b`: Diameter endpoints (base of triangle)
- `name-c`: Vertex with the right angle
- `center`: Circle center
- `radius`: Circle radius
- `base-angle`: Rotation angle for the diameter (default: 0)
- `orientation`: "left" or "right" - position of right angle vertex

6.4. Advanced Centers

ctz-euclide supports 10+ specialized triangle centers:

- `ctz-def-lemoine` — Symmedian point (Lemoine point)
- `ctz-def-nagel` — Nagel point
- `ctz-def-gergonne` — Gergonne point
- `ctz-def-spieker` — Spieker center (incenter of medial triangle)
- `ctz-def-euler` — Nine-point circle center
- `ctz-def-feuerbach` — Feuerbach point
- `ctz-def-mittenpunkt` — Mittenpunkt
- `ctz-def-excenter` — Excenter (specify vertex: "a", "b", or "c")

Example with Euler (nine-point) circle:

Code

```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 0), C: (1.5, 3.5))
  ctz-def-euler("N", "A", "B", "C")


  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)

  // Nine-point circle passes through midpoints
  ctz-def-midpoint("Ma", "B", "C")
  ctz-def-midpoint("Mb", "A", "C")
  ctz-def-midpoint("Mc", "A", "B")

  ctz-draw(circle-through: ("N", "Ma"), stroke:
purple + 0.7pt)

  ctz-draw(points: ("A", "B", "C", "N", "Ma", "Mb",
"Mc"), labels: (
    N: "below"
  ))
})
```

Figure



7. Transformations

7.1. Rotation — rotate

Rotate a point around a center:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(0: (2, 2), A: (5, 2))
  ctz-def-rotation("B", "A", "O", 60)
  ctz-def-rotation("C", "A", "O", 120)

  ctz-draw(circle-r: (_pt("O"), 3), stroke:
gray.lighten(50%))
  ctz-draw(segment: ("O", "A"), stroke: blue)
  ctz-draw(segment: ("O", "B"), stroke: blue)
  ctz-draw(segment: ("O", "C"), stroke: blue)
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)

  ctz-draw(points: ("O", "A", "B", "C"), labels: (
    0: "below left",
    A: "right",
    B: "above right",
    C: "left"
  ))
})
```

Figure



7.2. Reflection — ctz-def-reflect

Reflect a point across a line:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 3), P: (3, 0))
  ctz-def-reflect("Pp", "P", "A", "B")

  ctz-draw(segment: ("A", "B"), stroke: gray)
  ctz-draw(path: "P--Pp", stroke: blue + 0.5pt, mark:
(end: ">"))

  ctz-draw(points: ("A", "B", "P", "Pp"), labels: (
    P: "below",
    Pp: "above left"
  ))
})
```

Figure



7.3. Homothety (Scaling) — scale

Scale a point from a center:

Code


```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(0: (0, 0), A: (2, 1), B: (3, 2), C:
(1, 2.5))
  ctz-def-homothety("Ap", "A", "O", 2)
  ctz-def-homothety("Bp", "B", "O", 2)
  ctz-def-homothety("Cp", "C", "O", 2)

  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw(line: ("Ap", "Bp", "Cp", "Ap"), stroke:
blue)
  ctz-draw(segment: ("O", "Ap"), stroke: gray +
0.3pt)
  ctz-draw(segment: ("O", "Bp"), stroke: gray +
0.3pt)
  ctz-draw(segment: ("O", "Cp"), stroke: gray +
0.3pt)

  ctz-draw(points: ("O", "A", "B", "C", "Ap", "Bp",
"Cp"), labels: (
    0: "below left"
  ))
})
```

Figure



7.4. Projection — ctz-def-project

Project a point onto a line:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 1), P: (2, 3))
  ctz-def-project("H", "P", "A", "B")

  ctz-draw(segment: ("A", "B"), stroke: black)
  ctz-draw(segment: ("P", "H"), stroke: blue + 0.5pt)
  ctz-draw-mark-right-angle("A", "H", "P", size:
0.25)

  ctz-draw(points: ("A", "B", "P", "H"), labels: (
    P: "above",
    H: "below"
  ))
})
```

Figure



7.5. Inversion — ctz-def-inversion

Invert points, lines, or circles through a circle:

Code


```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(0: (0, 0), A: (-4, -1), B: (4, -1),
  C: (1.8, 1))
  ctz-def-line("L", "A", "B")
  ctz-def-circle("C1", "C", radius: 1.1)

  ctz-def-inversion("Li", "L", "0", 3)
  ctz-def-inversion("C1i", "C1", "0", 3)

  ctz-draw(circle-r: (_pt("0"), 3), stroke: black +
  1pt)
  ctz-draw("L", stroke: gray + 0.7pt)
  ctz-draw("C1", stroke: gray + 0.7pt)
  ctz-draw("Li", stroke: blue + 1pt)
  ctz-draw("C1i", stroke: red + 1pt)
  ctz-draw(points: ("0"), labels: (0: "below left"))
})
```

Figure



7.6. Object Duplication — ctz-duplicate

Duplicate any geometric object. For polygons, explicit point names must be provided.


Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  // Duplicate a circle
  ctz-def-circle("c1", (0, 0), radius: 1.5)
  ctz-duplicate("c2", "c1")
  ctz-draw("c1", stroke: blue)

  // Duplicate a polygon
  ctz-def-regular-polygon("tri", ("A", "B", "C"),
  (3, 0), (4, 0), n: 3)
  ctz-duplicate("tri2", "tri",
  points: ("A2", "B2", "C2"))
  ctz-draw("tri", stroke: green)
  ctz-draw-labels("A", "B", "C")
})
```

Figure



For points, lines, and circles, duplication is straightforward. For polygons, you must provide explicit point names so the vertices can be referenced independently.


7.7. Polymorphic Rotation

The `ctz-def-rotation()` function works on all object types: points, lines, circles, and polygons.

Code

```
#ctz-canvas(length: 0.75cm, {  
  import cetz.draw: *  
  ctz-init()  
  
  // Rotate a circle  
  ctz-def-points(0: (0, 0))  
  ctz-def-circle("c1", (2, 0), radius: 1)  
  ctz-def-rotation("c2", "c1", "0", 45)  
  
  ctz-draw("c1", stroke: blue)  
  ctz-draw("c2", stroke: red)  
  ctz-draw(points: ("0"), labels: (  
    0: "below"  
  ))  
})
```

Figure



For lines, both endpoints are rotated. For circles, the center is rotated while radius remains constant. For polygons, all constituent points are rotated in place.

8. Drawing & Styling

8.1. Points — `ctz-draw-points`

Draw points at named locations:

```
ctz-draw(points: ("A", "B", "C"))
```

8.2. Unified Drawing — `ctz-draw`

The `ctz-draw()` function provides a unified interface for drawing both **named objects** and **unnamed constructs**.

8.2.1. Drawing Named Objects

Use `ctz-draw()` to draw any object type without remembering type-specific commands. It automatically detects whether the object is a point, line, circle, or polygon.


Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-circle("c1", (0, 0), radius: 1.5)
  ctz-def-line("l1", (-2, 0), (2, 0))
  ctz-def-polygon("tri", "A", "B", "C")
  ctz-def-points(A: (1, 2), B: (2, 0), C: (0, 1))

  ctz-draw("c1", stroke: blue, fill: none)
  ctz-draw("l1", stroke: red + 1.5pt)
  ctz-draw("tri", stroke: green)
  ctz-draw("A")
})
```

Figure



8.2.2. Drawing Unnamed Constructs

You can also use `ctz-draw()` to draw geometric objects directly without defining them first using named parameters.

8.2.2.1. Points with Labels


Draw multiple points at once, optionally with labels:

Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()
  ctz-def-points(A: (0, 0), B: (2, 0), C: (2, 2), D:
(0, 2))

  // Draw points with custom label positions
  ctz-draw(points: ("A", "B", "C", "D"), labels: (
    A: "below left",
    B: "below right",
    C: "above right",
    D: "above left"
  ))
})
```

Figure



Use `labels: true` for default label positioning, or omit the `labels` parameter to draw points without labels.

8.2.2.2. Paths and Polylines

Draw paths using the `path:` parameter for CeTZ-style path syntax, or `line:` for polylines through points:

```
ctz-draw(path: "A--B--C--A", stroke: black) // Close the path by repeating first point
ctz-draw(line: ("A", "B", "C", "D"), stroke: red) // Open polyline
```

8.2.2.3. Circles

Draw circles without naming them:

```
// Circle through two points (center and point on circumference)
ctz-draw(circle-through: ("O", "A"), stroke: blue)

// Circle by center and radius
ctz-draw(circle-r: ((0, 0), 1.5), stroke: green)

// Circle by diameter endpoints
ctz-draw(circle-diameter: ("A", "B"), stroke: purple)

// Circumcircle of triangle
ctz-draw(circumcircle: ("A", "B", "C"), stroke: red)

// Incircle of triangle
ctz-draw(incircle: ("A", "B", "C"), stroke: teal)
```

8.2.2.4. Arcs and Semicircles

```
// Arc by center and two points
ctz-draw(arc: (center: "O", start: "A", end: "B"), stroke: orange)

// Arc by center, radius, and angles (in degrees)
ctz-draw(arc-r: ((0, 0), 2, 0, 90), stroke: black)

// Semicircle by diameter endpoints
ctz-draw(semicircle: ("A", "B"), stroke: blue, fill: blue.lighten(80%))
```

8.2.2.5. Line Segments


```
ctz-draw(segment: ("A", "B"), stroke: maroon + 1.5pt)
```

8.2.3. Complete Example

Code

```
#ctz-canvas(length: 0.6cm, {  
  import ctz.draw: *  
  ctz-init()  
  ctz-def-points(A: (0, 0), B: (3, 0), C: (1.5, 2))  
  
  // Named circle  
  ctz-def-circle("myCircle", (1.5, 1), radius: 2.5)  
  ctz-draw("myCircle", stroke: gray + 0.5pt)  
  
  // Unnamed constructs  
  ctz-draw(path: "A-B-C-A", stroke: black)  
  ctz-draw(circumcircle: ("A", "B", "C"), stroke:  
blue)  
  ctz-draw(incircle: ("A", "B", "C"), stroke: red)  
  ctz-draw(points: ("A", "B", "C"), labels: true)  
})
```

Figure



8.3. Labels — ctz-draw-labels

Add labels to points with positioning:

```
ctz-draw-labels("A", "B", "C",  
  A: "below left",  
  B: "below right",  
  C: "above")
```

Positions: "above", "below", "left", "right", "above left", etc.

Custom offset:

```
ctz-draw-labels("0", 0: (pos: "below", offset: (0, -0.15)))
```

More placement controls (position, offset, distance):

```
ctz-draw-labels("A", "B", "C",  
  A: (pos: "above", dist: 0.25),  
  B: (pos: "right", offset: (0.1, 0)),  
  C: (pos: "below left", offset: (-0.05, -0.05)))
```

8.4. Segments — ctz-draw-segment

Draw a segment with optional arrow or bar tips and a dimension label:


```
ctz-draw-segment("A", "B", arrows: "|-|", dim: $5$, dim-pos: "above")
```

Supported arrows: -- (none), ->, <-, <->, |-|, |->, <-|.

Code

```
#ctz-canvas(length: 0.8cm, {  
  import ctz.draw: *  
  ctz-init()  
  
  ctz-def-points(A: (0, 0), B: (4, 0), C: (6, 1.5))  
  
  ctz-draw-segment("A", "B", arrows: "|-|", dim: $5$,  
    dim-pos: "above")  
  ctz-draw-segment("B", "C", arrows: "->", dim: $v$,  
    dim-pos: "below")  
  ctz-draw(points: ("A", "B", "C"), labels: (A:  
    "below", B: "below", C: "above"))  
})
```

Figure



Mark equal-length segments with ticks:

```
ctz-draw-mark-segment("A", "B", mark: 1)  
ctz-draw-mark-segment("C", "D", mark: 2)
```


Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 0), C: (4, 2.5),
D: (0, 2.5))
  ctz-draw(line: ("A", "B", "C", "D"), stroke: black)

  // Opposite sides equal
  ctz-draw-mark-segment("A", "B", mark: 1)
  ctz-draw-mark-segment("C", "D", mark: 1)
  ctz-draw-mark-segment("B", "C", mark: 2)
  ctz-draw-mark-segment("D", "A", mark: 2)

  ctz-draw(points: ("A", "B", "C", "D"), labels: (
    A: "below left",
    B: "below right",
    C: "above right",
    D: "above left"
  ))
})
```

Figure



Code

```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()


  ctz-def-points(O: (0, 0), A: (3, 0))
  ctz-def-regular-polygon("Hex", ("A", "B", "C", "D",
"E", "F"), "O", "A")

  ctz-draw-regular-polygon(("A", "B", "C", "D", "E",
"F"),
  stroke: black, mark: 1)

  // Mark all sides with the same tick
  // (use mark-opts to customize size/position)

  ctz-draw(points: ("A", "B", "C", "D", "E", "F"),
labels: (
    A: "right",
    B: "above right",
    C: "above left",
    D: "left",
    E: "below",
    F: "below"
  ))
})
```

Figure



8.5. Segment Measurements — ctz-draw-measure-segment

Draw an offset measurement line with dotted fences and a centered label. The line breaks around the label and uses open arrowheads by default.

```
ctz-draw-measure-segment("A", "B", label: $5$, offset: 0.3, side: "left")
```

Code


```
#ctz-canvas(length: 0.8cm, {
  import ctz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 1.2))
  ctz-draw-segment("A", "B", stroke: black + 1pt)

  // Minimal measurement example
  ctz-draw-measure-segment("A", "B", label: $ell$,
    offset: 0.45, side: "left",
    fence-dash: "dotted")

  ctz-draw(points: ("A", "B"), labels: (
    A: "below",
    B: "below"
  ))
})
```

Figure



Code


```
#ctz-canvas(length: 0.8cm, {
  import ctz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 0), C: (5, 3), D:
    (0, 3))
  ctz-draw(line: ("A", "B", "C", "D"), stroke: black
    + 1pt)

  // Rectangle measurements (width and height)
  ctz-draw-measure-segment("A", "B", label: $w$,
    offset: 0.45, side: "below")
  ctz-draw-measure-segment("C", "B", label: $h$,
    offset: -0.45, side: "right")

  ctz-draw(points: ("A", "B", "C", "D"), labels: (
    A: "below left",
    B: "below right",
    C: "above right",
    D: "above left"
  ))
})
```

Figure



8.6. Paths — ctz-draw-path

Draw polylines with per-segment tips using a TikZ-like string:

```
ctz-draw-path("A--B->C|-|D", stroke: black)
```

Supported connectors: --, ->, <-, <->, |-|, |->, <-|.

By default, `ctz-draw-path` draws points as crosses for normal segments and hides points that touch a bar connector (`|-|`, `|->`, `<-|`). Labels default to `below`. You can override per-point placements or point styles in the path with `{...}`, or via `label-overrides`.

Default behavior, label are placed below


Code

```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(
    A: (0, 0), B: (3, 0), C: (6, 1.5), D: (8, 0),
  )

  // Default labels below, default point styles
  ctz-draw-path("A--B->C|-|D", stroke: black)
})
```

Figure




Code

```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(
    A: (0, 0), B: (3, 0), C: (6, 1.5), D: (8, 0),
  )

  ctz-draw-path("A{below}--B{below}->C{above}|-|
D{below}", stroke: black)
})
```

Figure



Override placements using label-overrides:

```
ctz-draw-path("A--B->C|-|D",
  label-overrides: (A: "left", C: "above right"))
```

Customize point appearance or disable points/labels:

```
ctz-draw-path("A--B->C|-|D",
  point-style: "circle",
  point-color: red,
  label-pos: "above")
```

```
ctz-draw-path("A--B->C|-|D",
  points: false,
  labels: false)
```

Per-point overrides inside the path:

```
ctz-draw-path("A{below, style: circle}--B{below}->C{above, style: none}|-|D{below}",
  stroke: black)
```


Code

```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(
    A: (0, 0), B: (3, 0), C: (6, 1.5), D: (8, 0),
  )

  ctz-draw-path("A{below, style: circle}-B{below}->C{above}-D{below}",
    stroke: black)
})
```

Figure



8.7. Global Styling — ctz-style

Set default styles for points and labels:

Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "dot", size: 0.1, fill:
    red))

  ctz-def-points(A: (0, 0), B: (3, 0), C: (1.5, 2.5))
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw(points: ("A", "B", "C"))

  ctz-style(point: (shape: "cross", size: 0.15,
    stroke: blue + 1.5pt))
  ctz-def-centroid("G", "A", "B", "C")
  ctz-draw(points: ("G"))

  ctz-draw-labels("A", "B", "C", "G",
    A: "below left", B: "below right",
    C: "above", G: "right")
})
```

Figure



Point shapes: "dot", "cross", "circle", "square"

8.8. Angle Marking — ctz-draw-angle

Mark and label angles:

Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 0), C: (1, 3))
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)

  ctz-draw-angle("A", "B", "C",
    label:  $\alpha$ ,
    radius: 0.7,
    fill: blue.lighten(70%),
    stroke: blue)

  ctz-draw(points: ("A", "B", "C"), labels: (
    A: "below left",
    B: "below right",
    C: "above"
  ))
})
```

Figure



8.9. Right Angle Mark — ctz-draw-mark-right-angle

Mark a right angle with a small square:

Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 0), C: (0, 3))
  ctz-draw(segment: ("A", "B"), stroke: black)
  ctz-draw(segment: ("A", "C"), stroke: black)

  ctz-draw-mark-right-angle("B", "A", "C", size: 0.4)

  ctz-draw(points: ("A", "B", "C"), labels: (
    A: "below left",
    B: "right",
    C: "above"
  ))
})
```

Figure



9. Circles

9.1. Named Circle — **ctz-def-circle** / **ctz-draw-circle**

Define a circle once and draw/label it by name. This uses the “define → draw → label” pattern:

- **ctz-def-circle** stores geometry under a name.
- **ctz-draw-circle** renders it later (you can style it each time).
- **ctz-label-circle** places text relative to the circle without recomputing center/radius.

```
ctz-def-points(O: (0, 0), A: (3, 0))
ctz-def-circle("C1", "O", through: "A")
ctz-draw("C1", stroke: gray)
ctz-label-circle("C1", $C_1$, pos: "above right", dist: 0.2)
```

More label placement controls:

```
ctz-label-circle("C1", $C_1$,
  pos: "above",
  dist: 0.25,
  offset: (0.1, 0))
```

9.2. Circumcircle — **ctz-draw-circumcircle**

Draw the circumscribed circle of a triangle:

```
ctz-draw(circumcircle: ("A", "B", "C"), stroke: blue + 1pt)
```

9.3. Incircle — **ctz-draw-incircle**

Draw the inscribed circle of a triangle:

```
ctz-draw(incircle: ("A", "B", "C"), stroke: green + 1pt)
```

9.4. Circle Through Point — **ctz-draw-circle-through**

Draw a circle with given center passing through a point:

```
ctz-draw(circle-through: ("O", "A"), stroke: blue)
```

9.5. Semicircle — **ctz-draw-semicircle**

Draw a semicircle on a diameter:

```
ctz-draw(semicircle: ("A", "B"), stroke: blue)
```

10. Clipping

Lines that extend infinitely need to be clipped to the visible region.

10.1. Set Clip Region — `ctz-set-clip`

Define a rectangular clip boundary:

```
ctz-set-clip(xmin, ymin, xmax, ymax)
```

10.2. Draw Clipped Line — `ctz-draw-line-global-clip`

Draw a line that is automatically clipped:

```
ctz-draw-line-global-clip("A", "B", add: (2, 2), stroke: blue)
```

The `add` parameter extends the line beyond the two points before clipping.

10.3. Draw Clipped Segment — `ctz-draw-seg-global-clip`

Draw a segment with clipping:

```
ctz-draw-seg-global-clip("A", "B", stroke: red)
```

Code

```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (2, 3))


  // Set clip boundary
  ctz-set-clip(-1, -1, 4, 5)

  // Draw extended line (clipped)
  ctz-draw-line-global-clip("A", "B", add: (5, 5),
    stroke: blue)

  // Show clip boundary
  ctz-show-clip(stroke: gray + 0.5pt)

  ctz-draw(points: ("A", "B"), labels: (
    A: "below",
    B: "above left"
  ))
})
```

Figure



11. Raw Algorithms

For direct computation without the point registry, use the `raw` dictionary:

```
// Direct centroid calculation
let center = raw.ctz-def-centroid((0,0,0), (3,0,0), (1.5,2.5,0))

// Distance between points
let d = raw.dist((0,0,0), (3,4,0)) // Returns 5

// Line-line intersection
let pt = raw.line-line((0,0,0), (1,1,0), (0,1,0), (1,0,0), ray: true)
```

Available raw functions:

- **Intersections:** `line-line`, `line-circle`, `circle-circle`
- **Triangle centers:** `ctz-def-centroid`, `ctz-def-circumcenter`, `ctz-def-incenter`, `ctz-def-orthocenter`, `euler-center`, `ctz-def-lemoine`, etc.
- **Transformations:** `ctz-def-rotation`, `reflection`, `translation`, `ctz-def-homothety`, `projection`, `ctz-def-inversion`
- **Utilities:** `ctz-def-midpoint`, `dist`, `angle-at-vertex`, `triangle-area`, etc.

12. Function Reference

12.1. Point Definition

- `ctz-def-points(A: (x, y), ...)` — Define named points
- `ctz-def-line(name, a, b)` — Named line from two points
- `ctz-def-circle(name, center, radius|through)` — Named circle
- `ctz-def-polygon(name, a, b, c, ...)` — Named polygon
- `ctz-def-midpoint(name, a, b)` — Midpoint of segment
- `ctz-def-linear(name, a, b, k)` — Point at ratio k along line
- `ctz-def-regular-polygon([name,] names, center, first)` — Regular n-gon vertices (optionally register polygon name)
- `ctz-def-point-on-circle(name, center, radius, angle)` — Point on circle at angle
- `ctz-def-equilateral(name, a, b)` — Third vertex of equilateral triangle
- `ctz-def-golden(name, a, b)` — Golden ratio point

12.2. Line Constructions

- `ctz-def-perp(n1, n2, line, through)` — Perpendicular through point
- `ctz-def-para(n1, n2, line, through)` — Parallel through point
- `ctz-def-bisect(n1, n2, a, vertex, c)` — Angle bisector
- `ctz-def-mediator(n1, n2, a, b)` — Perpendicular bisector

12.3. Intersections

- `ctz-def-ll(name, line1, line2)` — Line-line intersection
- `ctz-def-lc(names, line, circle)` — Line-circle intersections
- `ctz-def-cc(names, circle1, circle2)` — Circle-circle intersections

12.4. Triangle Centers

- `ctz-def-centroid`, `ctz-def-circumcenter`, `ctz-def-incenter`, `ctz-def-orthocenter`
- `ctz-def-euler`, `ctz-def-lemoine`, `ctz-def-nagel`, `ctz-def-gergonne`, `ctz-def-spieker`
- `ctz-def-feuerbach`, `ctz-def-mittenpunkt`, `ctz-def-excenter`

12.5. Special Triangles

- `ctz-def-medial-triangle(na, nb, nc, a, b, c)` — Medial triangle
- `ctz-def-orthic-triangle(na, nb, nc, a, b, c)` — Orthic triangle
- `ctz-def-intouch-triangle(na, nb, nc, a, b, c)` — Intouch triangle
- `ctz-def-thales-triangle(na, nb, nc, center, radius, ...)` — Right triangle via Thales' theorem

12.6. Transformations

- `ctz-def-rotation(name, source, center, angle)` — Rotation (works on all object types)
- `ctz-def-reflect(name, source, line-a, line-b)` — Reflection
- `ctz-def-translate(name, source, vector)` — Translation
- `ctz-def-homothety(name, source, center, factor)` — Homothety
- `ctz-def-project(name, source, line-a, line-b)` — Projection
- `ctz-def-inversion(name, source, center, radius)` — Inversion (works on points, lines, circles, polygons)
- `ctz-duplicate(target, source, points: auto)` — Duplicate any geometric object

12.7. Drawing

- `ctz-draw(name, ...)` — Draw any object type (polymorphic)
- `ctz-draw-points(names...)` — Draw points
- `ctz-draw-labels(names, placements)` — Label points
- `ctz-style(point: (...))` — Set styling
- `ctz-draw-angle(vertex, a, b, ...)` — Mark angle
- `ctz-draw-mark-right-angle(a, vertex, c, ...)` — Right angle mark

- `ctz-draw-segment(a, b, ...)` — Draw segment
- `ctz-draw-measure-segment(a, b, ...)` — Offset measurement with fences and label
- `ctz-draw-path(spec, ...)` — Draw path with per-segment tips
- `ctz-draw-polygon(points...)` — Draw polygon (triangle, quadrilateral, etc.)
- `ctz-draw-fill-polygon(points...)` — Fill polygon
- `ctz-draw-regular-polygon(names, ...)` — Draw regular polygon by vertex names
- `ctz-draw-fill-regular-polygon(names, ...)` — Fill regular polygon by vertex names
- `ctz-draw-circle(name, ...)` — Draw named circle
- `ctz-label-circle(name, label, ...)` — Label named circle
- `ctz-label-polygon(name, label, ...)` — Label named polygon
- `ctz-draw-circumcircle(a, b, c, ...)` — Circumscribed circle
- `ctz-draw-incircle(a, b, c, ...)` — Inscribed circle


12.8. Clipping

- `ctz-set-clip(xmin, ymin, xmax, ymax)` — Set clip region
- `ctz-clear-clip()` — Clear clip region
- `ctz-draw-line-global-clip(a, b, ...)` — Draw clipped line
- `ctz-draw-seg-global-clip(a, b, ...)` — Draw clipped segment

13. Gallery Examples

The following pages showcase advanced geometric constructions using `ctz-euclide`. Each example demonstrates different features and techniques.

Triangle Centers



```
#ctz-canvas(length: 0.95cm, {
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "dot", size: 0.07, fill: black))

  ctz-def-points(A: (0, 0), B: (7, 0.5), C: (2.5, 5))
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black + 1.5pt)

  ctz-def-centroid("G", "A", "B", "C")
  ctz-def-circumcenter("O", "A", "B", "C")
  ctz-def-incenter("I", "A", "B", "C")
  ctz-def-orthocenter("H", "A", "B", "C")


  // Euler line (H, G, O are collinear)
  ctz-draw(segment: ("H", "O"), stroke: (
    paint: red.darken(20%),
    dash: "dashed",
    thickness: 1.2pt
  ))

  // Circumcircle and incircle
  ctz-draw(circle-through: ("O", "A"), stroke: blue + 1pt)
  ctz-draw(incircle: ("A", "B", "C"), stroke: green.darken(20%) + 1pt)

  // Draw medians to centroid
  ctz-def-midpoint("Ma", "B", "C")
  ctz-def-midpoint("Mb", "A", "C")
  ctz-def-midpoint("Mc", "A", "B")
  ctz-draw(segment: ("A", "Ma"), stroke: gray + 0.7pt)
  ctz-draw(segment: ("B", "Mb"), stroke: gray + 0.7pt)
  ctz-draw(segment: ("C", "Mc"), stroke: gray + 0.7pt)

  ctz-draw(points: ("A", "B", "C", "G", "O", "I", "H"), labels: (
    A: "below left",
    B: "below right",
    C: "above",
    G: "right",
    O: "below",
    I: "right",
    H: "left"
  ))
})
```

Nine-Point Circle



```
#ctz-canvas(length: 0.9cm, {
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "circle", size: 0.06, stroke: black + 0.8pt, fill: white))

  ctz-def-points(A: (0, 0), B: (7, 0), C: (2, 5))
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black + 1.5pt)

  // Midpoints of sides
  ctz-def-midpoint("Ma", "B", "C")
  ctz-def-midpoint("Mb", "A", "C")
  ctz-def-midpoint("Mc", "A", "B")

  // Feet of altitudes
  ctz-def-project("Ha", "A", "B", "C")
  ctz-def-project("Hb", "B", "A", "C")
  ctz-def-project("Hc", "C", "A", "B")


  // Orthocenter and midpoints to vertices
  ctz-def-orthocenter("H", "A", "B", "C")
  ctz-def-midpoint("MHa", "H", "A")
  ctz-def-midpoint("MHb", "H", "B")
  ctz-def-midpoint("MHc", "H", "C")

  // Nine-point circle passes through all 9 points
  ctz-def-euler("N", "A", "B", "C")
  ctz-draw(circle-through: ("N", "Ma"), stroke: purple.darken(10%) + 1.2pt)

  // Draw altitudes
  ctz-draw(segment: ("A", "Ha"), stroke: blue.lighten(30%) + 0.7pt)
  ctz-draw(segment: ("B", "Hb"), stroke: blue.lighten(30%) + 0.7pt)
  ctz-draw(segment: ("C", "Hc"), stroke: blue.lighten(30%) + 0.7pt)

  ctz-draw(points: ("A", "B", "C", "N", "Ma", "Mb", "Mc", "Ha", "Hb", "Hc", "MHa", "MHb", "MHc", "H"), labels: (
    A: "left",
    B: "right",
    C: "above",
    N: "below"
  ))
})
```

Regular Pentagon



```
#ctz-canvas(length: 1cm, {
  import ctz.draw: *
  ctz-init()
  ctz-style(point: (shape: "dot", size: 0.08, fill: black))

  ctz-def-points(0: (0, 0), V1: (4, 0))
  ctz-def-regular-polygon("Pent", ("A", "B", "C", "D", "E"), "O", "V1")


  // Pentagon
  ctz-draw("Pent", stroke: black + 1.5pt)

  // All diagonals
  ctz-draw(segment: ("A", "C"), stroke: blue + 0.8pt)
  ctz-draw(segment: ("A", "D"), stroke: blue + 0.8pt)
  ctz-draw(segment: ("B", "D"), stroke: red + 0.8pt)
  ctz-draw(segment: ("B", "E"), stroke: red + 0.8pt)
  ctz-draw(segment: ("C", "E"), stroke: green.darken(20%) + 0.8pt)

  // Center
  ctz-draw(circle-r: (_pt("O"), 4), stroke: gray.lighten(50%) + 0.5pt)

  ctz-draw(points: ("A", "B", "C", "D", "E", "O"), labels: (
    A: "right",
    B: (pos: "above right", offset: (0.1, 0.1),
    C: "above left",
    D: "below left",
    E: "below right",
    O: "below"
  ))
})
```

Inscribed Angle Theorem



```
#ctz-canvas(length: 1cm, {
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "cross", size: 0.11, stroke: black + 1.2pt))

  ctz-def-points(O: (0, 0), R: (4, 0))
  ctz-draw(circle-r: (_pt("O"), 4), stroke: black + 1.2pt)


  // Place points on circle
  ctz-def-rotation("A", "R", "0", 150)
  ctz-def-rotation("C", "R", "0", 30)
  ctz-def-rotation("B", "R", "0", 250)

  // Inscribed angle at B
  ctz-draw(segment: ("A", "B"), stroke: blue + 1.2pt)
  ctz-draw(segment: ("B", "C"), stroke: blue + 1.2pt)
  ctz-draw-angle("B", "A", "C", label: $alpha$, radius: 0.8,
    fill: blue.lighten(70%), stroke: blue)

  // Central angle at O (twice the inscribed angle)
  ctz-draw(segment: ("O", "A"), stroke: red + 1.2pt)
  ctz-draw(segment: ("O", "C"), stroke: red + 1.2pt)
  ctz-draw-angle("O", "A", "C", label: $2alpha$, radius: 1.2,
    fill: red.lighten(70%), stroke: red)

  ctz-draw(segment: ("A", "C"), stroke: gray.lighten(40%) + 0.8pt)
  ctz-draw(points: ("O", "A", "B", "C"), labels: (
    O: "below",
    A: "left",
    B: "right",
    C: "above"
  ))
})
```

Apollonius Circle



```
#ctz-canvas(length: 0.95cm, {
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "dot", size: 0.08, fill: black))

  ctz-def-points(A: (-3, 0), B: (3, 0))

  // Apollonius circle: locus of points P where PA/PB = k
  let k = 2

  // External and internal division points
  ctz-def-points(E: (-5, 0), I: (-1, 0))


  // Center is midpoint of E and I
  ctz-def-midpoint("O", "E", "I")
  ctz-draw(circle-through: ("O", "E"), stroke: purple.darken(10%) + 1.3pt)

  // Show some points on the circle
  ctz-def-rotation("P1", "E", "O", 60)
  ctz-def-rotation("P2", "E", "O", 120)
  ctz-def-rotation("P3", "E", "O", -60)
  ctz-def-rotation("P4", "E", "O", -120)

  // For P1: PA/PB = k = 2
  ctz-draw(segment: ("P1", "A"), stroke: blue + 0.8pt)
  ctz-draw(segment: ("P1", "B"), stroke: red + 0.8pt)
  ctz-draw(segment: ("A", "B"), stroke: black + 1pt)

  ctz-draw(points: ( "B", "O", "E", "I", "P1", "P2", "P3", "P4"), labels: (
    B: "below right",
    E: "left",
    I: "above right",
    P1: "above",
    O: "below"
  ))
})
```


Orthocenter and Altitudes



```
#ctz-canvas(length: 0.85cm, {
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "cross", size: 0.1, stroke: black + 1.2pt))

  ctz-def-points(A: (0, 0), B: (8, 0), C: (2.5, 5.5))
  ctz-set-clip(-1.5, -1.5, 9.5, 7)

  // Triangle
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black + 1.5pt)

  // Extended altitudes (automatically clipped)
  ctz-def-perp("Ha1", "Ha2", ("B", "C"), "A")
  ctz-def-perp("Hb1", "Hb2", ("A", "C"), "B")
  ctz-def-perp("Hc1", "Hc2", ("A", "B"), "C")

  ctz-draw-line-global-clip("A", "Ha1", add: (1, 1.5), stroke: blue + 1pt)
  ctz-draw-line-global-clip("B", "Hb1", add: (1, 1.5), stroke: red + 1pt)
  ctz-draw-line-global-clip("C", "Hc1", add: (1, 2.5), stroke: green.darken(20%) + 1pt)


  // Orthocenter (intersection of altitudes)
  ctz-def-orthocenter("H", "A", "B", "C")

  // Feet of altitudes
  ctz-def-project("Ha", "A", "B", "C")
  ctz-def-project("Hb", "B", "A", "C")
  ctz-def-project("Hc", "C", "A", "B")

  ctz-draw-mark-right-angle("A", "Ha", "B", size: 0.3)
  ctz-draw-mark-right-angle("B", "Hb", "C", size: 0.3)
  ctz-draw-mark-right-angle("C", "Hc", "A", size: 0.3)

  ctz-draw(points: ("A", "B", "C", "H", "Ha", "Hb", "Hc"), labels: (
    A: "left",
    B: "below",
    C: "above right",
    H: "right"
  ))
})
```

Equilateral Triangle Construction



```
#ctz-canvas({
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "cross", size: 0.1, stroke: black + 1.5pt))

  // Base of equilateral triangle
  ctz-def-points("A", (0, 0), "B", (5, 0))
  ctz-def-equilateral("C", "A", "B")

  // Draw triangle
  ctz-draw(line: ("A", "B", "C", "A"), stroke: blue + 1.5pt)

  // Mark 60° angles
  ctz-draw-angle("A", "B", "C", label: $60^\circ$, radius: 0.6, stroke: green + 0.8pt)
  ctz-draw-angle("B", "C", "A", label: $60^\circ$, radius: 0.6, stroke: green + 0.8pt)
  ctz-draw-angle("C", "A", "B", label: $60^\circ$, radius: 0.8, stroke: orange + 0.8pt)


  // Draw circles at vertices
  ctz-draw(circle-r: (_pt("A"), 0.3), stroke: green + 1pt)
  ctz-draw(circle-r: (_pt("B"), 0.3), stroke: green + 1pt)
  ctz-draw(circle-r: (_pt("C"), 0.3), stroke: orange + 1pt)

  // In equilateral triangle, all centers coincide
  ctz-def-centroid("G", "A", "B", "C")

  // Draw medians/altitudes
  ctz-def-midpoint("Ma", "B", "C")
  ctz-def-midpoint("Mb", "A", "C")
  ctz-def-midpoint("Mc", "A", "B")
  ctz-draw(segment: ("A", "Ma"), stroke: (paint: purple, thickness: 0.6pt, dash: "dashed"))
  ctz-draw(segment: ("B", "Mb"), stroke: (paint: purple, thickness: 0.6pt, dash: "dashed"))
  ctz-draw(segment: ("C", "Mc"), stroke: (paint: purple, thickness: 0.6pt, dash: "dashed"))

  ctz-draw(points: ("A", "B", "C", "G"), labels: (
    A: "left",
    B: "right",
    C: "above",
    G: "below"
  ))
})
```

Perpendicular Bisectors and Circumcircle



```
#ctz-canvas({
  import ctz.draw: *
  ctz-init()
  ctz-style(point: (shape: "dot", size: 0.08, fill: black))

  // Define triangle
  ctz-def-points("A", (0, 0), "B", (6, 0), "C", (2.5, 5))
  ctz-set-clip(-1, -1, 7, 6)

  // Calculate midpoints
  ctz-def-midpoint("Mab", "A", "B")
  ctz-def-midpoint("Mbc", "B", "C")
  ctz-def-midpoint("Mca", "C", "A")

  // Circumcenter is intersection of perpendicular bisectors
  ctz-def-circumcenter("O", "A", "B", "C")

  // Create perpendicular bisector lines
  ctz-def-mediator("Pab1", "Pab2", "A", "B")
  ctz-def-mediator("Pbc1", "Pbc2", "B", "C")
  ctz-def-mediator("Pca1", "Pca2", "C", "A")

  // Draw triangle
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black + 1.5pt)

  // Draw perpendicular bisectors (clipped)
  ctz-draw-seg-global-clip("Pab1", "Pab2", stroke: blue + 0.8pt)
  ctz-draw-seg-global-clip("Pbc1", "Pbc2", stroke: red + 0.8pt)
  ctz-draw-seg-global-clip("Pca1", "Pca2", stroke: green + 0.8pt)


  // Draw circumcircle
  ctz-draw(circumcircle: ("A", "B", "C"), stroke: purple + 1.2pt)

  // Radii (equal length)
  ctz-draw(segment: ("O", "A"), stroke: gray + 0.4pt)
  ctz-draw(segment: ("O", "B"), stroke: gray + 0.4pt)
  ctz-draw(segment: ("O", "C"), stroke: gray + 0.4pt)

  ctz-draw-mark-right-angle("A", "Mab", "O", size: 0.3)
  ctz-draw-mark-right-angle("B", "Mbc", "O", size: 0.3)
  ctz-draw-mark-right-angle("C", "Mca", "O", size: 0.3)

  ctz-draw(points: ("A", "B", "C", "O", "Mab", "Mbc", "Mca"), labels: (
    A: "left",
    B: "right",
    C: "above",
    O: "below"
  ))
})
```

Thales' Theorem



```
#ctz-canvas({
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "cross", size: 0.1, stroke: black + 1.5pt))

  // Circle with diameter AB
  ctz-def-points("O", (0, 0), "A", (-3, 0), "B", (3, 0))

  // Point C on circle
  ctz-def-point-on-circle("C", "O", 3, 110)

  // Draw circle and diameter
  ctz-draw(circle-r: (_pt("O"), 3), stroke: gray + 0.8pt)
  ctz-draw(segment: ("A", "B"), stroke: blue + 1.2pt)


  // Draw triangle ACB
  // By Thales' theorem: angle ACB = 90° (inscribed in semicircle)
  ctz-draw(line: ("A", "C", "B", "A"), stroke: black + 1.2pt)

  // Mark the right angle at C
  ctz-draw-mark-right-angle("A", "C", "B", size: 0.4)

  // Draw altitude from C to AB
  ctz-def-project("H", "C", "A", "B")
  ctz-draw(segment: ("C", "H"), stroke: (paint: green, thickness: 0.8pt, dash: "dashed"))

  ctz-draw(points: ("A", "B", "C", "O", "H"), labels: (
    A: "left",
    B: "right",
    C: "above",
    O: "below",
    H: "below left"
  ))
})
```

Inversion



```
#ctz-canvas({
  import cetz.draw: *
  ctz-init()

  ctz-set-clip(-6, -5, 6, 6)

  ctz-def-points(
    O: (0, 0),
    A: (-5, -1.5),
    B: (5, -1.5),
    C: (2, 1),
    D: (-2, 0),
  )

  ctz-def-line("l1", "A", "B")
  ctz-def-circle("c1", "C", radius: 1.2)
  ctz-def-circle("c2", "D", radius: 2)

  ctz-def-inversion("lli", "l1", "O", 3)
  ctz-def-inversion("cli", "c1", "O", 3)
  ctz-def-inversion("c2i", "c2", "O", 3)

  ctz-draw(circle-r: (_pt("O"), 3), stroke: black + 1pt)

  ctz-draw("l1", stroke: gray + 0.7pt)
  ctz-draw("c1", stroke: gray + 0.7pt)
  ctz-draw("c2", stroke: gray + 0.7pt)

  ctz-draw("lli", stroke: blue + 1.1pt)
  ctz-draw("cli", stroke: red + 1.1pt)
  ctz-draw("c2i", stroke: green.darken(20%) + 1.1pt)

  ctz-draw(points: ("O"), labels: (O: "below left"))
})
```

Inversion Packing



```
#ctz-canvas({
  import ctz.draw: *
  ctz-init()

  let n = 24

  // Inversion circle setup
  ctz-def-points(0: (-4.5, 0))
  ctz-def-line("l1", (-1, 0), (-1, 1))
  ctz-def-line("l2", (1, 0), (1, 1))


  ctz-def-inversion("l1i", "l1", "0", 1)
  ctz-def-inversion("l2i", "l2", "0", 1)

  // Draw inverted lines (outer boundary)
  ctz-draw("l1i", stroke: black + 0.5pt)
  ctz-draw("l2i", stroke: black + 0.5pt)

  // Invert a stack of circles to create the packing
  for i in range(-n, n + 1) {
    let name = "c" + str(i)
    let invname = "ci" + str(i)
    ctz-def-circle(name, (0, 2 * i), radius: 1)
    ctz-def-inversion(invname, name, "0", 1)

    ctz-draw(invname, fill: yellow, stroke: red + 0.4pt)
  }
})
```

Inversion Ladder



```
#ctz-canvas({
  import cetz.draw: *
  ctz-init()

  let 0 = (-4, 0)
  let R = 3
  let n = 6

  ctz-def-line("l1", (-1, 0), (-1, 1))
  ctz-def-line("l2", (1, 0), (1, 1))
  ctz-def-inversion("l1i", "l1", 0, R)
  ctz-def-inversion("l2i", "l2", 0, R)

  ctz-set-clip(-2, -2, 4, 8)

  ctz-draw-line-global-clip((-1, 0), (-1, 1), add: (10, 10), stroke: blue + 0.4pt)
  ctz-draw-line-global-clip((1, 0), (1, 1), add: (10, 10), stroke: green + 0.4pt)
  ctz-draw("l1i", stroke: blue + 0.4pt)
  ctz-draw("l2i", stroke: green + 0.4pt)

  for i in range(0, n + 1) {
    let cname = "C" + str(i)
    let cpname = "Cp" + str(i)
    ctz-def-circle(cname, (0, 2 * i), radius: 1)
    ctz-def-inversion(cpname, cname, 0, R)
    ctz-draw(cpname, stroke: red + 0.4pt)

    if calc.abs(i) < 4 {
      ctz-draw(cname, stroke: red + 0.4pt)

      ctz-def-points(P1: (1, 2 * i), P2: (-1, 2 * i))
      ctz-def-inversion("P1i", "P1", 0, R)
      ctz-def-inversion("P2i", "P2", 0, R)

      ctz-draw(segment: ("P1", "P1i"), stroke: green + 0.4pt)
      ctz-draw(segment: ("P2", "P2i"), stroke: blue + 0.4pt)
    }
  }
})
```