Orchid Manual

Orchid is a small tool to display ORCID iDs in Typst. Mainly inspired by LaTeX's `orcidlink` package.

The main function, `orchid.orcid`, only produces the iD itself. To combine it with a name, write them next to each other (`[Josiah Carberry #orchid.orcid(my-id)]`).

Options

Combine the icon, display, and link options to choose what appears. At least one of the icon or identifier text must be visible. Use `linked: "text"` only when identifier text is visible.

Option	Values	Description
`icon`	`"before"` (default), `"after"`, `none`	Position of the ORCID iD icon, or no icon.
`display`	`"url"` (default), `"id"`, `none`	Text shown: the full `https://orcid.org/...` URL, the bare iD, or nothing.
`linked`	`"all"` (default), `"text"`, `none`	What is a hyperlink: icon and text, only the text, or nothing.
`gap`	length, default `0.25em`	Space between icon and text.
`size`	length, default `1em`	Size of the icon.
`logo`	content, default `none`	Replaces the default icon.
`alt`	string, default `"ORCID iD"`	Alternative text of the default icon.

List of Examples

Example 1 Default without the name . . . 2
Example 2 Default with the name . . . 2
Example 3 Icon only . . . 2
Example 4 Bare iD with icon . . . 2
Example 5 Bare iD with icon after . . . 2
Example 6 No icon . . . 3
Example 7 No icon, iD only . . . 3
Example 8 Link only the text . . . 3
Example 9 No link . . . 3
Example 10 Link to the ORCID profile . . . 3
Example 11 Custom icon . . . 3

Accessibility

The default icon has alternative text (`alt`), so documents built with `--pdf-standard ua-1` compile. If you pass your own `logo` image, give it an `alt` too.

Validation

The iD is validated in two steps. The format must be `0000-0000-0000-000X`, and the last character must be a valid ISO 7064 mod 11-2 check digit. A mistyped iD that still looks valid fails at compile time. A full `https://orcid.org/...` URL is also accepted as input, and surrounding whitespace and a lowercase `x` are normalized.

These checks validate the identifier's format and checksum. Record existence and ownership require separate verification.

Examples

The default shows the icon and full URL as one link, following ORCID's full iD format. Consult the ORCID iD display guidelines for displaying unauthenticated iDs.

Example 1: Default without the name

```typst
#orchid.orcid(my-id)
```

https://orcid.org/0000-0002-1825-0097

Example 2: Default with the name

```typst
Josiah Carberry #orchid.orcid(my-id)
```

Josiah Carberry https://orcid.org/0000-0002-1825-0097

Example 3: Icon only

```typst
#orchid.orcid(my-id, display: none)
```

Example 4: Bare iD with icon

```typst
#orchid.orcid(my-id, display: "id")
```

0000-0002-1825-0097

Example 5: Bare iD with icon after

```typst
#orchid.orcid(my-id, display: "id", icon: "after")
```

0000-0002-1825-0097

Example 6: No icon

```typst
#orchid.orcid(my-id, icon: none)
```

https://orcid.org/0000-0002-1825-0097

Example 7: No icon, iD only

```typst
#orchid.orcid(my-id, icon: none, display: "id")
```

0000-0002-1825-0097

Controlling the link

By default the icon and the text form a single link. You can link only the text, or not link at all.

Example 8: Link only the text

```typst
#orchid.orcid(my-id, linked: "text")
```

https://orcid.org/0000-0002-1825-0097

Example 9: No link

```typst
#orchid.orcid(my-id, linked: none)
```

https://orcid.org/0000-0002-1825-0097

Getting only the URL

If you need the URL as a string, for example for your own link text:

Example 10: Link to the ORCID profile

```typst
#link(orchid.orcid-url(my-id))[My ORCID profile]
```

My ORCID profile

Customizing the icon

Pass any content to `logo` to replace the default icon. It is wrapped in the same sized box, so `size` and `icon` still apply.

Example 11: Custom icon

```typst
#orchid.orcid(my-id, logo: emoji.id)
```

https://orcid.org/0000-0002-1825-0097