1. Introduction

exp-resume is a small Typst package for writing an ATS-friendly resume. It configures a clean one-page layout, a name and contact row, and a set of components for the common resume sections. Personal documents should be kept outside the repository and import either the published package or the local clone.

2. Installation

Publish the package to the Typst package repository, then create a new document from the template:

```
typst init @preview/#pkg:#version
```

During development a sibling document can import the implementation from a local clone:

```
#import "exp-resume-template/src/lib.typ": *
```

3. Quick Start

The document starts with `#show: resume.with(...)`, which applies the global rules and renders the name and contact row. The rest of the document is the body:

```
#import "@preview/#pkg:#version": *

#show: resume.with(
  author: "John Doe",
  email: "john.doe@example.com",
  accent-color: "#26428b",
)

== Experience

#employer(
  company: "Example Corporation",
  location: "Example City, EX",
)[
  #role(
    title: "Software Engineer",
    dates: dates-helper(start-date: "Jun 2024", end-date: "Present"),
  )
  - Replace this placeholder with an accomplishment.
]

== Skills

#skills(
  category: "Languages",
  items: "Python, Go, TypeScript, SQL, Bash",
)
```

Lines that start with `==` are formatted into small-caps section headings with a rule underneath.

4. Resume Configuration

The `resume` function accepts the following parameters:

Parameter	Description
author	Your name, shown as a level-one heading

location	City and country or region, shown in the contact row
email	Email address, linked with `mailto:`
email-text	Optional display text for the email link
github	GitHub handle, linked with `https://`
github-text	Optional display text for the GitHub link
linkedin	LinkedIn handle, linked with `https://`
linkedin-text	Optional display text for the LinkedIn link
phone	Phone number, linked with `tel:`
personal-site	Personal site, linked with `https://`
personal-site-text	Optional display text for the personal site link
accent-color	Color for headings and links, defaults to black
font	Body font, defaults to “New Computer Modern”
paper	Page paper, defaults to “us-letter”
font-size	Body font size, defaults to 10pt
author-font-size	Name size, defaults to 20pt
lang	Document language, defaults to “en”
pronouns	Optional pronouns, shown in the contact row
author-position	Alignment of the name, defaults to left
personal-info-position	Alignment of the contact row, defaults to left
section-content-inset	Body indent under section titles, defaults to 2pt
spacing	Optional spacing overrides; see Spacing below

Parameters that are optional can be omitted or set to `""`. The template contains commented example values.

5. Spacing

`default-spacing` is exported from the package and used when `spacing` is omitted. It is a soft recommendation: examples leave it unset. Pass a partial dictionary to override keys:

```
#import "@preview/#pkg:#version": *

#show: resume.with(
  author: "John Doe",
  spacing: (gap: 0.85em, row: 0.65em),
)
```

Or merge with the exported defaults:

```
#show: resume.with(
  author: "John Doe",
  spacing: default-spacing + (leading: 0.5em),
)
```

Key	Role
`leading`	Paragraph leading (line rhythm inside a paragraph)

`gap`	Paragraph spacing and space above entry headers
`row`	Certificate/skill row spacing, and space under an entry title before its first bullet
`after-header`	Space under the contact row
`after-section-title`	Space between the section title and its rule
`after-section-rule`	Space between the section rule and body
`rule-stroke`	Stroke for section rules
`link-offset`	Underline offset under links

6. Section Components

Each component is placed directly below a `== Section` heading. Bold and italic emphasis inside the argument strings is preserved.

6.1. Summary

`summary` renders a justified paragraph below a heading:

```
== Summary

#summary[Backend engineer experienced in scaling distributed services.]
```

6.2. Education

```
#edu(
  institution: "Example University",
  location: "Example City, EX",
  dates: dates-helper(start-date: "Aug 2020", end-date: "May 2024"),
  degree: "Bachelor of Science, Computer Science",
)
```

The institution and location sit on the first line. The degree and dates sit on the second. Both lines use the body size.

6.3. Experience

`employer` is the same two-line header as a single job. The company is bold on the left and the location is italic on the right. The title is regular on the left and the dates are on the right. A later role repeats that title line, with the same `gap` above it as any other entry header.

```
#employer(
  company: "Example Corporation",
  location: "Remote",
)[
  #role(
    title: "Senior Software Engineer",
    dates: dates-helper(start-date: "Jun 2024", end-date: "Present"),
  )
  - Built reliable services and shipped measurable improvements.

  #role(
    title: "Software Engineer",
    dates: dates-helper(start-date: "Jun 2022", end-date: "May 2024"),
  )
  - Shipped the first version of the service.
]
```

6.4. Projects

```
#project(
  name: "Example Project",
  technologies: "Python, FastAPI, Redis",
  links: (
    (url: "github.com/johndoe/example-project", text: "Github"),
    (url: "example.com", text: "Live"),
  ),
)
```

Pass multiple `links` as `(url, text)` dictionaries. They are joined with • and shown on the right.

6.5. Certificates

One row per call. Consecutive rows share the `row` spacing token.

```
#certificates(
  name: "Example Certification",
  issuer: "Example Institute",
  url: "example.com/cert",
  url-text: "Certificate",
  date: "Jun 2024",
)
```

6.6. Skills

One row per call, same spacing path as certificates:

```
#skills(
  category: "Languages",
  items: "Python, Go, TypeScript, SQL, Bash",
)
```

6.7. Extracurricular Activities

```
#extracurriculars(
  activity: "Example Open Source Group",
  dates: dates-helper(start-date: "Jan 2022", end-date: "Present"),
)
```

7. Generic Helpers

These helpers provide layout without section-specific formatting and can be used to build custom entries.

7.1. dates-helper

Formats a start and end date with an em dash. Pass only an end date to omit the dash:

```
#dates-helper(start-date: "Jun 2024", end-date: "Present")
```

7.2. linked-text

Renders `value` as a hyperlink when a `link-prefix` is given, optionally using `text` as the visible label:

```
#linked-text("example.com", link-prefix: "https://")
```

7.3. generic-one-by-two

Places `left` and `right` on one line, with `right` pushed to the right edge. By default uses `gap` above and `row` below. Pass `spacing: <length>` to set both sides explicitly.

```
#generic-one-by-two(left: "Title", right: "Date")
```

7.4. generic-two-by-two

Places two pairs on two lines, with each right-hand cell pushed to the right edge. Both rows use the body size. Same default above/below behavior as `generic-one-by-two`.

```
#generic-two-by-two(
  top-left: "Title",
  top-right: "Date",
  bottom-left: "Company",
  bottom-right: "Location",
)
```