na-corexamen

Marking schemes (corrections) of exams and assignments for Typst — Arabic and Latin

version 0.1.0

Table of contents

1 Introduction . . . 2
- 1.1 The idea . . . 2
- 1.2 What the package does for you . . . 2

2 Quick start . . . 2
- 2.1 Import and header . . . 2
- 2.2 Exercises and summary . . . 2

3 How it works . . . 3
- 3.1 Reading and cutting the text . . . 3
- 3.2 Sub-titles and parts . . . 3
- 3.3 The three rules . . . 3

4 Functions . . . 4
- 4.1 Template and exercise . . . 4
- 4.2 Marks and sub-titles . . . 4
- 4.3 Helpers . . . 4

5 Automatic checks . . . 4
- 5.1 Checking an exercise . . . 4
- 5.2 Checking the summary table . . . 4

6 Options of `correction` . . . 5
- 6.1 Header and barcode . . . 5
- 6.2 Appearance and tables . . . 6
- 6.3 Fixed labels . . . 7
- 6.4 Language and fonts . . . 7

7 Languages . . . 7
- 7.1 Choosing the language . . . 7
- 7.2 What the language changes . . . 7

8 Files . . . 8

9 License . . . 8

1 Introduction

1.1 The idea

`na-corexamen` is the companion of `na-examen`. It draws the **same header** (barcode, text under it, school, school year, level, term, subject, duration) and the same footer "page X of Y", with the title « Corrigé / Marking scheme / تصحيح … ». All the exercises are drawn in **one continuous table** with two columns, **Solution** and **Marks**, which can break across pages (the header row is repeated at the top of each page). Each exercise is a full-width title row, then the solution rows, then a « Total » row; the next exercise starts right below, in the same table, with no gap.

1.2 What the package does for you

You write the solution **freely**: ordinary text and equations, with no brackets or cell syntax around each question. You only put the marks with `#mk(...)` at the end of each step. The package cuts your text at every `#mk`, puts each piece in a row of the table with its mark in front of it, and adds everything up:

- a « Total » row closes each exercise inside the table;
- the heading of the exercise takes the total too (« Exercise 1 (08 points) »);
- an optional summary table adds up all the exercises (« 20 / 20 »).

2 Quick start

2.1 Import and header

```
#import "@preview/na-corexamen:0.1.0": *

#show: correction.with(
  school: "ثانوية فلان الفلاني",
  year: "2026-2027",
  level: "أولى جذع مشترك علوم وتكنولوجيا",
  term: "الفصل الأول",
  subject: "الرياضيات",
  duration: "2 سا",
  code: "tashih-fard-1",          // text under the barcode
)
```

2.2 Exercises and summary

```
#exercise[
  #section[I.]                    // sub-title row (optional)

  #q[1] Write the solution freely, with equations $x = 3$ #mk(0.5)

  #q[2] Another step of the solution
  $ f(x) = x^2 + 1 $ #mk(1)

  A step worth two marks in two parts #mk(1, 1)
]
```

```
#exercise[
  #part[ #q[1] ... #mk(1) ]       // « Part A (01 point) »
  #part[ #q[1] ... #mk(2) ]       // « Part B (02 points) »
]

#summary(total: 20)               // recap table and grand total
```

3 How it works

3.1 Reading and cutting the text

Inside `#exercise[ ... ]` the text is read from top to bottom:

- everything written **before** a `#mk(...)` (since the previous one) becomes one row of the table, and the value of the mark goes in the Marks column of the same row;
- `#mk(1, 0.5)` adds the numbers (here 1.5) and shows only the sum;
- numbers like `0.25`, `0.5`, `1.5` are fine; the display is cleaned (`2` not `2.0`, `0.3` not `0.30000000000000004`);
- text after the last `#mk` (a remark such as "any other correct method is accepted") becomes a last row without marks.

3.2 Sub-titles and parts

- `#section[I.]` makes a full-width sub-title row;
- `#part[ ... ]` groups rows under a sub-title « Part A (03 points) » whose points are the sum of its own marks; parts are renumbered in each exercise.

Equations (inline `$ ... $` or display `$ ... $` with spaces) and paragraphs are all allowed inside a row.

3.3 The three rules

Three rules

1. Write `#exercise` at the top level of the document (not inside another command);
2. write `#mk`, `#section` and `#part` directly in the body of the exercise (not inside another command such as `#align[...]` or `#strong[...]`);
3. do not put `#set` or `#show` rules inside the body of an exercise or after `#show: correction` (put them before it).

Consecutive exercises are merged into one table; any other content between them (text or `#summary`) closes the table and a new one starts after it.

4 Functions

4.1 Template and exercise

Function	Description
`correction`	the template: `#show: correction.with(...)`. Page, header, footer and information block.
`exercise(points:, title:, gap:)[...]`	an exercise: title row « Exercise 1 (08 points) » (points from the marks), the solution rows and the « Total » row, all inside the single table. `gap` is kept for compatibility and has no effect.

4.2 Marks and sub-titles

Function	Description
`mk(..marks)`	a mark, written at the end of a step: `#mk(0.5)`, `#mk(0.5, 0.5)`.
`section[...]`	a full-width sub-title row inside the table.
`part(title:)[...]`	a part inside an exercise (« Part A (02 points) »); points = sum of its marks.

4.3 Helpers

Function	Description
`q[1]`	boxed question number (`coB` is the same function).
`summary(total:, title:, gap:)`	recap table: one row per exercise and the grand total.
`title-style[...]`	bold underlined title.

5 Automatic checks

5.1 Checking an exercise

`exercise(points: 8)`: if the sum of the marks is not 8, a red `⚠ stated: 8` appears in the « Total » row. Without `points`, the heading simply shows the computed sum.

5.2 Checking the summary table

`summary(total: 20)`: the last cell shows `20 / 20` when the exercises add up to exactly 20; if they do not, it shows the computed sum with a red `⚠ stated: 20`. Without `total`, it just shows the grand total.

6 Options of `correction`

6.1 Header and barcode

Option	Default	
`school`, `year`, `level`, `term`	from the language	header information
`kind`	`"فروض"` (Arabic)	word before the term; `none` removes it
`term-label`	`auto`	the whole term text, instead of `kind` + `term`
`exam`, `subject`	from the language	type of exam and subject
`title`	`auto`	the whole title line, instead of the auto-

Option	Default	
		matic « Corrigé de … »
`duration`	from the language	duration; `none` removes it
`code`	`"na-corexamen"`	text under the barcode; `none` removes it
`barcode`, `barcode-type`, `barcode-data`, `barcode-height`, `barcode-width`, `barcode-cut`	`true`, `"Code128"`, `auto`, `0.64cm`, `5cm`, `0.25`	the barcode (same as `na-examen`)

6.2 Appearance and tables

Option	Default	Meaning
`decimal`	`"."`	decimal separator of all marks
`head-fill`, `sub-fill`	`luma(215)`, `luma(238)`	colors of the header row, the sub-title rows and the « Total » row
`table-stroke`, `table-inset`, `mark-width`	`0.6pt + black`, `7pt`, `2.4cm`	lines, padding and width of the Marks column
`pad-points`	`true`	`8` gives `08`
`paper`, `margin`	`"a4"`, as in `na-examen`	page

6.3 Fixed labels

Option	Default	Meaning
`ex-label`, `ans-label`, `mark-label`, `total-label`, `summary-label`	from the language	fixed words of the tables
`year-label`, `level-label`, `duration-label`, `page-label`, `of-label`	from the language	fixed words of the header and footer

6.4 Language and fonts

Option	Default	Meaning
`lang`	`"ar"`	`"ar"`, `"fr"`, `"en"`, `"es"`, `"de"`
`font`, `title-font`, `size`	from the language	fonts and size

7 Languages

7.1 Choosing the language

`lang: "ar"` (default, right-to-left) or `lang: "fr"`, `"en"`, `"es"`, `"de"` (left-to-right). Shortcuts: `correction-fr`, `correction-en`, `correction-latin`. Every option left at `auto` is taken from the language.

7.2 What the language changes

Language	Title	Exercise	Total
`ar`	تصحيح الفرض المحروس في مادة ...	التمرين الأول (08 نقاط)	المجموع
`fr`	Corrigé — Devoir surveillé de ...	Exercice 1 (08 points)	Total
`en`	... Test — Marking scheme	Exercise 1 (08 points)	Total
`es`	Solucionario — Examen de ...	Ejercicio 1 (08 puntos)	Total
`de`	Lösung — Klassenarbeit in ...	Aufgabe 1 (08 Punkte)	Summe

8 Files

```
lib.typ  typst.toml  LICENSE  README.md
documentationEN.typ  documentationAR.typ     (compile them to get the PDFs)
examples/   basic.typ  latin-fr.typ  latin-en.typ
```

9 License

MIT.