

Manual

- `new()`
- `group()`
- `questions()`
- `solutions()`
- `formatting()`
- `show-ref()`

new

Create a new exercise environment.

Returns the function to be used when creating instances of this environment. If two arguments are provided when called, then the first is the question and the second the solution. If three arguments are provided, then the first is the title, the second the question, and the third the solution.

Parameters

```
new(  
  identifier: str,  
  supplement: none | content | function ,  
  numbering: none | str | function ,  
  group: none | function  
) -> function
```

identifier `str`

A unique key for the environment.

supplement `none` or `content` or `function`

The environment's supplement.

If a function is specified, it is passed the environment's body and should return content.

Default: `none`

numbering `none` or `str` or `function`

How to number the environment. Accepts a [numbering pattern or function](#).

Default: `"1"`

group `none` or `function`

Whether to further separate instances of this environment into groups based on its location in the document.

See `group()` for more information.

Default: `none`

group

Type signature of the function expected in `new.group`.

Parameters

```
group(location: location) -> str
```

questions

Display all the collected questions with the given formatting.

Requires `context`.

Parameters

```
questions(  
    identifier: str,  
    formatting: function,  
    group: none or str  
) -> content
```

identifier `str`

Key of the environment to use.

formatting `function`

How to format each question.

See `formatting()` for more information.

group `none` or `str`

If `new.group` was specified when creating the environment, then a specific instance of the value returned by `new.group` must be given.

Default: `none`

solutions

Display all the collected solutions with the given formatting.

Requires `context`.

Parameters

```
solutions(  
    identifier: str,  
    formatting: function,  
    group: none or str  
) -> content
```

identifier `str`

Key of the environment to use.

formatting `function`

How to format each solution.

See `formatting()` for more information.

group `none` or `str`

If `new.group` was specified when creating the environment, then a specific instance of the value returned by `new.group` must be given.

Default: `none`

formatting

Type signature of the function expected in `questions.formatting` and `solutions.formatting`.

Parameters

```
formatting(  
  body: content ,  
  supplement: none content ,  
  number: none content ,  
  title: none content ,  
  opposite: label  
) -> content
```

opposite `label`

Label pointing to the accompanying solution (question) of the current question (solution).

show-ref

Show rule to enable correct references to questions.

Should be applied with `#show ref: show-ref` at the start of the document.

Parameters

```
show-ref(it: ref) -> ref
```