1. Introduction

exp-resume is a small Typst package for writing an ATS-friendly resume. It configures a clean one-page layout, a name and contact row, and a set of components for the common resume sections. Personal documents should be kept outside the repository and import either the published package or the local clone.

2. Installation

Publish the package to the Typst package repository, then create a new document from the template:

```
typst init @preview/#pkg:#version
```

During development a sibling document can import the implementation from a local clone:

```
#import "exp-resume-template/src/lib.typ": *
```

3. Quick Start

The document starts with `#show: resume.with(...)`, which applies the global rules and renders the name and contact row. The rest of the document is the body:

```
#import "@preview/#pkg:#version": *

#show: resume.with(
  person: (
    name: "John Doe",
    email: "john.doe@example.com",
  ),
  page: (accent-color: "#26428b"),
)

== Experience

#employer(
  company: "Example Corporation",
  location: "Example City, EX",
)[
  #role(
    title: "Software Engineer",
    dates: dates-helper(start-date: "Jun 2024", end-date: "Present"),
  )
  - Replace this placeholder with an accomplishment.
]

== Skills

#skills(
  category: "Languages",
  items: "Python, Go, TypeScript, SQL, Bash",
)
```

Lines that start with == are formatted into small-caps section headings with a rule underneath.

4. Resume Configuration

Defaults live in `config.typ` as four dictionaries: `default-person`, `default-placement`, `default-page`, and `default-spacing`. Pass a partial dictionary to override one group:

```
#show: resume.with(
  person: (
    name: "John Doe",
    email: "john.doe@example.com",
  ),
  placement: (name: center, contact: center),
  page: (accent-color: "#26428b"),
  spacing: (block-spacing: 0.85em),
)
```

Empty person fields are skipped. The template shows the full set.

4.1. Person

Key	Role
`name`	Shown as the title and stored as the document author
`pronouns`	Contact row
`location`	Contact row
`phone`	Contact row, linked with `tel:` and not underlined
`email`	Contact row, linked with `mailto:`
`email-text`	Optional display text for the email link
`github`	Contact row, linked with `https://`
`github-text`	Optional display text for the GitHub link
`linkedin`	Contact row, linked with `https://`
`linkedin-text`	Optional display text for the LinkedIn link
`personal-site`	Contact row, linked with `https://`
`personal-site-text`	Optional display text for the personal site link

4.2. Placement

Key	Role
`name`	Alignment of the name. Default: left
`contact`	Alignment of the contact row. Default: left

4.3. Page

Key	Role
`font`	Body font. Default: “New Computer Modern”
`font-size`	Body size. Default: 10pt
`name-size`	Name size. Default: 20pt
`accent-color`	Headings and links. Default: `"#000000"`
`paper`	Page paper. Default: `"us-letter"`
`margin`	Space between the page edge and the content. Default: 0.5in
`lang`	Document language. Default: `"en"`

4.4. Spacing

Key	Role
`line-spacing`	Space between lines inside a paragraph. Default: 0.5em
`block-spacing`	Space between paragraphs and above an entry header. Default: 0.85em
`item-spacing`	Space under an entry title before its bullets, and between certificate and skill rows. Default: 0.75em
`after-header`	Space under the name and contact. Default: 0.25em
`section-rule`	Line under a section title. Default: `0.5pt`

5. Section Components

Each component is placed directly below a `== Section` heading. Pass Typst content to style a field: `title: emph[Engineer]` is italic, and a quoted string is printed as written. School, company, project name, certificate name, skill category, and activity are already bold, so `emph` on those is bold italic. Link addresses stay plain strings. `dates-helper` joins strings, so wrap its result, as in `dates: emph(dates-helper(...))`. Bullets and the summary take normal Typst markup.

5.1. Summary

A paragraph under the heading. It uses the same justified body text as the rest of the resume.

```
== Summary

Backend engineer experienced in scaling distributed services.
```

5.2. Education

```
#edu(
  institution: "Example University",
  location: "Example City, EX",
  dates: dates-helper(start-date: "Aug 2020", end-date: "May 2024"),
  degree: "Bachelor of Science, Computer Science",
)
```

The institution and location sit on the first line. The degree and dates sit on the second. The institution is bold. The location, degree, and dates are regular.

5.3. Experience

`employer` is the same two-line header as a single job. The company is bold on the left and the location is regular on the right. The title and the dates are regular. A later role repeats that title line, with the same `block-spacing` above it as any other entry header.

```
#employer(
  company: "Example Corporation",
  location: "Remote",
)[
  #role(
    title: "Senior Software Engineer",
    dates: dates-helper(start-date: "Jun 2024", end-date: "Present"),
  )
  - Built reliable services and shipped measurable improvements.

  #role(
    title: "Software Engineer",
    dates: dates-helper(start-date: "Jun 2022", end-date: "May 2024"),
```

```
  )
  - Shipped the first version of the service.
]
```

5.4. Projects

```
#project(
  name: "Example Project",
  technologies: "Python, FastAPI, Redis",
  links: (
    (url: "github.com/johndoe/example-project", text: "Github"),
    (url: "example.com", text: "Live"),
  ),
)
```

Pass multiple `links` as `(url, text)` dictionaries. They are joined with • and shown on the right.

5.5. Certificates

One row per call. Consecutive rows share the `item-spacing` length.

```
#certificates(
  name: "Example Certification",
  issuer: "Example Institute",
  url: "example.com/cert",
  url-text: "Certificate",
  date: "Jun 2024",
)
```

5.6. Skills

One row per call, same spacing path as certificates:

```
#skills(
  category: "Languages",
  items: "Python, Go, TypeScript, SQL, Bash",
)
```

5.7. Extracurricular Activities

```
#extracurriculars(
  activity: "Example Open Source Group",
  dates: dates-helper(start-date: "Jan 2022", end-date: "Present"),
)
```

6. Generic Helpers

These helpers provide layout without section-specific formatting and can be used to build custom entries.

6.1. dates-helper

Formats a start and end date with an en dash. Pass only an end date to omit the dash:

```
#dates-helper(start-date: "Jun 2024", end-date: "Present")
```

6.2. linked-text

Renders `value` as a hyperlink when a `link-prefix` is given, optionally using `text` as the visible label:

```
#linked-text("example.com", link-prefix: "https://")
```

6.3. generic-one-by-two

Places `left` and `right` on one line, with `right` pushed to the right edge. By default uses `block-spacing` above and `item-spacing` below. Pass `spacing: <length>` to set both sides explicitly.

```
#generic-one-by-two(left: "Title", right: "Date")
```

6.4. generic-two-by-two

Places two pairs on two lines, with each right-hand cell pushed to the right edge. Both rows use the body size. Same default above/below behavior as `generic-one-by-two`.

```
#generic-two-by-two(
  top-left: "Title",
  top-right: "Date",
  bottom-left: "Company",
  bottom-right: "Location",
)
```