dati-basati documentation

Contents

dati-basati 1
- dati-basati 1
- er-diagram 2
- entity 3
- subentities 4
- relation 5

attributes 6
- _draw-attributes 6
- _draw-composite-attribute 8

weak-entity 9
- _weak-entity-path 9
- get-angles 10
- _draw-we-path 10

custom-marks 11
- filled-circle-pk 11
- filled-circle-mpk 11
- filled-circle-wk 11
- empty-circle 12
- subentity-mark 12
- righetta 12

utils 12
- find-side 12
- get-idx 12
- get-next-cardinal 13
- get-prev-cardinal 13
- get-opp-cardinal 13
- get-aligned-coordinate 13
- update-dict 14
- get-rel-position 14
- get-rel-position-diagonal 14
- get-rel-subentity 15
- add-intersect-anchor 15
- draw-anchors 15
- get-diagonal-side 15

cardinality 15
- _draw-cardinality-box 15

entity 16
- _draw-entity-box 16

dati-basati

dati-basati

Default global settings.

Parameters

```
dati-basati(
  fill: dictionary,
  stroke: dictionary,
  radius: dictionary,
  spacing: dictionary,
  text: dictionary,
  attributes-position: dictionary,
  misc: dictionary,
  body
) -> dictionary
```

fill `dictionary`

The fill of each element.

Default: `(:)`

stroke `dictionary`

The stroke of each element.

Default: `(:)`

radius `dictionary`

The radius of entities, cardinality and hierarchy.

Default: `(:)`

spacing `dictionary`

The spacing of attributes.

Default: `(:)`

text `dictionary`

Text formatting of each element.

Default: `(:)`

attributes-position `dictionary`

The position and direction of attributes.

Default: `(:)`

misc `dictionary`

Miscellanous options.

Default: `(:)`

er-diagram

Draw an Entity-Relation Diagram. This is the function that wraps all the diagrams.

Parameters

```
er-diagram(
  theme: dictionary,
  ..args: dictionary,
  body: content
) -> content
```

theme `dictionary`

The theme of this diagram.

Default: `(:)`

..args `dictionary`

Arguments directly passed to `#cetz.canvas()`.

body `content`

Body of the diagram.

entity

Draw an entity.

Parameters

```
entity(
  coordinates: array,
  name: str,
  label: str content,
  attributes: dictionary,
  attributes-position: dictionary,
  primary-key: str array,
  weak-entity: array,
  misc: dictionary,
  ..args: args
) -> content
```

coordinates `array`

Coordinates of the entity.

name `str`

Unique name of the entity.

Default: `""`

label `str` or `content`

Label for the entity (e.g. Person, Book, Employee...).

Default: `"Entity"`

attributes `dictionary`

Attributes of the entity (e.g. id, name, surname, address...).

Default: `()`

attributes-position `dictionary`

Fine tune positioning of attributes.

Default: `(:)`

primary-key `str` or `array`

Primary key(s).

Default: `none`

weak-entity `array`

Whether this entity is weak and the corresponding attribute. The format is as follows:
- SQL mirror: `(attribute, strong entity, direction)`
- With cardinal points: `(cardinal pt, cardinal pt, direction)`

They can be mixed.

Default: `none`

misc `dictionary`

Miscellanous options:
- weak-entity-intersection

Default: `none`

..args `args`

Arguments passed to `#std.rect()`.

subentities

Connect subentities to the superentity.

Parameters

```
subentities(
  hierarchy: "(t,e)" "(p,e)" "(p,o)",
  entity: str,
  subentities: array
) -> content
```

hierarchy `"(t,e)"` or `"(p,e)"` or `"(p,o)"`

The hierarchy of the subentities:
- (t,e) = (total, exclusive)
- (p,e) = (partial, exclusive)
- (p,o) = (partial, overlapping)

Default: `"(t,e)"`

entity `str`

The superentity, the one to which the subentities will connect.

Default: `""`

subentities `array`

The subentities. Can be just one.

Default: `("",)`

relation

Draw a relation between (sub)entities.

Parameters

```
relation(
  coordinates: array,
  entities: array,
  name: str,
  label: str,
  attributes: dictionary,
  cardinality: array
) -> content
```

coordinates `array`

The specific coordinates of this relation. If left empty, they will the middle point between the two entities.

Default: `none`

entities `array`

Entities that are tied by this relation.

Default: `()`

name `str`

Unique name of relation.

Default: `""`

label `str`

Label for the relation (e.g. “occupies”, “relates”, “is part of”…).

Default: `""`

attributes `dictionary`

Attributes of the relation (e.g. id, name, surname, address…).

Default: `(:)`

cardinality `array`

Cardinality of the given relation:

Default: `()`

attributes

_draw-attributes

Draw the attributes on a specified side of the entity.

Parameters

```
_draw-attributes(
  start-coordinate: array,
  entity: str,
  position: "north" "east" "south" "west",
  attributes: array,
  primary-key: str,
  dir: "ltr" "rtl",
  drawing-mode: "from-short" "from-long",
  in-between: dictionary,
  padding: length,
  label-anchor: auto "north" "east" "south" "west",
  centered: bool,
  attr-stroke: auto str
) -> content
```

start-coordinate `array`

Starting coordinate from which the attributes will be actually drawn.

entity `str`

Unique name of the entity.

Default: `"bella"`

position `"north"` or `"east"` or `"south"` or `"west"`

Position of where the attributes will be drawn.

Default: `"north"`

attributes `array`

All attributes of the entity.

Default: `none`

primary-key `str`

A single primary key.

Default: `none`

dir `"ltr"` or `"rtl"`

Direction in which the attributes will be drawn. Can be either `ltr`, left to right, or `rtl`, right to left.

Default: `"ltr"`

drawing-mode `"from-short"` or `"from-long"`

Whether to draw starting from the smallest or longest attribute. Only applies to north, south sides: the others have always the same padding.

Default: `"from-short"`

in-between `dictionary`

Spacing in-between attributes.

Default: `(x: 1.2em, y: 1.2em)`

padding `length`

Padding from the entity. Note: this CANNOT BE different between x,y because of the weak entity path.

Default: `1.2em`

label-anchor `auto` or `"north"` or `"east"` or `"south"` or `"west"`

Label anchor, the opposite side of there the label will be displayed. It's automatically calculated based on `position` and `dir`.

Default: `auto`

centered `bool`

Whether to align to the center the attributes: they will be drawn as if centered around the `start-coordinate`.

Default: `false`

attr-stroke `auto` or `str`

Attributes stroke.

Default: `auto`

_draw-composite-attribute

Draw a composite attribute on a specified side.

Parameters

```
_draw-composite-attribute(
  coordinates: array,
  attributes: array,
  position: "north" "east" "south" "west",
  dimensions: int float length,
  dimensions-coefficient: int float,
  padding-coefficient: int float,
  in-between: dictionary,
  padding: length
) -> content
```

coordinates `array`

From where the composite attribute will be drawn. Note that it's NOT the ellipse, rather the line LEADING TO THE CENTER of the ellipse.

attributes `array`

The corresponding attributes.

position `"north"` or `"east"` or `"south"` or `"west"`

Side of where the composite attribute will be drawn. Note there will not be drawn any other attributes on this same side.

Default: `"west"`

dimensions `int` or `float` or `length`

Longest radius coefficient.

Default: `0.5`

dimensions-coefficient `int` or `float`

Longest radius coefficient.

Default: `5`

padding-coefficient `int` or `float`

Padding of the starting line (distance from the composite attribute and the entity).

Default: `0.5`

in-between `dictionary`

Spacing in-between attributes. Same dict as *`_draw-attributes()`*.

Default: `(x: 1.2em, y: 1.2em)`

padding `length`

Padding from the ellipse. Same dict as *`_draw-attributes()`*.

Default: `1.5em`

weak-entity

_weak-entity-path

Retrieve the path needed to draw the weak entity.

Parameters

```
_weak-entity-path(
  start: str,
  end: "north" "east" "south" "west",
  dir: "CW" "CCW" "cw" "ccw"
) -> array
```

start `str`

Starting coordinate (key, weak entity).

end `"north"` or `"east"` or `"south"` or `"west"`

Ending side.

dir `"CW"` or `"CCW"` or `"cw"` or `"ccw"`

Direction: can be clockwise or counterclockwise.

Default: `"CW"`

get-angles

Given a weak entity path, return the traversed angles.

Parameters

```
get-angles(path: array) -> array
```

path `array`

Weak entity path.

_draw-we-path

Draw the weak entity path.

Parameters

```
_draw-we-path(
  name: str,
  weak-entity: array,
  attributes: dictionary,
  spacing: length,
  intersection: array
) -> content
```

name `str`

Name of the entity.

weak-entity `array`

Weak entity in the following format: (attribute, end side, direction).

attributes `dictionary`

Entity attributes.

spacing `length`

Distance from the entity to the label(s) of the attributes (`#spacing.padding` dictionary).

intersection `array`

Specific final coordinate.

Default: `none`

custom-marks

filled-circle-pk

Filled circle for the primary keys.

Parameters

```
filled-circle-pk(fill: color) -> content
```

fill `color`

Fill colour.

Default: `black`

filled-circle-mpk

Filled circle for multiple primary keys.

Parameters

```
filled-circle-mpk(fill: color) -> content
```

fill `color`

Fill colour.

Default: `black`

filled-circle-wk

Filled circle for weak entities.

Parameters

```
filled-circle-wk(
  fill: color,
  _wk-mark-length: int float length
) -> content
```

fill `color`

Fill colour.

Default: `black`

_wk-mark-length `int` or `float` or `length`

Custom length based on x,y side.

empty-circle `content`

Empty circle used for attributes.

subentity-mark `content`

Subentity mark, a custom made arrow.

righetta `content`

Custom made “mark”, which is just a cute line.

utils

find-side

Given a value from an array, find its key.

Parameters

```
find-side(
  x,
  dict
) -> content
```

get-idx

Returns the index of `x` in `arr`.

Parameters

```
get-idx(
  x: str,
  arr: arrayay
) -> int
```

x `str`

Element to search

arr `arrayay`

The array from which to search.

Default: `cardinal-points`

get-next-cardinal

Gets the next cardinal point (e.g. “north” -> “east”).

Parameters

```
get-next-cardinal(pt) -> str
```

get-prev-cardinal

Gets the previous cardinal point (e.g. “north” -> “west”).

Parameters

```
get-prev-cardinal(pt) -> str
```

get-opp-cardinal

Gets the opposite cardinal point (e.g. “north” -> “south”).

Parameters

```
get-opp-cardinal(pt) -> str
```

get-aligned-coordinate

Get the corrected coordinates. For instance top-left != north-west, because there is a little horizontal spacing to be added.

Parameters

```
get-aligned-coordinate(
  entity,
  side,
  aligned,
  in-between,
  attributes-len
) -> array
```

update-dict

Update a dictionary.

Parameters

```
update-dict(
  old-dict,
  new-dict,
  are-val-dict: bool
) -> dictionary
```

are-val-dict `bool`

Whether the dictionaries have values that are themselves dictionaries.

Default: `false`

get-rel-position

Return where is **center with respects to other**.

Parameters

```
get-rel-position(
  center,
  other,
  ctx
) -> arrayay
```

get-rel-position-diagonal

Return where is **other with respects to center**, in CW direction.

Parameters

```
get-rel-position-diagonal(
  center,
  other,
  ctx
) -> arrayay
```

get-rel-subentity

Return where **center is with respects to first- and last-sub**.

Parameters

```
get-rel-subentity(
  center,
  subentities,
  ctx
) -> str
```

add-intersect-anchor

Apply `#cetz.draw.hide()` to `path` and add an anchor `intersection.0` which is the intersection between `path` and the line drawn from `line-coord`. Used for unorthodox relation positions.

Parameters

```
add-intersect-anchor(
  path,
  line-coord
) -> content
```

draw-anchors

Draw the diagonal anchors.

Parameters

```
draw-anchors(
  name,
  padding
) -> none
```

get-diagonal-side

Retrieve the side based on diagonal anchors.

Parameters

```
get-diagonal-side(
  coord,
  name,
  ctx
) -> str
```

cardinality

_draw-cardinality-box

Draw a cardinality box.

Parameters

```
_draw-cardinality-box(
  coordinates: array,
  name: str,
  label: str,
  hierarchy: bool,
  ..args: args
) -> content
```

coordinates `array`

Coordinates of the box.

name `str`

Its unique name to be referred as.

Default: `none`

label `str`

Its label (e.g. (0,1)).

Default: `none`

hierarchy `bool`

Whether this box is actually an hierarchy.

Default: `false`

..args `args`

All arguments passed to `#std.box()`.

entity

_draw-entity-box

Draw an entity box.

Parameters

```
_draw-entity-box(
  coordinates: array,
  label: content str,
  name: str,
  has-weak-entity: bool,
  ..args: args
) -> content
```

coordinates `array`

Coordinates.

label `content` or `str`

Label of the box.

name `str`

Unique name of this entity

has-weak-entity `bool`

Whether this entity has weak attributes.

..args `args`

Arguments passed to `#std.rect()`.