SpecSnip

v0.1.0

https://github.com/nineff/specsnip

Nikolai Neff-Sarnow

Abstract

A package to query C-Headers for function- and/or type definition line ranges.

Contents

I SpecSnip 2
- I.a function-linerange 2
- I.b typedef-linerange 2
- I.c query-code 3
- I.d get-tree 3
- I.e contains-identifier 3

I SpecSnip

- function-linerange()
- typedef-linerange()
- query-code()
- get-tree()
- contains-identifier()

I.a function-linerange

Get the range of lines of a C function definition incuding any comments attached immediately above it from the given sourve code by it's name (identifier) If the function is defined multiple times, only the last entry is returned. Lines are counted starting at one. Panics if the code or identifier are not valid and if the identifier is not found in the code

I.a.a Parameters

```
function-linerange(
  code: path str bytes,
  identifier: str bytes
) -> dictionary
```

I.a.a.a code `path` or `str` or `bytes`

The source code to search in. If a path is given, the file at the given path is read as the source code.

I.a.a.b identifier `str` or `bytes`

The function "name" to search for

I.b typedef-linerange

Get the range of lines of a C type definition incuding any comments attached immediately above it from the given sourve code by it's name (identifier) If the type is defined multiple times, only the last entry is returned. Lines are counted starting at one. Panics if the code or identifier are not valid and if the identifier is not found in the code

I.b.a Parameters

```
typedef-linerange(
  code: path str bytes,
  identifier: str bytes
) -> dictionary
```

I.b.a.a code `path` or `str` or `bytes`

The source code to search in. If a path is given, the file at the given path is read as the source code.

I.b.a.b identifier `str` or `bytes`

The type "name" to search for

I.c query-code

Runs an arbitrary Tree-Sitter-Query on the given source code Panics if the query or sourcecode are invalid

I.c.a Parameters

```
query-code(
  code: path str bytes,
  query: str bytes
) -> array dictionary
```

I.c.a.a code `path` or `str` or `bytes`

The source code to be queried. If a path is given, the file at the given path is read as the source code.

I.c.a.b query `str` or `bytes`

The Query to be run against the source code. Must be a valid Tree-Sitter Query according to: https://tree-sitter.github.io/tree-sitter/using-parsers/queries/index.html

I.d get-tree

Returns the complete syntax tree of the provided code. Panics if the code is invalid.

I.d.a Parameters

```
get-tree(code: path str bytes) -> array dictionary
```

I.d.a.a code `path` or `str` or `bytes`

The source code. If a path is given, the file at the given path is read as the source code.

I.e contains-identifier

Checks if the given identifier is contained in the source code (either as function or type definition) Panics if the code or identifier are invalid.

I.e.a Parameters

```
contains-identifier(
  code: path str bytes,
  identifier: str bytes
) -> bool
```

I.e.a.a code `path` or `str` or `bytes`

The source code to search in. If a path is given, the file at the given path is read as the source code.

I.e.a.b identifier `str` or `bytes`

The identifier to serach for