7.css
A design system for building faithful recreations of old UIs.

npm vv00..2211..11 mmiinnzziippppeedd ssiizzee 1199 KKiiBB

Intro

7.css is a CSS framework for building interface components that look like Windows 7. It is built on top of the GUI backbone of XP.css, which is an
extension of 98.css.

This framework relies on the usage of semantic HTML. To make a button, you'll need to use a <button>. Input elements require labels. Tabs rely on

the role="tab" attribute. This page will guide you through that process, but accessibility is a primary goal of this project.

You can override many of the styles of your elements while maintaining the appearance provided by this framework. Need more padding on your

buttons? Go for it. Need to add some color to your input labels? Be our guest.

This framework does not contain any JavaScript, it merely styles your HTML with some CSS. This means 7.css is compatible with your frontend
framework of choice.

Installation / Usage
The fastest way to use 7.css is to import it from unpkg.

<link rel="stylesheet" href="https://unpkg.com/7.css">

You can also install 7.css from npm.

Installation

npm install 7.css

Usage

import "7.css/dist/7.css";

Scoping

In case you need 7.css to coexist with another CSS/styling framework, you may use the 7.scoped.css stylesheet instead to scope the styling within a
win7 class.

unpkg:

https://unpkg.com/7.css/dist/7.scoped.css

or npm:

import "7.css/dist/7.scoped.css"

Then in your code, wrap the component with .win7:

<button>A Win7-styled button</button>

Also note that using the scoped stylesheet will eliminate the scrollbar styling as well.

Tree-shaking

In case you only need the styling of certain components rather than the complete stylesheet as a whole, you may import them separately as below:

unpkg:

https://unpkg.com/7.css/dist/gui/buttons.css
https://unpkg.com/7.css/dist/gui/tabs.css

or npm:

import "7.css/dist/gui/buttons.css"
import "7.css/dist/gui/tabs.css"

For more components, see the published gui folder.

Components

Balloon

A balloon is a small pop-up window that informs users of a non-critical problem or special condition in a control.

— Microsoft Windows User Experience - Balloons

A balloon or tooltip can be created using the role="tooltip" attribute.

A balloon is better known as tooltip in web development.

A control may bind to a balloon with the aria-describedby attribute. You will need to set up an event for the control to trigger the balloon.

Press Enter

<input type="text" placeholder="Press Enter" aria-describedby="balloon-password" />
<div role="tooltip" id="balloon-password" hidden>Press Backspace to dismiss

To change the position of the balloon, which subsequently change the placement of its tail, combine the respective vertical and horizontal classes:

Vertical: .is-top / .is-bottom

Horizontal: .is-left / .is-right

This balloon is positioned bottom right of the source control (default behavior).
This balloon is positioned bottom left of the source control.
This balloon is positioned top left of the source control.
This balloon is positioned top right of the source control.

Button

A command button, also referred to as a push button, is a control that causes the application to perform some action when the user clicks it.

— Microsoft Windows User Experience p. 160

A standard button measures 75px wide and 23px tall with 12px of horizontal padding by default. They are styled with 2 shades of gray as a vertical

gradient.

<button>Click me</button>

When buttons are clicked, the gray gradient is shifted to corresponding sky blues. The following button is simulated to be in the pressed (active) state.

<button>I am being pressed</button>

Disabled buttons have solid background and lighter border.

<button disabled>I cannot be clicked</button>

Button focus is communicated with a dotted border, set 4px within the contents of the button. The following example is simulated to be focused.

<button>I am focused</button>

A default button (in Windows, hitting the Enter key in a dialog context triggers the button) has a greenish-blue border and a light blue gradient shade.

<button class="default">I am the one!</button>

The button styles are also applied to the file input element. Due to the complex setup, the styles of the standard button's states (hover, active, focus

etc.) cannot be applied to the file input button.

No file chosen

<input type="file" />

You can use the below workaround to apply the complete button styles to a file input element. In this setup, the file input is hidden and a label with the

role="button" attribute is used to trigger the file selection dialog. The tabindex="0" attribute ensures the button is keyboard accessible. Some

JavaScript is required if you want the label to trigger when it is focused and activated with the keyboard.

<label role="button" tabindex="0"><input type="file" /> Choose file</label>
<label role="button" tabindex="0" class="default"><input type="file" /> Browse...</label>

CheckBox

A check box represents an independent or non-exclusive choice.

— Microsoft Windows User Experience p. 167

Checkboxes are represented with a sunken panel, populated with a "check" icon when selected, next to a label indicating the choice.

Note: You must include a corresponding label after your checkbox, using the <label> element with a for attribute pointed at the id of your input.

This ensures the checkbox is easy to use with assistive technologies, on top of ensuring a good user experience for all (navigating with the tab key,

being able to click the entire label to select the box).

<input type="checkbox" id="example1">
<label for="example1">This is a checkbox</label>

Checkboxes can be selected and disabled with the standard checked and disabled attributes.

<input checked type="checkbox" id="example2">
<label for="example2">I am checked</label>

<input disabled type="checkbox" id="example3">
<label for="example3">I am inactive</label>

<input checked disabled type="checkbox" id="example4">
<label for="example4">I am inactive but still checked</label>

Collapse

Users can show or hide additional information including data, options, or commands.

— Microsoft Windows User Experience - Progressive Disclosure

A collapsible section can be created using the elements details and summary.

<details>
<summary>Expand me to see something interesting</summary>

🎉 Tadah!

</details>

Add an open attribute to expand the content by default.

This is my family

This is my house

This is my car

<details open>
<summary>I open myself willingly</summary>
<ul>
<li>This is my family</li>
<li>This is my house</li>
<li>This is my car</li>
</ul>
</details>

Combobox

A combo box is a combination of a standard list box or a drop-down list and an editable text box, thus allowing users to enter a value that isn't in the list.

— Microsoft Windows User Experience - Combo Boxes

To render a combo box, use a text input, a button, a parent ul, and children li together, wrapped inside a container element with the

combobox class. For accessibility, follow the minimum requirements as below:

Add a role="combobox" attribute to the text input

Add a role="listbox" attribute to the ul

Add a role="option" attribute to each li

Specify the relationship between the list box and the text box by combining the id of the listbox with the aria-owns attribute on the text input

<input type="text" role="combobox" aria-owns="company" />
<button></button>
<ul role="listbox" id="company">
<li role="option">Facebook</li>
<li role="option">Amazon</li>
<li role="option">Apple</li>
<li role="option">Netflix</li>
<li role="option">Google</li>
</ul>

For more options of the list box, see the ListBox section.

Dropdown

A drop-down list box allows the selection of only a single item from a list. In its closed state, the control displays the current value for the control. The user opens the list to change the value.

— Microsoft Windows User Experience p. 175

Dropdowns can be rendered by using the select and option elements.

<select>
<option>5 - Incredible!</option>
<option>4 - Great!</option>
<option>3 - Pretty good</option>
<option>2 - Not so great</option>
<option>1 - Unfortunate</option>
</select>

By default, the first option will be selected. You can change this by giving one of your option elements the selected attribute.

<select>
<option>5 - Incredible!</option>
<option>4 - Great!</option>
<option selected>3 - Pretty good</option>
<option>2 - Not so great</option>
<option>1 - Unfortunate</option>
</select>

Disabled dropdown.

<select disabled>
<option>0 - Dropdown disabled</option>
</select>

GroupBox

A group box is a special control you can use to organize a set of controls. A group box is a rectangular frame with an optional label that surrounds a set of controls.

— Microsoft Windows User Experience p. 189

A group box can be used by wrapping your elements with the fieldset tag. It contains a sunken outer border and a raised inner border, resembling

an engraved box around your controls.

Select one:

<fieldset>
Select one:

<input id="radio5" type="radio" name="fieldset-example">
<label for="radio5">Diners</label>

<input id="radio6" type="radio" name="fieldset-example">
<label for="radio6">Drive-Ins</label>

<input id="radio7" type="radio" name="fieldset-example">
<label for="radio7">Dives</label>

</fieldset>

You can provide your group with a label by placing a legend element within the fieldset.

Today's mood

<fieldset>
<legend>Today's mood</legend>

<input id="radio8" type="radio" name="fieldset-example2">
<label for="radio8">Claire Saffitz</label>

<input id="radio9" type="radio" name="fieldset-example2">
<label for="radio9">Brad Leone</label>

<input id="radio10" type="radio" name="fieldset-example2">
<label for="radio10">Chris Morocco</label>

<input id="radio11" type="radio" name="fieldset-example2">
<label for="radio11">Carla Lalli Music</label>

</fieldset>

There is a handy group utility class provided out of the box which can be used to group elements without the need for a fieldset, and ensure a

consistent spacing between them.

<input checked type="checkbox" id="example12">
<label for="example12">I am checked</label>

<input disabled type="checkbox" id="example13">
<label for="example13">I am inactive</label>

<input checked disabled type="checkbox" id="example14">
<label for="example14">I am inactive but still checked</label>

ListBox

With a list box, users can select from a set of values presented in a list that is always visible.

— Microsoft Windows User Experience - List Boxes

There are 2 ways you can render a list box. The simple one is using the select element with a multiple attribute specified.

5 - Incredible!

4 - Great!

3 - Pretty good

2 - Not so great

<select multiple>
<option>5 - Incredible!</option>
<option selected>4 - Great!</option>
<option>3 - Pretty good</option>
<option>2 - Not so great</option>
<option>1 - Unfortunate</option>
</select>

The complex one is using a combination of the ul / li elements with the role attributes.

Facebook

Amazon

Apple
Netflix

Google

<ul role="listbox">
<li role="option">Facebook</li>
<li role="option" aria-selected="true">Amazon</li>
<li role="option">Apple</li>
<li role="option">Netflix</li>
<li role="option">Google</li>
</ul>

The latter offers more flexibility over using a mere select element. Choose the one that is more appropriate depending on your context or use case.

To add a drop shadow to the list box, use the has-shadow class. To add a hovering style on the list box items (using role attribute only), use the
has-hover class.

Facebook

Amazon

Apple
Netflix

Google

<ul role="listbox" class="has-shadow has-hover">
<li role="option">Facebook</li>
<li role="option">Amazon</li>
<li role="option">Apple</li>
<li role="option">Netflix</li>
<li role="option">Google</li>
</ul>

ListView (table)

With a list view, users can view and interact with a collection of data objects, using either single selection or multiple selection.

— Microsoft Windows User Experience - List View

Currently, the ListView is only implemented as the Details view, which styles tables.

<table>
<thead>
<tr>
<th>Name</th>
<th>Date Taken</th>
<th class="highlighted indicator">Tags</th>
<th>Size</th>
<th>Rating</th>
</tr>
</thead>
<tbody>
<tr>
<td>Toco Toucan</td>
<td>6/24/2005 12:22 PM</td>
<td>Sample; Wildlife</td>
<td>113 KB</td>
<td>* * * * *</td>
</tr>
<tr class="highlighted">
<td>Dock</td>
<td>6/22/2005 8:17 PM</td>
<td>Sample; Ocean</td>
<td>310 KB</td>
<td>* * * * *</td>
</tr>
<tr>
<td>Autumn Leaves</td>
<td>11/4/2005 6:12 PM</td>
<td>Sample; Landscape</td>
<td>270 KB</td>
<td>* * * * *</td>
</tr>
</tbody>
</table>

Here's another example showcasing advanced usage, for example:

The handling of long text (using the width property of the table to limit the width)

Using the has-shadow class to add a shadow to the table

Flipping the column header sort indicator by adding the up class

Changing text alignment using the text-align property

The highlighted column header style without sort indicator (I didn't want to add another table just for that)

<table class="has-shadow" style="width: 460px">
<thead>
<tr>
<th>Name</th>
<th>Original Location</th>
<th class="highlighted">Date deleted</th>
<th>Size</th>
<th class="highlighted indicator up">Type</th>
</tr>
</thead>
<tbody>
<tr>

<td>contents_files</td>
<td>D:\Users\user\Documents\contents_files</td>
<td>3/29/2007 12:00 AM</td>
<td style="text-align: right">4 KB</td>
<td>File Folder</td>
</tr>
<tr>

<td>Windows Vista User Experience Guidelines</td>
<td>
D:\Users\user\Documents\Windows Vista User Experience Guidelines
</td>
<td>3/29/2007 12:00 AM</td>
<td style="text-align: right">0 KB</td>
<td>File Folder</td>
</tr>
<tr>

<td>AutoRecovery save of Document.asd</td>
<td>D:\Users\user\Documents\AutoRecovery save of Document.asd</td>
<td>3/23/2007 12:00 AM</td>
<td style="text-align: right">27 KB</td>
<td>ASD File</td>
</tr>
<tr>

<td>AutoRecovery save of Tree Views.asd</td>
<td>
D:\Users\user\Documents\AutoRecovery save of Tree Views.asd
</td>
<td>3/13/2007 12:00 AM</td>
<td style="text-align: right">693 KB</td>
<td>ASD File</td>
</tr>
<tr>
<td>contents</td>
<td>D:\Users\user\Documents\contents</td>
<td>3/29/2007 12:00 AM</td>
<td style="text-align: right">2 KB</td>
<td>HTML Document</td>
</tr>
</tbody>
</table>

Navigation

The following components compose a complete navigation menu, also known as Navbar.

Menu Menus are hierarchical lists of commands or options available to users in the current context.
— Microsoft Windows User Experience - Menus

A menu can be rendered using a composition of a parent ul and child items li, role="menu" and role="menuitem" attributes must be specified

on the ul and li respectively.

If a menu item has a submenu, add an aria-haspopup="true" attribute to it to render a caret indicator.

To make the menu focusable, specify the tabindex attributes on the items. Alternatively, you can use an a to achieve the same.

<ul role="menu" style="width: 200px">
<li role="menuitem" tabindex="0" aria-haspopup="true">View</li>
<li role="menuitem" tabindex="0" aria-haspopup="true">
Sort by
<ul role="menu">
<li role="menuitem"><a href="#menu">Name</a></li>
<li role="menuitem"><a href="#menu">Size</a></li>
<li role="menuitem"><a href="#menu">Item type</a></li>
<li role="menuitem"><a href="#menu">Date modified</a></li>
</ul>
</li>
<li role="menuitem"><a href="#menu">Refresh</a></li>
<li role="menuitem"><a href="#menu">Paste</a></li>
<li role="menuitem"><a href="#menu">Paste shortcut</a></li>
<li role="menuitem"><a href="#menu">Screen resolution</a></li>
<li role="menuitem"><a href="#menu">Gadgets</a></li>
<li role="menuitem"><a href="#menu">Personalize</a></li>
</ul>

By default, the submenu is only shown when the linked item is focused/clicked. To add the hovering/mouse-over trigger, you can add a can-hover
class to the root container.

Use a has-divider class to make a horizontal line after the menu item. Disable a menu item by placing an aria-disabled attribute on it.

You may associate a menu item with an icon by using the img element. (Icons provided by Icons8)

<ul role="menu" class="can-hover" style="width: 200px">
<li role="menuitem" tabindex="0" aria-haspopup="true">View</li>
<li role="menuitem" tabindex="0" aria-haspopup="true">
Sort by
<ul role="menu">
<li role="menuitem"><a href="#menu">Name</a></li>
<li role="menuitem"><a href="#menu">Size</a></li>
<li role="menuitem"><a href="#menu">Item type</a></li>
<li role="menuitem"><a href="#menu">Date modified</a></li>
</ul>
</li>
<li role="menuitem" class="has-divider"><a href="#menu">Refresh</a></li>
<li role="menuitem" aria-disabled="true"><a href="#menu">Paste</a></li>
<li role="menuitem" aria-disabled="true" class="has-divider">
<a href="#menu">Paste shortcut</a>
</li>
<li role="menuitem">
<img src="https://img.icons8.com/color/18/000000/monitor--v1.png"/>
<a href="#menu">Screen resolution</a>
</li>
<li role="menuitem">
<img src="https://img.icons8.com/color/18/000000/virtual-machine2.png"/>
<a href="#menu">Gadgets</a>
</li>
<li role="menuitem">
<img src="https://img.icons8.com/color/18/000000/remote-desktop.png"/>
<a href="#menu">Personalize</a>
</li>
</ul>

To render menu items that are options with bullets and checkmarks, use the corresponding input type (radio or checkbox).

<ul role="menu" style="width: 200px">
<li role="menuitem">
<input type="radio" name="icon-size" id="example15">
<label for="example15">Large icons</label>
</li>
<li role="menuitem">
<input type="radio" name="icon-size" id="example16" checked>
<label for="example16">Medium icons</label>
</li>
<li role="menuitem" class="has-divider">
<input type="radio" name="icon-size" id="example17">
<label for="example17">Small icons</label>
</li>
<li role="menuitem">
<input type="checkbox" id="example18">
<label for="example18">Auto arrange icons</label>
</li>
<li role="menuitem">
<input type="checkbox" id="example19" checked>
<label for="example19">Align icons to grid</label>
</li>
</ul>

MenuBar A menu bar is a list of labeled menu categories typically located near the top of a window.
— Microsoft Windows User Experience - Menus

A menu bar can be created in a similar manner to the menu, however, use a role="menubar" attribute in place of role="menu".

<ul role="menubar">
<li role="menuitem" tabindex="0">File</li>
<li role="menuitem" tabindex="0">Edit</li>
<li role="menuitem" tabindex="0">View</li>
<li role="menuitem" tabindex="0">Help</li>
</ul>

Combining it with the Menu component, we will have a complete menu bar with the associated menu dropdowns.

To accommodate an extra piece of info for a menu item (like a shortcut mnemonic) on the right side, nest it with an span element.

<ul role="menubar" class="can-hover">
<li role="menuitem" tabindex="0" aria-haspopup="true">
File
<ul role="menu">
<li role="menuitem">
<a href="#menubar">
Open Ctrl+O
</a>
</li>
<li role="menuitem">
<a href="#menubar">
Save Ctrl+S
</a>
</li>
<li role="menuitem" class="has-divider">
<a href="#menubar">
Save As... Ctrl+Shift+S
</a>
</li>
<li role="menuitem"><a href="#menubar">Exit</a></li>
</ul>
</li>
<li role="menuitem" tabindex="0" aria-haspopup="true">
Edit
<ul role="menu">
<li role="menuitem"><a href="#menubar">Undo</a></li>
<li role="menuitem"><a href="#menubar">Copy</a></li>
<li role="menuitem"><a href="#menubar">Cut</a></li>
<li role="menuitem" class="has-divider"><a href="#menubar">Paste</a></li>
<li role="menuitem"><a href="#menubar">Delete</a></li>
<li role="menuitem"><a href="#menubar">Find...</a></li>
<li role="menuitem"><a href="#menubar">Replace...</a></li>
<li role="menuitem"><a href="#menubar">Go to...</a></li>
</ul>
</li>
<li role="menuitem" tabindex="0" aria-haspopup="true">
View
<ul role="menu">
<li role="menuitem" tabindex="0" aria-haspopup="true">
Zoom
<ul role="menu">
<li role="menuitem"><button>Zoom In</button></li>
<li role="menuitem"><button>Zoom Out</button></li>
</ul>
</li>
<li role="menuitem"><a href="#menubar">Status Bar</a></li>
</ul>
</li>
<li role="menuitem" tabindex="0" aria-haspopup="true">
Help
<ul role="menu">
<li role="menuitem"><a href="#menubar">View Help</a></li>
<li role="menuitem"><a href="#menubar">About</a></li>
</ul>
</li>
</ul>

OptionButton

An option button, also referred to as a radio button, represents a single choice within a limited set of mutually exclusive choices. That is, the user can choose only one set of options.

— Microsoft Windows User Experience p. 164

Option buttons can be used via the radio type on an input element.

Option buttons can be grouped by specifying a shared name attribute on each input.

<input id="radio20" type="radio" name="first-example">
<label for="radio20">Yes</label>

<input id="radio21" type="radio" name="first-example">
<label for="radio21">No</label>

Option buttons can also be checked and disabled with their corresponding HTML attributes.

<input id="radio22" type="radio" name="second-example">
<label for="radio22">Peanut butter should be smooth</label>

<input checked disabled id="radio23" type="radio" name="second-example">
<label for="radio23">I understand why people like crunchy peanut butter</label>

<input disabled id="radio24" type="radio" name="second-example">
<label for="radio24">Crunchy peanut butter is good</label>

ProgressBar

A common control that displays the progress of a particular operation as a graphical bar.

— Microsoft Windows User Experience Glossary

Progress bars can be created with a div using role="progressbar", and another nested div is required to make the inner bar.

Specify the width of the inner bar to indicate the progress.

For accessibility, you might want to specify the respective aria-* attributes. Refer to MDN for more information.

To indicate the progress bar in paused state, add a paused class.

To indicate the progress bar in error state, add an error class.

To animate the progress bar, add an animate class.

To create an indeterminate progress bar, add a marquee class and remove the nested div.

Scrollbar

A control that allows users to scroll the content of a window, either vertically or horizontally.

— Microsoft Windows User Experience Glossary

To override the browser scrollbar's system styling for a particular section, add a has-scrollbar class to the container element.

Note that this only works with WebKit-based browsers.

Lorem ipsum dolor sit amet, consectetur adipiscing
elit. In nibh massa, viverra non velit vitae, scelerisque
venenatis risus. Sed posuere risus tellus, sit amet
vehicula nunc venenatis ut. Nunc convallis augue
eget odio imperdiet, eu consequat massa fringilla
consectetur eleifend. Curabitur in egestas justo, vel
fermentum ante. Lorem ipsum dolor sit amet,
consectetur elit. Cras ullamcorper non nibh et
placerat. Nullam ornare lectus eget consequat
di i i L i d l it t t t

Lorem ipsum dolor sit amet, consectetur adipiscing elit. In nibh massa, viverra non velit vitae,
scelerisque venenatis risus. Sed posuere risus tellus, sit amet vehicula nunc venenatis ut.
Nunc convallis augue eget odio imperdiet, eu consequat massa fringilla consectetur eleifend.
Curabitur in egestas justo, vel fermentum ante. Lorem ipsum dolor sit amet, consectetur elit.
Cras ullamcorper non nibh et placerat. Nullam ornare lectus eget consequat dignissim.
Lorem ipsum dolor sit amet, consectetur adipiscing elit. In nibh massa, viverra non velit vitae,
scelerisque venenatis risus. Sed posuere risus tellus, sit amet vehicula nunc venenatis ut.
Nunc convallis augue eget odio imperdiet, eu consequat massa fringilla consectetur eleifend.
Curabitur in egestas justo, vel fermentum ante. Lorem ipsum dolor sit amet, consectetur elit.
Cras ullamcorper non nibh et placerat. Nullam ornare lectus eget consequat dignissim.

SearchBox

With a Search box, users can quickly locate specific objects or text within a large set of data by filtering or highlighting matches.

— Microsoft Windows User Experience - Search Boxes

There are 2 variants of the search box available.

An instant search, where the results are displayed immediately as the user types, can be rendered just by specifying a type="search" attribute on an

input element:

Search

<input type="search" placeholder="Search" />

A regular search, where a search is performed when the user clicks the search button, requires a search input and a button wrapped inside a container
a container element with the class searchbox.

<input type="search" placeholder="Search" />
<button aria-label="search"></button>

Slider

A slider, sometimes called a trackbar control, consists of a bar that defines the extent or range of the adjustment and an indicator that shows the current value for the control...

— Microsoft Windows User Experience p. 146

Sliders can rendered by specifying a range type on an input element.

Volume: Low High

<label>Volume:</label>
<label>Low</label>
<input type="range" min="1" max="11" value="5" />
<label>High</label>

You can make use of the has-box-indicator class replace the default indicator with a box indicator, furthermore the slider can be wrapped with a

div using is-vertical to display the input vertically.

Note: To change the length of a vertical slider, the input width and div height.

Cowbell

<label>Cowbell</label>

<input class="has-box-indicator" type="range" min="1" max="3" step="1" value="2" />

Spinner

A spinner or loader, also referred as ProgressRing, is a type of progress control to indicate that an operation is underway and its completion time is unknown.

To render a spinner element, use either a spinner or a loader class. To animate the spinner, add an animate class.

For accessibility, we use an aria-label attribute with a desired text to inform assistive technologies about the presence of the spinner.

Tabs Tabs provide a way to present related information on separate labeled pages.
— Microsoft Windows User Experience - Tabs

<section class="tabs" style="max-width: 500px">
<menu role="tablist" aria-label="Sample Tabs">
<button role="tab" aria-controls="tab-A" aria-selected="true">Instruction</button>
<button role="tab" aria-controls="tab-B">Example</button>
<button role="tab" aria-controls="tab-C">More instruction</button>
<button role="tab" aria-controls="tab-D" disabled>Disabled Tab</button>
</menu>
<!-- the tab content -->
<article role="tabpanel" id="tab-A">
<h3>Creating tabs</h3>

To create a tab, use a <code>menu</code> element with <code>role="tablist"</code>.
Then for the tab titles, use a <code>button</code> with <code>role="tab"</code>, and set the <code>aria-controls</code> attribute to
the corresponding id of the element with <code>role="tabpanel"</code>.

Read more at <a href="https://developer.mozilla.org/en-US/docs/Web/Accessibility/ARIA/Roles/Tab_Role"
target="_blank">MDN Web docs - ARIA: tab role</a>

</article>
<article role="tabpanel" id="tab-B" hidden>
<h3>More...</h3>
This tab contains a GroupBox
<fieldset>
<legend>Today's mood</legend>

<input id="radio25" type="radio" name="fieldset-example2">
<label for="radio25">Claire Saffitz</label>

<input id="radio26" type="radio" name="fieldset-example2">
<label for="radio26">Brad Leone</label>

<input id="radio27" type="radio" name="fieldset-example2">
<label for="radio27">Chris Morocco</label>

<input id="radio28" type="radio" name="fieldset-example2">
<label for="radio28">Carla Lalli Music</label>

</fieldset>
</article>
<article role="tabpanel" id="tab-C" hidden>
<h3>Disabling tabs</h3>
Simply add a <code>disabled</code> attribute on the tab.
<h3>Justified tabs</h3>
Add the <code>justified</code> class to the <code>tablist</code> menu to make the tabs, well, justified.
</article>
<article role="tabpanel" id="tab-D" hidden>
<h3>Disabled Tab</h3>
This tab is disabled, so you should not be able to read this.
</article>
</section>

A simplified template is as below:

<section class="tabs">
<menu role="tablist" aria-label="Tabs Template">
<button role="tab" aria-controls="tab-A" aria-selected="true">Tab A</button>
<button role="tab" aria-controls="tab-B">Tab B</button>
<button role="tab" aria-controls="tab-C">Tab C</button>
<button role="tab" aria-controls="tab-D" disabled>Tab D</button>
</menu>
<article role="tabpanel" id="tab-A">Tab A is active</article>
<article role="tabpanel" id="tab-B" hidden>Tab B is active</article>
<article role="tabpanel" id="tab-C" hidden>Tab C is active</article>
<article role="tabpanel" id="tab-D" hidden>Tab D is inactive</article>
</section>

TextBox

A text box (also referred to as an edit control) is a rectangular control where the user enters or edits text. It can be defined to support a single line or multiple lines of text.

— Microsoft Windows User Experience p. 181

Text boxes can be rendered by specifying a text type on an input element. As with checkboxes and radio buttons, you should provide a

corresponding label with a properly set for attribute.

Occupation

<label for="text29">Occupation</label>
<input id="text29" type="text" />

Additionally, you can make use of the group class to position your label above the input instead of beside it.

Address (Line 1)

Address (Line 2)

<label for="text30">Address (Line 1)</label>
<input id="text30" type="text" />

<label for="text31">Address (Line 2)</label>
<input id="text31" type="text" />

To support multiple lines in the user's input, use the textarea element instead.

Additional notes

<label for="text32">Additional notes</label>
<textarea id="text32" rows="8"></textarea>

TreeView

A tree view control is a special list box control that displays a set of objects as an indented outline based on their logical hierarchical relationship.

— Microsoft Windows User Experience p. 178

To render a tree view, use an ul element with the tree-view class. The children of this list (li elements), can contain whatever you'd like.

<ul class="tree-view has-container">
<li>We can put</li>

<li>✨ Whatever ✨</li>

<li>We want in here</li>
</ul>

To make this a tree, we can nest further ul elements (no class needed on these). This will provide them with indentation to illustrate the hierarchical
relations of the tree.

To create collapsible sections, wrap child lists inside details elements.

<ul class="tree-view has-container">
<li>Table of Contents</li>
<li>What is web development?</li>
<li>
CSS
<ul>
<li>Selectors</li>
<li>Specificity</li>
<li>Properties</li>
</ul>
</li>
<li>
<details open>
<summary>JavaScript</summary>
<ul>
<li>Avoid at all costs</li>
<li>
<details>
<summary>Unless</summary>
<ul>
<li>Avoid</li>
<li>
<details>
<summary>At</summary>
<ul>
<li>Avoid</li>
<li>At</li>
<li>All</li>
<li>Cost</li>
</ul>
</details>
</li>
<li>All</li>
<li>Cost</li>
</ul>
</details>
</li>
</ul>
</details>
</li>
<li>HTML</li>
<li>Special Thanks</li>
</ul>

The has-connector class may be used to render a dotted border to illustrate the structure more clearly, and the has-collapse-button class to

change the expand/collapse carets to buttons.

<ul class="tree-view has-collapse-button has-connector has-container">
<details open>
<summary>JavaScript</summary>
<ul>
<li>Avoid at all costs</li>
<li>
<details>
<summary>Unless</summary>
<ul>
<li>Avoid</li>
<li>
<details>
<summary>At</summary>
<ul>
<li>Avoid</li>
<li>At</li>
<li>All</li>
<li>Cost</li>
</ul>
</details>
</li>
<li>All</li>
<li>Cost</li>
</ul>
</details>
</li>
</ul>
</details>
</ul>

Window

The following components illustrate how to build complete windows using 7.css.

Title Bar At the top edge of the window, inside its border, is the title bar (also reffered to as the caption or caption bar), which extends across the width of the window. The title bar identifies the contents of the window.
— Microsoft Windows User Experience p. 118

Include command buttons associated with the common commands of the primary window in the title bar. These buttons act as shortcuts to specific window commands.

— Microsoft Windows User Experience p. 122

You can build a complete title bar by making use of three classes, title-bar, title-bar-text, and title-bar-controls.

A Title Bar

A Title Bar

<button aria-label="Close"></button>

We make use of aria-label to render the Close button, to let assistive technologies know the intent of this button. You may also use "Minimize",

"Maximize", "Restore" and "Help" like so:

A Title Bar

A maximized Title Bar

A help Title Bar

A Title Bar

<button aria-label="Minimize"></button>
<button aria-label="Maximize"></button>
<button aria-label="Close"></button>

A maximized Title Bar

<button aria-label="Minimize"></button>
<button aria-label="Restore"></button>
<button aria-label="Close"></button>

A help Title Bar

<button aria-label="Help"></button>
<button aria-label="Close"></button>

Alternatively, you can use the is-close, is-minimize, is-maximize, is-restore, is-help classes to target the respective controls for your

styling preference.

To give our title bar a home, we wrap it in a window container. This provides a drop shadow to it. We can freely resize the window by specifying a

width in the container style.

A complete window

<button aria-label="Help"></button>
<button aria-label="Minimize"></button>
<button aria-label="Maximize"></button>
<button aria-label="Close"></button>

Place an active class either on the window container or the title bar itself to enable the active styles for the controls.

A complete window

<button aria-label="Help"></button>
<button aria-label="Minimize"></button>
<button aria-label="Maximize" disabled></button>
<button aria-label="Close"></button>

Window body Every window has a boundary that defines its shape.

— Microsoft Windows User Experience p. 118

To draw the contents of the window, we use the window-body class under the title bar. You may use the has-space class to add some padding to

the window body.

A window with contents

<button aria-label="Minimize"></button>
<button aria-label="Maximize"></button>
<button aria-label="Close"></button>

There's so much room for activities!

Another window with contents

<button aria-label="Minimize"></button>
<button aria-label="Maximize"></button>
<button aria-label="Close"></button>

<menu role="tablist" aria-label="Window with Tabs">
<button role="tab" aria-controls="music" aria-selected="true">Music</button>
<button role="tab" aria-controls="dogs">Dogs</button>
<button role="tab" aria-controls="food">Food</button>
</menu>
<article role="tabpanel" id="music">
Set your listening preferences
<fieldset>
<legend>Today's mood</legend>

<input id="radio33" type="radio" name="fieldset-example2">
<label for="radio33">Nicki Minaj</label>

<input id="radio34" type="radio" name="fieldset-example2">
<label for="radio34">Bell Towers</label>

<input id="radio35" type="radio" name="fieldset-example2">
<label for="radio35">The Glamorous Monique</label>

<input id="radio36" type="radio" name="fieldset-example2">
<label for="radio36">EN. V</label>

</fieldset>
<section style="display: flex; gap: 6px; align-items: center">
<button>Reset Alarm...</button>
<label>Try this to get some attention</label>
</section>
</article>

<article role="tabpanel" hidden id="dogs">
<img style="width: 100%"
src="data:image/jpeg;base64,/9j/4AAQSkZJRgABAQAAAQABAAD/2wCEAAkGBxMSEhUTExMWFhMVFxgYGBgYGBgYFRcdGxgYFhYdGBoYHiggGBslGxoXIjEiJSkrLi4uFx8zODMtNygtLisBCgoKDg0OGhAQGislHyUtLS0tLS0uLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLTctN//AABEIAKUBMgMBIgACEQEDEQH/xAAcAAEAAwEBAQEBAAAAAAAAAAAABQYHBAMCAQj/xAA2EAABAwIEBAMIAgEEAwAAAAABAAIRAyEEBTFBBhJRcSJhkQcTMoGhscHw0eFCFCNS8RVygv/EABkBAQADAQEAAAAAAAAAAAAAAAACAwQBBf/EAB8RAQEAAgMBAAMBAAAAAAAAAAABAhEDITESMkFRBP/aAAwDAQACEQMRAD8Aw1ERAREQEREBERAREQERSfD2VnE1204dB+LliQJA38yEHNluDdWqNY0ElxAW15TwJSpAEMvF/Pr5eYPVTfDfBNDDhpaHc1p5oP4sOytrcOJVWWScij5twu2qwtLBe3cDYnvp81lOfcHPpVOUbuhp2IOnSCv6TGHB2UVnuSio2w8QMg/dJk7p/Nj+GcQ14Y5oExcEOF+karmzHJK1H42ROlwT6Bf0ZSyBjL8oNoGm2nZR+N4covPM9rSRpOy79ufL+cyI1X4tF9oeTYWn42SHx8LAIO0k/uizpTl2jZoREXXBERAREQEREBERAREQEREBERAREQEREBERAREQEREBERAREQFffZRgXHFgyRLTsCIkjxTuCFUsjwJrVmNAOokjbp2kr+huCsg9x4nQXQBOpHlMbaKGd60njFtoMgD8roaxfK534wfJZss9LccduqoQAuSvjA34tFz1MU4iWsLvsuWu+Z5p54kACw6qu8v8WTj/AKkjTDrhcuJoxtZfuV1SWCRBuPTTVdrzKuxu4qymqqeaZPSqjxNafOAsn484cp0GlzaZDuoNra2W34ujOipPFdMmm4P0g/t5lTxukbNsGRe+NphtRzWyQDAnX6LwV6oRFN8PcN1cU5nKP9tzw0ukW6x2F0EPTplxAaCSdABJPyC+jhngElrgBE2Np0lbvwtwbSwjg6mLlsFzvE4m+g0bYx8lPVshpPAaYB0mLnrfqq7nE/h/MqLXOPeA6RHvKIFOoBZjR4XQTrHwmI9FktRhaSCIIMEHUHeVOXaNmnyiIuuCIiAiIgIiICIiAiIgIiICIiAiIgIiIC6stwpqVGtAm4np8+65VePZZgPfYggkBrRJH+R6X6Lluo7JutD4MwFMhobhx4YvygCe5M+q0PCUiNV4YGgGi0AKSA5RO6otXSPDFPIB6/gr4w+FBhztBsvEnmgk6xbyC7mEabKnGfV2svU0rPEnGNDBEc5EmzW/fsuPB8WCtL2C29pjudhdeXF/BBxL3Fjy3nADo0Nw479Wt9FI8P8ADNLDUi14B08Tm9BA7aLmXFf6sxzxk8e1HOmnl6kgKTNaFk+c5u3DV3OY0+F3w3cHEui1wGiLyfqrzw/nIxWHp1+UsDwZab6EtkHcGJB6Fdxl12hySb6SuJfKovHmIaKLi4bfNWurWgwT/BWV+1jNmmKTTJkT5d/5VmHdVXqMzcbr8RFqUPXC0C97WDVxA9VvfCmUsw9JjWCwJMnc6T5WWIcP0+bEUxE3/C/oPJnHkAMWFlXyVPCJdoheGIqr15rLnrRCy2r5EFm7XczXDrczBB9Fm3tGyHlcMQwDlNnx12NtFpWa1+Vpt4db7LKuNs9NQim0kDfYEadbq3i3tHk1pT0RFpZxERAREQEREBERAREQEREBERAREQEREBal7I30mtcY/wB0u18gstWmeynDv5+QMME8xdHh0sPM/sbqvk/FPj9bhlbi65ELvxTJEdl4YKlygBe7qkC6z29aXxD5k8sIC9mYi1omP3RcuYVOaTFpXJzuANyCLT5bfhVYZaq647j6xOZ1Wmw7A6LizLOa4pEHD+8ndr2Bo+bivSvmZiH8rjtLQD9IKr2NxTnH/bZ6kx6Cfup3lRnGo3E2CrOfemIcb8rpA7SBPorzkOMZRw7KYgBjdNurvqSouvlNao/mdvsP7UxQyQRB03C592+Fx17ULnvEDj4G2ib6lZpxIXFwc687/wArW8ZkbB8LBKo/EmVASC2+1wrOO6qvObigovqoyCR0XytbKufs8yf3jzVc0kCzbiPOeh0+q2HK8OQ0Rttqs09lD+YPb0dp5G/3Wt4emABCz8uXa7CdPWbLkxFTWy7XGy4MQ8CSdLhURarPElaGOAbJj90WKZpXL6riYkGLaWstX48zBzMM6HN6AyQ6+3Q6BY8StPFP2p5L+n4iIrlQiIgIiICIiAiIgIiICIiAiIgIiICIiCx8J8P/AOoe0uBLZsP+Ufid+/Rb9wnkjaDNBOwGg/krOPZLjqLwWGA9gAiwnzHVbCx4gALLy5dtHHj07KR3XzX0QVbLmfidlRlVsjnrNkQuHGjlPcfZd5eI1XFinTrt6qKcrkZhGv1C7aOXNAiAmGpKQapYxHK1w1aQaNLBceJqAC0Luxg1XBVZI0Oi7cnJEVWqyqlxXgxVpkAwdj0/pWjEuAMecKHzOmBM7+i5jlqpXHpmlTg7FQS0Nf2cJ26x1UZislxFP46NQDrykj1FlrmWsnsrFhqIV0/0Xfaq8E/TL/ZHiQMRUYdXNBHWxM/dbOx0KOGUUXPD3MaKjZLXADnE2Nxde4p1Gu5YkO0M6dwo55fXcMMddPWriFAZzmopjxGxC8M+z+nh3uY/4htab3kLO+I+JBUOttmjqmGNrudkRfF2dOrv5f8AEf36KvL6qPkk9SvlbJNTTLbuiIi64IiICIiAiIgIiICIiAiIgIiICIiAiIg6MDjH0XtqU3FrmmQVsPCPtAOIZy1IFVu3XS4H48liykMgw5qYmiwEgue0W11vp5KvkwmU7WYZ3Gt4ocVS4zA+evZe7eIqbrA36HX0UbxHw9SLA4DlfoC2w0kBw/Ko1bB12H4jExP73Cw3j1fW2ZyzxpZzll/ELea8nZ6wG5n7LPKGEqk3JIU/gsqJABkjoVC7iUkqx4DiJnveQ2BNr6lWUY9p0OvT7qnUMmboSJ2+v1XJUdXoEkXHlHMY0HZdxyv7Ryxl8W/E1yNP+1A43MHM+E7aahVrEcWYho5fdHmPb9hV/GcQYhxPhAO86qXxvxyXXqbzTG1fi0Ciq+bufDSbNUNicbVqfG4x5aL8w7YgKfxpz72veRVZAkgT11Vpwbp1VSyPSI2Vnw0Hc230+yovq1Kl/KPsuDE5idBrr6L5q1iNXCFGY7GhokdTO56KWNu0MpNM746x5e0DlEucXOd/lrAE9I+6pSv/ABFh21XmGxLfoBaB3kqgL0OPxi5fRERWKxERAREQEREBERAREQEREBERAREQEREBERAXvgsU6lUbUYYcwhw7heCIP6CyrNW4zC06ouHNAeJ+Fw+Kel9F61QASGwQBcRM389/4Cx3gfiQ4OqeafdVAA4bA7OjykrS8TX5XNfB5XXEaHzlZs8NVowy3EiMMwnmbcaRuNtLLowYERMRY9frsuPCYtsSHTNiNxuJtK/Pfkus60GOb+e6oyi6VMNdy/CLev3XE6sCTzanroo1uaNJLXyNt489d91418WOaGgO8unWyr0m+sXQaZdzCe30BKrOIwgEkjXrqpyq4Hrr8MgQdel1GZkfDG5+itxQqt1S2bBe+EoS4fui8qxbTP7qpDJKZceYqV8cizZbTMWU4y1r/YKOwAspZoPIdOW09fkqNLdozMKsA3/fmq5jK7jqZHeI81KZ2bgNP7877KpZhiw0QdzMwCSNldhgryyfeZYpnM0tNwINrRqOvl9VQyrFiarix55YsddQq4teEZM6IiKaAiIgIiICIiAiIgIiICIiAiIgIiICIiAiIgIiIC2/gykMTl1EgFzqbC2BE+GQJ+ixBbD7GKp/0lcXtUsNrtb91Xyfinx+vHMa5okcoIkwb3kC9vRR1POXz4Z0sNb/ALsrXnOXcwJdEuJMekd/+1B5LkHNWbLgXahoEn5nQLLLtq1opDE4iAXco1iBrupLD5O9kHmkkHTW1yrjhcsFGXEa7QDNly4pji0+7DWkTrJD9df6UMr2lPFZbTbygNIJGokc3zB0vIUdmFQATeR5Kfr0BUHjaG1Lx5EbAqm8VF1ORo52rZsPMKeM2hldISvVbWqy3QffdWrLKENsqXkR9Zur/lFIkD9ClyTXTmF32lMFSMSphlHwkTcx21XzhMPa66sVoYCpkWWqFxbUsTflBAA/j5qjHGh1QHl+HSevVafnmC5wBAt6g91Qv/GgVi13Xt8/ur8bqK7Nudpc8QbgCPz9yo3NcjdSaHtkt3Gpb3jZX7CZKIkQepGny+QXfVwkCSByEwBsbaf9rs5dVHLj3GNIrbxZkIpj3rWwDsNP6VSWmWWbjPZoREXXBERAREQEREBERAREQEREBERAREQEREBERAWwew9o91XJJPjHhm3wi8dfPyWPrU/YhjfFXomIhrx1/wCJ+Wnqocn4pYerxmmFmSL+Ui2y9eEcL4yS2/b0E6+fyXTmGunaFI8OUOVpcZknfpEBY8fWq/i6ceNoEeWnZQ9dnIy0z9ZU1jHh23z8lE46QNdCNdNv7UbN13G9ITMGGo0NFjqDvP7Kp3FpDqR95aowa7+RHUK9Y7DujUc2v8KkcVVxUYWuADgCCNiFZgjkpnC8OJm5ladktKAFlXCuIDa0GLrXsreICnzTtDjvSewxAF1+V6wNhquR1RefvFStc+ZPHLBGosenUHyVVfTBeCRIBB7jX7KbzKpKgG1IeB5wpXxyRZcE0BpDSLttHUm4jay9K7ZY1ms7R6LxylliXW81INpcxmAQ3rbdV5LIgMza145SwiLEH9+/kqDn3DJbL6QMbt3HZajmjg958MFsAbnv2/lcx5CPEJCs4+SxDk45WIEL8V14v4faJq07eWoKpS245bm2OzQiIuuCIiAiIgIiICIiAiIgIiICIiAiIgIiIC1D2KUBzV37+Fo67k3+YWXrQ/Y5XIr1WzYsBjqQdfRRz/FLD1ruMp88CY0U7RbytHZV11eHt/8AYT9VOPqSFj202eOKrXIJnRRdarqXnQHsu/nBMfvX97rjzGg0tvOt436KGKVV3MMe7nJeS3TQaf0qBxzmPNBbY6EjdaXmGHABJdzWtN/rH0WS8Y1hJadT+Cr+Odqs70rNN5aQRqDK1rhrM+djepAn0WRLSfZ/Wa5gAN22PVW8s3FfHdVdzVsvqo0wjCOYDbVMViQO/wBlkaoicS6/r9FBZjSDSpXGB3KTsTt3v+FGVxzTI0XYV3ZBmUt5SbAyf30VpbUBi8CFj3/mP9PXe0XYSNP8Vccjz73vNUZ8LbAG0mPxb1U8+PU2hjnu6WbM6RID2G4IMdRvO65areWmSD8ILiNYXHSqVeVrwNZ67GNOm6/cyzBvKWP8NXTw/C7aCT1Cpnq6+IjF4xr2OBIgg6/n5rNcdR5HuaNAVbsyc2k13i1mJBm1jbcdiqXUfJJ6rbxTpj5fXyiIrVQiIgIiICIiAiIgIiICIiAiIgIiICIiApThvOH4Su2qwAn4SDuDr2RFyuz1t2CxJq1GSLFzbT2d+Fa8ZUgGOiIsN8a/3EM6s7msY0/fouTF1jyxO32CIq8VmStZtjnspCDJ1n/6hZbn2IL6pnUflEWzhZeVGqb4Sxz6dcBps7UbWBIRFbl5VWPrWMFWJBedY+y+qniI6nX9/dURYW18YxvKz5H8qu8RHkY0t1db8oinghkzbHVC6o4nWf6XrgszqUrNd4d27GdV+otmumXa6uzqryNfMTcj0sofPc4qObLrk7yQZ6+ZhEVGOM+l9yvyrVXEPd8Tie5leSItDOIiICIiAiIgIiICIiD/2Q==" /> </article>

<article role="tabpanel" hidden id="food">

You create the content for each tab by using an <code>article</code> tag.

<iframe width="100%" height="200" src="https://www.youtube.com/embed/TODJBQ0tnow" frameborder="0"
allow="accelerometer; autoplay; encrypted-media; gyroscope; picture-in-picture"
allowfullscreen></iframe>
</article>
<section style="display: flex; justify-content: flex-end; gap: 6px">
<button class="default">OK</button>
<button>Cancel</button>
</section>

Status Bar A status bar is a special area within a window, typically the bottom, that displays information about the current state of what is being viewed in the window or any other contextual information, such as keyboard state.
— Microsoft Windows User Experience p. 146

You can render a status bar with the status-bar class, and status-bar-field for every child text element.

A Window With A Status Bar

 There are just so many possibilities:
<ul>
<li>A Task Manager</li>
<li>A Notepad</li>
<li>Or even a File Explorer!</li>
</ul>

Press F1 for help
Slide 1
CPU Usage: 14%

Glass frame &

Color

The glass window frames are a striking new aspect of the Microsoft Windows aesthetic, aiming to be both attractive and lightweight. These translucent frames give windows an open, less intrusive appearance, helping users focus on content and
functionality rather than the interface surrounding it.

— Microsoft Windows User Experience - Glass window frames

You can produce this "striking aspect" of the window with a glass class. The window frame then becomes translucent, the background is blurred
behind the window.

A glass window frame

<button aria-label="Minimize"></button>
<button aria-label="Close"></button>

The background behind is blurred.

If you want to override the default color of the window, you can redefine the --w7-w-bg variable as an inline value of the style attribute.

A violet window frame

<button aria-label="Minimize"></button>
<button aria-label="Close"></button>

You can change the window color just as simple.

A glass violet window frame

<button aria-label="Minimize"></button>
<button aria-label="Close"></button>

And even the glass window frame as well.

To make the aero effect stick to the window when scrolling, or changing the viewport size, change the background-attachment property of the

. title-bar to local or scroll (default is fixed), depending on your requirements.

A glass window frame with local background-attachment

<button aria-label="Minimize"></button>
<button aria-label="Close"></button>

The aero effect is now staying in place with the scroll position.

Dialog Box

A dialog box is a secondary window that allows users to perform a command, asks users a question, or provides users with information or progress feedback.

— Microsoft Windows User Experience - Dialog Boxes

Without JavaScript, a dialog box can be triggered by utilizing the URL fragment of an a element (denoted by the # sign), targeting a corresponding

dialog box element with the matching id.

For accessibility, define the role="dialog" attribute on the element. Additionally, label the dialog using the aria-labelledby attribute, with the

value pointing to the id of the title bar's text element.

Open Dialog

<a href="#dialog-demo">Open Dialog</a>

Problem Diagnostics

<button aria-label="Close" onclick="history.back()"></button>

<h2 class="instruction instruction-primary">Identifying your problem...</h2>

<footer style="text-align: right">
<button onclick="history.back()">Cancel</button>
</footer>

Issues, Contributing, etc.
7.css is MIT licensed. Refer to the GitHub issues page to report any issue in the code.

Started as a clone of XP.css, 7.css is a fun project I worked on in my free time to enhance my tech skills.

Consider starring this project if it is useful to you in some way or if you also share the love for Windows 7 with me ;)

Share Share Share Fork

My First Program

Hello, world!

OK Cancel

A Win7-styled button

Show code

Copy Code

A balloon is better known as tooltip in web development.

Show code

Copy Code

Show code

Copy Code

This balloon is positioned bottom right of the source control (default behavior).

This balloon is positioned bottom left of the source control.

This balloon is positioned top left of the source control.

This balloon is positioned top right of the source control.

Show code

Copy Code

Click me

Show code

Copy Code

I am being pressed

Show code

Copy Code

I cannot be clicked

Show code

Copy Code

I am focused

Show code

Copy Code

I am the one!

Show code

Copy Code

Choose File

Show code

Copy Code

Choose file Browse...

Show code

Copy Code

This is a checkbox

Show code

Copy Code

✔ I am checked

I am inactive

✔ I am inactive but still checked

Show code

Copy Code

Expand me to see something interesting

Show code

Copy Code

I open myself willingly

Show code

Copy Code

Facebook

Amazon

Apple
Netflix

Google

Show code

Copy Code

5 - Incredible!

Show code

Copy Code

3 - Pretty good

Show code

Copy Code

0 - Dropdown disabled

Show code

Copy Code

Diners

Drive-Ins

Dives

Show code

Copy Code

Claire Saffitz

Brad Leone

Chris Morocco

Carla Lalli Music

Show code

Copy Code

✔ I am checked

I am inactive

✔ I am inactive but still checked

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Toco Toucan 6/24/2005 12:22 PM Sample; Wildlife 113 KB * * * * *

Dock 6/22/2005 8:17 PM Sample; Ocean 310 KB * * * * *

Autumn Leaves 11/4/2005 6:12 PM Sample; Landscape 270 KB * * * * *

Name Date Taken Tags Size Rating

Show code

Copy Code

contents_files D:\Users\us… 3/29/2007 1… 4 KB File Folder

Windows Vi… D:\Users\us… 3/29/2007 1… 0 KB File Folder

AutoRecove… D:\Users\us… 3/23/2007 1… 27 KB ASD File

AutoRecove… D:\Users\us… 3/13/2007 1… 693 KB ASD File

contents D:\Users\us… 3/29/2007 1… 2 KB HTML Docu…

Name Original Loc… Date deleted Size Type

Show code

Copy Code

View

Sort by

Refresh

Paste

Paste shortcut

Screen resolution

Gadgets

Personalize

Show code

Copy Code

View

Sort by

Refresh

Paste Paste shortcut
Screen resolution

Gadgets

Personalize

Show code

Copy Code

Large icons

Medium icons

Small icons

Auto arrange icons

✔ Align icons to grid

Show code

Copy Code

File Edit View Help

Show code

Copy Code

File Edit View Help

Show code

Copy Code

Yes

No

Show code

Copy Code

Peanut butter should be smooth

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Search

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

We can put

✨ Whatever ✨

We want in here

Show code

Copy Code

Table of Contents

What is web development?

CSS

Selectors

Specificity

Properties

JavaScript
Avoid at all costs

Unless

HTML

Special Thanks

Show code

Copy Code

– JavaScript
Avoid at all costs

+ Unless

Show code

Copy Code

Show code

Copy Code

Show code

Copy Code

A complete window

Show code

Copy Code

A complete window

Show code

Copy Code

A window with contents

There's so much room for activities!

Show code

Copy Code

Another window with contents

OK Cancel

Dogs Food

Set your listening preferences

Today's mood

Try this to get some attention

Nicki Minaj

Bell Towers

The Glamorous Monique

EN. V

Reset Alarm...

Music

Show code

Copy Code

A Window With A Status Bar

There are just so many possibilities:

A Task Manager

A Notepad

Or even a File Explorer!

Press F1 for help Slide 1 CPU Usage: 14%

Show code

Copy Code

A glass window frame

The background behind is blurred.

Show code

Copy Code

A violet window frame

You can change the window color just as simple.

A glass violet window frame

And even the glass window frame as well.

Show code

Copy Code

A glass window frame with local background-attachment

The aero effect is now staying in place with the scroll position.

Show code

Copy Code

Show code

Copy Code

Example More instruction

Disabled Tab

Tab B Tab C

Tab D

Creating tabs

To create a tab, use a menu element with role="tablist". Then for the tab titles, use

a button with role="tab", and set the aria-controls attribute to the

corresponding id of the element with role="tabpanel".

Read more at MDN Web docs - ARIA: tab role

Tab A is active

Instruction

Tab A

Intro

Installation

Scoping

Tree-shaking

– Components
Balloon

Button

CheckBox

Collapse
ComboBox

Dropdown

GroupBox
ListBox

ListView (table)

– Navigation
Menu

MenuBar

OptionButton

ProgressBar
Scrollbar

SearchBox

Slider

Spinner
Tabs

TextBox

TreeView

– Window

Title Bar

Window body
Status Bar

Glass frame & Color

Dialog Box

Issues, Contributing, etc.