Spiral Tubeformer SBTF-2020

High-capacity spiral duct machine

High-capacity spiral tubeformer for round ducts up to Φ2500 mm. Designed for thicker materials (galvanized up to 2 mm) and higher production speeds. Plasma cut and flying slitter; changeable forming compartment for different thicknesses. Aluminum forming heads for precise operation. Suits heavy-duty ventilation, dust removal and industrial HVAC.



Technical specifications

Parameter	Specification
Diameter	Φ80–Φ2500 mm
Galvanized steel	0.4–2.0 mm
Stainless steel	0.4–1.2 mm
Aluminum	0.4–2.0 mm
Strip width	137 mm (0.4–1.0 mm) / 140 mm (1.1–1.3 mm) / 150 mm (1.4–2.0 mm)
Lock seam	Outside lock, inside lock as request
Cutting system	Plasma cut and flying slitter
Options	Controlled corrugation unit / one or two beads (optional)
Power	Mainframe 22 kW / Cooling water pump 0.25 kW
Weight	3200 kg
Mainframe dimension	2100×1800×1500 mm
Decoiler dimension	2000×1100×1300 mm
Run-out table	2450×1200×1200 mm
Voltage	380V / 50Hz / 3PH

Australian supplier of HVAC duct machinery · manufacturing since 1995 · ISO 9001:2015 · CE certified · 5,000+ machines installed in 100+ countries

Request a quotation — a mechanical engineer (not a salesperson) replies within 12 hours. sales@sbkjduct.com · WhatsApp +61 435 074 994 · taokron.com/product/sbtf-2020

Specifications taken from the Taokron Product Catalog 2026 and are subject to change without notice. © Taokron · taokron.com