Auto Duct Line SBAL-III

Automatic duct line with hydraulic notching & shearing

Line III integrates two electrical feeding frames, leveler grooving roller, hydraulic notch and square punching, hydraulic shearer and folder. Computer control with closed-loop servo ensures accurate cutting. Max. feeding speed 18 m/min; length tolerance ±0.5 mm; diagonal ±0.8 mm.



Technical specifications

Parameter	Specification
Model	SBAL-III-1250 / SBAL-III-1550
Thickness	0.5–2.0 mm
Max width	1250 / 1550 mm
Max feeding speed	18 m/min
Max weight capacity	8000 kg
Power	10.7 kW
Weight	3250 / 4000 kg
Mainframe dimension	2300×1800×1400 / 2300×2100×1400 mm
Decoiler dimension	2300×1750×1650 / 2300×2050×1650 mm
Voltage	380V / 50Hz / 3PH

HVAC duct machinery since 1995 · Australian office: Box Hill North, VIC · ISO 9001:2015 · CE certified · 5,000+ machines installed in 100+ countries

Request a quotation — a mechanical engineer (not a salesperson) replies within 12 hours. sales@taokron.com · WhatsApp +61 435 074 994 · taokron.com/product/sbal-iii

Specifications taken from the Taokron Product Catalog 2026 and are subject to change without notice. © Taokron · taokron.com