Transverse Duct Connector Flange Forming Machine

Connector flange forming for duct joints

Forms connector flange profiles on rectangular duct ends for bolted or clipped connections. Complements TDF flange machines for applications requiring connector-style joints. Used in duct assembly lines and fitting production.



Technical specifications

Parameter	Specification
Model (A series)	SBTDC-20A / 25A / 30A / 35A / 40A
Strip width (A)	89 / 99 / 121 / 131 / 146 mm
Thickness (A)	0.8 / 0.8 / 1.0 / 1.0 / 1.2 mm
Power (A)	3 / 3 / 3 / 3 / 4 kW
Weight (A)	2000 / 2000 / 2200 / 3000 / 3000 kg
Model (B series)	SBTDC-20B / 25B / 30B / 35B
Strip width (B)	86 / 96 / 118 / 128 mm
Thickness (B)	0.8 / 0.8 / 1.0 / 1.0 mm

HVAC duct machinery since 1995 · Australian office: Box Hill North, VIC · ISO 9001:2015 · CE certified · 5,000+ machines installed in 100+ countries

Request a quotation — a mechanical engineer (not a salesperson) replies within 12 hours. sales@taokron.com · WhatsApp +61 435 074 994 · taokron.com/product/transverse-duct-connector-flange

Specifications taken from the Taokron Product Catalog 2026 and are subject to change without notice. © Taokron · taokron.com