

# Semi Rigid Aluminum Duct Forming SBLF-500

## Aluminum semi-rigid duct forming

Semi rigid aluminum duct forming machine. Custom-built molding wheel forms rigid tube that will not easily fall off. Easy to operate for aluminum strip ducts. Diameter range  $\Phi 80$ – $\Phi 500$  mm.



### Technical specifications

| Parameter           | Specification                       |
|---------------------|-------------------------------------|
| Model               | SBLF-500                            |
| Diameter            | $\Phi 80$ – $\Phi 500$ mm           |
| Thickness           | 0.08–0.15 mm                        |
| Width               | 60 mm                               |
| Corrugated standard | 6 corrugations                      |
| Feeding speed       | 0–25 m/min                          |
| Lock form           | Double-decked tabby locking / Twill |
| Power               | 2 kW                                |
| Weight              | 260 kg                              |
| Mainframe dimension | 2210×830×1530 mm                    |
| Voltage             | 380V / 50Hz / 3PH                   |

**Australian supplier** of HVAC duct machinery · manufacturing since 1995 · ISO 9001:2015 · CE certified · 5,000+ machines installed in 100+ countries

**Request a quotation** — a mechanical engineer (not a salesperson) replies within 12 hours. [sales@sbkjduct.com](mailto:sales@sbkjduct.com) · [taokron.com/product/sblf-500](http://taokron.com/product/sblf-500)

Specifications taken from the Taokron Product Catalog 2026 and are subject to change without notice. © Taokron · taokron.com