FET

Ve311 Electronic Circuits (Fall 2021)

Dr. Chang-Ching Tu

NMOS FET

- MOS = Metal-Oxide-Semiconductor
- FET = Field effect Transistor
- CMOS Technology keeps on reducing t_{ox} and L_{eff} (Moore's Law).
- Substrate (Body) of NMOS is generally connected to ground.
- See Chapter 17 for the introduction of CMOS fabrication technology.

Latest: TSMC 5 nm FinFET Technology

CMOS

- CMOS = Complementary MOS
- Substrate (Body) of NMOS is generally connected to ground.
- N-well (Body) of PMOS is generally connected to V_{DD}.

# Layout

NMOS

PMOS

**p⁻ substrate**

Threshold Voltage (V_{TH}) for NMOS

- $V_G = 0$ V
- No current flow

- As V_G increases from zero, holes in *p*-substrate are repelled, leaving negative ions (ionized boron dopants) behind to form a **depletion region**.
- Positive charges are mirrored at the gate.
- No charge carriers (electrons or holes) in the channel, so no current flow.

Threshold Voltage (V_{TH}) for NMOS

Interface as n-type as the substrate is p-type

- Higher V_G further increases the width of the **depletion region**.

- When V_G reaches a sufficiently positive value, a channel of electrons (**inversion layer**) is formed beneath the gate oxide.

- Electrons flow from "source" to "drain". Equivalently, current flows from "drain" to "source".

- The value of V_G at which the inversion layer forms is the **threshold voltage (V_{TH})**.

- If V_G rises further, the charges in the depletion region remain relatively constant, whereas the charges in the inversion layer increase rapidly.

I-V Characteristics for NMOS (Triode)

For $V_{GS} \geq V_{TH}$

$Q = -WL_{eff}C_{ox}(V_{GS} - V_{TH})$ (unit: coulomb)

$Q_d = -WC_{ox}(V_{GS} - V_{TH})$ (unit: coulomb·m^{-1})

C_{ox} (gate oxide capacitance per unit area)
$= \epsilon_{silicon\ oxide} / t_{ox}$
$= [8.85 \times 10^{-12}\ (F/m) \times 3.9] / t_{ox}$

I-V Characteristics for NMOS (Triode)

Gate–Sub. Voltage Difference V_{GS} ... $(V_{GS} - V_{DS})$

$V(x = 0) = 0$
$V(x = L_{eff}) = V_{DS}$

$$I_D = Q_d \times v = Q_d \times (\mu_n \mathcal{E}) = -WC_{ox}[V_{GS} - V_{TH} - V(x)] \times (\mu_n \mathcal{E})$$

$$\mathcal{E} = -dV(x)/dx$$

$$= WC_{ox}[V_{GS} - V_{TH} - V(x)] \times \mu_n \times \frac{dV(x)}{dx}$$

$$\int_{x=0}^{x=L_{eff}} I_D \cdot dx = \int_{V(0)=0}^{V(L)=V_{DS}} \mu_n C_{ox} W[V_{GS} - V_{TH} - V(x)] \cdot dV(x)$$

I_D: constant along channel

$$\boxed{I_D = \mu_n C_{ox} \frac{W}{L_{eff}} \left[(V_{GS} - V_{TH})V_{DS} - \frac{1}{2}V_{DS}{}^2 \right]}$$

I-V Characteristics for NMOS (Triode)

$$I_D = \mu_n C_{ox} \frac{W}{L_{eff}} \left[(V_{GS} - V_{TH}) V_{DS} - \frac{1}{2} V_{DS}^2 \right]$$

$$I_{D,max} = \frac{1}{2} \mu_n C_{ox} \frac{W}{L_{eff}} (V_{GS} - V_{TH})^2 \quad V_{DS} = V_{GS} - V_{TH}$$

$V_{DS} << 2(V_{GS} - V_{TH})$
Deep triode region

$$R_{on} = \frac{1}{\mu_n C_{ox} \left(\frac{W}{L_{eff}} \right) (V_{GS} - V_{TH})}.$$

- For digital circuit, MOSFET, as a switch, usually operates in deep triode region.
- This is why reducing t_{ox} and L_{eff} can improve speed.

I-V Characteristics for NMOS (Saturation)

- In reality, for $V_{DS} > V_{GS} - V_{TH}$, I_D becomes relatively constant.
- $V_{DS} = V_{GS} - V_{TH}$ is the minimum value for the NMOS to operate in saturation region.

$$\int_{x=0}^{x=L'} I_D \cdot dx = \int_{V(0)=0}^{V(L')=V_{GS}-V_{TH}} \mu_n C_{ox} W[V_{GS} - V_{TH} - V(x)] \cdot dV(x)$$

$$\boxed{I_D = \frac{1}{2} \mu_n C_{ox} \frac{W}{L'} (V_{GS} - V_{TH})^2}$$

I_D: constant along channel

L': the point at which Q_d drops to zero

$V_{GS} - V_{TH}$: the overdrive voltage

- Electron velocity ($v = I_D / Q_d$) becomes tremendously high at the pinch off point ($Q_d \to 0$), such that electrons shoot through the depletion region and arrive at the drain terminal.

NMOS vs PMOS

Channel-Length Modulation

$$I_D = \frac{1}{2}\mu_n C_{ox}\frac{W}{L'}(V_{GS} - V_{TH})^2$$

$$L' = L_{eff} - \Delta L$$

$$\frac{1}{L'} = \frac{1}{L_{eff} - \Delta L} = \frac{1}{L_{eff}} \cdot \frac{1}{1 - \frac{\Delta L}{L_{eff}}} \approx \frac{1}{L_{eff}} \cdot \left(1 + \frac{\Delta L}{L_{eff}}\right)$$

$$I_D = \frac{1}{2}\mu_n C_{ox}\frac{W}{L_{eff}}(V_{GS} - V_{TH})^2\left(1 + \frac{\Delta L}{L_{eff}}\right)$$

$$= \frac{1}{2}\mu_n C_{ox}\frac{W}{L_{eff}}(V_{GS} - V_{TH})^2(1 + \lambda V_{DS})$$

Channel-Length Modulation

$$\mathbf{r_o} = \frac{\partial V_{DS}}{\partial I_D} = 1 / \frac{\partial I_D}{\partial V_{DS}}$$

$$= \frac{1}{\frac{1}{2}\mu_n C_{ox} \frac{W}{L}(V_{GS} - V_{TH})^2 \cdot \lambda}$$

$$\approx \frac{\mathbf{1}}{\mathbf{I_D} \cdot \boldsymbol{\lambda}}$$

Transconductance

- For the NMOS operating in the saturation region ($V_{DS} \geq V_{GS} - V_{TH}$):

$$I_D = \frac{1}{2}\mu_n C_{ox}\frac{W}{L'}(V_{GS} - V_{TH})^2$$

V_D

V_G

V_S

- ΔV_{GS} results in $\Delta I_D = gm \times \Delta V_{GS}$.

$$gm = \frac{\partial I_D}{\partial V_{GS}} = \mu_n C_{ox}\frac{W}{L'}(V_{GS} - V_{TH})$$

$$= \sqrt{2\mu_n C_{ox}\frac{W}{L'}I_D} = \frac{2I_D}{V_{GS} - V_{TH}}$$

Transcendance

$$V_{DS} \geq V_{GS} - V_{TH}$$

$$I_D = \frac{1}{2} \mu_n C_{ox} \frac{W}{L'} (V_{GS} - V_{TH})^2$$

- For a given NMOS, gm changes according to the DC biasing condition.
- If a small signal is applied to a NMOS with defined biasing values, we assume the signal amplitude is small enough that the variation in gm is negligible.

Body Effect

$$\mathbf{V_{TH} = V_{TH0} + \gamma(\sqrt{|2\Phi_F + V_{SB}|} - \sqrt{|2\Phi_F|})}$$

$$\Phi_F = \frac{kT}{q}\ln\frac{N_{sub}}{n_i} \qquad \gamma = \frac{\sqrt{2q\epsilon_{Si}N_{sub}}}{C_{ox}}$$

$$I_D = \frac{1}{2}\mu_n C_{ox}\frac{W}{L'}(V_{GS} - V_{TH})^2$$

Body Effect

$$\mathbf{gmb} = \frac{\partial I_D}{\partial V_{SB}} = \frac{\partial I_D}{\partial V_{TH}} \cdot \frac{\partial V_{TH}}{\partial V_{SB}}$$

$$= -\mu_n C_{ox} \frac{W}{L} (V_{GS} - V_{TH}) \cdot \frac{\partial V_{TH}}{\partial V_{SB}}$$

$$= -\mu_n C_{ox} \frac{W}{L} (V_{GS} - V_{TH}) \cdot \frac{\gamma}{2} \frac{1}{\sqrt{|2\Phi_F + V_{SB}|}}$$

$$= -\mathbf{gm} \cdot \mathbf{\eta}$$

$\mathbf{V_D}$

$\mathbf{V_G}$

$\mathbf{V_S}$

$\Delta I_D = \Delta V_{GS} \times gm$ $\Delta I_D = \Delta V_{SB} \times gmb$

- V_{GS} increases, I_D increases.
- V_{SB} increases, V_{TH} increases and thus I_D decreases.

Small-Signal Model for NMOS

$$V_d = V_D + v_d$$

$$V_g = V_G + v_g$$

$$I_D \downarrow \quad i_d = gm \cdot v_{gs} \uparrow \quad i_d = gmb \cdot v_{sb}$$

$$V_s = V_S + v_s$$

V_g V_d

$gm \cdot v_{gs}$ r_o $gmb \cdot v_{sb}$

V_s

Transconductance   Channel-Length Modulation   Body Effect

Small-Signal Model for PMOS

$$V_s = V_S + v_s$$

$$V_g = V_G + v_g$$

$$I_D \quad i_d = gm \cdot v_{gs} \quad i_d = gmb \cdot v_{sb}$$

$$V_d = V_D + v_d$$

V_g V_d

$gm \cdot v_{gs}$ r_o $gmb \cdot v_{sb}$

V_s

Transconductance   Channel-Length Modulation   Body Effect

Example

Sketch I_D as a function of V_X increasing from $-\infty$ to 0. Assume $V_{TH} = 0.6$ V, $\gamma = 0.4$ $V^{1/2}$ and $2\Phi_F = 0.7$ V.

Solution:

$$1.2 = 0.6 + 0.4(\sqrt{0.7 - V_X} - \sqrt{0.7}), \; V_X = -4.76 \text{ V.}$$

Layout

NMOS

PMOS

- W/L is chosen to determine gm. Minimum L is dictated by the process.
- Design rules: (1) Poly-Si extends beyond the channel area by some amount. (2) Enough n^+, p^+ or poly-Si area surrounding each via. (3) Enough distance between two vias. (4) Many others.

SPICE Model

NMOS Model

LEVEL = 1	VTO = 0.7	GAMMA = 0.45	PHI = 0.9
NSUB = 9e+14	LD = 0.08e−6	UO = 350	LAMBDA = 0.1
TOX = 9e−9	PB = 0.9	CJ = 0.56e−3	CJSW = 0.35e−11
MJ = 0.45	MJSW = 0.2	CGDO = 0.4e−9	JS = 1.0e−8

PMOS Model

LEVEL = 1	VTO = −0.8	GAMMA = 0.4	PHI = 0.8
NSUB = 5e+14	LD = 0.09e−6	UO = 100	LAMBDA = 0.2
TOX = 9e−9	PB = 0.9	CJ = 0.94e−3	CJSW = 0.32e−11
MJ = 0.5	MJSW = 0.3	CGDO = 0.3e−9	JS = 0.5e−8

- Simulators such as SPICE and Cadence need accurate models for each device.
- Above is the simplest MOS SPICE model, known as "Level 1," and provide typical values for each parameter corresponding to 0.5-μm technology.

NMOS vs PMOS in Performance

- PMOS devices are quite inferior to NMOS in most CMOS technology.

- Lower mobility of holes ($\mu_p C_{ox} \approx 0.5 \mu_n C_{ox}$) yield lower current drive and conductance.

- NMOS exhibit higher output resistance, providing more ideal current sources and higher voltage gain.

- It is preferable to use NMOS rather than PMOS wherever possible.