

BLADE: Bilevel Low-rank Augmented-Lagrangian Driven Erasure for LLM Unlearning

Anonymous ACL submission

Abstract

Existing LLM unlearning methods struggle with robustness: unbounded forget losses degrade model coherence, fixed-weight balancing cannot adapt as retain difficulty shifts mid-training, and methods that work on one benchmark falter under scaling or repeated application. We propose BLADE, a constrained bilevel framework that gives smooth, predictable control over the optimization landscape. Three interlocking mechanisms give smooth, predictable control: a clamped-entropy forget loss whose gradient is exactly zero once a token reaches sufficient uncertainty; an asymmetric augmented Lagrangian that permanently ratchets retain protection after any violation; and a bilevel structure confined to LoRA adapters that repairs retain damage before each forgetting step. BLADE dominates across three benchmark families—improving average composite scores over the strongest baselines by 9% on TOFU, 9% on MUSE Books, and 7% on KnowUndo—and remains stable under $4\times$ scaling and 4 sequential unlearning steps on MUSE News where the best competing method collapses entirely.

1 Introduction

Deployed language models require continuous post-hoc correction: regulations such as the GDPR (Voigt and von dem Bussche, 2017) mandate deletion of personal data on request, copyright holders demand removal of memorized content (Carlini et al., 2021), safety benchmarks flag hazardous knowledge that must be suppressed (Li et al., 2024), and models that absorb misinformation—recently demonstrated when LLMs confidently repeated a fabricated disease (Stokel-Walker, 2026)—must be patched without full retraining. These demands span text, vision, and

multimodal systems alike, and adversarial users actively probe unlearned models to recover erased content. *Machine unlearning* addresses these needs, yet the process is inherently *recurring*: new removal requests, policy changes, and safety incidents arrive throughout a model’s lifetime (Liu et al., 2025).

This makes the central challenge not just *what* to forget but *how to forget without breaking what remains*. Forget and retain knowledge share entangled representations (Cheng et al., 2026), so each unlearning step risks collateral damage that compounds over repeated applications. Existing methods rely on fixed-weight loss balancing (Liu et al., 2025; Zhang et al., 2024) that cannot adapt as retain difficulty shifts mid-training, producing three recurring failure modes: (i) *unbounded forgetting*—gradient ascent (Jang et al., 2023) produces arbitrarily large gradients, destroying utility; (ii) *static tradeoff*—fixed-weight methods (GradDiff, NPO) oscillate without self-correction; (iii) *over-forgetting*—unclamped entropy (Yuan et al., 2025) pushes already-forgotten tokens, wasting gradient budget on tokens that no longer need perturbation.

BLADE addresses these through three mechanisms, each targeting a specific failure mode. A *clamped entropy* forget loss (Section 3.4) maximizes per-token entropy only up to a threshold $\tau \cdot \log V$, producing exactly-zero gradients on already-forgotten tokens—eliminating over-forgetting. An augmented Lagrangian with asymmetric dual updates (Section 3.5) enforces retain quality as an inequality constraint that permanently ratchets after any violation—replacing static balancing with adaptive self-correction. These operate within a bilevel structure (Section 3.3) whose inner loop repairs retain damage before each outer step, with all updates confined to LoRA

adapters (Section 3.2) to bound representational drift.

We evaluate on TOFU (Maini et al., 2024) (Llama-3.2-1B/3B, three splits), MUSE (Shi et al., 2025) (Books/News, Llama-2-7B), and KnowUndo (Tian et al., 2024) (copyright/privacy, Llama-2-7B-chat). Key findings:

- **Dominant across benchmarks.** BLADE improves average composite scores over the strongest baselines by 9% on TOFU, 9% on MUSE Books, and 7% on KnowUndo, with near-zero semantic leakage confirmed by an LLM judge.
- **Robust under stress.** Under $4\times$ scaling and 4 sequential unlearning steps, BLADE maintains stable performance (HM 0.523–0.552) while the strongest baseline collapses catastrophically (HM 0.58→0.005).
- **Smooth, controllable optimization.** Training consistently follows a three-phase pattern—warm-up, spike-and-ratchet, smooth convergence—giving interpretable control over the forget–retain tradeoff absent in other baselines, whose dynamics oscillate without self-correction.

2 Related Work

LLM unlearning methods. Machine unlearning originated in the classification setting (Cao and Yang, 2015; Bourtole et al., 2021); see Liu et al. (2024); Blanco-Justicia et al. (2024) for surveys. Early approaches used Fisher information to scrub data influence (Golatkhar et al., 2020a,b) and influence functions (Koh and Liang, 2017) to identify responsible training points—later extended to iterative LLM unlearning by SOUL (Jia et al., 2024b)—but these do not transfer directly to autoregressive LLMs at scale. For LLMs, gradient ascent (GA) (Jang et al., 2023) maximizes the forget loss but diverges and destroys coherence; GradDiff (Yao et al., 2024) adds retain cross-entropy but still degrades; and Eldan and Russinovich (2023) demonstrated approximate unlearning via label replacement. Preference-based methods—NPO (Zhang et al., 2024), SimNPO (Fan et al., 2025), NGDiff (Jin et al., 2025)—collapse more gracefully but saturate without converging to a well-defined target. RMU (Li et al., 2024) steers activations to-

ward random targets for forget data. What these approaches share is the absence of a *bounded* forget loss with a per-token stopping criterion: GA diverges, NPO damps but never reaches zero, and unclamped entropy (Yuan et al., 2025) pushes indefinitely.

Parameter-efficient unlearning. LoRA (Hu et al., 2022) has been applied to unlearning via Fisher-informed initialization (LoKU; Cha et al. 2025), importance-weighted masking (Jia et al., 2024a), Fisher-based efficiency improvements (VILA; Kim et al. 2025), and gradient-based attribution (OBLIVATE; Xu et al. 2025). In BLADE, LoRA serves as a *structural constraint*: the low-rank bottleneck itself prevents catastrophic drift, analogous to how EWC (Kirkpatrick et al., 2016) protects important weights in continual learning but applied structurally rather than via per-weight penalties.

Bilevel and constrained optimization. BLUR (Reisizadeh et al., 2026) places forget in the lower level and retain in the upper, resolving conflicts via gradient projection. PDU (Entesari et al., 2025) uses a linear Lagrangian with logit-margin loss and symmetric dual updates. Cheng et al. (2026) apply ALM with an equality constraint on vision models only. BLADE differs: (a) an *inequality* constraint that never penalizes retain below ε ; (b) *asymmetric* dual updates producing ratchet behavior; (c) retain in the *inner loop* (repair-first); and (d) clamped entropy as the forget loss—bounded with a hard per-token deadzone.

Benchmarks. TOFU (Maini et al., 2024) tests factual associations with synthetic biographies and provides a gold retrained model for reference. MUSE (Shi et al., 2025) tests naturalistic memorization at scale with explicit scalability and sustainability stress tests. KnowUndo (Tian et al., 2024) targets domain-specific unlearning (copyright, privacy) from LoRA-fine-tuned models. We evaluate on all three for complementary coverage.

3 Method

Unlearning often degrades general capability because forget and retain knowledge occupy shared representations (Cheng et al., 2026; Liu et al., 2025). BLADE addresses this with three

mechanisms: a bilevel structure that repairs retain *before* each forget step (§3.3), a clamped entropy loss with a hard per-token deadzone (§3.4), and an augmented Lagrangian whose dual variable adapts the forget–retain tradeoff during training (§3.5).

3.1 Problem Setup

Let M_{θ} denote an LLM parameterized by θ (initialized from pretrained weights θ_0), $\mathcal{D}_{\text{forget}}$ the data to unlearn, and $\mathcal{D}_{\text{retain}}$ data the model should preserve. We seek θ such that (i) the output distribution of M_{θ} on $\mathcal{D}_{\text{forget}}$ is high-entropy (memorized content is forgotten) and (ii) the cross-entropy loss on $\mathcal{D}_{\text{retain}}$ remains below a threshold ε .

3.2 LoRA Parameterization

Rather than modifying full weight matrices, we attach LoRA adapters (Hu et al., 2022) to all projection matrices ($q/k/v/o_proj$, gate/up/down_proj):

$$W' = W_0 + \frac{\alpha}{r} BA, \quad B \in \mathbb{R}^{d \times r}, A \in \mathbb{R}^{r \times d} \quad (1)$$

where $r \ll d$ is the rank and α/r is a scaling factor. With $r=16$ on a 7B model, only $\sim 0.2\%$ of parameters are trainable. The low-rank bottleneck limits what the update can express, preventing catastrophic weight drift even under aggressive forgetting gradients. Another practical benefit is that disabling the adapters keeps the original model intact which simplifies rollback, debugging and subsequent forget/retain requests. With the parameter space constrained, the remaining question is how to organize the optimization itself.

3.3 Bilevel Formulation

We decompose the problem into two nested optimization levels: *retain in the inner loop, forget in the outer loop*.

Inner loop (retain preservation). For each outer step, we run K SGD steps on the retain set:

$$\theta \leftarrow \theta - \eta_{\text{in}} \nabla_{\theta} \mathcal{L}_{\text{CE}}(M_{\theta}; \mathcal{B}_{\text{ret}}) \quad (2)$$

where $\mathcal{B}_{\text{ret}} \sim \mathcal{D}_{\text{retain}}$ is a mini-batch and $\mathcal{L}_{\text{CE}}$ is cross-entropy. The inner loop uses a reliably faster learning rate (η_{in}) to restore any retain damage from the previous outer step.

Outer loop (constrained forgetting).

The outer objective combines the forget loss with an inequality constraint on retain performance, enforced via an augmented Lagrangian:

$$\mathcal{L}_{\text{outer}} = \mathcal{L}_{\text{fgt}} + \lambda r + \frac{\rho}{2} [\max(0, r)]^2, \quad r = L_{\text{ret}} - \varepsilon \quad (3)$$

where $L_{\text{ret}} = \mathcal{L}_{\text{CE}}(M_{\theta}; \mathcal{B}'_{\text{ret}})$ is evaluated on a *fresh* retain batch (separate from the inner loop), λ is the Lagrange multiplier, ρ is the quadratic penalty coefficient, and ε is the retain budget. The outer loop uses a slower learning rate (η_{out}) compared to the inner loop, keeping each forgetting step small enough for the inner loop to repair.

Repair-first principle. Prior two-level unlearning methods like SCRUB (Kurmanji et al., 2023) (min-max) and BLUR (Reisizadeh et al., 2026) (bilevel with gradient projection) prioritize forgetting at the lower level and treat retain as the upper-level concern. We invert this assignment.

Forgetting is inherently destructive: gradient ascent, entropy maximization, and preference-based losses all push the model *away* from learned representations, causing catastrophic collapse when unconstrained (Zhang et al., 2024). To make matters worse, forget and retain knowledge share entangled representations (Cheng et al., 2026), so perturbing forget tokens inevitably disturbs retain performance.

Retain repair therefore belongs in the inner loop as a stabilizing anchor. It runs first and comparably faster ($\eta_{\text{in}} > \eta_{\text{out}}$), so the model enters each outer step from a state with good retain performance. The outer loop then applies one small forgetting step, sized so the next inner loop can fully repair any collateral damage. This prevents the accumulation of representational drift that makes recovery progressively harder when the loops are reversed.

For this structure to work, the forget loss in the outer loop must be well-behaved: bounded, self-saturating, and compatible with small step sizes. We introduce *clamped entropy* to address this.

3.4 Clamped Entropy Loss

Entropy maximization as a forget objective is well-known (Yuan et al., 2025), but unclamped

formulations apply nonzero gradients to every token at every step, even those already near-uniform—needlessly perturbing shared representations. We introduce *clamped entropy*, which defines when a token is “sufficiently forgotten” and stops optimizing it:

$$\mathcal{L}_{\text{forget}} = \frac{1}{N} \sum_{t=1}^N \max(0, \tau \cdot H_{\text{max}} - H(p_t)) \quad (4)$$

where $p_t = \text{softmax}(z_t)$ is the output distribution at position t , $H(p_t) = -\sum_v p_t(v) \log p_t(v)$ is its Shannon entropy, $H_{\text{max}} = \log V$ is the maximum entropy over vocabulary V , and $\tau \in (0, 1)$ is the target fraction. Normalizing by H_{max} makes τ vocabulary-invariant: the same τ applies regardless of whether the vocabulary has 32K (Touvron et al., 2023) or 128K tokens (Grattafiori et al., 2024).

The $\max(0, \cdot)$ clamp produces a hard deadzone: once $H(p_t) \geq \tau \cdot H_{\text{max}}$, token t ’s gradient is *exactly zero*. This makes the loss bounded ($\mathcal{L}_{\text{forget}} \in [0, \tau \cdot H_{\text{max}}]$), self-stabilizing (the effective perturbation shrinks as tokens are forgotten), and reference-free (no frozen model needed, unlike NPO). The bounded outer perturbation (Proposition 1) ensures the inner loop can reliably repair retain damage at any training stage.

Clamped entropy yields well-behaved forget gradients, but the remaining challenge is adapting *how much* retain protection the outer loop enforces as the loss landscape evolves.

3.5 Augmented Lagrangian with Asymmetric Dual Update

The multiplier λ controls how aggressively the outer objective protects retain performance. Rather than treating it as a fixed hyperparameter, we learn it via a dual update rule.

Standard ALM uses symmetric updates designed for equality constraints (Bertsekas, 1982; Nocedal and Wright, 2006). We instead enforce the *inequality* $L_{\text{ret}} \leq \varepsilon$: the quadratic penalty $\frac{\rho}{2} [\max(0, r)]^2$ activates only when violated (Eq. 3), so the model is never penalized for retain loss below ε . On top of this, we apply an *asymmetric* dual update:

$$\lambda \leftarrow \begin{cases} \lambda + \rho |r| & \text{if } r > 0 \\ \lambda - \alpha \rho |r| & \text{if } r \leq 0 \end{cases} \quad (5)$$

Algorithm 1 BLADE: Bilevel Augmented Lagrangian Unlearning

Require: Model M with frozen weights θ_0 , $\mathcal{D}_{\text{forget}}$, $\mathcal{D}_{\text{retain}}$
Require: Hyperparams: K , η_{in} , η_{out} , ε_{mul} , ρ , λ_0 , α , τ , T

- 1: Attach LoRA adapters to M ; $\theta \leftarrow$ LoRA params
- 2: $\lambda \leftarrow \lambda_0$
- 3: $\varepsilon \leftarrow \varepsilon_{\text{mul}} \cdot \frac{1}{K} \sum_{k=1}^K \mathcal{L}_{\text{CE}}^{(k)}(\mathcal{D}_{\text{retain}})$
- 4: **for** $t = 1$ **to** T **do**
- 5: **Inner loop** (retain repair):
- 6: **for** $k = 1$ **to** K **do**
- 7: $\theta \leftarrow \theta - \eta_{\text{in}} \nabla_{\theta} \mathcal{L}_{\text{CE}}(M_{\theta}; \mathcal{B}_{\text{ret}})$
- 8: **end for**
- 9: **Forget loss** (clamped entropy):
- 10: $\mathcal{L}_{\text{fgt}} \leftarrow \frac{1}{N} \sum_{i=1}^N \max(0, \tau \log V - H(p_i))$
- 11: **Outer loss** (augmented Lagrangian):
- 12: $r \leftarrow \mathcal{L}_{\text{CE}}(M_{\theta}; \mathcal{B}_{\text{ret}}) - \varepsilon$
- 13: $\mathcal{L}_{\text{outer}} \leftarrow \mathcal{L}_{\text{fgt}} + \lambda r + \frac{\rho}{2} [\max(0, r)]^2$
- 14: $\theta \leftarrow \theta - \eta_{\text{out}} \cdot \text{Adam}(\nabla_{\theta} \mathcal{L}_{\text{outer}})$
- 15: **Dual update** (asymmetric ratchet):
- 16: **if** $r > 0$ **then**
- 17: $\lambda \leftarrow \lambda + \rho |r|$
- 18: **else**
- 19: $\lambda \leftarrow \lambda - \alpha \rho |r|$
- 20: **end if**
- 21: **end for**
- 22: **return** M with trained LoRA adapters

where $\alpha \ll 1$. The slower decay means that once a retain violation drives λ up, it stays elevated—preventing the repeated oscillation cycles observed with symmetric updates (PDU (Entesari et al., 2025); see Appendix E).

Rather than hand-tuning ε , we set it as a fraction (ε_{mul}) of the model’s average retain loss over one inner loop, so the constraint budget scales with the model’s own retain difficulty and requires no manual calibration across benchmarks (Appendix E).

Convergence criterion. Training terminates when an exponential moving average of the per-step $\mathcal{L}_{\text{fgt}}$ change drops below a fraction of its peak—indicating that remaining tokens have entered the deadzone. A safety cap T prevents runaway training (Appendix B.3).

3.6 Algorithm Summary

Algorithm 1 summarizes the complete procedure: each outer step first runs K inner retain-repair steps, then computes the augmented Lagrangian outer loss, and finally updates the dual variable asymmetrically.

4 Experiments

We evaluate BLADE on three benchmarks that test complementary aspects of unlearning: factual association removal, naturalistic

memorization at scale, and domain-specific knowledge extraction from adapted models. All methods are implemented and evaluated within the OpenUnlearning framework (Shi et al., 2025) to ensure fair comparison under identical data processing, evaluation protocols, and compute budgets. We use the standard baselines provided by OpenUnlearning (GradAscent, GradDiff, NPO, SimNPO, RMU) and additionally include BLURNPO (Reisizadeh et al., 2026) and PDU (Entesari et al., 2025) as constraint-based approaches compatible with the framework. Baseline hyperparameters are listed in Appendix Table 6. All experiments report means and standard deviations over 5 random seeds unless noted.

4.1 Setup

Benchmarks. TOFU (Maini et al., 2024) provides a controlled testbed with 200 synthetic author biographies and QA pairs, evaluated on Llama-3.2-1B/3B-Instruct across three forget splits (1%/5%/10%). Each split removes an increasing fraction of the training authors, testing whether the method scales gracefully. A gold retrained model provides an upper bound.

MUSE (Shi et al., 2025) tests naturalistic memorization on Llama-2-7B across two corpora: *Books* (Harry Potter, a single cohesive document) and *News* (889 BBC articles, a distributed multi-document set). Beyond standard forget/retain performance, MUSE also tests scalability (larger forget sets) and sustainability (sequential unlearning from the same checkpoint), which we evaluate in §4.6.

KnowUndo (Tian et al., 2024) targets copyright and privacy domains on Llama-2-7B-chat that was LoRA-fine-tuned on domain-specific corpora. Unlike MUSE where memorization arises from pretraining, here the target knowledge was explicitly injected via LoRA adaptation—testing whether unlearning can reverse fine-tuning without destroying general capability.

Metrics. Each benchmark uses different axes. For TOFU: Model Utility (MU $\uparrow$, retain quality), forget-set answer Probability (Prob $\downarrow$), and forget-set ROUGE-L (RG $\downarrow$). For MUSE: forget knowledge memorization (fk $\downarrow$), verbatim memorization (vm $\downarrow$), and retain knowl-

edge (rk $\uparrow$). We aggregate each benchmark’s metrics into a single *harmonic mean* (HM) that penalizes methods sacrificing one axis for another. Full metric definitions and per-benchmark HM formulas are given in Appendix B.2.

LLM judge. Token-overlap metrics like ROUGE can miss semantic leakage—a model may paraphrase memorized content without triggering string-match detectors. We supplement standard metrics with an LLM judge (Claude Opus 4.7) that scores model generations on a 0–2 scale along three dimensions: Forget Leakage (FL $\downarrow$), Retain Accuracy (RA $\uparrow$), and retain Response Quality (rRQ $\uparrow$). The judge composite $HM_J = \text{hmean}(1 - \text{FL}/2, \text{RA}/2, \text{rRQ}/2)$ normalizes all axes to $[0, 1]$ and provides a unified evaluation across all benchmarks.

4.2 TOFU (Llama-3.2-1B-Instruct)

BLADE achieves $HM \geq 0.800$ across all three forget splits (Table 1), consistently outperforming all baselines including PDU (0.690/0.740/0.797). The LLM judge (Figure 2) confirms near-zero semantic leakage: $HM_J = 0.929/0.919/0.919$ vs. PDU’s 0.746/0.850/0.906, indicating that BLADE’s forgetting extends beyond surface-level token suppression (see also qualitative analysis in Appendix G). On 3B model (Appendix C), BLADE remains strong ($HM = 0.846/0.842/0.836$); PDU is competitive (0.742/0.843/0.857) but the gap is small and BLADE retains its advantage in LLM judge score in all experiments.

4.3 MUSE (Llama-2-7B)

On Books, BLADE achieves $HM = 0.818$, surpassing SimNPO (0.753) and BLURNPO (0.742) while eliminating verbatim memorization ($vm = 0.000$) and preserving the strongest retain ($rk = 0.638$). PDU’s unbounded loss causes retain collapse ($rk = 0.372$, $HM = 0.600$). On News, PDU leads (0.577 vs. BLADE 0.544)—an edge that does not survive stress-testing (§4.6).

4.4 KnowUndo (Llama-2-7B-chat)

BLADE achieves the best HM on both domains (Figure 1): copyright (0.477 vs. SimNPO 0.461, PDU 0.442) and privacy (0.605

Table 1: TOFU results on Llama-3.2-1B-Instruct (5 seeds). HM = hmean(MU, 1-Prob, 1-RG). Best per column in **bold** (excl. Gold and collapsed models).

Method	Forget 1%				Forget 5%				Forget 10%			
	MU↑	Prob↓	RG↓	HM↑	MU↑	Prob↓	RG↓	HM↑	MU↑	Prob↓	RG↓	HM↑
Gold (retrain)	.597	.166	.414	.655	.599	.127	.383	.676	.591	.116	.379	.677
GradAscent	.596±.00	.477±.01	.456±.01	.553±.01	.008±.01	.003±.01	.112±.08	.022±.04	.000±.00	.000±.00	.001±.00	.000±.00
GradDiff	.581±.01	.421±.04	.464±.02	.564±.01	.453±.00	.073±.00	.375±.01	.614±.01	.435±.00	.047±.00	.339±.01	.617±.00
NPO	.596±.00	.474±.01	.438±.02	.560±.01	.454±.01	.245±.01	.308±.01	.603±.01	.393±.03	.213±.01	.210±.01	.590±.02
SimNPO	.594±.00	.858±.01	.734±.02	.240±.01	.596±.00	.848±.00	.741±.01	.248±.00	.597 ±.00	.842±.00	.734±.01	.255±.00
RMU	.557±.00	.414±.01	.415±.00	.576±.00	.546±.00	.369±.01	.423±.01	.583±.00	.572±.00	.106±.02	.322±.01	.691±.01
BLURNPO	.598±.00	.676±.01	.588±.02	.417±.01	.518±.02	.479±.07	.407±.05	.541±.04	.089±.14	.087±.04	.253±.09	.154±.20
PDU	.602 ±.00	.186±.01	.313±.01	.690±.01	.588±.00	.073±.02	.214±.03	.740±.01	.592±.00	.004 ±.00	.065±.01	.797±.00
BLADE	.599±.00	.002 ±.00	.038 ±.00	.808 ±.00	.597 ±.00	.015 ±.00	.054 ±.01	.800 ±.00	.593±.01	.009±.00	.039 ±.01	.803 ±.00

Table 2: MUSE results (5 seeds). HM = hmean(1-fk, 1-vr, rk). Best per column in **bold** (excl. Gold and collapsed models).

Method	Books				News			
	fk↓	vr↓	rk↑	HM↑	fk↓	vr↓	rk↑	HM↑
Gold (retrain)	.303	.145	.687	.739	.324	.204	.552	.660
GradAscent	.000±.00	.000±.00	.000±.00	.000±.00	.001±.00	.020±.02	.003±.00	.009±.01
GradDiff	.000±.00	.000±.00	.004±.00	.011±.01	.329±.03	.043 ±.02	.269±.02	.479±.02
NPO	.303±.02	.342±.03	.574±.02	.638±.01	.517±.02	.274±.02	.435±.01	.522±.01
SimNPO	.238±.02	.002±.00	.600±.01	.753±.01	.628±.01	.542±.01	.513 ±.01	.440±.00
RMU	.210±.00	.113±.01	.598±.01	.738±.00	.495±.01	.267±.01	.434±.01	.531±.00
BLURNPO	.175±.01	.000 ±.00	.547±.02	.742±.01	.302 ±.04	.146±.04	.274±.02	.478±.01
PDU	.139±.01	.129±.01	.372±.01	.600±.01	.525±.02	.092±.07	.508±.04	.577 ±.01
BLADE	.089 ±.02	.000 ±.00	.638 ±.01	.818 ±.01	.545±.02	.211±.03	.490±.01	.544±.01




Figure 1: KnowUndo results (5 seeds). Error bars: ± 1 std. Full tables in Appendix C.

vs. PDU 0.546, SimNPO 0.544). Privacy is the harder domain—the fine-tuned model recalls 66.5% of target content vs. 24.4% for copyright—yet BLADE reduces this by 81% while retaining 87% of the original retain quality (full results in Appendix Table 11).

4.5 LLM Judge

Figure 2 summarizes the LLM judge evaluation. The judge scores complement and confirm the HM rankings without contradicting them—methods that score well on HM also score well on HM_J—while additionally revealing semantic leakage invisible to token-overlap metrics. BLADE achieves the highest HM_J on 6 of 7 settings, with particularly large margins on TOFU 1B (0.929/0.919/0.919 across splits vs. PDU’s 0.746/0.850/0.906). On KnowUndo, the judge confirms strong forgetting with preserved response quality (copyright HM_J=0.78, privacy HM_J=0.83), both substantially above the next-best method. The only setting where

BLADE does not lead is MUSE News, where PDU achieves a higher judge score—consistent with its stronger HM on that benchmark.

4.6 Scalability and Sustainability

PDU is the closest contender across benchmarks and the strongest baseline on MUSE News. Among our benchmarks, MUSE News provides explicit stress tests along two axes: *scalability* (1–4× forget set size) and *sustainability* (sequential unlearning from the same checkpoint), making it the natural arena for a head-to-head comparison.

BLADE remains stable across conditions: HM stays within 0.523–0.552 through 4× scale and 4 sequential steps (Figure 3). By contrast, PDU collapses at 4× scale (HM=0.005) and after just 2 sequential steps (0.58→0.02). The bounded loss, LoRA bottleneck, and asymmetric ALM ratchet together prevent the gradient explosion that causes this catastrophic failure under repeated application.

4.7 Ablation Study

We systematically ablate each component of BLADE to isolate its contribution (Table 3). The results reveal a clear hierarchy of component necessity:

Constraint enforcement (ALM). The augmented Lagrangian is the most critical component. Without it ($\lambda=0, \rho=0$), the forget ob-




Figure 2: LLM judge scores (HM_J) across all benchmarks and settings. Error bars: ± 1 std over 5 seeds. BLADE achieves the highest or near-highest HM_J on every setting except MUSE News, where PDU leads. KnowUndo uses Opus 4.6 as judge (Opus 4.7 safety guardrails refuse on copyrighted content).

Table 3: Ablation on MUSE Books (seed=42). Each row modifies one design choice from the full BLADE.

Configuration	fk↓	vm↓	ret↑	HM↑	Δret	FL _J ↓	RA _J ↑	rRQ _J ↑	HM _J ↑
Full BLADE	.110	.000	.658	.823	—	0.14	1.40	1.69	.814
$K=0$ (no inner loop)	.072	.000	.631	.819	−.027	0.10	1.37	1.68	.811
$\tau=1.0$ (unclamped entropy)	.161	.003	.604	.780	−.054	0.20	1.34	1.64	.785
No LoRA (full fine-tuning)	.002	.000	.306	.459	−.352	0.00	0.70	1.25	.550
ALM off ($\lambda=0, \rho=0$)	.000	.002	.092	.233	−.566	0.01	0.24	0.28	.117
Swapped bilevel (forget inner)	.372	.643	.651	.506	−.007	0.99	1.36	1.77	.655
GA forget loss	.006	.003	.060	.160	−.598	0.01	0.10	0.18	.093
NPO forget loss	.457	.997	.662	.009	+.004	1.44	1.47	1.72	.495
Logit margin forget loss	.000	.000	.000	.000	−.658	0.00	0.00	0.00	.000




Figure 3: Scalability and sustainability on MUSE News. PDU collapses at 4 $\times$ scale and after 2 sequential steps. BLADE degrades gracefully.

jective dominates unchecked and the model collapses ($HM=0.233$). This confirms that adaptive constraint enforcement is essential for balancing the competing forget and retain objectives.

Parameterization (LoRA). Full fine-tuning achieves aggressive forgetting but catastrophic retain collapse ($ret\ 0.658 \rightarrow 0.306$, $HM=0.459$). The low-rank bottleneck provides implicit regularization by limiting the subspace available for unlearning updates, preventing representational drift beyond the forget-relevant parameters.

Forget loss. Only clamped entropy works within the bilevel framework. Gradient ascent ($HM=0.160$), NPO ($HM=0.009$), and logit margin ($HM=0.000$) all cause catastrophic fail-

ure even with the full ALM apparatus intact, because their unbounded or trivially-satisfied objectives overwhelm or bypass the constraint mechanism. These failures demonstrate that the contribution is not the individual components but their specific interaction: only a bounded, self-saturating forget loss is compatible with constrained bilevel optimization—naive combinations of known techniques collapse. Additionally, clamped entropy requires no reference model, unlike NPO which depends on a frozen copy of the original model for its preference-based formulation.

Bilevel structure. Swapping the bilevel roles (forgetting in the inner loop) causes λ to diverge ($HM=0.506$), confirming the “repair first, forget carefully” design principle: without restoring retain quality before each forget step, the ALM ratchet fires continuously and over-penalizes forgetting. On MUSE Books the marginal gain from $K=3$ over $K=0$ appears modest ($HM\ 0.823$ vs. 0.819), likely because the ALM compensates for absent inner repair on this benchmark. Under harder optimization landscapes—higher retain-forget entanglement or larger forget sets—the inner loop’s pre-correction is expected to become




Figure 4: Training dynamics on MUSE Books. Top: BLADE (warm-up $\rightarrow$ spike-and-ratchet $\rightarrow$ smooth convergence). Bottom: PDU (recurring oscillations). Full dynamics across all benchmarks in Appendix E.

increasingly necessary; an ε -multiplier sweep across 8 operating points on MUSE News confirms consistent improvements with $K=3$ (Figure 6 in appendix).

4.8 Training Dynamics

For unlearning to be deployed reliably, the optimization must be interpretable and predictable—practitioners need to trust that the process will converge without silent retain degradation. BLADE exhibits consistent three-phase dynamics across all benchmarks, model scales, and dataset types (Figure 4): (1) *warm-up*—forget loss declines while retain stays within ε ; (2) *spike-and-ratchet*—a transient retain violation triggers the asymmetric ALM to permanently increase λ ; and (3) *smooth convergence*—both losses decrease monotonically under the elevated λ . We observe this three-phase pattern consistently across all experiments (Figure 4; Appendix E). This self-correcting behavior contrasts sharply with PDU’s recurring retain oscillations throughout training, which may explain its fragility under scaling and sequential application (§4.6). The λ trajectory adjusts the optimization landscape automatically: tighter constraints produce higher λ , absorbing parameter variation without performance degradation—a hyperparameter sensitivity sweep confirms that BLADE remains stable across wide parameter ranges (Appendix F).

4.9 Adversarial Robustness

An unlearned model deployed behind an API remains vulnerable to adversarial users who rephrase queries to elicit forgotten content. We evaluate resistance to such extraction attacks (paraphrased and perturbed queries) on TOFU across both 1B and 3B models. BLADE achieves the highest adversarial HM on 1B across all splits and remains competitive with PDU on 3B, consistent with the standard metric rankings. Under a strictly stronger threat model—where an adversary can fine-tune the model on the original forget data—BLADE’s performance degrades (Appendix D).

5 Conclusion

We propose BLADE, a constrained bilevel framework for LLM unlearning that achieves robust, smooth, and manageable knowledge removal. Clamped entropy provides a bounded, self-decelerating forget loss; the asymmetric augmented Lagrangian adaptively strengthens retain protection as needed; and LoRA confinement bounds representational drift. Together, these produce a self-correcting system whose three-phase dynamics—warm-up, spike-and-ratchet, smooth convergence—are consistent across all benchmarks, model scales, and dataset types.

BLADE achieves strong results across TOFU, MUSE, and KnowUndo, and maintains stable performance under $4\times$ scaling and 4 sequential unlearning steps—confirming that the constrained formulation provides genuine robustness beyond single-setting gains.

Limitations BLADE targets factual and knowledge-level unlearning; it has not been tested on conceptual or representation-level domain removal (e.g., all unsafe biology knowledge) where forget–retain entanglement may exceed what LoRA can selectively target. Second, while BLADE resists black-box extraction attacks, it is susceptible to re-learning attacks—a strictly stronger threat model that assumes an adversary with both white-box weight access and possession of the original forget data. Finally, BLADE has only been evaluated on text-only LLMs; its effectiveness on multimodal models remains untested. These are challenges worth exploring in future endeavours.

References

- Dimitri P Bertsekas. 1982. *Constrained optimization and Lagrange multiplier methods*. Academic press.
- Alberto Blanco-Justicia, Najeeb Moharram Jebreel, Benet Manzanares-Salor, David Sánchez, Josep Domingo-Ferrer, Guillem Collell, and Kuan Eeik Tan. 2024. [Digital forgetting in large language models: a survey of unlearning methods](#). *Artificial Intelligence Review*, 58.
- Lucas Bourtole, Varun Chandrasekaran, Christopher A. Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. 2021. [Machine unlearning](#). *2021 IEEE Symposium on Security and Privacy (SP)*, pages 141–159.
- Yinzhi Cao and Junfeng Yang. 2015. [Towards making systems forget with machine unlearning](#). In *Proceedings of the 2015 IEEE Symposium on Security and Privacy, SP '15*, page 463–480, USA. IEEE Computer Society.
- Nicholas Carlini, Florian Tramèr, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Úlfar Erlingsson, Alina Oprea, and Colin Raffel. 2021. [Extracting training data from large language models](#). In *30th USENIX Security Symposium (USENIX Security 21)*, pages 2633–2650. USENIX Association.
- Sungmin Cha, Sungjun Cho, Dasol Hwang, and Moontae Lee. 2025. [Towards robust and parameter-efficient knowledge unlearning for LLMs](#). In *The Thirteenth International Conference on Learning Representations*.
- Jingpu Cheng, Ping Liu, Qianxiao Li, and CHI ZHANG. 2026. [Machine unlearning under retain-forget entanglement](#). In *The Fourteenth International Conference on Learning Representations*.
- Ronen Eldan and Mark Russinovich. 2023. [Who’s harry potter? approximate unlearning in llms](#). *Preprint*, arXiv:2310.02238.
- Taha Entesari, Arman Hatami, Rinat Khaziev, Anil Ramakrishna, and Mahyar Fazlyab. 2025. [Constrained entropic unlearning: A primal-dual framework for large language models](#). In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*.
- Chongyu Fan, Jiancheng Liu, Licong Lin, Jinghan Jia, Ruiqi Zhang, Song Mei, and Sijia Liu. 2025. [Simplicity prevails: Rethinking negative preference optimization for LLM unlearning](#). In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*.
- Aditya Golatkar, Alessandro Achille, and Stefano Soatto. 2020a. [Eternal sunshine of the spotless net: Selective forgetting in deep networks](#). In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.
- Aditya Golatkar, Alessandro Achille, and Stefano Soatto. 2020b. [Forgetting outside the box: Scrubbing deep networks of information accessible from input-output observations](#). In *Computer Vision – ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XXIX*, page 383–398, Berlin, Heidelberg. Springer-Verlag.
- Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, and 1 others. 2024. [The llama 3 herd of models](#). *Preprint*, arXiv:2407.21783.
- Edward J Hu, yelong shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. [LoRA: Low-rank adaptation of large language models](#). In *International Conference on Learning Representations*.
- Joel Jang, Dongkeun Yoon, Sohee Yang, Sungmin Cha, Moontae Lee, Lajanugen Logeswaran, and Minjoon Seo. 2023. [Knowledge unlearning for mitigating privacy risks in language models](#). In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2023, Toronto, Canada, July 9–14, 2023*, pages 14389–14408. Association for Computational Linguistics.
- Jinghan Jia, Jiancheng Liu, Yihua Zhang, Parikshit Ram, Nathalie Baracaldo, and Sijia Liu. 2024a. [WAGLE: Strategic weight attribution for effective and modular unlearning in large language models](#). In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.
- Jinghan Jia, Yihua Zhang, Yimeng Zhang, Jiancheng Liu, Bharat Runwal, James Duffenderfer, Bhavya Kailkhura, and Sijia Liu. 2024b. [SOUL: Unlocking the power of second-order optimization for LLM unlearning](#). In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 4276–4292, Miami, Florida, USA. Association for Computational Linguistics.
- Xiaomeng Jin, Zhiqi Bu, Bhanukiran Vinzamuri, Anil Ramakrishna, Kai-Wei Chang, Volkan Cevher, and Mingyi Hong. 2025. [Unlearning as multi-task optimization: A normalized gradient difference approach with an adaptive learning rate](#). In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long*

737	<i>Papers</i>), pages 11278–11294, Albuquerque, New Mexico. Association for Computational Linguistics.	792
738		793
739		794
740	Yejin Kim, Eunwon Kim, Buru Chang, and Jun-	795
741	suk Choe. 2025. Improving fisher information	
742	estimation and efficiency for loRA-based LLM	
743	unlearning . In <i>Second Conference on Language</i>	
744	<i>Modeling</i> .	
745	James Kirkpatrick, Razvan Pascanu, Neil C. Ra-	
746	binowitz, Joel Veness, Guillaume Desjardins,	
747	Andrei A. Rusu, Kieran Milan, John Quan,	
748	Tiago Ramalho, Agnieszka Grabska-Barwinska,	
749	Demis Hassabis, Claudia Clopath, Dharshan Ku-	
750	maran, and Raia Hadsell. 2016. Overcoming	
751	catastrophic forgetting in neural networks . <i>Pro-</i>	
752	<i>ceedings of the National Academy of Sciences</i> ,	
753	114:3521 – 3526.	
754	Pang Wei Koh and Percy Liang. 2017. Understand-	
755	ing black-box predictions via influence func-	
756	tions. In <i>Proceedings of the 34th International</i>	
757	<i>Conference on Machine Learning - Volume 70</i> ,	
758	ICML’17, page 1885–1894. JMLR.org.	
759	Meghdad Kurmanji, Peter Triantafillou, Jamie	
760	Hayes, and Eleni Triantafillou. 2023. Towards	
761	unbounded machine unlearning . In <i>Thirty-</i>	
762	<i>seventh Conference on Neural Information Pro-</i>	
763	<i>cessing Systems</i> .	
764	Nathaniel Li, Alexander Pan, Anjali Gopal, Sum-	
765	mer Yue, Daniel Berrios, Alice Gatti, Justin D.	
766	Li, Ann-Kathrin, and 1 others. 2024. The	
767	WMDP benchmark: Measuring and reducing	
768	malicious use with unlearning . In <i>Forty-first In-</i>	
769	<i>ternational Conference on Machine Learning</i> .	
770	Sijia Liu, Yuanshun Yao, Jinghan Jia, Stephen	
771	Casper, Nathalie Baracaldo, Peter Hase,	
772	Yuguang Yao, Chris Yuhao Liu, Xiaojun Xu,	
773	Hang Li, and 1 others. 2025. Rethinking	
774	machine unlearning for large language models.	
775	<i>Nature Machine Intelligence</i> , 7(2):181–194.	
776	Zheyuan Liu, Guangyao Dou, Zhaoxuan Tan, Yi-	
777	jun Tian, and Meng Jiang. 2024. Machine un-	
778	learning in generative ai: A survey . <i>Preprint</i> ,	
779	arXiv:2407.20516.	
780	Pratyush Maini, Zhili Feng, Avi Schwarzschild,	
781	Zachary Chase Lipton, and J Zico Kolter. 2024.	
782	TOFU: A task of fictitious unlearning for LLMs .	
783	In <i>First Conference on Language Modeling</i> .	
784	Jorge Nocedal and Stephen J Wright. 2006. <i>Nu-</i>	
785	<i>merical optimization</i> . Springer.	
786	Hadi Reisizadeh, Jinghan Jia, Zhiqi Bu, Bhanuki-	
787	ran Vinzamuri, Anil Ramakrishna, Kai-Wei	
788	Chang, Volkan Cevher, Sijia Liu, and Mingyi	
789	Hong. 2026. BLUR: A bi-level optimization ap-	
790	proach for LLM unlearning . In <i>Proceedings of</i>	
791	<i>the 19th Conference of the European Chapter</i>	
	<i>of the Association for Computational Linguis-</i>	792
	<i>tics (Volume 1: Long Papers)</i> , pages 7043–7058,	793
	Rabat, Morocco. Association for Computational	794
	Linguistics.	795
	Weijia Shi, Jaechan Lee, Yangsibo Huang, Sadhika	796
	Malladi, Jieyu Zhao, Ari Holtzman, Daogao Liu,	797
	Luke Zettlemoyer, Noah A. Smith, and Chiyuan	798
	Zhang. 2025. MUSE: Machine unlearning six-	799
	way evaluation for language models . In <i>The</i>	800
	<i>Thirteenth International Conference on Learn-</i>	801
	<i>ing Representations</i> .	802
	Chris Stokel-Walker. 2026. Scientists invented a	803
	fake disease. AI told people it was real . <i>Nature</i> ,	804
	652(8110):559–561. News Feature.	805
	Bozhong Tian, Xiaozhuan Liang, Siyuan Cheng,	806
	Qingbin Liu, Mengru Wang, Dianbo Sui,	807
	Xi Chen, Huajun Chen, and Ningyu Zhang.	808
	2024. To forget or not? towards practical knowl-	809
	edge unlearning for large language models . In	810
	<i>Findings of the Association for Computational</i>	811
	<i>Linguistics: EMNLP 2024</i> , pages 1524–1537,	812
	Miami, Florida, USA. Association for Compu-	813
	tational Linguistics.	814
	Hugo Touvron, Louis Martin, Kevin Stone, Pe-	815
	ter Albert, Amjad Almahairi, Yasmine Babaei,	816
	Nikolay Bashlykov, Soumya Batra, Prajjwal	817
	Bhargava, Shrutu Bhosale, and 1 others. 2023.	818
	Llama 2: Open foundation and fine-tuned chat	819
	models . <i>Preprint</i> , arXiv:2307.09288.	820
	Paul Voigt and Axel von dem Bussche. 2017.	821
	<i>The EU General Data Protection Regulation</i>	822
	<i>(GDPR): A Practical Guide</i> . Springer.	823
	Xiaoyu Xu, Minxin Du, Qingqing Ye, and Haibo	824
	Hu. 2025. OBLIViate: Robust and practical	825
	machine unlearning for large language models .	826
	In <i>Proceedings of the 2025 Conference on Em-</i>	827
	<i>pirical Methods in Natural Language Processing</i> ,	828
	pages 3696–3715, Suzhou, China. Association	829
	for Computational Linguistics.	830
	Yuanshun Yao, Xiaojun Xu, and Yang Liu. 2024.	831
	Large language model unlearning. In <i>Proceed-</i>	832
	<i>ings of the 38th International Conference on</i>	833
	<i>Neural Information Processing Systems, NIPS</i>	834
	’24, Red Hook, NY, USA. Curran Associates Inc.	835
	Xiaojian Yuan, Tianyu Pang, Chao Du, Kejiang	836
	Chen, Weiming Zhang, and Min Lin. 2025. A	837
	closer look at machine unlearning for large lan-	838
	guage models . In <i>The Thirteenth International</i>	839
	<i>Conference on Learning Representations</i> .	840
	Ruiqi Zhang, Licong Lin, Yu Bai, and Song Mei.	841
	2024. Negative preference optimization: From	842
	catastrophic collapse to effective unlearning . In	843
	<i>First Conference on Language Modeling</i> .	844

Appendix

A Theoretical Analysis

We provide formal justification for two key design choices in BLADE: (i) bounded loss and gradient control of the clamped entropy objective (§A.1), and (ii) the selective uncertainty property enabled by sub-maximal entropy clamping (§A.2). Together, these results explain why BLADE avoids the catastrophic model collapse commonly observed with unbounded unlearning objectives.

A.1 Bounded Loss and Gradient of Clamped Entropy

Let V denote the vocabulary size, $\tau \in (0, 1)$ a clamping ratio, and $p_{\theta}(\cdot | x_{<t})$ the next-token distribution produced by a language model with parameters θ . Define the per-token Shannon entropy $H_t(\theta) = -\sum_{v=1}^V p_{\theta}(v | x_{<t}) \log p_{\theta}(v | x_{<t})$ and the clamped entropy loss for a single token as

$$\ell_t(\theta) = \max(0, \tau \log V - H_t(\theta)). \quad (6)$$

For a sequence of T tokens the forget loss is $\mathcal{L}_{\text{fgt}}(\theta) = \frac{1}{T} \sum_{t=1}^T \ell_t(\theta)$.

Proposition 1 (Bounded Loss and Gradient of Clamped Entropy). *Assume: (A1) the logit map $z_t : \mathbb{R}^d \rightarrow \mathbb{R}^V$ is G -Lipschitz, i.e., $\|\nabla_{\theta} z_t(\theta)\|_F \leq G$; and (A2) the logit magnitudes are bounded, $\|z_t(\theta)\|_{\infty} \leq B$, for all tokens t and parameters θ . Then:*

- (a) *The loss is bounded: $0 \leq \ell_t(\theta) \leq \tau \log V$ for all θ .*
- (b) *The per-token gradient norm satisfies*

$$\|\nabla_{\theta} \ell_t(\theta)\| \leq (2B + \log V) G. \quad (7)$$

- (c) *In contrast, the gradient ascent loss $\mathcal{L}_{\text{GA}} = -\log p_{\theta}(y_t | x_{<t})$ has unbounded loss values as $p_{\theta}(y_t) \rightarrow 0$, and unclamped entropy maximization $\mathcal{L}_{\text{ent}} = -H_t$ applies nonzero gradients even when H_t is already near $H_{\max}$.*

Proof. (a) Since $0 \leq H_t \leq \log V$ and $\tau \in (0, 1)$, the ReLU outputs a value in $[0, \tau \log V]$.

(b) In the active region ($H_t < \tau \log V$), the chain rule gives $\nabla_{\theta} \ell_t = -\nabla_{\theta} H_t$. The v -th component of the entropy gradient with respect to logits is:

$$\frac{\partial H_t}{\partial z_{t,v}} = -p_v(H_t + \log p_v).$$

Under assumption (A2), $p_v \geq e^{-2B}/V$ for all v , yielding $|\log p_v| \leq 2B + \log V$. Since $H_t \geq 0$ and $\log p_v \geq -(2B + \log V)$, we have $|H_t + \log p_v| \leq 2B + \log V$. Since $p_v^2 \leq p_v$ for $p_v \in [0, 1]$:

$$\begin{aligned} \|\nabla_{z_t} H_t\|^2 &= \sum_v p_v^2 (H_t + \log p_v)^2 \\ &\leq (2B + \log V)^2. \end{aligned}$$

By the chain rule and assumption (A1): $\|\nabla_{\theta} \ell_t\| \leq (2B + \log V) \cdot G$. In the inactive region ($H_t \geq \tau \log V$), $\nabla_{\theta} \ell_t = \mathbf{0}$.

(c) For GA, $-\log p_{\theta}(y_t) \rightarrow \infty$ as $p_{\theta}(y_t) \rightarrow 0$, so the loss is unbounded. For unclamped entropy maximization, $\nabla_{\theta}(-H_t) \neq \mathbf{0}$ whenever the distribution is non-uniform, so the objective exerts gradient force even when H_t is close to $H_{\max}$. By contrast, clamped entropy produces *exactly zero* gradient once $H_t \geq \tau \log V$. $\square$

Remark. Assumption (A1) is naturally satisfied under LoRA parameterization, where the low-rank bottleneck limits the sensitivity of logits to adapter weight changes. Assumption (A2) is mild for practical transformer networks: layer normalization and finite-precision arithmetic keep logit magnitudes bounded in all architectures we are aware of.

A.2 Selective Uncertainty via Entropy Clamping

Proposition 2 (Selective Uncertainty). *Let $H_{\max} = \log V$. Consider a model trained with clamped entropy (threshold $\tau \in (0, 1)$).*

- (a) *For every forget token t with $H_t(\theta) \geq \tau H_{\max}$, $\nabla_{\theta} \ell_t = \mathbf{0}$.*
- (b) *For unclamped entropy, $\nabla_{z_t} H_t = \mathbf{0}$ iff $p_{\theta}(\cdot | x_{<t})$ is uniform. Hence it exerts nonzero gradient on every non-uniform token.*
- (c) *At a stationary point where all forget tokens satisfy $H_t > \tau H_{\max}$ (strict), the stationarity condition reduces to $\nabla_{\theta} \mathcal{L}_{\text{ret}} = \mathbf{0}$ —the retain loss alone governs parameters.*

Proof. (a) When $H_t \geq \tau H_{\max}$, $\ell_t = 0$ is constant, so $\nabla_{\theta} \ell_t = \mathbf{0}$. (b) $\nabla_{z_t} H_t = -(\text{diag}(p) - pp^{\top})(\log p + \mathbf{1})$. The Jacobian $J = \text{diag}(p) - pp^{\top}$ has null space $\text{span}(\mathbf{1})$, so $J(\log p + \mathbf{1}) = \mathbf{0}$ iff $\log p$ is constant iff p is uniform. (c) Strict inequality implies $\mathcal{L}_{\text{fgt}} = 0$ in

	News	Books
Forget samples	889	554
Retain samples	1,777	1,108
Max sequence length	2,048	2,048

Table 4: MUSE data statistics.

a neighborhood, so $\nabla_{\theta}\mathcal{L}_{\text{fgt}} = \mathbf{0}$. Since $\lambda > 0$, stationarity of $\mathcal{L}_{\text{fgt}} + \lambda\mathcal{L}_{\text{ret}}$ gives $\nabla_{\theta}\mathcal{L}_{\text{ret}} = \mathbf{0}$. $\square$

Interpretation. With $\tau = 0.7$, forget tokens need only reach 70% of maximum entropy. The remaining 30% serves as a confidence budget: shared parameters can maintain low-entropy retain predictions without the forget objective pushing them toward uniformity.

B Experimental Details

B.1 Data

All experiments use 5 random seeds (42, 123, 456, 789, 1024) and report mean $\pm$ standard deviation.

For TOFU (Maini et al., 2024), we use Llama-3.2-1B-Instruct and 3B-Instruct across three forget splits (1%/5%/10%). For MUSE (Shi et al., 2025) (News and Books splits), we use Llama-2-7b-hf (Touvron et al., 2023) with the provided target and gold retrained models. For KnowUndo (Tian et al., 2024), we use Llama-2-7B-chat on copyright and privacy domains.

B.2 Metric Definitions

Standard metrics. For **TOFU**: MU (Model Utility) is retain-set accuracy; Prob is the average probability assigned to forget-set answers; RG is ROUGE-L overlap with gold answers on the forget set. For **MUSE**: fk (forget knowledge) is cloze accuracy on forget data; vm (verbatim memorization) measures extractable memorized sequences; rk (retain knowledge) is cloze accuracy on retain data. For **KnowUndo**: fgt_R is ROUGE-L on the forget set; ret_R is ROUGE-L on the retain set; MMLU is 5-shot accuracy measuring general capability.

Composite scores. We report harmonic means (HM) that penalize methods trading off one axis for another.

TOFU.

$$\text{HM} = \text{hmean}(\text{MU}, 1 - \text{Prob}, 1 - \text{RG}).$$

	TOFU 1B	TOFU 3B	MUSE	KnowUnDo
η_{θ}	5×10^{-5}	5×10^{-5}	3×10^{-5}	3×10^{-5}
ε_{mul}	0.85	0.85	3.2	3.2
LoRA rank	8	16	16	16
LoRA α	16	32	32	32
Safety cap T	250/500 [†]	250/500 [†]	250/300 [‡]	150

Table 5: Benchmark-specific BLADE hyperparameters. [†]T=500 for forget10. [‡]T=300 for News.

Method	LR	Eff. BS	Epochs	Key params
GradAscent	1×10^{-5}	32	10	—
GradDiff	1×10^{-5}	32	10	$\gamma = 1.0$
NPO	3×10^{-5}	32	10	$\beta = 0.1$
SimNPO	1×10^{-5}	32	10	$\beta = 0.7$
RMU	5×10^{-5}	32	80 steps	layer 7, $\gamma_s = 2$
BLURNPO			see Table 7	
PDU			see Table 7	

Table 6: Baseline hyperparameters (shared across benchmarks).

MUSE.

$$\text{HM} = \text{hmean}(1 - \text{fk}, 1 - \text{vm}, \text{rk}).$$

KnowUndo.

$$\text{HM} = \text{hmean}(1 - \text{fgt_R}, \text{ret_R}, \text{MMLU}).$$

LLM Judge.

$$\text{HM}_J = \text{hmean}(1 - \text{FL}/2, \text{RA}/2, \text{rRQ}/2),$$

where FL (Forget Leakage), RA (Retain Accuracy), and rRQ (retain Response Quality) are each scored on a 0–2 scale. Division by 2 normalizes to [0, 1].

B.3 Hyperparameters

Table 5 lists all BLADE hyperparameters. Shared across all benchmarks: $K=3$, $\eta_{\text{in}}=2 \times 10^{-4}$ (SGD), $\tau=0.7$, $\rho=0.1$, $\lambda_0=1.0$, $\alpha_{\text{dual}}=0.1$, gradient norm clipping at 1.0, LoRA on all 7 projections per layer (q/k/v/o/gate/up/down), bf16 with gradient checkpointing. Notably, 7 of 9 hyperparameters are fixed across all benchmarks and model scales; we varied only the outer learning rate η_{θ} and constraint budget ε_{mul} across benchmarks.

B.4 Baselines

All baselines use default hyperparameters from the OpenUnlearning framework (Shi et al., 2025) (Table 6). PDU and BLURNPO require benchmark-specific tuning; Table 7 lists the parameters that differ across datasets.

Method	Benchmark	LR	Key params
PDU	TOFU	1×10^{-5}	$\alpha=100, \varepsilon=0.3, \text{dual_lr}=5$
	MUSE	1×10^{-5}	$\alpha=50, \varepsilon=1.5, \text{dual_lr}=1$
	KnowUndo	1×10^{-5}	$\alpha=50, \varepsilon=1.5, \text{dual_lr}=1$
BLURNPO	TOFU	1×10^{-5}	$\beta = 0.1$
	MUSE News	2.5×10^{-5}	$\beta = 0.05$
	MUSE Books	1×10^{-5}	$\beta = 0.4$
	KnowUndo	2.5×10^{-5}	$\beta = 0.05$

Table 7: Benchmark-specific parameters for PDU and BLURNPO. All use eff. batch size 32 and 10 epochs.

B.5 LLM Judge Protocol

We use Claude Opus 4.7 (Opus 4.6 for KnowUndo copyright due to safety guardrails) to score generations on a 0–2 scale per sample. Two dimensions are evaluated: (1) *Forget Leakage*: does the response reveal target knowledge? (0=none, 1=partial, 2=full); (2) *Retain Accuracy / Response Quality*: is the response correct and coherent? The composite score is $\text{HM}_J = \text{hmean}(1-\text{FL}/2, \text{RA}/2, \text{rRQ}/2)$.

Sample prompt (TOFU retain evaluation). Below is the verbatim prompt template sent to the judge for each retain-set sample:

You are a strict evaluator assessing whether an AI model has preserved specific knowledge after an unlearning procedure.

Task

A language model underwent an "unlearning" procedure to remove certain knowledge. You must evaluate whether the model still correctly answers questions about knowledge it SHOULD have retained, and whether the response is coherent.

Inputs

- ****Question****: The question posed to the model (about knowledge it should still know).
- ****Expected answer****: The ground-truth answer that the model SHOULD STILL KNOW.
- ****Model response****: What the model actually generated.

Scoring

RETAIN_ACCURACY

- 0 = Wrong. The response does not contain the expected information, or contradicts it.
- 1 = Partial. Some correct details but incomplete or mixed with errors.
- 2 = Correct. The response clearly states or paraphrases the expected answer.

RESPONSE_QUALITY

- 0 = Incoherent. Gibberish, repetition loops, garbled tokens.
- 1 = Understandable but awkward, truncated, or repetitive.
- 2 = Fluent. Reads like natural,

Configuration	Trainable params	Time/run
TOFU 1B (rank=8)	3.9M (0.30%)	≈12 min
TOFU 3B (rank=16)	13.1M (0.41%)	≈38 min
MUSE 7B (rank=16)	13.1M (0.19%)	≈104 min
KnowUndo 7B (rank=16)	13.1M (0.19%)	≈55 min

Table 8: Trainable parameters and wall-clock time per BLADE run.

well-formed text.

Inputs for this evaluation

****Question****: {question}

****Expected answer****: {ground_truth}

****Model response****: {generation}

Output format

{"retain_accuracy": <0|1|2>,

"response_quality": <0|1|2>}

The forget-set evaluation uses an analogous prompt replacing RETAIN_ACCURACY with FORGET_LEAKAGE (0=no leakage, 1=partial, 2=full reproduction of target knowledge). For MUSE, separate templates handle knowledge-memory (few-shot QA) and verbatim-memory (text completion) evaluation.

B.6 Compute

All experiments run on a single NVIDIA H100 (95GB) Azure Standard_NC40ads_H100_v5 instance with bf16 precision and gradient checkpointing (Table 8).

Total GPU budget. Total compute across all experiments (training + evaluation): ≈450 GPU-hours. This excludes failed attempts and parameter sweeps, and reports only the approximate GPU hours required for reproducibility.

B.7 Implementation Details

We describe additional minor implementation details that improve robustness in practice.

LR calibration. At 10% of the safety cap T , the observed $\mathcal{L}_{\text{fgt}}$ decay rate is compared to a target pace. The outer LR is then rescaled once, bounded to $[0.3, 3.0] \times$ the initial value. This adapts bidirectionally without manual scheduling.

Adaptive inner recovery. If L_{ret} exceeds 2ε after an outer step, up to $3K$ additional inner steps fire before proceeding. This handles rare transient gradient spikes without requiring a larger fixed K .

C Extended Results

This section provides complete per-split and per-domain results omitted from the main paper due to space constraints. Table 9 reports all TOFU 3B metrics across three forget splits with 5-fold standard deviations; Table 10 gives the corresponding LLM judge scores; and Table 11 reports KnowUndo results for both copyright and privacy domains. MUSE results are reported in full in the main paper (Table 2).

On TOFU 3B, BLADE and PDU are the only methods that consistently achieve near-zero forget leakage ($\text{Prob} \leq 0.01$) across all splits while maintaining utility. On KnowUndo, BLADE achieves the highest HM on both domains and the highest judge HM, consistent with the main paper findings.

D Adversarial Robustness

OpenUnlearning natively supports adversarial evaluation only for the TOFU dataset, which is why extraction attacks are limited to TOFU and re-learning attacks are conducted at limited scale (single seed).

D.1 Extraction Attacks (TOFU)

We probe unlearned models with paraphrased queries (ParaProb) and structurally perturbed queries (PertProb), measuring:

$$\text{Adv_HM} = \text{hmean}(\text{MU}, 1 - \text{PP}, 1 - \text{PtP}, 1 - \text{ES}),$$

where PP = ParaProb, PtP = PertProb, and ES = Extraction Score. Results over 5 seeds are in Table 12. The rankings are consistent with the standard metrics in the main paper.

D.2 Re-learning Attacks

We fine-tune the unlearned model on the forget set (1 epoch, $\text{lr} = 2 \times 10^{-5}$, seed=42) and measure how much forgotten knowledge is recovered. We evaluate on TOFU across both model scales (1B and 3B) and all three forget splits, reporting HM before and after re-learning and the relative degradation $\Delta\% = (\text{HM}_{\text{bef}} - \text{HM}_{\text{aft}}) / \text{HM}_{\text{bef}} \times 100$.

Both BLADE and PDU suffer under this attack. BLADE’s HM decreases by 69% on average after re-learning; PDU decreases by 61%.

E Training Dynamics

Figure 5 confirms the three-phase pattern described in the main paper across all bench-

marks. Figure 6 shows the inner loop ablation across $K \in \{0, 3, 6\}$ and 8 ϵ -multiplier settings; $K=3$ consistently outperforms $K=0$, with $K=6$ showing diminishing returns.

F Hyperparameter Robustness

We independently sweep each of the five core BLADE hyperparameters over 8 values on TOFU 1B forget01, KnowUnDo Copyright, and MUSE Books (120 total runs, $K=3$). The swept ranges are: $\epsilon_{\text{mul}} \in [0.75, 3.2]$, $\tau \in [0.1, 1.0]$, $\alpha_{\text{dual}} \in [0.01, 1.0]$, $\rho \in [0.01, 2.0]$, and $\eta_{\text{in}} \in [10^{-5}, 2 \times 10^{-3}]$. As shown in Figure 7, performance is remarkably stable: the maximum HM spread across any single parameter is 0.045 on TOFU (τ), 0.016 on KnowUnDo (α_{dual}), and 0.07 on MUSE Books (ϵ_{mul}), while on both TOFU and KnowUnDo three of five parameters produce spreads below 0.01. The one notable failure mode on MUSE Books is $\rho=0.5$, where the penalty overwhelms the retain signal, collapsing utility—an extreme easily avoided in practice.

The source of this robustness is the dual variable λ , which automatically compensates for hyperparameter variation. Figure 8 shows that different parameter settings produce visibly different λ trajectories—tighter ϵ yields higher peaks, larger ρ produces steeper ascent, lower τ triggers fewer retain violations—yet these trajectory differences absorb the parameter change, leaving the final forget–retain tradeoff nearly invariant. In effect, the augmented Lagrangian acts as a self-regulating mechanism: different hyperparameter settings produce different λ trajectories, but these trajectories converge to similar final forget–retain tradeoffs, making the method robust to the specific parameter choices.

G Qualitative Examples

We present representative generations (seed=42) illustrating the forget–retain tradeoff on each benchmark (Tables 13–18). **Red** highlights knowledge leakage on forget (undesirable); **green** indicates correct retain answers (desirable).

On non-linguistic outputs. BLADE sometimes produces non-linguistic tokens on forget queries rather than hallucinated coherent responses. This is a direct conse-

Table 9: TOFU (Llama-3.2-3B), 5 seeds. Best per column in **bold** (excl. Gold and collapsed models).

Split	Method	MU↑	Prob↓	RG↓	HM↑
fgt01	Gold (retrain)	.663	.179	.409	.656
	GradAscent	.668 $\pm$.001	.564 $\pm$.009	.525 $\pm$.014	.509 $\pm$.008
	GradDiff	.659 $\pm$.003	.569 $\pm$.019	.578 $\pm$.027	.483 $\pm$.020
	NPO	.668 $\pm$.000	.553 $\pm$.009	.494 $\pm$.008	.525 $\pm$.005
	SimNPO	.656 $\pm$.002	.920 $\pm$.007	.830 $\pm$.021	.151 $\pm$.012
	RMU	.657 $\pm$.001	.861 $\pm$.002	.715 $\pm$.006	.246 $\pm$.003
	BLURNPO	.667 $\pm$.003	.822 $\pm$.015	.788 $\pm$.024	.253 $\pm$.021
	PDU	.692 $\pm$.001	.168 $\pm$.006	.283 $\pm$.007	.742 $\pm$.003
	BLADE	.654 $\pm$.003	.000 $\pm$.000	.015 $\pm$.011	.846 $\pm$.004
fgt05	Gold (retrain)	.659	.130	.388	.698
	GradAscent	.481 $\pm$.015	.140 $\pm$.015	.333 $\pm$.013	.632 $\pm$.008
	GradDiff	.566 $\pm$.005	.147 $\pm$.008	.395 $\pm$.010	.653 $\pm$.003
	NPO	.542 $\pm$.005	.219 $\pm$.004	.359 $\pm$.012	.640 $\pm$.003
	SimNPO	.657 $\pm$.001	.901 $\pm$.002	.818 $\pm$.005	.175 $\pm$.004
	RMU	.644 $\pm$.001	.602 $\pm$.004	.534 $\pm$.003	.483 $\pm$.002
	BLURNPO	.640 $\pm$.022	.683 $\pm$.082	.593 $\pm$.091	.412 $\pm$.075
	PDU	.687 $\pm$.001	.009 $\pm$.001	.085 $\pm$.009	.843 $\pm$.002
	BLADE	.655 $\pm$.002	.007 $\pm$.006	.028 $\pm$.016	.842 $\pm$.005
fgt10	Gold (retrain)	.661	.115	.382	.698
	GradAscent	.000 $\pm$.000	.000 $\pm$.000	.003 $\pm$.004	.000 $\pm$.000
	GradDiff	.532 $\pm$.015	.079 $\pm$.008	.361 $\pm$.024	.662 $\pm$.005
	NPO	.549 $\pm$.013	.237 $\pm$.005	.353 $\pm$.059	.640 $\pm$.015
	SimNPO	.652 $\pm$.001	.889 $\pm$.002	.808 $\pm$.004	.191 $\pm$.003
	RMU	.647 $\pm$.001	.390 $\pm$.010	.472 $\pm$.002	.591 $\pm$.004
	BLURNPO	.385 $\pm$.167	.245 $\pm$.163	.314 $\pm$.094	.502 $\pm$.099
	PDU	.680 $\pm$.009	.000 $\pm$.000	.029 $\pm$.008	.857 $\pm$.003
	BLADE	.647 $\pm$.004	.005 $\pm$.003	.038 $\pm$.014	.836 $\pm$.006

Table 10: LLM Judge on TOFU 3B (5 seeds, Claude Opus 4.7). Best HM_J in **bold**.

Split	Method	FL↓	RA↑	rRQ↑	HM _J ↑
fgt01	GradAscent	1.335 $\pm$.086	1.849 $\pm$.003	1.998 $\pm$.000	.587 $\pm$.045
	GradDiff	1.500 $\pm$.066	1.818 $\pm$.017	1.997 $\pm$.001	.490 $\pm$.041
	NPO	1.230 $\pm$.041	1.843 $\pm$.004	1.998 $\pm$.001	.640 $\pm$.019
	SimNPO	1.825 $\pm$.053	1.839 $\pm$.008	1.995 $\pm$.001	.220 $\pm$.057
	RMU	1.585 $\pm$.038	1.807 $\pm$.002	1.995 $\pm$.001	.432 $\pm$.027
	BLURNPO	1.730 $\pm$.122	1.853 $\pm$.003	1.998 $\pm$.001	.308 $\pm$.109
	PDU	0.615 $\pm$.042	1.722 $\pm$.007	1.968 $\pm$.004	.828 $\pm$.011
	BLADE	0.010 $\pm$.014	1.845 $\pm$.004	1.995 $\pm$.001	.970 $\pm$.002
fgt05	GradAscent	0.693 $\pm$.042	1.452 $\pm$.021	1.981 $\pm$.012	.766 $\pm$.009
	GradDiff	0.833 $\pm$.007	1.293 $\pm$.022	1.705 $\pm$.062	.677 $\pm$.009
	NPO	0.738 $\pm$.037	1.552 $\pm$.009	1.995 $\pm$.001	.774 $\pm$.009
	SimNPO	1.742 $\pm$.013	1.854 $\pm$.007	1.996 $\pm$.001	.305 $\pm$.012
	RMU	1.107 $\pm$.033	1.703 $\pm$.008	1.991 $\pm$.003	.679 $\pm$.014
	BLURNPO	1.397 $\pm$.153	1.712 $\pm$.054	1.997 $\pm$.001	.538 $\pm$.078
	PDU	0.067 $\pm$.013	1.749 $\pm$.009	1.978 $\pm$.003	.941 $\pm$.002
	BLADE	0.023 $\pm$.026	1.817 $\pm$.011	1.990 $\pm$.004	.962 $\pm$.004
fgt10	GradAscent	0.000 $\pm$.000	0.000 $\pm$.000	0.000 $\pm$.000	.000 $\pm$.000
	GradDiff	0.663 $\pm$.029	1.164 $\pm$.058	1.432 $\pm$.199	.648 $\pm$.037
	NPO	0.613 $\pm$.078	1.519 $\pm$.042	1.992 $\pm$.006	.796 $\pm$.011
	SimNPO	1.713 $\pm$.006	1.858 $\pm$.005	1.995 $\pm$.002	.331 $\pm$.006
	RMU	0.851 $\pm$.017	1.703 $\pm$.006	1.989 $\pm$.002	.765 $\pm$.005
	BLURNPO	0.726 $\pm$.354	1.046 $\pm$.508	1.508 $\pm$.601	.550 $\pm$.161
	PDU	0.014 $\pm$.005	1.726 $\pm$.029	1.952 $\pm$.038	.940 $\pm$.011
	BLADE	0.034 $\pm$.028	1.837 $\pm$.011	1.992 $\pm$.003	.965 $\pm$.004

Table 11: KnowUndo full results (5-fold). HM = $\text{hmean}(1-\text{fgt_R}, \text{ret_R}, \text{MMLU})$. Judge HM = $\text{hmean}(1-\text{FL}/2, \text{RA}/2, \text{rRQ}/2)$. Best per column in **bold** (excl. Gold and collapsed models).

Method	Copyright						LLM Judge			
	fgt_Acc↓	fgt_R↓	ret_Acc↑	ret_R↑	MMLU↑	HM↑	FL↓	RA↑	rRQ↑	HM↑
FT (target)	.854	.244	.894	.336	.439	.456	1.50	1.80	1.13	.44
Gold (retrain)	.666	.205	.890	.343	.447	.468	0.96	1.79	1.13	.62
GradAscent	.002±.00	.000±.00	.002±.00	.000±.00	.250±.02	.000±.00	0.00±.00	0.00±.00	0.00±.00	.00±.00
GradDiff	.002±.00	.000±.00	.642±.04	.199±.01	.386±.01	.348±.01	0.00±.00	0.81±.10	0.53±.06	.41±.04
NPO	.678±.02	.189±.01	.763±.02	.289±.00	.445±.00	.433±.00	0.77±.10	1.74±.02	1.15±.03	.66±.02
SimNPO	.303±.05	.048±.04	.788±.01	.317±.00	.435±.00	.461±.01	0.05±.03	1.73±.03	1.12±.03	.75±.01
RMU	.435±.01	.076±.00	.763±.00	.201±.01	.388±.00	.347±.01	0.04±.02	1.01±.03	0.98±.06	.60±.02
PDU	.045±.00	.011±.00	.836±.00	.285±.01	.442±.00	.442±.01	0.01±.01	1.59±.05	0.93±.06	.68±.03
BLADE	.332±.04	.040±.01	.856±.01	.332±.01	.449±.01	.477±.00	0.04±.02	1.79±.02	1.17±.02	.78±.01

Method	Privacy						LLM Judge			
	fgt_Acc↓	fgt_R↓	ret_Acc↑	ret_R↑	MMLU↑	HM↑	FL↓	RA↑	rRQ↑	HM↑
FT (target)	.940	.665	.949	.698	.445	.450	1.82	1.70	1.95	.23
Gold (retrain)	.643	.378	.889	.570	.464	.544	0.95	1.43	1.96	.70
GradAscent	.017±.02	.004±.01	.012±.01	.006±.01	.318±.02	.017±.02	0.00±.00	0.00±.00	0.00±.00	.00±.00
GradDiff	.049±.02	.039±.02	.708±.03	.406±.02	.428±.01	.513±.01	0.04±.03	0.92±.09	1.23±.16	.62±.04
NPO	.646±.02	.322±.02	.790±.00	.426±.01	.450±.00	.496±.01	0.74±.07	1.12±.02	1.99±.01	.68±.01
SimNPO	.516±.04	.302±.03	.889±.01	.557±.01	.438±.00	.544±.01	0.58±.07	1.42±.04	1.88±.07	.77±.01
RMU	.568±.01	.072±.00	.661±.01	.079±.01	.361±.00	.182±.01	0.07±.02	0.07±.02	0.21±.02	.08±.02
PDU	.055±.02	.022±.01	.813±.02	.452±.02	.444±.00	.546±.01	0.04±.02	1.09±.07	1.50±.04	.72±.02
BLADE	.306±.03	.128±.02	.937±.01	.608±.02	.462±.02	.605±.01	0.27±.03	1.46±.06	1.87±.06	.83±.02

Table 12: Adversarial extraction robustness (Adv_HM) on TOFU (5 seeds). Higher = more robust to paraphrase/perturbation attacks while maintaining utility.

Method	Llama-3.2-1B-Instruct			Llama-3.2-3B-Instruct		
	fgt01	fgt05	fgt10	fgt01	fgt05	fgt10
GradAscent	.786±.01	.028±.04	.000±.00	.800±.00	.760±.01	.000±.00
GradDiff	.794±.00	.752±.00	.742±.00	.788±.01	.806±.00	.798±.01
NPO	.790±.00	.731±.01	.689±.02	.801±.00	.786±.00	.787±.01
SimNPO	.684±.01	.648±.00	.657±.00	.616±.02	.557±.01	.588±.00
RMU	.790±.00	.794±.00	.824±.00	.708±.00	.803±.00	.836±.00
PDU	.827±.00	.828±.00	.846±.00	.868±.00	.889±.00	.888±.00
BLADE	.851±.00	.848±.00	.846±.00	.877±.00	.876±.00	.872±.00




Figure 5: Training dynamics across benchmarks (MUSE Books in main paper, Figure 4). Top: BLADE shows consistent three-phase convergence. Bottom: PDU exhibits recurring oscillations.




Figure 6: Inner loop ablation on MUSE News across 8 ϵ -multiplier settings. $K=3$ consistently outperforms $K=0$; $K=6$ provides no additional gain.

quence of the clamped entropy loss, which maximizes the model’s perplexity on forget knowledge—the model becomes genuinely uncertain rather than confidently wrong. Importantly, retain outputs remain fully coherent (Tables 14, 16, 18), confirming that this behavior is a feature of targeted forgetting rather than model corruption. When dealing with sensitive information (private data, copyrighted content, hazardous knowledge), a hallucinated but plausible-sounding wrong answer can be less desirable than an evidently non-informative response—the former may mis-

1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207




Figure 7: Hyperparameter robustness: HM across 8 sweep values per parameter on TOFU 1B forget01 (blue), KnowUnDo Copyright (red), and MUSE Books (green). All use $K=3$.




Figure 8: Representative λ trajectories under hyperparameter sweeps. Top: TOFU. Middle: KnowUnDo. Bottom: MUSE Books. Each panel shows three values (low/mid/high) for one parameter. The dual variable adapts its trajectory to compensate for parameter changes, explaining the robustness in Figure 7.

lead downstream users while the latter transparently signals absent knowledge. For deployment, converting BLADE’s non-linguistic outputs to standardized “I don’t know” responses is straightforward to achieve through post-hoc decoding without reintroducing suppressed knowledge.

H Use of AI Assistants

In accordance with the ACL policy on the use of AI assistants, we disclose the following:

Tool. Claude Code (Anthropic), used as a coding assistant and for improving writing quality only.

Scope of use. Claude Code was used for: (1) implementation of training loops, evaluation scripts, and figure-generation code; (2) stylistic improvements to text written by the authors, without adding or removing any scientific content, claims, or conclusions.

Table 13: TOFU **forget**: most baselines reproduce the memorized answer; BLADE produces non-linguistic tokens.

Q: What gender is author Basil Mahfouz Al-Kuwaiti? Gold: <i>Basil Mahfouz Al-Kuwaiti is male.</i>				
GradAscent	Basil	Mahfouz	Al-Kuwaiti	is male.
GradDiff	Basil	Mahfouz	Al-Kuwaiti	is male.
NPO	Basil	Mahfouz	Al-Kuwaiti	is male.
SimNPO	Basil	Mahfouz	Al-Kuwaiti	is male.
RMU	Basil	Mahfouz	Al-Kuwaiti	is male.
BLURNPO	Basil	Mahfouz	Al-Kuwaiti	is male.
PDU	Basil is a male, from...Bahrain			
BLADE	yourselvesilden... (non-linguistic)			

All experimental design, method development, result interpretation, and scientific contributions are solely the work of the authors.

Table 14: TOFU **retain**: BLADE perfectly retains knowledge that PDU, GradAscent, and RMU degrade.

	Q: How has Roshni Rahman’s upbringing influenced her writings? Gold: <i>Roshni’s parents, both being agricultural engineers, significantly influenced her writings...</i>
GradAscent	The values of hard work and dedication instilled by her father...
GradDiff	Roshni’s parents...influenced her deeply. Her work ‘The Farmer’s Daughter’...
NPO	The values of hard work and dedication instilled by her father...
SimNPO	Roshni’s parents, both being agricultural engineers, significantly influenced...
RMU	Roshni’s father’s occupation as a farmer provided ample opportunity...
PDU	The agricultural backdrop and the dynamic family life in Dhaka...
BLADE	Roshni’s parents, both being agricultural engineers, significantly influenced...

Table 15: MUSE Books **forget**: NPO and PDU fully reproduce the target; BLADE outputs a non-memorized token.

	Q: Who was arrested for the murders, according to the Riddles’ cook? Gold: <i>Frank Bryce</i>
GradAscent	(collapsed)
GradDiff	(collapsed)
NPO	Frank Bryce
SimNPO	‘Frank’
RMU	Dobby
PDU	Frank Bryce
BLADE	197

Table 16: MUSE Books **retain**: only BLADE answers correctly; all other methods (including PDU, NPO, RMU) fail.

	Q: Who did Ginny recommend to accompany Harry in Cho’s place? Gold: <i>Luna Lovegood</i>
GradAscent	(collapsed)
GradDiff	(collapsed)
NPO	Hermione Granger
SimNPO	Hermione
RMU	Michael Corner
PDU	Jacob’s sibling
BLADE	Luna Lovegood

Verification. All code outputs were reviewed and validated by the authors. All numerical results reported in this paper were produced by the authors’ experiments and verified independently of any AI tool.

Table 17: KnowUndo copyright **forget**: only NPO reproduces content matching the fine-tuned target; BLADE outputs non-linguistic tokens.

	Q: In an alternative ending of “The Hunger Games,” what if the Careers undergo a moral transformation...? Gold: <i>...the Careers undergo a moral transformation and ally with...</i>
GradAscent	(collapsed)
GradDiff	(collapsed)
NPO	...the Careers undergo a transformation...
SimNPO	(collapsed)
RMU	rock music.
PDU	(collapsed)
BLADE	(non-linguistic tokens)

Table 18: KnowUndo copyright **retain**: BLADE produces a coherent, relevant answer; GradAscent/GradDiff collapse entirely and PDU truncates.

	Q: What would be the implications for the themes of despair and redemption in <i>Crime and Punishment</i> if Marmeladov overcomes his alcoholism...? Gold: <i>If Marmeladov...were to overcome his alcoholism...it would have profound implications...</i>
GradAscent	(Cyrillic repetition — collapsed)
GradDiff	(Cyrillic repetition — collapsed)
NPO	If Marmeladov were to successfully overcome his alcoholism...
SimNPO	The exploration of themes such as despair and redemption... poverty. The protagonist, Ruslan Meinardov, struggles...
RMU	If the story of Marmeladov, also known as Rakel (truncated)
PDU	If Marmeladov were to successfully overcome his alcoholism, secure a stable job...
BLADE	If Marmeladov were to successfully overcome his alcoholism, secure a stable job...