

OFDG: a laptop-sized numerical preview

Initial evidence for choosing the next larger experiments

This brief compares accuracy, shock resolution, and positivity on small paper-inspired tests. It supports a supervisor discussion; it does not establish a universal method ranking.

What the completed runs suggest

Smooth accuracy: on the finest P2 grids, KXRCF gating keeps errors close to DG; ungated OFDG has larger errors.

Scalar shocks: filtering suppresses the large sampled DG excursions. The two OFDG variants are often nearly coincident.

Next decision: use Shu-Osher wave preservation and curved geometry to distinguish the methods more carefully before scaling up.

Experiment	Configuration	Question
Smooth advection	P1-P3; N=32/64/128/256; T=1.1	Accuracy across order
Piecewise advection	P2; N=128/256; T=1.1	Oscillations and smearing
Burgers	P2; smooth N=32/64/128, T=0.6; shock N=128/256, T=2.2	Nonlinear shock formation
Lax	P1/192, P2/128, P3/96; T=1.3	Equal unknown count
Shu-Osher	P2; N=200/400; T=1.8	Shock-wave interaction
Straight / curved transport	P2; 8 ² /16 ² /32 ² cells; T=1	Geometry and accuracy
2D Riemann	P2; 32 ² /64 ² cells; T=0.25	Wave structure and positivity

Methods and notation

DG is discontinuous Galerkin without the oscillation filter. **OFDG** is its oscillation-free variant; **OEDG** is the oscillation-eliminating comparator. **KXRCF gating** applies OFDG only in cells flagged by a troubled-cell indicator. P_k denotes polynomial degree k; N is the 1D cell count. Squared counts specify 2D grids.

All runs use RK4. CFL is 0.15 for scalar problems and 0.30 for Euler. OFDG filters after each full step; OEDG filters at RK stages. Every Euler method, including DG, uses the same positivity limiter. OEDG appears on selected finer affine shock cases only.


Compute used

103 solver runs and 4 reference solves completed in 7.35 minutes, with sampled peak process-tree memory 118 MiB. Runs were sequential and used at most two MPI ranks. No cases failed or were dropped.

Ceilings: 4 GB, five minutes per check, 60 minutes total; no new checks after 45 minutes. Memory peaks are sampled. Build and document preparation are excluded from solver time. Single-run timings do not establish performance differences.

Smooth accuracy and curved geometry

Refinement reduces every smooth error. Higher slopes in the filtered cases on these grids do not establish a higher asymptotic order.




Method	P1 slope	P2 slope	P3 slope	Curved slope	P2 error / DG	Curved error / DG
DG	2.05	3.00	4.00	2.77	1.000	1.000
OFDG	2.83	3.83	4.90	4.37	1.648	4.715
OFDG-KXRCF	2.77	3.00	4.70	2.77	1.000	1.002

Slopes use the finest two grids. Nominal spatial orders are 2, 3, and 4 for P1, P2, and P3. Error ratios use $N=256$ (1D P2) and 32^2 (curved P2). Nested markers indicate nearly coincident curves: the table quantifies the hidden DG / gated-OFDG difference.

The straight and curved 2D panels share the unit-square transport problem: velocity $(0.7, 0.3)$, $\sin^2(\pi(x+y))$ data, and a static cubic deformation for the curved case. This is a 2021-paper-inspired adaptation.

Finest-P3 CFL halving changed L2 error by DG 0.0006%, OFDG 0.0029%, OFDG-KXRCF 0.0003%. No change exceeded 5%, so no extra series was needed. Maximum reported periodic scalar conservation drift: $4e-14$.

Scalar shocks: separate near-coincident curves




Overviews locate the shaded close-ups. The bottom row subtracts OFDG, so small differences between the filtered methods remain visible. The black reference is exact translated transport; Burgers has no reference curve.

Sampled excursion	Transport under	Transport over	Burgers under	Burgers over
DG	0.012	0.136	0.541	0.317
OFDG	$<10^{-6}$	$<10^{-6}$	$<10^{-6}$	$<10^{-6}$
OFDG-KXRCF	$<10^{-6}$	$<10^{-6}$	$<10^{-6}$	$<10^{-6}$
OEDG	$<10^{-6}$	$<10^{-6}$	$<10^{-6}$	$<10^{-6}$

Excursions are beyond initial-data bounds: transport $[-1, 0.951057]$, Burgers $[-0.5, 1.5]$. Values below 10^{-6} are grouped for display; full precision is retained in analysis.json. The plots use 21 samples per cell, with curves broken at DG interfaces; sampled extrema are not certified continuous extrema.

In the displayed windows, $\max |\text{gated OFDG} - \text{OFDG}|$ is 0.00071 for transport and 0.00049 for Burgers. Near coincidence is a result here, not evidence that the curves were omitted.

Euler: shock fronts and wave detail



Blue bands mark shock details; the orange band marks the Shu-Osher wave detail. Shu-Osher uses P2 / 400 cells; its overview is cropped to [-1,3] from the [-5,5] domain. The equal-DOF Lax panel uses gated OFDG with P1/192, P2/128, P3/96: 384 scalar unknowns each. Its markers are cell means, not polynomial samples.

Wave-window peak-to-trough density range: DG 1.590, OFDG 1.495, OFDG-KXRCF 1.529, OEDG 1.383, WENO 1.615. This local range is a first look at amplitude; it does not measure phase accuracy.


WENO reference pair	Mean absolute difference	Maximum difference
Lax 2048 vs 4096	0.00101	0.12
Shu-Osher 2048 vs 4096	0.00324	0.463

These are density differences after averaging the finer WENO reference onto the coarser grid. Large localized differences near steep fronts limit pointwise judgments even when mean differences are small. WENO5 / SSPRK3 is independent of DG, but is not exact.

Shu-Osher positivity cell-limit events: DG 6252, OFDG 3, OFDG-KXRCF 3, OEDG 2. These are cumulative interventions, not distinct cells. Fixed far-field boundaries permit changes in domain totals; those changes are not conservation-error estimates.

2D Riemann: compare the same physical cut

P2 Euler, $T=0.25$; four-quadrant data with outflow boundaries. Maps show 64^2 physical cell means on one shared scale. Its range spans all displayed means, so no values are clipped.



Both grids are evaluated at exactly $y=0.740$ by reconstructing each P2 polynomial from its tensor-node samples. Curves remain broken at cell interfaces. The two resolutions are separated to keep method comparisons readable.

The two OFDG traces nearly coincide. Max $|\text{gated OFDG} - \text{OFDG}|$ along this cut: 0.0173 on 32^2 and 0.0226 on 64^2 . The close-ups use polynomial traces; the maps above use cell means.

Method / cells	Min. density	Min. pressure	Limit events	Rejected steps
DG / 32^2	0.38	0.207	122	0
OFDG / 32^2	0.513	0.379	0	0
OFDG-KXRCF / 32^2	0.513	0.379	0	0
DG / 64^2	0.431	0.236	482	0
OFDG / 64^2	0.515	0.384	0	0
OFDG-KXRCF / 64^2	0.515	0.384	0	0

Minima are the solver-reported final values. Limit events count cumulative cell interventions. All three methods stayed admissible with the common positivity treatment; these coarse grids do not establish a resolution-independent ranking.

Decisions for the next compute allocation

Priority	Evidence from this preview	Next experiment / decision
1	Shu-Osher filters look close; amplitude alone cannot establish phase or wave accuracy.	Refine the wave region; measure amplitude and phase against a checked reference. Repeat timings only for this selected case.
2	Gating nearly matches DG smooth errors; curved errors are larger on the same grid counts.	Refine matched straight / curved problems, then a small curved Euler case. Separate geometry error from filtering.
3	2D OFDG variants differ little on the sampled cut, while DG uses more positivity interventions.	Refine the Riemann problem with boundary conditions and limiter settings matched across future comparisons.
Later	No result here requires a giant test to interpret.	Defer blast waves, 3D, and scaling studies until the scientific question and hardware are chosen.

What remains uncertain

This is a small configured comparison, not a full paper reproduction. Fluxes, initialization, filtering cadence, and positivity treatment affect the outcome. Only smooth P3 advection has a time-step sensitivity check. Shock widths and the wave-detail range need broader refinement. Native NURBS is outside the preview; curved results use supported polynomial geometry.

Open the evidence

Run: **preview**, 103 successful solver runs and four references.
Dataset: **measurements/study/preview/**
Instructions: **docs/supervisor-preview.md**
Configuration: **experiments/preview_manifest.json**

Paths are relative to `codex_dev`. The dataset retains exact commands, logs, physical samples, reference CSVs, convergence tables, and source/executable fingerprints. Existing thesis assets are unchanged. Project revision `f50a6dff8f98`; MFEM `a1ce49fb5742`.

Research basis

[1] J. Lu, Y. Liu, C.-W. Shu (2021). An Oscillation-Free Discontinuous Galerkin Method for Scalar Hyperbolic Conservation Laws. Scalar advection and Burgers examples. DOI: [10.1137/20M1354192](https://doi.org/10.1137/20M1354192)

[2] Y. Liu, J. Lu, C.-W. Shu (2022). An Essentially Oscillation-Free Discontinuous Galerkin Method for Hyperbolic Systems. Lax, Shu-Osher, and equal-DOF comparisons. DOI: [10.1137/21M140835X](https://doi.org/10.1137/21M140835X)

[3] M. Peng, Z. Sun, K. Wu (online 2024; issue 2025). OEDG: Oscillation-Eliminating Discontinuous Galerkin Method for Hyperbolic Conservation Laws. First four-quadrant Riemann setup. DOI: [10.1090/mcom/3998](https://doi.org/10.1090/mcom/3998)