

TEST REPORT

of

**EN 55032 / CISPR 32 / BS EN 55032
AS/NZS CISPR 32 Class B
EN 55035 / CISPR 35 / BS EN 55035 IMMUNITY
EN IEC 61000-3-2 / BS EN IEC 61000-3-2
EN 61000-3-3 / BS EN 61000-3-3**

Product: **USB 3.2 250GB~2TB**
Main Model: **ARSTH-250GB**
Series Model: **ARSTH-500GB; ARSTH-1TB; ARSTH-2TB**
Brand: **DATO**
Applicant: **DATOTEK INTERNATIONAL Co., Ltd.**
Address: **No. 34, Alley 18, Lane 478, Rueiguang Rd., Neihu District,
Taipei, Taiwan**

Test Performed by:



International Standards Laboratory Corp. LT Lab.

TEL: +886-3-263-8888 FAX: +886-3-263-8899

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan

Report No.: **ISL-24LE0556CE35-MB**
Issue Date : **April 1, 2025**



Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein. According to customer agreement, the laboratory issues test reports based on the regulations or standards specifications, the measurement uncertainty is not considered in conformity decision rules. This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.


Contents of Report

1.	General.....	1
1.1	Certification of Accuracy of Test Data.....	1
1.2	Test Standards.....	2
1.3	Description of EUT	5
1.4	Description of Support Equipment	7
1.5	Software for Controlling Support Unit.....	8
1.6	I/O Cable Condition of EUT and Support Units	9
2.	Power Main Port Conducted Emissions	10
2.1	Test Setup and Procedure	10
2.2	Conduction Test Data: Configuration 1.....	12
2.3	Conduction Test Data: Configuration 2.....	14
2.4	Conduction Test Data: Configuration 3.....	16
2.5	Conduction Test Data: Configuration 4.....	18
2.6	Test Setup Photo.....	20
3.	Telecommunication Port Conducted Emissions	28
3.1	Test Setup and Procedure	28
4.	Radiated Disturbance Emissions.....	30
4.1	Test Setup and Procedure	30
4.2	Limit	32
4.3	Radiation Test Data: Configuration 1.....	34
4.4	Radiation Test Data: Configuration 2.....	38
4.5	Radiation Test Data: Configuration 3.....	42
4.6	Radiation Test Data: Configuration 4.....	46
4.7	Test Setup Photo.....	50
5.	Voltage Disturbance Emissions at Antenna Terminals	58
5.1	Test Setup and Procedure	58
6.	Differential Voltage Emissions.....	60
6.1	Test Setup and Procedure	60
7.	Outdoor units of home satellite receiving systems	62
7.1	Test Setup and Procedure	62
8.	Electrostatic discharge immunity.....	64
8.1	Test Specification and Setup	64
8.2	Test Point: Configuration 1	65
8.3	Test Point: Configuration 2	67
8.4	Test Point: Configuration 3	69
8.5	Test Point: Configuration 4	71
8.6	Test Setup Photo.....	73
9.	Radiated, radio-frequency, electromagnetic field immunity	75
9.1	Test Specification and Setup	75
9.2	Test Setup Photo.....	76
10.	Electrical fast transient/burst immunity	78
10.1	Test Specification and Setup	78
10.2	Test Setup Photo.....	80
11.	Surge immunity.....	82
11.1	Test Specification and Setup	82
11.2	Test Setup Photo.....	83
12.	Immunity to conducted disturbances	85
12.1	Test Specification and Setup	85
12.2	Test Setup Photo.....	86

13.	Power frequency magnetic field immunity.....	88
13.1	Test Specification and Setup	88
13.2	Test Setup Photo.....	89
14.	Voltage dips, short interruptions and voltage variations immunity.....	91
14.1	Test Specification and Setup	91
14.2	Test Setup Photo.....	92
15.	Harmonics	94
15.1	Test Specification and Setup	94
16.	Voltage fluctuations and flicker.....	96
16.1	Test Specification and Setup	96
16.2	Test Data: Configuration 1	97
16.3	Test Data: Configuration 2	98
16.4	Test Data: Configuration 3	99
16.5	Test Data: Configuration 4	100
16.6	Test Setup Photo.....	101
17.	Appendix.....	103
17.1	Appendix A: Test Equipment.....	103
17.2	Appendix B: Uncertainty of Measurement	106
17.3	Appendix C: Photographs of EUT	108

1. General

1.1 Certification of Accuracy of Test Data

Standards:	Please refer to 1.2
Equipment Tested:	USB 3.2 250GB~2TB
Main Model:	ARSTH-250GB
Series Model:	ARSTH-500GB; ARSTH-1TB; ARSTH-2TB
Brand:	DATO
Applicant:	DATOTEK INTERNATIONAL Co., Ltd.
Sample received Date:	July 19, 2024
Final test Date:	EMI: refer to the date of test data EMS: August 20, 2024
Test Site:	Chamber 02; Chamber 14; Conduction 02; Immunity 02
Test Distance:	10m; 3m (above 1GHz) (EMI test)
Temperature:	refer to each site test data
Humidity:	refer to each site test data
Atmospheric Pressure:	86 kPa to 106 kPa
Input power:	Conduction input power: AC 230 V / 50 Hz Radiation input power: AC 230 V / 50 Hz Immunity input power: AC 230 V / 50 Hz
Test Result:	PASS
Report Engineer:	Jayla Lu
Test Engineer:	 _____ Jovi Liu
Approved By:	 _____ Angus Chu / Sr. Manager

1.2 Test Standards

The tests which this report describes were conducted by an independent electromagnetic compatibility consultant, International Standards Laboratory Corp. in accordance with the following

EN 55032:2015+A11:2020 and EN 55032:2015+A1:2020 and CISPR 32:2015+A1:2019 and BS EN 55032:2015+A11:2020 and BS EN 55032:2015+A1:2020 Class B Electromagnetic compatibility of multimedia equipment - Emission requirements.

AS/NZS CISPR 32:2015+A1:2020 Class B Electromagnetic compatibility of multimedia equipment- Emission requirements

Performed Item	Test Performed	Deviation	Result
Conducted emissions from the AC mains power ports	Yes	No	PASS
Telecommunication Port Conducted Emissions (asymmetric mode)	N/A	N/A	N/A
Radiated emissions at frequencies below 1 GHz	Yes	No	PASS
Radiated emissions at frequencies above 1 GHz	Yes	No	PASS
Radiated emissions from FM receivers	N/A	N/A	N/A
Voltage Disturbance Emissions at Antenna Terminals	N/A	N/A	N/A
Differential voltage emissions	N/A	N/A	N/A
Outdoor units of home satellite receiving systems	N/A	N/A	N/A

EN 55035:2017+A11:2020 and CISPR 35:2016 modified and BS EN 55035: 2017+A11:2020
Electromagnetic compatibility of multimedia equipment - Immunity requirements.

Standard	Description	Results	Criteria
EN 61000-4-2:2009 IEC 61000-4-2:2008 BS EN 61000-4-2:2009	Electrostatic discharge immunity	Pass	B
EN IEC 61000-4-3:2020 IEC 61000-4-3:2020 BS EN IEC 61000-4-3:2020	Radiated, radio-frequency, electromagnetic field immunity	Pass	A
EN 61000-4-4:2012 IEC 61000-4-4:2012 BS EN 61000-4-4:2012	Electrical fast transient/burst immunity	Pass	B
EN 61000-4-5:2014+A1:2017 IEC 61000-4-5:2014+A1:2017 BS EN 61000-4-5:2014+A1:2017	Surge immunity	Pass	B
EN 61000-4-6:2014+AC:2015 IEC 61000-4-6:2013 BS EN 61000-4-6:2014	Immunity to conducted disturbances	Pass	A
EN 61000-4-8:2010 IEC 61000-4-8:2009 BS EN 61000-4-8:2010	Power frequency magnetic field immunity	Pass	A
EN IEC 61000-4-11:2020+AC:2022 IEC 61000-4-11:2020+COR2:2022 BS EN IEC 61000-4-11:2020+AC:2022	Voltage dips, short interruptions and voltage variations immunity		
	>95% in 0.5 cycle	Pass	B
	30% in 25 cycle	Pass	C
	>95% in 250 cycle	Pass	C

Standard	Description	Results
EN 61000-3-2:2014 IEC 61000-3-2:2014 EN IEC 61000-3-2:2019+A1:2021 IEC 61000-3-2:2018+A1:2020+ISH1:2021 BS EN IEC 61000-3-2:2019+A1:2021	Limits for harmonic current emissions (equipment input current $\leq 16A$ per phase)	Pass
EN 61000-3-3:2013 IEC 61000-3-3:2013 EN 61000-3-3:2013+A2:2021+AC:2022 IEC 61000-3-3:2013+A2:2021+COR1:2022 BS EN 61000-3-3:2013+A2:2021+AC:2022	Limits for voltage fluctuations and flicker in low-voltage supply systems (equipment with input current $\leq 16 A$ per phase)	Pass

1.2.1 Performance Criteria for Compliance: EN 55035 and BS EN 55035

Performance criterion A

The equipment shall continue to operate as intended without operator intervention. No degradation of performance, loss of function or change of operating state is allowed below a performance level specified by the manufacturer when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

Performance criterion B

During the application of the disturbance, degradation of performance is allowed. However, no unintended change of actual operating state or stored data is allowed to persist after the test.

After the test, the equipment shall continue to operate as intended without operator intervention; no degradation of performance or loss of function is allowed, below a performance level specified by the manufacturer, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance.

If the minimum performance level (or the permissible performance loss), or recovery time, is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

Performance criterion C

Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions. A reboot or re-start operation is allowed.

Information stored in non-volatile memory, or protected by a battery backup, shall not be lost.

1.3 Description of EUT

EUT

This report test data using the report number ISL-24LE0556CE35

Product Name	USB 3.2 250GB~2TB
Condition	Pre-Production
Main Model	ARSTH-250GB
Series Model	ARSTH-500GB; ARSTH-1TB; ARSTH-2TB
Serial Number	NA
Power	From Personal Computer Supply
Control IC	PS2251-17
PCB Number	P066117UP0000N1N; P066117UP0000NXXXXXXXXX (X=0~9;A~Z,or Blank)
Memory Capacity	1GB-4TB
Highest working frequency	5GHz
TYPE-C to TYPE-C cable	0.3m
TYPE-C to USB A cable	0.3m

The memory capacities listed below is chosen by the applicant to be the representative configuration for testing in this report.

Test configurations:

Configuration	Control IC	PCB Number	Memory Capacity	Appearance	Cable
1	PS2251-17	P066117UP0000N1N	4TB	METAL	TYPE-C to TYPE-C
2					TYPE-C to USB A
3				PLASTIC	TYPE-C to TYPE-C
4					TYPE-C to USB A

Model Difference:

Model	Market
ARSTH-250GB; ARSTH-500GB; ARSTH-1TB; ARSTH-2TB	Different customer

PCB Number Difference:

Model	Market
P066117UP0000N1N; P066117UP0000NXXXXXXXXX (X=0~9;A~Z,or Blank)	Different customer

EMI Noise Source

refer to the photo	Control IC	Point
EUT-7	PS2251-17	U1
refer to the photo	Crystal	Point
EUT-8	25MHz	Y1

EMI Solution:

Refer to the photo	Materials	Spec(L*W*H) (mm)	Manufacturer	Point	Appearance
EUT-13	Gasket	7.0x5.0x3.5	NEO-APEX ENTERPRISE INC.	1	METAL

1.4 Description of Support Equipment

For EMI test Configuration Support unit: 1~6

For EMS test Configuration Support unit: 4, 6~10

No	Unit	Model / Serial No.	Brand	Power Cord	FCC ID
1	USB Keyboard	KB216 S/N: N/A	DELL	N/A	FCC DOC
2	USB Mouse	MS116 S/N: N/A	DELL	N/A	FCC DOC
3	LCD Monitor	P2723QE S/N: N/A	DELL	Non-shielded	FCC DOC
4	Printer	C930 S/N: N/A	HP	Non-shielded	FCC DOC
5	External HDD	My Passport Ultra S/N: N/A	WD	N/A	FCC DOC
6	Personal Computer	NUC8BEH S/N: N/A	Intel	Non-shielded	FCC DOC
7	USB Keyboard	SK-8115 S/N: N/A	DELL	N/A	FCC DOC
8	USB Mouse	MOCZUL S/N: N/A	DELL	N/A	FCC DOC
9	External HDD	SK2-U31AS-AKT S/N: N/A	AKiTiO	N/A	FCC DOC
10	LCD Monitor	P2715D S/N: N/A	DELL	Non-shielded	FCC DOC

1.5 Software for Controlling Support Unit

Test programs exercising various part of EUT were used. The programs were executed as follows:

1. PC running WINTHRAX to PC TYPE-C Port read and write the EUT. (For Config1 、3)
2. PC running WINTHRAX to PC USB Port read and write the EUT. (For Config2 、4)
3. Send signal to the Printer through PC USB Port.
4. Read and write External HDD through PC USB Port (For Config 1 、3).
5. Read and write External HDD through PC TYPE C Port (For Config 2 、4).
6. Send Color Bar to the LCD Monitor through PC HDMI Port.
7. Repeat the above steps.

	Filename	Version
EUT	WINTHRAX	3.09.02
LCD Monitor	Windows Media Player	12.0
Printer	IntelEMC	1.1
External HDD	IntelEMC	1.1

1.6 I/O Cable Condition of EUT and Support Units

Description	Path	Length	Shielding	Core	Remark
AC Power Cable	100V (~240V) to PC SPS	1.8m	No	No	
HDMI Cable	LCD Monitor HDMI Port to PC HDMI Port	1.8m	Yes	No	
USB Keyboard Data Cable	USB Keyboard to PC USB Port	1.8m	Yes	No	
USB Mouse Data Cable	USB Mouse to PC USB Port	1.8m	Yes	No	
Printer Data Cable	Printer to PC USB Port	1.8m	Yes	No	
TYPE-C cable (For Config1、3)	External HDD to PC USB port	1.5m	Yes	No	
TYPE-C cable (For Config2、4)	External HDD to PC TYPE-C port	1.5m	Yes	No	
TYPE-C cable (For Config1、3)	EUT TYPE-C port to PC TYPE-C Port	0.3m	Yes	No	
TYPE-C cable (For Config2、4)	EUT Type-C port to PC USB Port	0.3m	Yes	No	

2.1.4 Limit

Conducted emissions from the AC mains power ports of Class A equipment:


Frequency	QP	AV
MHz	dB(μ V)	dB(μ V)
0.15-0.50	79	66
0.50-30	73	60
Note: The lower limit shall apply at the transition frequencies		

Conducted emissions from the AC mains power ports of Class B equipment:

Frequency	QP	AV
MHz	dB(μ V)	dB(μ V)
0.15-0.50	66-56	56-46
0.50-5.0	56	46
5.0-30	60	50
Note: The lower limit shall apply at the transition frequencies		

2.2 Conduction Test Data: Configuration 1

-Live



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1*	0.152	43.48	15.99	9.68	53.16	65.88	-12.72	25.67	55.88	-30.21
2	2.945	27.28	14.89	9.77	37.05	56.00	-18.95	24.66	46.00	-21.34
3	3.401	23.09	12.20	9.79	32.88	56.00	-23.12	21.99	46.00	-24.01
4	5.089	25.71	15.75	9.82	35.53	60.00	-24.47	25.57	50.00	-24.43
5	5.485	26.39	16.05	9.83	36.22	60.00	-23.78	25.88	50.00	-24.12
6	15.720	20.10	11.87	9.95	30.05	60.00	-29.95	21.82	50.00	-28.18

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

- Neutral



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888


Conducted Emission Measurement

Date: 2024/7/31

operator: Mamie_Chen

Temperature: 24 °C

Humidity: 57 %



Site: Conduction 02

Phase: N

No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1*	0.152	43.94	12.64	9.69	53.63	65.88	-12.25	22.33	55.88	-33.55
2	0.672	22.57	8.27	9.70	32.27	56.00	-23.73	17.97	46.00	-28.03
3	2.942	25.56	12.87	9.77	35.33	56.00	-20.67	22.64	46.00	-23.36
4	3.401	21.53	10.91	9.79	31.32	56.00	-24.68	20.70	46.00	-25.30
5	5.545	25.24	15.07	9.84	35.08	60.00	-24.92	24.91	50.00	-25.09
6	15.643	19.68	11.50	10.00	29.68	60.00	-30.32	21.50	50.00	-28.50

Note:

Margin = QP/AVG Emission - Limit


QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

2.3 Conduction Test Data: Configuration 2

-Live



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1*	0.152	42.30	16.37	9.68	51.98	65.88	-13.90	26.05	55.88	-29.83
2	0.679	25.04	8.43	9.70	34.74	56.00	-21.26	18.13	46.00	-27.87
3	2.958	27.24	14.17	9.77	37.01	56.00	-18.99	23.94	46.00	-22.06
4	5.534	26.98	17.02	9.83	36.81	60.00	-23.19	26.85	50.00	-23.15
5	14.064	19.69	11.79	9.94	29.63	60.00	-30.37	21.73	50.00	-28.27
6	15.823	20.13	12.32	9.95	30.08	60.00	-29.92	22.27	50.00	-27.73

Note:


Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

- Neutral



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1*	0.158	43.04	12.29	9.69	52.73	65.56	-12.83	21.98	55.56	-33.58
2	0.685	23.06	8.84	9.70	32.76	56.00	-23.24	18.54	46.00	-27.46
3	1.255	20.07	13.47	9.73	29.80	56.00	-26.20	23.20	46.00	-22.80
4	1.714	19.97	12.61	9.75	29.72	56.00	-26.28	22.36	46.00	-23.64
5	2.945	24.28	11.84	9.77	34.05	56.00	-21.95	21.61	46.00	-24.39
6	5.543	25.25	15.71	9.84	35.09	60.00	-24.91	25.55	50.00	-24.45

Note:
Margin = QP/AVG Emission - Limit
QP/AVG Emission = QP_R/AVG_R + Correct Factor
Correct Factor = LISN Loss + Cable Loss
A margin of -8dB means that the emission is 8dB below the limit

2.4 Conduction Test Data: Configuration 3

-Live



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1*	0.152	42.25	14.50	9.68	51.93	65.88	-13.95	24.18	55.88	-31.70
2	0.672	23.23	6.83	9.70	32.93	56.00	-23.07	16.53	46.00	-29.47
3	2.945	28.16	15.66	9.77	37.93	56.00	-18.07	25.43	46.00	-20.57
4	5.087	25.82	16.04	9.82	35.64	60.00	-24.36	25.86	50.00	-24.14
5	5.588	26.00	14.91	9.83	35.83	60.00	-24.17	24.74	50.00	-25.26
6	6.866	22.97	14.52	9.86	32.83	60.00	-27.17	24.38	50.00	-25.62

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

- Neutral



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1*	0.152	42.45	11.47	9.69	52.14	65.88	-13.74	21.16	55.88	-34.72
2	0.672	21.28	7.91	9.70	30.98	56.00	-25.02	17.61	46.00	-28.39
3	2.945	25.62	13.62	9.77	35.39	56.00	-20.61	23.39	46.00	-22.61
4	5.087	24.08	14.15	9.82	33.90	60.00	-26.10	23.97	50.00	-26.03
5	5.537	25.14	14.88	9.84	34.98	60.00	-25.02	24.72	50.00	-25.28
6	5.930	23.93	13.07	9.84	33.77	60.00	-26.23	22.91	50.00	-27.09

Note:
Margin = QP/AVG Emission - Limit
QP/AVG Emission = QP_R/AVG_R + Correct Factor
Correct Factor = LISN Loss + Cable Loss
A margin of -8dB means that the emission is 8dB below the limit

2.5 Conduction Test Data: Configuration 4

-Live



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1*	0.159	41.98	13.43	9.68	51.66	65.52	-13.86	23.11	55.52	-32.41
2	0.672	22.91	6.30	9.70	32.61	56.00	-23.39	16.00	46.00	-30.00
3	2.942	28.71	16.58	9.77	38.48	56.00	-17.52	26.35	46.00	-19.65
4	5.087	25.94	16.07	9.82	35.76	60.00	-24.24	25.89	50.00	-24.11
5	5.532	26.38	16.24	9.83	36.21	60.00	-23.79	26.07	50.00	-23.93
6	5.930	25.03	13.79	9.83	34.86	60.00	-25.14	23.62	50.00	-26.38

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

- Neutral



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1*	0.152	41.84	11.44	9.69	51.53	65.88	-14.35	21.13	55.88	-34.75
2	0.672	21.57	7.83	9.70	31.27	56.00	-24.73	17.53	46.00	-28.47
3	2.942	26.16	14.19	9.77	35.93	56.00	-20.07	23.96	46.00	-22.04
4	3.401	21.51	10.32	9.79	31.30	56.00	-24.70	20.11	46.00	-25.89
5	5.494	25.52	14.95	9.83	35.35	60.00	-24.65	24.78	50.00	-25.22
6	15.695	20.08	11.69	10.00	30.08	60.00	-29.92	21.69	50.00	-28.31

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit


2.6 Test Setup Photo

Configuration 1

Front View



Back View



Configuration 2

Front View





Configuration 3

Front View




Back View



Configuration 4

Front View





3.1 Test Setup and Procedure

Conducted Emission Test Setup

Diagram illustrating the setup for a Conducted Emission Test. The setup includes a table with two blocks labeled EUT (Equipment Under Test) and EUT/AE (Equipment Under Test / Antenna Equipment). A Cable to AE is connected to the EUT/AE block. A Current probe is placed on the cable between the EUT and EUT/AE blocks. A CVP (Current Voltage Probe) is connected to the cable. A Cable 0.04 m from VRGP (Vertical Reference Ground Plane) is connected to the EUT block. An AMN / LISN (Artificial Magnetic Noise / Line Impedance Stabilization Network) is connected to the EUT block. The setup is on a Vertical reference ground plane with AMNs bonded to a reference ground plane. Dimensions are given: 0.1 m, 0.3 m, 0.8 m, 0.4 m, 0.1 m, 0.8 m, 0.4 m, 0.1 m, 0.8 m, 0.4 m.

Frequency Range: 150kHz--30MHz
 Detector Function: Quasi-Peak / Average Mode
 Resolution Bandwidth: 9kHz

3.1.4 Limit

Asymmetric mode conducted emissions from Class_A equipment:

Applicable to

1. wired network ports.
2. optical fiber ports with metallic shield or tension members.
3. antenna ports.

Frequency range MHz	Coupling device	Detector type / bandwidth	Class_A voltage limits dB(μV)	Class_A current limits dB(μA)
0.15-0.5	AAN	Quasi Peak / 9 kHz	97-87	n/a
0.5-30			87	
0.15-0.5	AAN	Average / 9 kHz	84-74	
0.5-30			74	
0.15-0.5	CVP and current probe	Quasi Peak / 9 kHz	97-87	53-43
0.5-30			87	43
0.15-0.5	CVP and current probe	Average / 9 kHz	84-74	40-30
0.5-30			74	30
0.15-0.5	Current Probe	Quasi Peak / 9 kHz	n/a	53-43
0.5-30				43
0.15-0.5	Current Probe	Average / 9 kHz		40-30
0.5-30				30

Asymmetric mode conducted emissions from Class_B equipment:

Applicable to:

1. wired network ports.
2. optical fiber ports with metallic shield or tension members.
3. broadcast receiver tuner ports.
4. antenna ports.




Frequency range MHz	Coupling device	Detector type / bandwidth	Class_B voltage limits dB(μV)	Class_B current limits dB(μA)
0.15-0.5	AAN	Quasi Peak / 9 kHz	84-74	n/a
0.5-30			74	
0.15-0.5	AAN	Average / 9 kHz	74-64	
0.5-30			64	
0.15-0.5	CVP and current probe	Quasi Peak / 9 kHz	84-74	40-30
0.5-30			74	30
0.15-0.5	CVP and current probe	Average / 9 kHz	74-64	30-20
0.5-30			64	20
0.15-0.5	Current Probe	Quasi Peak / 9 kHz	n/a	40-30
0.5-30				30
0.15-0.5	Current Probe	Average / 9 kHz		30-20
0.5-30				20

****Remarks: It is not necessary to be tested on this item.**

4. Radiated Disturbance Emissions

4.1 Test Setup and Procedure

4.1.1 Test Setup



The 3dB beam width of the horn antenna used for the test is as shown in the table below.

Frequency (GHz)	E-plane	H-plane	$\theta_{3dB}(\text{min})$	d= 3 m
				w (m)
1	88°	147°	88°	5.79
2	68°	119°	68°	4.04
3	73°	92°	73°	4.44
4	70°	89°	70°	4.20
5	55°	60°	55°	3.12
6	63°	62°	62°	3.60

4.1.2 Test Procedure

The radiated emissions test will then be repeated on the chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipment are set up on the turntable of one of 10 meter chamber. Desktop EUT are set up on a FRP stand 0.8 meter above the ground or floor-standing arrangement shall be placed on the horizontal ground reference plane.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. The highest emissions between 30 MHz to 1000 MHz were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The highest emissions between 1 GHz to 6 GHz were analyzed in details by operating the spectrum analyzer in peak and average mode to determine the precise amplitude of the emissions. The test volume for a height of up to 30 cm may be obstructed by absorber placed on the ground plane.

At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum measurement. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings. All of the interface cables were manipulated according to EN 55032 / BS EN 55032 requirements.

The highest internal source of an EUT is defined as the highest frequency generated or used within the EUT or on which the EUT operates or tunes.

If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz.

If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz.

If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz.

If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 6 GHz, whichever is less.

4.1.3 Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range: 30MHz--1000MHz
 Detector Function: Quasi-Peak Mode
 Resolution Bandwidth: 120kHz

Frequency Range: Above 1 GHz to 6 GHz
 Detector Function: Peak/Average Mode
 Resolution Bandwidth: 1MHz

4.2 Limit

Radiated emissions at frequencies up to 1 GHz for Class_A equipment:

Radiated emissions at frequencies up to 1 GHz for Class_A equipment:			
Frequency range MHz	Measurement		Class_A limits dB(μV/m)
	Distance m	Detector type / bandwidth	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	40
230-1000			47
30-230	3		50
230-1000			57

Radiated emissions at frequencies above 1 GHz for Class_A equipment of the EN 55032:2015+A11:2020:

Frequency range MHz	Measurement		Class_A limits dB(μ V/m)
	Distance m	Detector type / bandwidth	FSOATS
1000-3000	3	Average / 1MHz	56
3000-6000			60
1000-3000		Peak / 1MHz	76
3000-6000			80

Radiated emissions at frequencies above 1 GHz for Class_A equipment of the EN 55032:2015+A1:2020:

Frequency range MHz	Measurement		Class_A limits dB(μ V/m)
	Distance m	Detector type / bandwidth	FSOATS
1000-6000	3	Average / 1MHz	60
1000-6000		Peak / 1MHz	80

Note 1: The radiated emissions at frequencies above 1 GHz test limit in this report is based on EN 55032:2015+A11:2020.

Note 2: Test data in this report has been taken against the EN 55032:2015+A11:2020 limit as it is the most stringent limit. By complying with the more restrictive EN 55032:2015+A11:2020 limit compliance with the EN 55032:2015+A1:2020 limit is also demonstrated.

Radiated emissions at frequencies up to 1 GHz for Class_B equipment:

Frequency range MHz	Measurement		Class_B limits dB(μV/m)
	Distance m	Detector type / bandwidth	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	30
230-1000			37
30-230	3		40
230-1000			47

**Radiated emissions at frequencies above 1 GHz for Class_B equipment of the
EN 55032:2015+A11:2020:**

Frequency range MHz	Measurement		Class_B limits dB(μ V/m)
	Distance m	Detector type / bandwidth	FSOATS
1000-3000	3	Average / 1MHz	50
3000-6000			54
1000-3000		Peak / 1MHz	70
3000-6000			74

**Radiated emissions at frequencies above 1 GHz for Class_B equipment of the
EN 55032:2015+A1:2020:**

Frequency range MHz	Measurement		Class_B limits dB(μ V/m)
	Distance m	Detector type / bandwidth	FSOATS
1000-6000	3	Average / 1MHz	54
1000-6000		Peak / 1MHz	74

Note 1: The radiated emissions at frequencies above 1 GHz test limit in this report is based on EN 55032:2015+A11:2020.


Note 2: Test data in this report has been taken against the EN 55032:2015+A11:2020 limit as it is the most stringent limit. By complying with the more restrictive EN 55032:2015+A11:2020 limit compliance with the EN 55032:2015+A1:2020 limit is also demonstrated.

Radiated emissions from FM receivers:

Frequency range MHz	Measurement		Class_B limits dB(μV/m)	
	Distance m	Detector type / bandwidth	Fundamental	Harmonics
			OATS/SAC	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	50	42
230-300				42
300-1000				46
30-230	3		60	52
230-300				52
300-1000				56

4.3 Radiation Test Data: Configuration 1

- Radiated Emissions (Horizontal)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1*	37.76	38.74	-17.49	21.25	30.00	-8.75	100	360	QP
2	106.63	37.70	-19.57	18.13	30.00	-11.87	400	221	QP
3	118.27	38.94	-18.49	20.45	30.00	-9.55	389	143	QP
4	182.29	35.94	-17.04	18.90	30.00	-11.10	400	182	QP
5	231.76	34.62	-17.31	17.31	37.00	-19.69	201	156	QP
6	333.61	34.12	-12.62	21.50	37.00	-15.50	114	307	QP

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters


If the peak measured value meets the QP limit, The QP value is inherently compliant.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Radiated Emission Measurement
Date: 2024/8/1

Operator: Kevin Chan
Temperature: 25 °C
Humidity: 61 %



Site : Chamber 14

Polarization: Horizontal

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1996.80	48.82	-11.80	37.02	50.00	-12.98	100	135	AVG
2	2000.00	67.56	-11.80	55.76	70.00	-14.24	100	129	peak
3	2390.00	65.75	-11.25	54.50	70.00	-15.50	200	256	peak
4*	2390.96	48.68	-11.26	37.42	50.00	-12.58	200	249	AVG
5	3035.00	59.83	-9.92	49.91	74.00	-24.09	100	139	peak
6	3430.00	60.18	-9.84	50.34	74.00	-23.66	200	269	peak
7	3430.45	48.77	-9.84	38.93	54.00	-15.07	200	260	AVG
8	4500.00	59.71	-8.11	51.60	74.00	-22.40	100	157	peak
9	4501.60	44.71	-8.10	36.61	54.00	-17.39	101	160	AVG
10	4784.68	45.49	-8.34	37.15	54.00	-16.85	150	160	AVG
11	4785.00	62.05	-8.34	53.71	74.00	-20.29	150	152	peak

* Note:

Margin = Emission - Limit

Emission = Radiated Amplitude + Correct Factor


Correct Factor = Antenna Correction Factor + Cable Loss - Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

If the peak measured value meets the Average limit, The Average value is inherently compliant.

-Radiated Emissions (Vertical)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	38.73	39.82	-17.48	22.34	30.00	-7.66	100	354	QP
2	57.16	35.72	-16.63	19.09	30.00	-10.91	100	67	QP
3!	119.24	42.63	-18.56	24.07	30.00	-5.93	100	221	QP
4	182.29	38.30	-17.04	21.26	30.00	-8.74	100	26	QP
5*	228.85	43.20	-17.75	25.45	30.00	-4.55	200	342	QP
6	968.96	27.91	-0.36	27.55	37.00	-9.45	300	199	QP

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters


If the peak measured value meets the QP limit, The QP value is inherently compliant.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Radiated Emission Measurement
Date: 2024/8/1

Operator: Kevin Chan
Temperature: 25 °C
Humidity: 61 %



Site : Chamber 14

Polarization: Vertical

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1325.00	63.08	-14.71	48.37	70.00	-21.63	150	228	peak
2	1325.17	48.11	-14.71	33.40	50.00	-16.60	150	226	AVG
3*	1994.98	52.05	-11.80	40.25	50.00	-9.75	100	132	AVG
4	1995.00	71.31	-11.80	59.51	70.00	-10.49	100	129	peak
5	2390.00	67.20	-11.25	55.95	70.00	-14.05	100	132	peak
6	2391.89	47.03	-11.27	35.76	50.00	-14.24	100	127	AVG
7	3104.98	48.59	-10.19	38.40	54.00	-15.60	100	235	AVG
8	3105.00	60.52	-10.19	50.33	74.00	-23.67	100	218	peak
9	3585.00	61.42	-9.95	51.47	74.00	-22.53	100	149	peak
10	3585.25	47.09	-9.95	37.14	54.00	-16.86	100	138	AVG
11	4790.00	63.25	-8.34	54.91	74.00	-19.09	100	168	peak
12	4790.12	48.14	-8.34	39.80	54.00	-14.20	100	170	AVG

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain


A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

If the peak measured value meets the Average limit, The Average value is inherently compliant.

4.4 Radiation Test Data: Configuration 2

- Radiated Emissions (Horizontal)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	38.73	39.67	-17.48	22.19	30.00	-7.81	300	272	QP
2	71.71	39.59	-19.15	20.44	30.00	-9.56	100	54	QP
3	118.27	40.12	-18.49	21.63	30.00	-8.37	400	331	QP
4*	180.35	39.66	-16.77	22.89	30.00	-7.11	400	174	QP
5	884.57	30.28	-1.74	28.54	37.00	-8.46	100	289	QP
6	971.87	29.06	-0.36	28.70	37.00	-8.30	293	0	QP

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters


If the peak measured value meets the QP limit, The QP value is inherently compliant.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Radiated Emission Measurement
Date: 2024/8/1

Operator: Kevin Chan
Temperature: 25 °C
Humidity: 61 %



Site : Chamber 14

Polarization: Horizontal

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1994.97	47.62	-11.80	35.82	50.00	-14.18	200	135	AVG
2	1995.00	67.07	-11.80	55.27	70.00	-14.73	200	142	peak
3	2390.00	66.40	-11.25	55.15	70.00	-14.85	200	243	peak
4*	2392.24	48.08	-11.27	36.81	50.00	-13.19	200	238	AVG
5	2659.54	45.92	-10.70	35.22	50.00	-14.78	151	139	AVG
6	2660.00	59.85	-10.70	49.15	70.00	-20.85	150	146	peak
7	3015.00	59.77	-9.93	49.84	74.00	-24.16	150	138	peak
8	3015.50	48.07	-9.93	38.14	54.00	-15.86	150	133	AVG
9	4509.79	47.44	-8.03	39.41	54.00	-14.59	150	182	AVG
10	4510.00	59.82	-8.03	51.79	74.00	-22.21	150	179	peak
11	4785.00	61.87	-8.34	53.53	74.00	-20.47	150	158	peak
12	4785.04	45.26	-8.34	36.92	54.00	-17.08	150	155	AVG

* Note:

Margin = Emission - Limit

Emission = Radiated Amplitude + Correct Factor


Correct Factor = Antenna Correction Factor + Cable Loss - Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

If the peak measured value meets the Average limit, The Average value is inherently compliant.

-Radiated Emissions (Vertical)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	38.73	39.81	-17.48	22.33	30.00	-7.67	100	113	QP
2	57.16	36.26	-16.63	19.63	30.00	-10.37	100	261	QP
3*	118.27	42.75	-18.49	24.26	30.00	-5.74	100	283	QP
4	180.35	39.63	-16.77	22.86	30.00	-7.14	100	274	QP
5	231.76	42.80	-17.31	25.49	37.00	-11.51	100	83	QP
6	924.34	29.87	-0.88	28.99	37.00	-8.01	100	44	QP

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters


If the peak measured value meets the QP limit, The QP value is inherently compliant.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Radiated Emission Measurement
Date: 2024/8/1

Operator: Kevin Chan
Temperature: 25 °C
Humidity: 61 %



Site : Chamber 14

Polarization: Vertical

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1325.00	62.32	-14.71	47.61	70.00	-22.39	200	203	peak
2	1325.24	47.26	-14.71	32.55	50.00	-17.45	199	206	AVG
3	1994.18	49.61	-11.80	37.81	50.00	-12.19	150	141	AVG
4*	1995.00	70.54	-11.80	58.74	70.00	-11.26	150	138	peak
5	2390.00	66.71	-11.25	55.46	70.00	-14.54	150	128	peak
6	2390.12	48.71	-11.25	37.46	50.00	-12.54	150	124	AVG
7	3105.00	60.37	-10.19	50.18	74.00	-23.82	150	238	peak
8	3105.97	48.23	-10.19	38.04	54.00	-15.96	150	242	AVG
9	3785.00	59.55	-9.17	50.38	74.00	-23.62	100	203	peak
10	3786.82	47.67	-9.17	38.50	54.00	-15.50	102	192	AVG
11	4794.74	48.38	-8.35	40.03	54.00	-13.97	100	176	AVG
12	4795.00	65.05	-8.35	56.70	74.00	-17.30	100	179	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain


A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

If the peak measured value meets the Average limit, The Average value is inherently compliant.

4.5 Radiation Test Data: Configuration 3

- Radiated Emissions (Horizontal)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	37.76	39.29	-17.49	21.80	30.00	-8.20	328	309	QP
2	71.71	36.77	-19.15	17.62	30.00	-12.36	100	112	QP
3	106.63	35.30	-19.57	15.73	30.00	-14.27	102	147	QP
4	166.77	30.69	-15.56	15.13	30.00	-14.87	336	201	QP
5	890.39	29.23	-1.42	27.81	37.00	-9.19	223	332	QP
6*	969.93	29.99	-0.33	29.66	37.00	-7.34	100	23	QP

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters


If the peak measured value meets the QP limit, The QP value is inherently compliant.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Radiated Emission Measurement
Date: 2024/8/1

Operator: Kevin Chan
Temperature: 25 °C
Humidity: 61 %



Site : Chamber 14

Polarization: Horizontal

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1*	1715.00	74.03	-14.65	59.38	70.00	-10.62	100	207	peak
2	1716.97	44.37	-14.61	29.76	50.00	-20.24	100	212	AVG
3	1998.92	47.28	-11.80	35.48	50.00	-14.52	200	131	AVG
4	2000.00	67.95	-11.80	56.15	70.00	-13.85	200	125	peak
5	2390.00	65.70	-11.25	54.45	70.00	-15.55	150	252	peak
6	2391.73	48.15	-11.27	36.88	50.00	-13.12	150	246	AVG
7	3003.86	45.54	-9.93	35.61	54.00	-18.39	150	134	AVG
8	3005.00	60.31	-9.93	50.38	74.00	-23.62	150	129	peak
9	3754.24	47.01	-9.24	37.77	54.00	-16.23	100	125	AVG
10	3755.00	59.66	-9.24	50.42	74.00	-23.58	100	121	peak
11	4788.45	46.24	-8.35	37.89	54.00	-16.11	100	158	AVG
12	4790.00	64.01	-8.34	55.67	74.00	-18.33	100	166	peak

* Note:

Margin = Emission - Limit

Emission = Radiated Amplitude + Correct Factor


Correct Factor = Antenna Correction Factor + Cable Loss - Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

If the peak measured value meets the Average limit, The Average value is inherently compliant.

-Radiated Emissions (Vertical)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	37.76	38.95	-17.49	21.46	30.00	-8.54	100	353	QP
2	119.24	38.31	-18.56	19.75	30.00	-10.25	253	179	QP
3	181.32	37.98	-16.98	21.00	30.00	-9.00	123	143	QP
4*	229.82	39.16	-17.62	21.54	30.00	-8.46	214	289	QP
5	900.09	29.78	-1.38	28.40	37.00	-8.60	100	286	QP
6	1000.00	28.22	-0.05	28.17	37.00	-8.83	196	238	QP

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters


If the peak measured value meets the QP limit, The QP value is inherently compliant.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Radiated Emission Measurement
Date: 2024/8/1

Operator: Kevin Chan
Temperature: 25 °C
Humidity: 61 %



Site : Chamber 14

Polarization: Vertical

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1325.00	64.02	-14.71	49.31	70.00	-20.69	150	225	peak
2	1326.97	45.61	-14.71	30.90	50.00	-19.10	150	222	AVG
3	1713.14	44.44	-14.69	29.75	50.00	-20.25	101	360	AVG
4	1715.00	62.66	-14.65	48.01	70.00	-21.99	100	352	peak
5*	1994.58	53.78	-11.80	41.98	50.00	-8.02	150	125	AVG
6	1995.00	69.67	-11.80	57.87	70.00	-12.13	150	129	peak
7	2390.00	66.13	-11.25	54.88	70.00	-15.12	100	118	peak
8	2390.04	49.33	-11.25	38.08	50.00	-11.92	100	122	AVG
9	2740.00	60.03	-10.96	49.07	70.00	-20.93	150	239	peak
10	2741.32	45.24	-10.96	34.28	50.00	-15.72	150	244	AVG
11	4793.64	45.93	-8.35	37.58	54.00	-16.42	100	197	AVG
12	4795.00	64.54	-8.35	56.19	74.00	-17.81	100	201	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain


A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

If the peak measured value meets the Average limit, The Average value is inherently compliant.

4.6 Radiation Test Data: Configuration 4

- Radiated Emissions (Horizontal)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	38.73	41.05	-17.48	23.57	30.00	-6.43	300	91	QP
2	71.71	40.65	-19.15	21.50	30.00	-8.50	114	0	QP
3	106.63	40.96	-19.57	21.39	30.00	-8.61	399	360	QP
4	386.96	34.91	-11.12	23.79	37.00	-13.21	150	133	QP
5	774.96	33.41	-2.61	30.80	37.00	-6.20	300	213	QP
6*	959.26	31.48	-0.40	31.08	37.00	-5.92	100	39	QP

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters


If the peak measured value meets the QP limit, The QP value is inherently compliant.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Radiated Emission Measurement
Date: 2024/8/1

Operator: Kevin Chan
Temperature: 25 °C
Humidity: 61 %



Site : Chamber 14

Polarization: Horizontal

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1990.00	67.76	-11.81	55.95	70.00	-14.05	200	125	peak
2	1990.27	47.99	-11.81	36.18	50.00	-13.82	200	130	AVG
3	2395.00	65.97	-11.29	54.68	70.00	-15.32	200	233	peak
4*	2395.39	48.84	-11.29	37.55	50.00	-12.45	200	249	AVG
5	2655.00	61.31	-10.66	50.65	70.00	-19.35	150	208	peak
6	2655.26	45.18	-10.66	34.52	50.00	-15.48	150	214	AVG
7	3103.21	49.05	-10.19	38.86	54.00	-15.14	100	152	AVG
8	3105.00	62.46	-10.19	52.27	74.00	-21.73	100	149	peak
9	3415.00	60.47	-9.85	50.62	74.00	-23.38	200	255	peak
10	3416.45	47.34	-9.85	37.49	54.00	-16.51	200	260	AVG
11	4779.88	45.44	-8.33	37.11	54.00	-16.89	100	168	AVG
12	4780.00	62.87	-8.33	54.54	74.00	-19.46	100	172	peak

* Note:

Margin = Emission - Limit

Emission = Radiated Amplitude + Correct Factor


Correct Factor = Antenna Correction Factor + Cable Loss - Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

If the peak measured value meets the Average limit, The Average value is inherently compliant.

-Radiated Emissions (Vertical)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1!	30.00	42.45	-17.96	24.49	30.00	-5.51	100	360	QP
2'	77.53	46.41	-20.51	25.90	30.00	-4.10	200	163	QP
3	116.33	41.41	-18.74	22.67	30.00	-7.33	150	214	QP
4	158.04	35.39	-15.40	19.99	30.00	-10.01	200	289	QP
5	235.64	34.00	-16.69	17.31	37.00	-19.69	100	67	QP
6	929.19	31.78	-0.85	30.93	37.00	-6.07	250	3	QP

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters


If the peak measured value meets the QP limit, The QP value is inherently compliant.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Radiated Emission Measurement
Date: 2024/8/1

Operator: Kevin Chan
Temperature: 25 °C
Humidity: 61 %



Site : Chamber 14

Polarization: Vertical

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1325.00	61.91	-14.71	47.20	70.00	-22.80	200	227	peak
2	1325.17	47.69	-14.71	32.98	50.00	-17.02	200	230	AVG
3	1995.00	69.69	-11.80	57.89	70.00	-12.11	200	142	peak
4*	1995.29	53.18	-11.80	41.38	50.00	-8.62	200	138	AVG
5	2390.00	66.63	-11.25	55.38	70.00	-14.62	150	123	peak
6	2391.18	48.73	-11.26	37.47	50.00	-12.53	150	119	AVG
7	2950.00	59.59	-10.36	49.23	70.00	-20.77	150	224	peak
8	2950.32	44.97	-10.36	34.61	50.00	-15.39	150	233	AVG
9	3095.00	61.57	-10.16	51.41	74.00	-22.59	100	238	peak
10	3096.66	47.70	-10.17	37.53	54.00	-16.47	100	240	AVG
11	4789.25	46.09	-8.34	37.75	54.00	-16.25	101	207	AVG
12	4790.00	65.24	-8.34	56.90	74.00	-17.10	100	199	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

If the peak measured value meets the Average limit, The Average value is inherently compliant.


4.7 Test Setup Photo

Configuration 1

Front View (30MHz~1GHz)




Back View (30MHz~1GHz)



Front View (above 1GHz)



Back View (above 1GHz)



Configuration 2


Front View (30MHz~1GHz)




Back View (30MHz~1GHz)



Front View (above 1GHz)



Back View (above 1GHz)




Configuration 3

Front View (30MHz~1GHz)



Back View (30MHz~1GHz)



Front View (above 1GHz)



Back View (above 1GHz)




Configuration 4


Front View (30MHz~1GHz)



Back View (30MHz~1GHz)



Front View (above 1GHz)




Back View (above 1GHz)



5. Voltage Disturbance Emissions at Antenna Terminals

5.1 Test Setup and Procedure

5.1.1 Test Setup



5.1.2 Test Procedure

The output level of the auxiliary signal generator was set to 70dB μ V at the EUT antenna terminal with 75 ohms impedance with an un-modulated carrier.

The highest emissions were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The power of EUT was switched off to make sure the emission was not contributed by the auxiliary signal generator. While doing so, the interconnecting cables and major parts of the system were moved around to maximize the emission.

5.1.3 EMI Receiver Configuration (for the frequencies tested)

Frequency Range:	30MHz-2150MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz

5.1.4 Limit

Applicable to:

1. TV broadcast receiver tuner ports with an accessible connector.
2. RF modulator output ports.
3. FM broadcast receiver tuner ports with an accessible connector.

Applicable to

1. TV broadcast receiver tuner ports (3.1.8) with an accessible connector

2. RF modulator output ports (3.1.29)

3. FM broadcast receiver tuner ports (3.1.8) with an accessible connector

Table clause	Frequency range MHz	Detector type/ bandwidth	Class B limits dB(μV) 75 Ω			Applicability
			Other	Local Oscillator Fundamental	Local Oscillator Harmonics	
A13.1	30 to 950	For frequencies ≤1 GHz	46	46	46	See ^a
	950 to 2 150		46	54	54	
A13.2	950 to 2 150	Quasi Peak/ 120 kHz	46	54	54	See ^b
A13.3	30 to 300		46	54	50	See ^c
	300 to 1 000	52				
A13.4	30 to 300	For frequencies ≥1 GHz	46	66	59	See ^d
	300 to 1 000				52	
A13.5	30 to 950	Peak/ 1 MHz	46	76	46	See ^e
	950 to 2 150			n/a	54	

a

Television receivers (analogue or digital), video recorders and PC TV broadcast receiver tuner cards working in channels between 30 MHz and 1 GHz, and digital audio receivers.

b

Tuner units (not the LNB) for satellite signal reception.

c

Frequency modulation audio receivers and PC tuner cards.

d

Frequency modulation car radios.

e

Applicable to EUTs with RF modulator output ports (for example DVD equipment, video recorders, camcorders and decoders etc.) designed to connect to TV broadcast receiver tuner ports. Limits specified for the LO are for the RF modulator carrier signal and harmonics.

The term 'other' refers to all emissions other than the fundamental and the harmonics of the LO.

The measurement shall cover the entire frequency range.


The EUT shall be tuned in accordance with Table B.3 and clause C.4.2.1.

****Remarks: It is not necessary to be tested on this item.**

6. Differential Voltage Emissions

6.1 Test Setup and Procedure

6.1.1 Test Setup



6.1.2 Test Procedure

The output level of the auxiliary signal generator was set to 70dB μ V at the EUT antenna terminal with 75 ohms impedance with an un-modulated carrier.

The highest emissions were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The power of EUT was switched off to make sure the emission was not contributed by the auxiliary signal generator. While doing so, the interconnecting cables and major parts of the system were moved around to maximize the emission.

6.1.3 EMI Receiver Configuration (for the frequencies tested)

Frequency Range:	30MHz-2150MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz

6.1.4 Limit

Applicable to:

1. TV broadcast receiver tuner ports with an accessible connector.
2. RF modulator output ports.
3. FM broadcast receiver tuner ports with an accessible connector.

Applicable to

1. TV broadcast receiver tuner ports (3.1.8) with an accessible connector

2. RF modulator output ports (3.1.29)

3. FM broadcast receiver tuner ports (3.1.8) with an accessible connector

Table clause	Frequency range MHz	Detector type/ bandwidth	Class B limits dB(μV) 75 Ω			Applicability
			Other	Local Oscillator Fundamental	Local Oscillator Harmonics	
A13.1	30 to 950	For frequencies ≤1 GHz	46	46	46	See ^a
	950 to 2 150		46	54	54	
A13.2	950 to 2 150	Quasi Peak/ 120 kHz	46	54	54	See ^b
A13.3	30 to 300		46	54	50	See ^c
	300 to 1 000			52		
A13.4	30 to 300	For frequencies ≥1 GHz	46	66	59	See ^d
	300 to 1 000				52	
A13.5	30 to 950	Peak/ 1 MHz	46	76	46	See ^e
	950 to 2 150			n/a	54	

^a Television receivers (analogue or digital), video recorders and PC TV broadcast receiver tuner cards working in channels between 30 MHz and 1 GHz, and digital audio receivers.

^b Tuner units (not the LNB) for satellite signal reception.

^c Frequency modulation audio receivers and PC tuner cards.

^d Frequency modulation car radios.

^e Applicable to EUTs with RF modulator output ports (for example DVD equipment, video recorders, camcorders and decoders etc.) designed to connect to TV broadcast receiver tuner ports. Limits specified for the LO are for the RF modulator carrier signal and harmonics.

The term 'other' refers to all emissions other than the fundamental and the harmonics of the LO.

The measurement shall cover the entire frequency range.



The EUT shall be tuned in accordance with Table B.3 and clause C.4.2.1.

****Remarks: It is not necessary to be tested on this item.**

7. Outdoor units of home satellite receiving systems

7.1 Test Setup and Procedure

7.1.1 Test Setup

	
Description of $\pm 7^\circ$ of the main beam axis of the EUT	Measurement arrangements of transmit antenna for the wanted signal

7.1.2 Test Procedure

The input signal shall be adjusted to get the maximum rated output level from the EUT. For the measurement in the frequency range from 30 MHz to 18 GHz the input signal shall be adjusted so that the output frequency is within this frequency range. For the measurement in the frequency range above 1 GHz, the frequency of the input signal shall be adjusted in such a way that the EUT is measured, as a minimum, at the lowest, middle and highest rated output frequency within the measured frequency range.

7.1.3 Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range: 30MHz--1000MHz
 Detector Function: Quasi-Peak Mode
 Resolution Bandwidth: 120kHz

Frequency Range: Above 1000MHz
 Detector Function: Peak/Average Mode
 Resolution Bandwidth: 1MHz

7.1.4 Limit

EN 55032:2015+A11:2020

Table Clause	Frequency Range MHz	Measurement			Class B Limits	Applicable to
		Facility (see Table A.1)	Distance m	Detector type / Bandwidth		
A7.1	30 to 1 000	SAC / OATS / FAR	See Table A.4	Quasi Peak / 120 kHz	See Table A.4	
A7.2	1 000 to 2 500	FSOATS	3	Average / 1 MHz	50 dB(μV/m)	LO leakage and spurious radiated emissions from the EUT, in the region outside ±7° of the main beam axis. See Figure H.1
	2 500 to 18 000				64 dB(μV/m)	
A7.3	1 000 to 18 000	FSOATS	3	Average / 1 MHz	37 dB(μV/m)	LO leakage from the EUT, in the region within ±7° of the main beam axis. See Figure H.1
A7.4	1 000 to 18 000	Conducted (Clause H.4)	n/a	Average / 1 MHz	30 dBpW	

For details of the EUT configuration, see Annex H.

For radiated emissions measurements at frequencies up to 1 GHz, the requirements defined in Table A.4 shall be satisfied.

Apply the appropriate limits across the entire frequency range.

Apply the limits defined in table Clause A7.1 and A7.2. Also apply the limits defined in either table Clause A7.3 or A7.4.

EN 55032:2015+A11:2020

Table Clause	Frequency Range MHz	Measurement			Class B Limits	Notes
		Facility (see Table A.1)	Distance m	Detector type / Bandwidth		
A7.1	30 to 1 000	SAC / OATS / FAR	See Table A.4	Quasi Peak / 120 kHz	See Table A.4	See Annex H
A7.2	1 000 to 2 500	FSOATS	3	Average / 1 MHz	50 dB(μV/m)	LO leakage and spurious radiated emissions from the EUT, in the region outside ±7° azimuth of the main beam axis. See Annex H
	2 500 to 18 000				64 dB(μV/m)	
A7.3	1 000 to 18 000	FSOATS	3	Average / 1 MHz	70 dB(μV/m)	LO leakage from the EUT, in the region within ±7° azimuth of the main beam axis. See Annex H
A7.4	1 000 to 18 000	Conducted (Clause H.4)	n/a	Average / 1 MHz	63 dBpW	

Apply the limits defined in table Clause A7.1 and A7.2. Also apply the limits defined in either table Clause A7.3 or A7.4.

For details of the EUT configuration, see Annex H.

For radiated emissions measurements at frequencies up to 1 GHz, the requirements defined in Table A.4 shall be satisfied.

Apply the appropriate limits across the entire frequency range.

Note 1: The test limit in this report is based on EN 55032:2015+A11:2020.

Note 2: Test data in this report has been taken against the EN 55032:2015+A11:2020 limit as it is the most stringent limit. By complying with the more restrictive EN 55032:2015+A11:2020 limit compliance with the EN 55032:2015+A1:2020 limit is also demonstrated.

****Remarks: It is not necessary to be tested on this item.**

8. Electrostatic discharge immunity

8.1 Test Specification and Setup

8.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-2 / IEC 61000-4-2 / BS EN 61000-4-2 (details referred to Sec 1.2)
Test Level:	Air +/- 2 kV, +/- 4 kV, +/- 8 kV Contact +/- 4 kV
Criteria:	B
Test Procedure:	refer to ISL QA -T4-E-S7
Temperature:	22°C
Humidity:	40%

Selected Test Point


Air: discharges were applied to slots, aperture or insulating surfaces. 10 single air discharges were applied to each selected points.

Contact: 10 discharges minimum were to the selected contact points.

Indirect Contact Points: 10 discharges were applied to center of one edge of VCP and each EUT side of HCP with 10 cm away from EUT.

8.1.2 Test Setup

EUT is 1m from the wall and other metallic structure. When Battery test mode is needed, a cable with one 470kΩ resistor at two rare ends is connected from metallic part of EUT and screwed to HCP.



8.1.3 Test Result

Performance of EUT complies with the given specification.

8.2 Test Point: Configuration 1

Red arrow lines indicate the contact points, and blue arrow lines indicate the air points.

Figure 1: Test Point Assignments Discharge:



Figure 2: Test Point Assignments Discharge:



Figure 3: Test Point Assignments Discharge:



8.3 Test Point: Configuration 2

Red arrow lines indicate the contact points, and blue arrow lines indicate the air points.

Figure 1: Test Point Assignments Discharge:



Figure 2: Test Point Assignments Discharge:



Figure 3: Test Point Assignments Discharge:



8.4 Test Point: Configuration 3

Red arrow lines indicate the contact points, and blue arrow lines indicate the air points.

Figure 1: Test Point Assignments Discharge:



Figure 2: Test Point Assignments Discharge:



Figure 3: Test Point Assignments Discharge:



8.5 Test Point: Configuration 4

Red arrow lines indicate the contact points, and blue arrow lines indicate the air points.

Figure 1: Test Point Assignments Discharge:



Figure 2: Test Point Assignments Discharge:




Figure 3: Test Point Assignments Discharge:



Configuration 3



Configuration 4



9. Radiated, radio-frequency, electromagnetic field immunity


9.1 Test Specification and Setup

9.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN IEC 61000-4-3 / IEC 61000-4-3 / BS EN IEC 61000-4-3 (details referred to Sec 1.2)
Test Level:	3 V/m
Modulation:	AM 1kHz 80%
Frequency range:	80 MHz~1 GHz 1800MHz, 2600MHz, 3500MHz, 5000MHz
Frequency Step:	1% of last step frequency
Dwell time:	2s
Polarization:	Vertical and Horizontal
EUT Azimuth Angle	☒ 0° ☒ 90° ☒ 180° ☒ 270°
Criteria:	A
Test Procedure:	refer to ISL QA -T4-E-S8
Temperature:	23°C
Humidity:	54%

9.1.2 Test Setup

The field sensor is placed at one calibration grid point to check the intensity of the established fields on both polarizations. EUT is adjusted to have each side of EUT face coincident with the calibration plane. A CCD camera and speakers are used to monitor the condition of EUT for the performance judgment.



9.1.3 Test Result

Performance of EUT complies with the given specification.

9.2 Test Setup Photo

Configuration 1




Configuration 2



Configuration 3



Configuration 4



10. Electrical fast transient/burst immunity

10.1 Test Specification and Setup

10.1.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-4-4 / IEC 61000-4-4 / BS EN 61000-4-4 (details referred to Sec 1.2)
Test Level:	AC Power Port: +/- 1 kV
Rise Time:	5ns
Hold Time:	50ns
Burst Period:	300ms
Repetition Frequency:	5kHz
Criteria:	B
Test Procedure:	refer to ISL QA -T4-E-S9
Temperature:	25°C
Humidity:	55%

Test Procedure


The EUT was setup on a nonconductive table 0.1 m above a reference ground plane.

Test Points	Polarity	Result	Comment
Line	+	N	60 sec
	-	N	60 sec
Neutral	+	N	60 sec
	-	N	60 sec
Ground	+	N	60 sec
	-	N	60 sec
Line and Neutral	+	N	60 sec
	-	N	60 sec
Line and Ground	+	N	60 sec
	-	N	60 sec
Neutral and Ground	+	N	60 sec
	-	N	60 sec
Line and Neutral and Ground	+	N	60 sec
	-	N	60 sec

Note: 'N' means normal, the EUT function is correct during the test.

10.1.2 Test Setup

EUT is at least 50cm from the conductive structure.



10.1.3 Test Result

Performance of EUT complies with the given specification.

10.2 Test Setup Photo

Configuration 1



Configuration 2



Configuration 3



Configuration 4




11. Surge immunity

11.1 Test Specification and Setup

11.1.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-4-5 / IEC 61000-4-5 / BS EN 61000-4-5 (details referred to Sec 1.2)
Test Level:	Line to Line: +/- 0.5 kV, +/- 1 kV Line to Earth: +/- 0.5 kV, +/- 1 kV, +/- 2kV
Rise Time:	1.2us
Hold Time:	50us
Repetition Rate:	30 seconds
Angle:	☐ 0° ☒ 90° ☐ 180° ☒ 270°
Criteria:	B
Test Procedure:	refer to ISL QA -T4-E-S10
Temperature:	23°C
Humidity:	55%

11.1.2 Test Setup



11.1.3 Test Result

Performance of EUT complies with the given specification.

11.2 Test Setup Photo

Configuration 1



Configuration 2



Configuration 3



Configuration 4




12. Immunity to conducted disturbances

12.1 Test Specification and Setup

12.1.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-4-6 / IEC 61000-4-6 / BS EN 61000-4-6 (details referred to Sec 1.2)
Frequency range and Test Level:	0.15MHz to 10MHz: 3 Vrms 10MHz to 30MHz: 3Vrms to 1Vrms 30MHz to 80MHz: 1Vrms
Modulation:	AM 1kHz 80%
Frequency Step:	1% of last Frequency
Dwell time:	2s
Criteria:	A
CDN Type:	CDN M2+M3
Test Procedure:	refer to ISL QA -T4-E-S11
Temperature:	24°C
Humidity:	55%

12.1.2 Test Setup



12.1.3 Test Result

Performance of EUT complies with the given specification.

12.2 Test Setup Photo

Configuration 1



Configuration 2



Configuration 3



Configuration 4




13. Power frequency magnetic field immunity

13.1 Test Specification and Setup

13.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-8 / IEC 61000-4-8 / BS EN 61000-4-8 (details referred to Sec 1.2)
Test Level:	1A/m
Polarization:	X, Y, Z
Criteria:	A
Test Procedure:	refer to ISL QA -T4-E-S12
Temperature:	24°C
Humidity:	54%

13.1.2 Test Setup



13.1.3 Test Result

Performance of EUT complies with the given specification.

13.2 Test Setup Photo

Configuration 1



Configuration 2



Configuration 3



Configuration 4




14. Voltage dips, short interruptions and voltage variations immunity

14.1 Test Specification and Setup

14.1.1 Test Specification

Port:	AC mains
Basic Standard:	EN IEC 61000-4-11 / IEC 61000-4-11 / BS EN IEC 61000-4-11 (details referred to Sec 1.2)
When the product is greater than 16A does not apply to this Standard, it is not necessary to be tested on this item. In addition, IEC/EN 61000-4-34 Standard was used to evaluating.	
Test Level:	>95% in 0.5 cycle
Criteria:	B
Test Level:	30% in 25 cycle
Criteria:	C
Test Level:	>95% in 250 cycle
Criteria:	C
Phase:	0°; 180°
Test intervals:	3 times with 10s each
Test Procedure:	refer to ISL QA -T4-E-S13
Temperature:	24°C
Humidity:	54%

14.1.2 Test Setup



14.1.3 Test Result

Performance of EUT complies with the given specification.

14.2 Test Setup Photo

Configuration 1



Configuration 2



Configuration 3



Configuration 4



15. Harmonics

15.1 Test Specification and Setup

15.1.1 Test Specification


Port:	AC mains
Active Input Power:	<75W
Basic Standard:	EN IEC 61000-3-2 / IEC 61000-3-2 / BS EN IEC 61000-3-2 (details referred to Sec 1.2)
Test Duration:	2.5min
Class:	A
Test Procedure:	refer to ISL QA -T4-E-S14
Temperature:	24°C
Humidity:	55%

Test Procedure

The EUT is supplied in series with shunts or current transformers from a source having the same nominal voltage and frequency as the rated supply voltage and frequency of the EUT. The EUT is configured to its rated current with additional resistive load when the testing is performed.

Equipment having more than one rated voltage shall be tested at the rated voltage producing the highest harmonics as compared with the limits.

15.1.2 Test Setup



15.1.3 Limit

Limits of Class A Harmonics Currents

Harmonics Order n	Maximum Permissible harmonic current A	Harmonics Order n	Maximum Permissible harmonic current A
Odd harmonics		Even harmonics	
3	2.30	2	1.08
5	1.14	4	0.43
7	0.77	6	0.30
9	0.40	$8 \leq n \leq 40$	$0.23 * 8/n$
11	0.33		
13	0.21		
$15 \leq n \leq 39$	$0.15 * 15/n$		

15.1.4 Test Result

Active input power under 75W, no limit apply, declare compliance

16. Voltage fluctuations and flicker

16.1 Test Specification and Setup


16.1.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-3-3 / IEC 61000-3-3 / BS EN 61000-3-3 (details referred to Sec 1.2)
Test Procedure:	refer to ISL QA -T4-E-S14
Observation period:	For Pst 10min
	For Plt 2 hours
Temperature:	24°C
Humidity:	55%

Test Procedure

The EUT is supplied in series with reference impedance from a power source with the voltage and frequency as the nominal supply voltage and frequency of the EUT.

16.1.2 Test Setup



16.1.3 Test Result

Performance of EUT complies with the given specification.

16.2 Test Data: Configuration 1

Test File: F-20240821_1241
Test Class: Flicker Test, All Parameters (Ext Ref. Imped.) (1PH-FMR3)
Test Result: PASS
Test Duration (min): 10

Last Test Parameters:

Phase A

Vrms (Volts):	229.50	Frequency (Hz):	50.00
I_rms (Amps):	0.109	Power (W):	18.78
V-THD (%):	0.379	T-Max (ms):	0 (500)
dmax (%):	0.000 (4.000)	Hi dmax (%):	0.000 (4.000)
dc (%):	0.000 (3.300)	Hi dc (%):	0.000 (3.300)
Pst-001 :	0.039 (1.000)		

Pst Spectrum



16.3 Test Data: Configuration 2

Test File: F-20240821_1242
Test Class: Flicker Test, All Parameters (Ext Ref. Imped.) (1PH-FMR3)
Test Result: PASS
Test Duration (min): 10

Last Test Parameters:

Phase A

Vrms (Volts):	229.50	Frequency (Hz):	50.00
I_rms (Amps):	0.096	Power (W):	16.48
V-THD (%):	0.375	T-Max (ms):	0 (500)
dmax (%):	0.000 (4.000)	Hi dmax (%):	0.000 (4.000)
dc (%):	0.000 (3.300)	Hi dc (%):	0.000 (3.300)
Pst-001 :	0.039 (1.000)		

Pst Spectrum



16.4 Test Data: Configuration 3

Test File: F-20240821_1243
Test Class: Flicker Test, All Parameters (Ext Ref. Imped.) (1PH-FMR3)
Test Result: PASS
Test Duration (min): 10

Last Test Parameters:

Phase A

Vrms (Volts):	229.50	Frequency (Hz):	50.00
I_rms (Amps):	0.098	Power (W):	16.92
V-THD (%):	0.377	T-Max (ms):	0 (500)
dmax (%):	0.000 (4.000)	Hi dmax (%):	0.000 (4.000)
dc (%):	0.000 (3.300)	Hi dc (%):	0.000 (3.300)
Pst-001 :	0.039 (1.000)		

Pst Spectrum



16.5 Test Data: Configuration 4

Test File: F-20240821_1244
Test Class: Flicker Test, All Parameters (Ext Ref. Imped.) (1PH-FMR3)
Test Result: PASS
Test Duration (min): 10

Last Test Parameters:

Phase A

Vrms (Volts):	229.50	Frequency (Hz):	50.00
I _{rms} (Amps):	0.096	Power (W):	16.68
V-THD (%):	0.378	T-Max (ms):	0 (500)
dmax (%):	0.000 (4.000)	Hi dmax (%):	0.000 (4.000)
dc (%):	0.000 (3.300)	Hi dc (%):	0.000 (3.300)
Pst-001 :	0.055 (1.000)		

Pst Spectrum



16.6 Test Setup Photo


Configuration 1




Configuration 2



Configuration 3



Configuration 4



17. Appendix

17.1 Appendix A: Test Equipment

17.1.1 Test Equipment List

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction 02	EMI Receiver 20	R&S	ESR7	101326	05/30/2024	05/30/2025
Conduction 02	Conduction 02-1 Cable	WOKEN	CFD 300-NL	Conduction 02 -1	10/17/2023	10/17/2024
Conduction 02	LISN 26	R&S	ENV216	102378	12/08/2023	12/08/2024
Conduction 02	LISN 21	R&S	ENV216	101476	07/27/2024	07/27/2025

Location Chamber02	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Radiation	BILOG Antenna 17 (30MHz~1GHz)	SCHWARZBECK	VULB 9168+EMCI-N-6-05	645	11/16/2023	11/16/2024
Radiation	Preamplifier 25	EMCI	EMC9135	980295	03/12/2024	03/12/2025
Radiation	Coaxial Cable Chmb 02-10M-02	EMC	RG214U	Chmb 02-10M-02	10/04/2023	10/04/2024
Radiation	EMI Receiver 14	R&S	ESCI	101034	05/09/2024	05/09/2025

Location Chmb14	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Rad. Above 1GHz	Spectrum Analyzer 25	R&S	FSV 40	101499	10/24/2023	10/24/2024
Rad. Above 1GHz	Horn Antenna 08	ETS-Lindgren	3117	00128602	11/27/2023	11/27/2024
Rad. Above 1GHz	Preamplifier 20	EMCI	EMC051845	980084	11/22/2023	11/22/2024
Rad. Above 1GHz	Microwave Cable-41	woken	WCBA-WCA04NM.SM5	1-18G	03/01/2024	03/01/2025
Rad. Above 1GHz	Microwave Cable 26	EMCI	EMC104-NM-SM-800	141112	03/01/2024	03/01/2025

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
EN61K-4-2	ESD Gun 12	EM TEST	Dito	P1650188689	03/26/2024	03/26/2025
EN61K-4-3	Broadband Log-Periodic Antenna	AR	AT1080	310698	N/A	N/A
EN61K-4-3	Horn Antenna RF-01	AR	ATS700M11G	0335864	N/A	N/A
EN61K-4-3	Amplifier 80Mz~1GHz 250W	AR	250W1000C	358877	N/A	N/A
EN61K-4-3	Amplifier 0.7~6GHz 60W	AR	60S1G6	358973	N/A	N/A
EN61K-4-3	Broadband Coupler 80M~1GHz	Amplifier Research	DC6180A	0341805	N/A	N/A
EN61K-4-3	Coaxial Cable	INSULATED	NPS-4806-2360-NP3	108599.003.01.03	N/A	N/A
EN61K-4-3	Broadband Coupler 1-6GHz	Woken	STI07-0005-40	N/A	N/A	N/A
EN61K-4-3	Power Meter 05	BOONTON	4232A	12933	10/19/2023	10/19/2024
EN61K-4-3	Power Sensor 05	BOONTON	51013-4E	35242	10/19/2023	10/19/2024
EN61K-4-3	Power Sensor 09	BOONTON	51075A	36964	10/19/2023	10/19/2024
EN61K-4-3	Signal Generator 07	R&S	SMB100A	107780	12/26/2023	12/26/2024
EN61K-4-4	Signal Generator 10	EMC Partner	IMU3000	1547	09/07/2023	09/07/2024
EN61K-4-5	CDN-UTP8_03	EMC-PARTNER	CDN-UPT8ESD3	1546	03/14/2024	03/14/2025
EN61K-4-5	Surge Tester 01	EMC Partner	MIG0603IN3	778	11/23/2023	11/23/2024
EN61K-4-6	CDN M2+M3 04	TESEQ	CDN M016	43257	08/27/2023	08/27/2024
EN61K-4-6	Coaxial Cable 4-6 02-1			4-6 02-1	N/A	N/A
EN61K-4-6	CIT-100	FRANKONIA	CIT-100-75-MIL	11865-1	11/09/2023	11/09/2024
EN61K-4-8	Magnetic Field Immunity Loop	FCC	F-1000-4-8-L-1 M	01037	04/11/2024	04/11/2025
EN61K-4-8	Magnetic Field Test Generator	FCC	F-1000-4-8-G-12 5A	01038	04/11/2024	04/11/2025
EN61K-4-11	Voltage Dip and UP Simulator 01	NoiseKen	VDS-2002	VDS1750439	09/05/2023	09/05/2024
EN61K-3-2/3, EN61K-3-11-12	Harmonics & Flickers Test System 04	PACIFIC*APS	ECTS2-3600F-n	550072	05/15/2024	05/15/2025

PS: N/A => The equipment does not need calibration.

****Software for Controlling Spectrum/Receiver and Calculating Test Data**

Test Item	Filename	Version
EN IEC 61000-3-2	HFa-16 Program	v1.0.27.0
EN 61000-3-3	HFa-16 Program	v1.0.27.0
EN 61000-4-2	N/A	2.0
EN IEC 61000-4-3	i2	529b
EN 61000-4-4	TEM A3000	v4.6.1
EN 61000-4-5	EMC Partner	1.69
EN 61000-4-6	i2	529b
EN 61000-4-8	N/A	
EN IEC 61000-4-11 (<16A)	NOISE KEN	2.0

Site	Filename	Version
Conduction/Radiation	EZ EMC	ISL-03A2

17.2 Appendix B: Uncertainty of Measurement

The laboratory measurement uncertainty accordance with refers to CISPR 16-4-2. If U_{lab} is less than or equal to U_{cisp} in Table 1, then the test report may either state the value of U_{lab} or state that U_{lab} is less than U_{cisp} .

The coverage factor $k = 2$ yields approximately a 95 % level of confidence.

<Conduction 02>

AMN: ± 3.0 dB

<Chamber 02 (10m)>

Horizontal

30MHz~200MHz: ± 4.5 dB

200MHz~1000MHz: ± 4.3 dB

Vertical

30MHz~200MHz: ± 4.9 dB

200MHz~1000MHz: ± 4.7 dB

<Chamber 14 (3m)>

1GHz~6GHz: ± 5.1 dB

<Immunity 02>

Test item	Uncertainty	Test item	Uncertainty
EN 61000-4-2 (ESD)		EN 61000-4-6 (CS)	
Rise time tr	$\leq 11\%$	CDN	1.9 dB
Peak current Ip	$\leq 5.9\%$	EM Clamp	3.4 dB
current at 30 ns	$\leq 6.0\%$	EN 61000-4-8 (Magnetic)	5.6 %
current at 60 ns	$\leq 5.9\%$	EN IEC 61000-4-11 (Dips)	0.57 %
EN IEC 61000-4-3 (RS)	2.7 dB	EN IEC 61000-3-2 (Harmonics)	1.2 %
EN 61000-4-4 (EFT)		EN 61000-3-3 (Fluctuations and Flicker)	8.1 %
voltage rise time (tr)	7.2 %		
peak voltage value (VP)	6.3 %		
voltage pulse width (t _w)	5.1 %		
EN 61000-4-5 (Surge)			
open-circuit voltage front time	12 %		
open-circuit voltage peak value	8.7 %		
open-circuit voltage duration (T _d)	0.55%		

17.3 Appendix C: Photographs of EUT

Please refer to the File of **ISL-24LE0556P-MB**

--- END ---