

TEST REPORT

of

EN 55032 / CISPR 32 / BS EN 55032
AS/NZS CISPR 32 Class B
EN 55035 / CISPR 35 / BS EN 55035 IMMUNITY
EN IEC 61000-3-2 / BS EN IEC 61000-3-2
EN 61000-3-3 / BS EN 61000-3-3

Product: **USB 3.0 500GB~4TB**
Main Model: **ARSQ3-500G**
Series Model: **ARSQ3-1TB; ARSQ3-2TB; ARSQ3-4TB;
ARSASE-500GB; ARSASE-1TB; ARSASE-2TB;
ARSASE-4TB**
Brand: **ARES**
Applicant: **DATOTEK INTERNATIONAL Co., Ltd.**
Address: **No. 34, Alley 18, Lane 478, Rueiguang Rd., Neihu District,
Taipei, Taiwan**

Test Performed by:



International Standards Laboratory Corp. LT Lab.

TEL: +886-3-263-8888 FAX: +886-3-263-8899

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan

Report No.: **ISL-22LE0256CE35-MD**
Issue Date : **April 1, 2025**



Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein. According to customer agreement, the laboratory issues test reports based on the regulations or standards specifications, the measurement uncertainty is not considered in conformity decision rules.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.


Contents of Report

1.	General.....	1
1.1	Certification of Accuracy of Test Data.....	1
1.2	Test Standards.....	2
1.3	Description of EUT	5
1.4	Description of Support Equipment	7
1.5	Software for Controlling Support Unit.....	8
1.6	I/O Cable Condition of EUT and Support Units	9
2.	Power Main Port Conducted Emissions	10
2.1	Test Setup and Procedure	10
2.2	Conduction Test Data: Configuration 1.....	12
2.3	Conduction Test Data: Configuration 2.....	14
2.4	Test Setup Photo.....	16
3.	Telecommunication Port Conducted Emissions	20
3.1	Test Setup and Procedure	20
4.	Radiated Disturbance Emissions.....	22
4.1	Test Setup and Procedure	22
4.2	Limit	24
4.3	Radiation Test Data: Configuration 1.....	26
4.4	Radiation Test Data: Configuration 2.....	30
4.5	Test Setup Photo.....	34
5.	Voltage Disturbance Emissions at Antenna Terminals	38
5.1	Test Setup and Procedure	38
6.	Differential Voltage Emissions.....	40
6.1	Test Setup and Procedure	40
7.	Outdoor units of home satellite receiving systems	42
7.1	Test Setup and Procedure	42
8.	Electrostatic discharge (ESD) immunity	44
8.1	Test Specification and Setup	44
8.2	Test Point: Configuration 1	45
8.3	Test Point: Configuration 2	46
8.4	Test Setup Photo.....	47
9.	Radio-Frequency, Electromagnetic Field immunity.....	48
9.1	Test Specification and Setup	48
9.2	Test Setup Photo.....	49
10.	Electrical Fast transients/burst immunity.....	50
10.1	Test Specification and Setup	50
10.2	Test Setup Photo.....	52
11.	Surge Immunity	53
11.1	Test Specification and Setup.....	53
11.2	Test Setup Photo.....	54
12.	Immunity to Conductive Disturbance.....	55
12.1	Test Specification and Setup	55
12.2	Test Setup Photo.....	56
13.	Power Frequency Magnetic Field immunity.....	57
13.1	Test Specification and Setup	57
13.2	Test Setup Photo.....	58
14.	Voltage Dips, Short Interruption and Voltage Variation immunity	59
14.1	Test Specification and Setup	59
14.2	Test Setup Photo.....	60

15.	Harmonics	61
15.1	Test Specification and Setup	61
16.	Voltage Fluctuations	63
16.1	Test Specification and Setup	63
16.2	Test Data: Configuration 1	64
16.3	Test Data: Configuration 2	65
16.4	Test Setup Photo.....	66
16.5	Appendix	67
16.6	Appendix A: Test Equipment.....	67
16.7	Appendix B: Uncertainty of Measurement	70
16.8	Appendix C: Photographs of EUT	71

1. General

1.1 Certification of Accuracy of Test Data

Standards:	Please refer to 1.2
Equipment Tested:	USB 3.0 500GB~4TB
Main Model:	ARSQ3-500G
Series Model:	ARSQ3-1TB; ARSQ3-2TB; ARSQ3-4TB; ARSASE-500GB; ARSASE-1TB; ARSASE-2TB; ARSASE-4TB
Brand:	ARES
Applicant:	DATOTEK INTERNATIONAL Co., Ltd.
Sample received Date:	March 25, 2022
Final test Date:	EMI: refer to the date of test data EMS: April 14, 2022
Test Site:	Chamber 02; Chamber 14; Conduction 02; Immunity 02
Test Distance:	10m; 3m (above 1GHz) (EMI test)
Temperature:	refer to each site test data
Humidity:	refer to each site test data
Atmospheric Pressure:	86 kPa to 106 kPa
Input power:	Conduction input power: AC 230 V / 50 Hz Radiation input power: AC 230 V / 50 Hz Immunity input power: AC 230 V / 50 Hz
Test Result:	PASS
Report Engineer:	Jayla Lu
Test Engineer:	 _____ Jovi Liu
Approved By:	 _____ Angus Chu / Sr. Manager

1.2 Test Standards

The tests which this report describes were conducted by an independent electromagnetic compatibility consultant, International Standards Laboratory Corp. in accordance with the following

EN 55032:2015+A11:2020 and CISPR 32:2015+A1:2019 and BS EN 55032:2015+A11:2020 Class B Electromagnetic compatibility of multimedia equipment - Emission requirements.

AS/NZS CISPR 32:2015+A1:2020 Class B Electromagnetic compatibility of multimedia equipment- Emission requirements

Performed Item	Test Performed	Deviation	Result
Conducted emissions from the AC mains power ports	Yes	No	PASS
Telecommunication Port Conducted Emissions (asymmetric mode)	N/A	N/A	N/A
Radiated emissions at frequencies below 1 GHz	Yes	No	PASS
Radiated emissions at frequencies above 1 GHz	Yes	No	PASS
Radiated emissions from FM receivers	N/A	N/A	N/A
Voltage Disturbance Emissions at Antenna Terminals	N/A	N/A	N/A
Differential voltage emissions	N/A	N/A	N/A
Outdoor units of home satellite receiving systems	N/A	N/A	N/A

EN 55035:2017+A11:2020 and CISPR 35:2016 modified and BS EN 55035: 2017+A11:2020
Electromagnetic compatibility of multimedia equipment - Immunity requirements.

Standard	Description	Results	Criteria
EN 61000-4-2:2009 IEC 61000-4-2:2008 BS EN 61000-4-2:2009	Electrostatic Discharge	Pass	B
EN 61000-4-3:2006+A1:2008 +A2:2010 IEC 61000-4-3:2006+A1:2007+A2:2010 BS EN 61000-4-3:2006+A2:2010	Radio-Frequency, Electromagnetic Field	Pass	A
EN 61000-4-4:2012 IEC 61000-4-4:2012 BS EN 61000-4-4:2012	Electrical Fast Transient/Burst	Pass	B
EN 61000-4-5:2014+A1:2017 IEC 61000-4-5:2014+A1:2017 BS EN 61000-4-5:2014+A1:2017	Surge	Pass	B
EN 61000-4-6:2014+AC:2015 IEC 61000-4-6:2013 BS EN 61000-4-6:2014	Conductive Disturbance	Pass	A
EN 61000-4-8:2010 IEC 61000-4-8:2009 BS EN 61000-4-8:2010	Power Frequency Magnetic Field	Pass	A
EN 61000-4-11:2004+A1:2017 IEC 61000-4-11:2004+A1:2017 BS EN 61000-4-11:2004+A1:2017	Voltage Dips / Short Interruption and Voltage Variation		
	>95% in 0.5 cycle	Pass	B
	30% in 25 cycle	Pass	C
	>95% in 250 cycle	Pass	C

Standard	Description	Results
EN IEC 61000-3-2:2019 IEC 61000-3-2:2018 BS EN IEC 61000-3-2:2019	Limits for harmonics current emissions	Pass
EN 61000-3-3:2013+A1:2019 IEC 61000-3-3:2013+A1:2017 BS EN 61000-3-3:2013+A1:2019	Limits for voltage fluctuations and flicker in low-voltage supply systems.	Pass

1.2.1 Performance Criteria for Compliance: EN 55035 and BS EN 55035

Performance criterion A

The equipment shall continue to operate as intended without operator intervention. No degradation of performance, loss of function or change of operating state is allowed below a performance level specified by the manufacturer when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

Performance criterion B

During the application of the disturbance, degradation of performance is allowed. However, no unintended change of actual operating state or stored data is allowed to persist after the test.

After the test, the equipment shall continue to operate as intended without operator intervention; no degradation of performance or loss of function is allowed, below a performance level specified by the manufacturer, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance.

If the minimum performance level (or the permissible performance loss), or recovery time, is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

Performance criterion C

Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions. A reboot or re-start operation is allowed.

Information stored in non-volatile memory, or protected by a battery backup, shall not be lost.

1.3 Description of EUT

EUT

This report test data using the report number ISL-22LE0256CE35

Product Name	USB 3.0 500GB~4TB
Condition	Pre-Production
Main Model	ARSQ3-500G
Series Model	ARSQ3-1TB; ARSQ3-2TB; ARSQ3-4TB; ARSASE-500GB; ARSASE-1TB; ARSASE-2TB; ARSASE-4TB
Serial Number	N/A
Control IC	PS2251-18
PCB Number	P066117UP0000N1N
Memory Capacity	1TB
Highest working frequency	1200MHz

The I/O ports of EUT are listed below:

I/O Port Type	Quantity
TYPE-C	1

The memory capacities listed below is chosen by the applicant to be the representative configuration for testing in this report.

Pretest configurations:

Configuration	Control IC	PCB Number	Memory Capacity	Cable	Appearance
1	PS2251-18	P066117UP0000N1N	1TB	TYPE-C TO C	PLASTIC
2				TYPE-C TO A	PLASTIC

Test configurations:

Configuration	Control IC	PCB Number	Memory Capacity	Cable	Appearance
1	PS2251-18	P066117UP0000N1N	1TB	TYPE-C TO C	PLASTIC
2					METAL

Different Model list:

Model	Market
ARSQ3-500G; ARSQ3-1TB; ARSQ3-2TB; ARSQ3-4TB; ARSASE-500GB; ARSASE-1TB; ARSASE-2TB; ARSASE-4TB	Different customer

EMI Noise Source

Refer to the photo	Control IC	Point
EUT-11	PS2251-18	U1

Refer to the photo	Crystal	Point
EUT-12	25MHz	Y1

EMI Solution:

NA

1.4 Description of Support Equipment

For EMI test configuration support unit: 1~6

For EMS test configuration support unit: 4~10

No	Unit	Model / Serial No.	Brand	Power Cord	FCC ID
1	USB Keyboard	SK-8175 S/N: N/A	DELL	N/A	FCC DOC
2	USB Mouse	MOCZUL S/N: N/A	DELL	N/A	FCC DOC
3	AKiTIO Type-C HDD	SK2-U31AS-AKT S/N: N/A	AKiTIO	N/A	FCC DOC
4	Personal Computer	NUC8BEH S/N: N/A	INTEL	Non-shielded	FCC DOC
5	LCD Monitor	P2416D S/N: N/A	DELL	Non-shielded	FCC DOC
6	Printer	C930 S/N: N/A	HP	Non-shielded	FCC DOC
8	Traveling USB 3.0 Disk	TS16GJF700 S/N: N/A	Transcend	N/A	FCC DOC
9	USB Keyboard	SK-8115 S/N: N/A	DELL	N/A	FCC DOC
10	USB Mouse	MOC5UD S/N: N/A	DELL	N/A	FCC DOC

1.5 Software for Controlling Support Unit

Test programs exercising various part of EUT were used. The programs were executed as follows:

For EMS test configuration:

1. PC running Winthrax to read and write the EUT.
2. Send signal to the Printer through PC USB Port.
3. Send signal to the Traveling USB 3.0 Disk through PC USB Port.
4. Send Color Bar to the LCD Monitor through PC HDMI Port.
5. Repeat the above steps.

	Filename	Version
EUT	Winthrax.exe	3.09.02
LCD Monitor	Media Player.exe	1.9.1
Printer	IntelEMC	1.1
Traveling USB 3.0	IntelEMC	1.1

For EMI test configuration:

1. PC running Winthrax to read and write the EUT.
2. Send signal to the Printer through PC USB Port.
3. Send signal to the AKiTIO Type-C HDD through PC USB Port.
4. Send Color Bar to the LCD Monitor through PC HDMI Port.
5. Repeat the above steps.

	Filename	Version
EUT	Winthrax.exe	3.09.02
LCD Monitor	Media Player.exe	1.9.1
Printer	IntelEMC	1.1
AKiTIO Type-C HDD	IntelEMC	1.1

1.6 I/O Cable Condition of EUT and Support Units

For EMS test configuration:

Description	Path	Length	Shielding	Core	Remark
AC Power Cable	100V (~240V) to PC SPS	0.8m	No	No	
Monitor Cable	Monitor HDMI Port to PC HDMI Port	1.8m	Yes	No	
Keyboard Cable	USB Keyboard to PC USB Port	1.8m	Yes	No	
Mouse Cable	USB Mouse to PC USB Port	1.8m	Yes	No	
Printer Cable	Printer to PC USB Port	1.8m	Yes	No	
Traveling USB 3.0	Traveling USB 3.0 to PC USB 3.0 Port	1.0m	Yes	No	
Type-C cable	EUT to PC Type-C Port	0.3m	Yes	No	

For EMI test configuration:

Description	Path	Length	Shielding	Core	Remark
AC Power Cable	100V (~240V) to PC SPS	0.8m	No	No	
Monitor Cable	Monitor HDMI Port to PC HDMI Port	1.8m	Yes	No	
Keyboard Cable	USB Keyboard to PC USB Port	1.8m	Yes	No	
Mouse Cable	USB Mouse to PC USB Port	1.8m	Yes	No	
Printer Cable	Printer to PC USB Port	1.8m	Yes	No	
USB data cable	AKiTIO Type-C HDD to PC USB 3.0 Port	1.27m	Yes	No	
Type-C cable	EUT to PC Type-C Port	0.3m	Yes	No	

2.1.4 Limit

Conducted emissions from the AC mains power ports of Class A equipment:


Frequency	QP	AV
MHz	dB(μ V)	dB(μ V)
0.15-0.50	79	66
0.50-30	73	60
Note: The lower limit shall apply at the transition frequencies		

Conducted emissions from the AC mains power ports of Class B equipment:

Frequency	QP	AV
MHz	dB(μ V)	dB(μ V)
0.15-0.50	66-56	56-46
0.50-5.0	56	46
5.0-30	60	50
Note: The lower limit shall apply at the transition frequencies		

2.2 Conduction Test Data: Configuration 1

-Live



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.158	34.33	7.22	9.68	44.01	65.57	-21.56	16.90	55.57	-38.67
2	0.170	28.55	8.36	9.68	38.23	64.96	-26.73	18.04	54.96	-36.92
3	0.190	26.19	1.84	9.67	35.86	64.04	-28.18	11.51	54.04	-42.53
4	0.206	24.73	7.81	9.67	34.40	63.37	-28.97	17.48	53.37	-35.89
5	0.338	14.42	-1.41	9.68	24.10	59.25	-35.15	8.27	49.25	-40.98
6	2.914	24.48	9.49	9.76	34.24	56.00	-21.76	19.25	46.00	-26.75

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor


Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

- Neutral



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.154	30.73	3.53	9.67	40.40	65.78	-25.38	13.20	55.78	-42.58
2	0.162	29.90	3.08	9.67	39.57	65.36	-25.79	12.75	55.36	-42.61
3	0.182	28.71	2.81	9.67	38.38	64.39	-26.01	12.48	54.39	-41.91
4	0.190	26.12	1.05	9.67	35.79	64.04	-28.25	10.72	54.04	-43.32
5	0.210	24.02	1.34	9.67	33.69	63.21	-29.52	11.01	53.21	-42.20
6	2.914	22.37	7.75	9.76	32.13	56.00	-23.87	17.51	46.00	-28.49

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss


A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

2.3 Conduction Test Data: Configuration 2

-Live



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.150	31.35	4.91	9.67	41.02	66.00	-24.98	14.58	56.00	-41.42
2	0.166	29.63	5.19	9.68	39.31	65.16	-25.85	14.87	55.16	-40.29
3	0.202	24.71	5.22	9.67	34.38	63.53	-29.15	14.89	53.53	-38.64
4	0.238	22.01	6.03	9.67	31.68	62.17	-30.49	15.70	52.17	-36.47
5	0.298	21.70	-0.15	9.67	31.37	60.30	-28.93	9.52	50.30	-40.78
6	2.986	25.21	10.11	9.76	34.97	56.00	-21.03	19.87	46.00	-26.13

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor


Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

- Neutral



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.158	30.00	3.15	9.67	39.67	65.57	-25.90	12.82	55.57	-42.75
2	0.170	28.11	3.58	9.67	37.78	64.96	-27.18	13.25	54.96	-41.71
3	0.178	31.55	3.24	9.67	41.22	64.58	-23.36	12.91	54.58	-41.67
4	0.186	26.27	1.21	9.67	35.94	64.21	-28.27	10.88	54.21	-43.33
5	0.226	22.59	-0.31	9.67	32.26	62.60	-30.34	9.36	52.60	-43.24
6	2.950	23.34	8.59	9.76	33.10	56.00	-22.90	18.35	46.00	-27.65

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

2.4 Test Setup Photo

Configuration 1

Front View



Back View



Configuration 2

Front View



Back View



3.1.4 Limit

Asymmetric mode conducted emissions from Class_A equipment:

Applicable to

1. wired network ports.
2. optical fibre ports with metallic shield or tension members.
3. antenna ports.

Frequency range MHz	Coupling device	Detector type / bandwidth	Class_A voltage limits dB(μV)	Class_A current limits dB(μA)
0.15-0.5	AAN	Quasi Peak / 9 kHz	97-87	n/a
0.5-30			87	
0.15-0.5	AAN	Average / 9 kHz	84-74	
0.5-30			74	
0.15-0.5	CVP and current probe	Quasi Peak / 9 kHz	97-87	53-43
0.5-30			87	43
0.15-0.5	CVP and current probe	Average / 9 kHz	84-74	40-30
0.5-30			74	30
0.15-0.5	Current Probe	Quasi Peak / 9 kHz	n/a	53-43
0.5-30				43
0.15-0.5	Current Probe	Average / 9 kHz		40-30
0.5-30				30

Asymmetric mode conducted emissions from Class_B equipment:

Applicable to:

1. wired network ports.
2. optical fibre ports with metallic shield or tension members.
3. broadcast receiver tuner ports.
4. antenna ports.


Frequency range MHz	Coupling device	Detector type / bandwidth	Class_B voltage limits dB(μV)	Class_B current limits dB(μA)
0.15-0.5	AAN	Quasi Peak / 9 kHz	84-74	n/a
0.5-30			74	
0.15-0.5	AAN	Average / 9 kHz	74-64	
0.5-30			64	
0.15-0.5	CVP and current probe	Quasi Peak / 9 kHz	84-74	40-30
0.5-30			74	30
0.15-0.5	CVP and current probe	Average / 9 kHz	74-64	30-20
0.5-30			64	20
0.15-0.5	Current Probe	Quasi Peak / 9 kHz	n/a	40-30
0.5-30				30
0.15-0.5	Current Probe	Average / 9 kHz		30-20
0.5-30				20

****Remarks: It is not necessary to be tested on this item.**


4. Radiated Disturbance Emissions

4.1 Test Setup and Procedure


4.1.1 Test Setup



30MHz~1GHz Test Setup



1GHz~6GHz Test Setup



The 3dB beam width of the horn antenna used for the test is as shown in the table below.

Frequency (GHz)	E-plane	H-plane	$\theta_{3dB}(\text{min})$	d= 3 m
				w (m)
1	88°	147°	88°	5.79
2	68°	119°	68°	4.04
3	73°	92°	73°	4.44
4	70°	89°	70°	4.20
5	55°	60°	55°	3.12
6	63°	62°	62°	3.60

4.1.2 Test Procedure

The radiated emissions test will then be repeated on the chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipment are set up on the turntable of one of 10 meter chamber. Desktop EUT are set up on a FRP stand 0.8 meter above the ground or floor-standing arrangement shall be placed on the horizontal ground reference plane.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. The highest emissions between 30 MHz to 1000 MHz were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The highest emissions between 1 GHz to 6 GHz were analyzed in details by operating the spectrum analyzer in peak and average mode to determine the precise amplitude of the emissions. The test volume for a height of up to 30 cm may be obstructed by absorber placed on the ground plane.

At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum measurement. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings. All of the interface cables were manipulated according to EN 55032 / BS EN 55032 requirements.

The highest internal source of an EUT is defined as the highest frequency generated or used within the EUT or on which the EUT operates or tunes.

If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz.

If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz.

If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz.

If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 6 GHz, whichever is less.

4.1.3 Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range: 30MHz--1000MHz
 Detector Function: Quasi-Peak Mode
 Resolution Bandwidth: 120kHz

Frequency Range: Above 1 GHz to 6 GHz
 Detector Function: Peak/Average Mode
 Resolution Bandwidth: 1MHz

4.2 Limit

Radiated emissions at frequencies up to 1 GHz for Class A equipment:

Radiated emissions at frequencies up to 1 GHz for Class A equipment:			
Frequency range MHz	Measurement		Class_A limits dB(μV/m)
	Distance m	Detector type / bandwidth	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	40
230-1000			47
30-230	3		50
230-1000			57

Radiated emissions at frequencies above 1 GHz for Class A equipment:

Frequency range MHz	Measurement		Class_A limits dB(μ V/m)
	Distance m	Detector type / bandwidth	FSOATS
1000-3000	3	Average / 1MHz	56
3000-6000			60
1000-3000		Peak / 1MHz	76
3000-6000			80

Radiated emissions at frequencies up to 1 GHz for Class B equipment:

Radiated emissions at frequencies up to 1 GHz for Class_B equipment:			
Frequency range MHz	Measurement		Class_B limits dB(μV/m)
	Distance m	Detector type / bandwidth	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	30
230-1000			37
30-230	3		40
230-1000			47


Radiated emissions at frequencies above 1 GHz for Class_B equipment:

Frequency range MHz	Measurement		Class_B limits dB(μ V/m)
	Distance m	Detector type / bandwidth	FSOATS
1000-3000	3	Average / 1MHz	50
3000-6000			54
1000-3000		Peak / 1MHz	70
3000-6000			74

Radiated emissions from FM receivers:

Frequency range MHz	Measurement		Class_B limits dB(μV/m)	
	Distance m	Detector type / bandwidth	Fundamental	Harmonics
			OATS/SAC	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	50	42
230-300				42
300-1000				46
30-230	3		60	52
230-300				52
300-1000				56

4.3 Radiation Test Data: Configuration 1 - Radiated Emissions (Horizontal)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	37.76	34.65	-18.02	16.63	30.00	-13.37	299	360	QP
2	69.77	35.74	-19.02	16.72	30.00	-13.28	342	0	QP
3	174.53	35.06	-16.60	18.46	30.00	-11.54	350	153	QP
4	465.53	31.76	-9.60	22.16	37.00	-14.84	147	0	QP
5	729.37	30.77	-4.38	26.39	37.00	-10.61	300	347	QP
6	911.73	30.89	-1.76	29.13	37.00	-7.87	300	8	QP

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters


Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Radiated Emission Measurement
Date: 2022/4/1

Operator: Reyes
Temperature: 22 °C
Humidity: 53 %



Site : Chamber 14

Polarization: Horizontal

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	2115.00	56.08	-12.15	43.93	70.00	-26.07	150	233	peak
2	2400.00	58.51	-11.40	47.11	70.00	-22.89	200	144	peak
3	2400.46	40.16	-11.40	28.76	50.00	-21.24	103	47	AVG
4	3185.00	59.10	-9.85	49.25	74.00	-24.75	200	155	peak
5	3575.00	57.65	-9.30	48.35	74.00	-25.65	150	216	peak
6	4785.00	57.64	-8.53	49.11	74.00	-24.89	200	162	peak
7	5280.00	56.29	-7.76	48.53	74.00	-25.47	100	155	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor


Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

-Radiated Emissions (Vertical)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	63.95	40.11	-17.99	22.12	30.00	-7.88	150	272	QP
2	78.50	44.73	-20.90	23.83	30.00	-6.17	200	223	QP
3	99.84	45.56	-21.43	24.13	30.00	-5.87	150	303	QP
4	174.53	36.55	-16.60	19.95	30.00	-10.05	100	202	QP
5	662.44	31.04	-5.70	25.34	37.00	-11.66	300	316	QP
6	897.18	31.05	-2.19	28.86	37.00	-8.14	250	153	QP

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters


Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Radiated Emission Measurement
Date: 2022/4/1

Operator: Reyes
Temperature: 22 °C
Humidity: 53 %



Site : Chamber 14

Polarization: Vertical

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1600.00	55.80	-15.48	40.32	70.00	-29.68	200	219	peak
2	2005.00	54.93	-12.29	42.64	70.00	-27.36	200	157	peak
3	2390.00	56.99	-11.44	45.55	70.00	-24.45	100	113	peak
4	2725.00	55.66	-10.99	44.67	70.00	-25.33	150	189	peak
5	3194.65	41.59	-9.87	31.72	54.00	-22.28	160	47	AVG
6	3195.00	61.04	-9.87	51.17	74.00	-22.83	100	201	peak
7	4780.00	59.50	-8.51	50.99	74.00	-23.01	150	145	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain


A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

4.4 Radiation Test Data: Configuration 2

- Radiated Emissions (Horizontal)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	49.40	32.91	-17.12	15.79	30.00	-14.21	400	113	QP
2	64.92	35.52	-18.06	17.46	30.00	-12.54	350	270	QP
3	178.41	37.30	-16.98	20.32	30.00	-9.68	300	231	QP
4	709.00	30.95	-4.87	26.08	37.00	-10.92	400	2	QP
5	893.30	30.66	-2.25	28.41	37.00	-8.59	350	317	QP
6	969.93	30.37	-1.03	29.34	37.00	-7.66	150	327	QP

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters


Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Radiated Emission Measurement
Date: 2022/4/1

Operator: Reyes
Temperature: 22 °C
Humidity: 53 %



Site : Chamber 14

Polarization: *Horizontal*

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	2415.00	56.03	-11.39	44.64	70.00	-25.36	100	141	peak
2	2730.00	55.47	-10.99	44.48	70.00	-25.52	100	146	peak
3	3495.00	58.94	-10.32	48.62	74.00	-25.38	150	142	peak
4	4415.00	56.82	-8.98	47.84	74.00	-26.16	100	162	peak
5	4800.00	57.85	-8.59	49.26	74.00	-24.74	200	241	peak
6	5335.00	57.87	-7.77	50.10	74.00	-23.90	100	173	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor


Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

-Radiated Emissions (Vertical)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	76.56	42.03	-20.26	21.77	30.00	-8.23	150	179	QP
2	99.84	42.58	-21.43	21.15	30.00	-8.85	200	112	QP
3	158.04	34.30	-15.88	18.42	30.00	-11.58	100	283	QP
4	177.44	35.36	-16.85	18.51	30.00	-11.49	100	280	QP
5	202.66	35.36	-18.62	16.74	30.00	-13.26	100	300	QP
6	925.31	31.05	-1.68	29.37	37.00	-7.63	222	0	QP

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters


Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Radiated Emission Measurement
Date: 2022/4/1

Operator: Reyes
Temperature: 22 °C
Humidity: 53 %



Site : Chamber 14

Polarization: Vertical

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1955.00	53.89	-12.29	41.60	70.00	-28.40	100	15	peak
2	2375.00	54.60	-11.51	43.09	70.00	-26.91	100	59	peak
3	2640.00	54.95	-11.05	43.90	70.00	-26.10	100	46	peak
4	3190.00	60.75	-9.86	50.89	74.00	-23.11	100	179	peak
5	3540.00	55.65	-9.02	46.63	74.00	-27.37	100	196	peak
6	4785.00	59.05	-8.53	50.52	74.00	-23.48	100	129	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit


Antenna Distance: 3 meters

Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.


4.5 Test Setup Photo

Configuration 1


Front View (30MHz~1GHz)




Back View (30MHz~1GHz)



Front View (above 1GHz)




Back View (above 1GHz)




Configuration 2


Front View (30MHz~1GHz)




Back View (30MHz~1GHz)



Front View (above 1GHz)




Back View (above 1GHz)



5. Voltage Disturbance Emissions at Antenna Terminals

5.1 Test Setup and Procedure

5.1.1 Test Setup



5.1.2 Test Procedure

The output level of the auxiliary signal generator was set to 70dBuV at the EUT antenna terminal with 75 ohms impedance with an un-modulated carrier.

The highest emissions were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The power of EUT was switched off to make sure the emission was not contributed by the auxiliary signal generator. While doing so, the interconnecting cables and major parts of the system were moved around to maximize the emission.

5.1.3 EMI Receiver Configuration (for the frequencies tested)

Frequency Range:	30MHz-2150MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz

5.1.4 Limit

Applicable to:

1. TV broadcast receiver tuner ports with an accessible connector.
2. RF modulator output ports.
3. FM broadcast receiver tuner ports with an accessible connector.


Table clause	Frequency range MHz	Detector type/ bandwidth	Class B limits dB(μV) 75 Ω			Applicability
			Other	Local Oscillator Fundamental	Local Oscillator Harmonics	
A12.1	30 – 950	For frequencies ≤1 GHz	46	46	46	See a)
	950 – 2 150		46	54	54	
A12.2	950 – 2 150	Quasi Peak/ 120 kHz	46	54	54	See b)
A12.3	30 – 300		46	54	50	See c)
	300 – 1 000	52				
A12.4	30 – 300	For frequencies ≥1 GHz	46	66	59	See d)
	300 – 1 000				52	
A12.5	30 – 950	Peak/ 1 MHz	46	76	46	See e)
	950 – 2 150			n/a	54	
a) Television receivers (analogue or digital), video recorders and PC TV broadcast receiver tuner cards working in channels between 30 MHz and 1 GHz, and digital audio receivers.						
b) Tuner units (not the LNB) for satellite signal reception.						
c) Frequency modulation audio receivers and PC tuner cards.						
d) Frequency modulation car radios.						
e) Applicable to EUTs with RF modulator output ports (for example DVD equipment, video recorders, camcorders and decoders etc.) designed to connect to TV broadcast receiver tuner ports.						

****Remarks: It is not necessary to be tested on this item.**

6. Differential Voltage Emissions

6.1 Test Setup and Procedure

6.1.1 Test Setup



6.1.2 Test Procedure

The output level of the auxiliary signal generator was set to 70dBuV at the EUT antenna terminal with 75 ohms impedance with an un-modulated carrier.

The highest emissions were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The power of EUT was switched off to make sure the emission was not contributed by the auxiliary signal generator. While doing so, the interconnecting cables and major parts of the system were moved around to maximize the emission.

6.1.3 EMI Receiver Configuration (for the frequencies tested)

Frequency Range:	30MHz-2150MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz

6.1.4 Limit

Applicable to:

1. TV broadcast receiver tuner ports with an accessible connector.
2. RF modulator output ports.
3. FM broadcast receiver tuner ports with an accessible connector.



Table clause	Frequency range MHz	Detector type/ bandwidth	Class B limits dB(μV) 75 Ω			Applicability
			Other	Local Oscillator Fundamental	Local Oscillator Harmonics	
A12.1	30 – 950	For frequencies ≤1 GHz	46	46	46	See a)
	950 – 2 150		46	54	54	
A12.2	950 – 2 150	Quasi Peak/ 120 kHz	46	54	54	See b)
A12.3	30 – 300		46	54	50	See c)
	300 – 1 000	52				
A12.4	30 – 300	For frequencies ≥1 GHz	46	66	59	See d)
	300 – 1 000				52	
A12.5	30 – 950	Peak/ 1 MHz	46	76	46	See e)
	950 – 2 150			n/a	54	
a) Television receivers (analogue or digital), video recorders and PC TV broadcast receiver tuner cards working in channels between 30 MHz and 1 GHz, and digital audio receivers.						
b) Tuner units (not the LNB) for satellite signal reception.						
c) Frequency modulation audio receivers and PC tuner cards.						
d) Frequency modulation car radios.						
e) Applicable to EUTs with RF modulator output ports (for example DVD equipment, video recorders, camcorders and decoders etc.) designed to connect to TV broadcast receiver tuner ports.						

****Remarks: It is not necessary to be tested on this item.**

7. Outdoor units of home satellite receiving systems

7.1 Test Setup and Procedure

7.1.1 Test Setup

	
Description of $\pm 7^\circ$ of the main beam axis of the EUT	Measurement arrangements of transmit antenna for the wanted signal

7.1.2 Test Procedure

The input signal shall be adjusted to get the maximum rated output level from the EUT. For the measurement in the frequency range from 30 MHz to 18 GHz the input signal shall be adjusted so that the output frequency is within this frequency range. For the measurement in the frequency range above 1 GHz, the frequency of the input signal shall be adjusted in such a way that the EUT is measured, as a minimum, at the lowest, middle and highest rated output frequency within the measured frequency range.

7.1.3 Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range: 30MHz--1000MHz
 Detector Function: Quasi-Peak Mode
 Resolution Bandwidth: 120kHz

Frequency Range: Above 1000MHz
 Detector Function: Peak/Average Mode
 Resolution Bandwidth: 1MHz

7.1.4 Limit

Table Clause	Frequency Range MHz	Measurement			Class B Limits	Applicable to
		Facility (see Table A.1)	Distance m	Detector type / Bandwidth		
A7.1	30 to 1 000	SAC / OATS / FAR	See Table A.4	Quasi Peak / 120 kHz	See Table A.4	
A7.2	1 000 to 2 500	FSOATS	3	Average / 1 MHz	50 dB(μV/m)	LO leakage and spurious radiated emissions from the EUT, in the region outside ±7° of the main beam axis. See Figure H.1
	2 500 to 18 000				64 dB(μV/m)	
A7.3	1 000 to 18 000	FSOATS	3	Average / 1 MHz	37 dB(μV/m)	LO leakage from the EUT, in the region within ±7° of the main beam axis. See Figure H.1
A7.4	1 000 to 18 000	Conducted (Clause H.4)	n/a	Average / 1 MHz	30 dBpW	
For details of the EUT configuration, see Annex H.						
For radiated emissions measurements at frequencies up to 1 GHz, the requirements defined in Table A.4 shall be satisfied.						
Apply the appropriate limits across the entire frequency range.						
Apply the limits defined in table Clause A7.1 and A7.2. Also apply the limits defined in either table Clause A7.3 or A7.4.						

****Remarks: It is not necessary to be tested on this item.**

8. Electrostatic discharge (ESD) immunity

8.1 Test Specification and Setup

8.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-2 / IEC 61000-4-2 / BS EN 61000-4-2 (details referred to Sec 1.2)
Test Level:	Air +/- 2 kV, +/- 4 kV, +/- 8 kV Contact +/- 4 kV
Criteria:	B
Test Procedure:	refer to ISL QA -T4-E-S7
Temperature:	22°C
Humidity:	40%

Selected Test Point


Air: discharges were applied to slots, aperture or insulating surfaces. 10 single air discharges were applied to each selected points.

Contact: 10 discharges minimum were to the selected contact points.

Indirect Contact Points: 10 discharges were applied to center of one edge of VCP and each EUT side of HCP with 10 cm away from EUT.

8.1.2 Test Setup

EUT is 1m from the wall and other metallic structure. When Battery test mode is needed, a cable with one 470kΩ resistor at two rare ends is connected from metallic part of EUT and screwed to HCP.



8.1.3 Test Result

Performance of EUT complies with the given specification.

8.2 Test Point: Configuration 1

Red arrow lines indicate the contact points, and blue arrow lines indicate the air points.

Figure 1: Test Point Assignments Discharge:



Figure 2: Test Point Assignments Discharge:




8.3 Test Point: Configuration 2

Red arrow lines indicate the contact points, and blue arrow lines indicate the air points.


Figure 1: Test Point Assignments Discharge:




Figure 2: Test Point Assignments Discharge:



8.4 Test Setup Photo Configuration 1



Configuration 2



9. Radio-Frequency, Electromagnetic Field immunity


9.1 Test Specification and Setup

9.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-3 / IEC 61000-4-3 / BS EN 61000-4-3 (details referred to Sec 1.2)
Test Level:	3 V/m
Modulation:	AM 1kHz 80%
Frequency range:	80 MHz~1 GHz 1800MHz, 2600MHz, 3500MHz, 5000MHz
Frequency Step:	1% of last step frequency
Dwell time:	2s
Polarization:	Vertical and Horizontal
EUT Azimuth Angle	☒ 0° ☒ 90° ☒ 180° ☒ 270°
Criteria:	A
Test Procedure:	refer to ISL QA -T4-E-S8
Temperature:	22°C
Humidity:	58%

9.1.2 Test Setup


The field sensor is placed at one calibration grid point to check the intensity of the established fields on both polarizations. EUT is adjusted to have each side of EUT face coincident with the calibration plane. A CCD camera and speakers are used to monitor the condition of EUT for the performance judgment.



9.1.3 Test Result

Performance of EUT complies with the given specification.

9.2 Test Setup Photo Configuration 1



Configuration 2



10. Electrical Fast transients/burst immunity

10.1 Test Specification and Setup

10.1.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-4-4 / IEC 61000-4-4 / BS EN 61000-4-4 (details referred to Sec 1.2)
Test Level:	AC Power Port: +/- 1 kV
Rise Time:	5ns
Hold Time:	50ns
Burst Period:	300ms
Repetition Frequency:	5kHz
Criteria:	B
Test Procedure:	refer to ISL QA -T4-E-S9
Temperature:	22°C
Humidity:	56%

Test Procedure


The EUT was setup on a nonconductive table 0.1 m above a reference ground plane.

Test Points	Polarity	Result	Comment
Line	+	N	60 sec
	-	N	60 sec
Neutral	+	N	60 sec
	-	N	60 sec
Ground	+	N	60 sec
	-	N	60 sec
Line to Neutral	+	N	60 sec
	-	N	60 sec
Line to Ground	+	N	60 sec
	-	N	60 sec
Neutral to Ground	+	N	60 sec
	-	N	60 sec
Line to Neutral to Ground	+	N	60 sec
	-	N	60 sec

Note: 'N' means normal, the EUT function is correct during the test.

10.1.2 Test Setup

EUT is at least 50cm from the conductive structure.



10.1.3 Test Result

Performance of EUT complies with the given specification.

10.2 Test Setup Photo Configuration 1



Configuration 2




11. Surge Immunity

11.1 Test Specification and Setup

11.1.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-4-5 / IEC 61000-4-5 / BS EN 61000-4-5 (details referred to Sec 1.2)
Test Level:	Line to Line: +/- 0.5 kV, +/- 1 kV Line to Earth: +/- 0.5 kV, +/- 1 kV, +/- 2kV
Rise Time:	1.2us
Hold Time:	50us
Repetition Rate:	30 seconds
Angle:	☐ 0° ☒ 90° ☐ 180° ☒ 270°
Criteria:	B
Test Procedure:	refer to ISL QA -T4-E-S10
Temperature:	22°C
Humidity:	63%


11.1.2 Test Setup



11.1.3 Test Result

Performance of EUT complies with the given specification.

11.2 Test Setup Photo Configuration 1



Configuration 2




12. Immunity to Conductive Disturbance

12.1 Test Specification and Setup

12.1.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-4-6 / IEC 61000-4-6 / BS EN 61000-4-6 (details referred to Sec 1.2)
Frequency range and Test Level:	0.15MHz to 10MHz: 3 Vrms 10MHz to 30MHz: 3Vrms to 1Vrms 30MHz to 80MHz: 1Vrms
Modulation:	AM 1kHz 80%
Frequency Step:	1% of last Frequency
Dwell time:	2s
Criteria:	A
CDN Type:	CDN M2+M3
Test Procedure:	refer to ISL QA -T4-E-S11
Temperature:	21°C
Humidity:	59%

12.1.2 Test Setup



12.1.3 Test Result

Performance of EUT complies with the given specification.

12.2 Test Setup Photo Configuration 1



Configuration 2




13. Power Frequency Magnetic Field immunity

13.1 Test Specification and Setup

13.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-8 / IEC 61000-4-8 / BS EN 61000-4-8 (details referred to Sec 1.2)
Test Level:	1A/m
Polarization:	X, Y, Z
Criteria:	A
Test Procedure:	refer to ISL QA -T4-E-S12
Temperature:	21°C
Humidity:	59%

13.1.2 Test Setup



13.1.3 Test Result

Performance of EUT complies with the given specification.

13.2 Test Setup Photo Configuration 1



Configuration 2




14. Voltage Dips, Short Interruption and Voltage Variation immunity

14.1 Test Specification and Setup

14.1.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-4-11 / IEC 61000-4-11 / BS EN 61000-4-11 (details referred to Sec 1.2)
When the product is greater than 16A does not apply to this Standard, it is not necessary to be tested on this item. In addition, IEC/EN 61000-4-34 Standard was used to evaluating.	
Test Level:	>95% in 0.5 cycle
Criteria:	B
Test Level:	30% in 25 cycle
Criteria:	C
Test Level:	>95% in 250 cycle
Criteria:	C
Phase:	0°; 180°
Test intervals:	3 times with 10s each
Test Procedure:	refer to ISL QA -T4-E-S13
Temperature:	22°C
Humidity:	63%

14.1.2 Test Setup




14.1.3 Test Result

Performance of EUT complies with the given specification.

14.2 Test Setup Photo Configuration 1



Configuration 2



15. Harmonics

15.1 Test Specification and Setup

15.1.1 Test Specification


Port:	AC mains
Active Input Power:	<75W
Basic Standard:	EN IEC 61000-3-2 / IEC 61000-3-2 / BS EN IEC 61000-3-2 (details referred to Sec 1.2)
Test Duration:	2.5min
Class:	A
Test Procedure:	refer to ISL QA -T4-E-S14
Temperature:	21°C
Humidity:	59%

Test Procedure

The EUT is supplied in series with shunts or current transformers from a source having the same nominal voltage and frequency as the rated supply voltage and frequency of the EUT. The EUT is configured to its rated current with additional resistive load when the testing is performed.

Equipment having more than one rated voltage shall be tested at the rated voltage producing the highest harmonics as compared with the limits.

15.1.2 Test Setup



15.1.3 Limit

Limits of Class A Harmonics Currents

Harmonics Order n	Maximum Permissible harmonic current A	Harmonics Order n	Maximum Permissible harmonic current A
Odd harmonics		Even harmonics	
3	2.30	2	1.08
5	1.14	4	0.43
7	0.77	6	0.30
9	0.40	$8 \leq n \leq 40$	$0.23 * 8/n$
11	0.33		
13	0.21		
$15 \leq n \leq 39$	$0.15 * 15/n$		

15.1.4 Test Result

Active input power under 75W, no limit apply, declare compliance

16. Voltage Fluctuations

16.1 Test Specification and Setup


16.1.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-3-3 / IEC 61000-3-3 / BS EN 61000-3-3 (details referred to Sec 1.2)
Test Procedure:	refer to ISL QA -T4-E-S14
Observation period:	For Pst 10min
	For Plt 2 hours
Temperature:	21°C
Humidity:	59%

Test Procedure

The EUT is supplied in series with reference impedance from a power source with the voltage and frequency as the nominal supply voltage and frequency of the EUT.

16.1.2 Test Setup



16.1.3 Test Result

Performance of EUT complies with the given specification.

16.2 Test Data: Configuration 1

Flicker Test Summary per EN/IEC61000-3-3 Ed. 3.0 (2013) (Run time)

Test duration (min): 10


Data file name: CTSMXL_F-000782.cts_data

Test Result: Pass


Status: Test Completed

Pst_i and limit line

European Limits



Plt and limit line



Parameter values recorded during the test:

Vrms at the end of test (Volt): 229.60

T-max (mS): 0.0

Highest dc (%): 0.00

Highest dmax (%): 0.07

Highest Pst (10 min. period): 0.154

Highest Plt (2 hr. period): 0.067

Test limit (mS): 500.0 Pass

Test limit (%): 3.30 Pass

Test limit (%): 4.00 Pass

Test limit: 1.000 Pass

Test limit: 0.650 Pass

16.3 Test Data: Configuration 2

Flicker Test Summary per EN/IEC61000-3-3 Ed. 3.0 (2013) (Run time)

Test duration (min): 10


Data file name: CTSMXL_F-000783.cts_data

Test Result: Pass


Status: Test Completed

Pst_i and limit line

European Limits



Plt and limit line



Parameter values recorded during the test:

Vrms at the end of test (Volt): 229.58

T-max (mS): 0.0

Highest dc (%): 0.00

Highest dmax (%): 0.05

Highest Pst (10 min. period): 0.097

Highest Plt (2 hr. period): 0.042

Test limit (mS): 500.0 Pass

Test limit (%): 3.30 Pass

Test limit (%): 4.00 Pass

Test limit: 1.000 Pass

Test limit: 0.650 Pass

16.4 Test Setup Photo Configuration 1



Configuration 2



16.5 Appendix

16.6 Appendix A: Test Equipment

16.6.1 Test Equipment List

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction 02	EMI Receiver 14	ROHDE&SCHWARZ	ESCI	101034	05/25/2021	05/25/2022
Conduction 02	Conduction 02-1 Cable	WOKEN	CFD 300-NL	Conduction 02 -1	10/13/2021	10/13/2022
Conduction 02	LISN 26	R&S	ENV216	102378	12/03/2021	12/03/2022
Conduction 02	LISN 21	R&S	ENV216	101476	07/05/2021	07/05/2022

Location Chamber02	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Radiation	BILOG Antenna 19 (30MHz~1GHz)	SCHWARZBECK	VULB 9168+EMCI-N-6-05	643	05/10/2021	05/10/2022
Radiation	Preamplifier 28	EMCI	EMC9135	980296	08/18/2021	08/18/2022
Radiation	Coaxial Cable Chmb 02-10M-02	EMC	RG214U	Chmb 02-10M-02	10/13/2021	10/13/2022
Radiation	EMI Receiver 12	ROHDE & SCHWARZ	ESCI	100804	08/04/2021	08/04/2022

Location Chmb14	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Rad. Above 1GHz	Spectrum Analyzer 25	R&S	FSV 40	101499	10/29/2021	10/29/2022
Rad. Above 1GHz	Horn Antenna 06	ETS-Lindgren	3117	00066665	12/20/2021	12/20/2022
Rad. Above 1GHz	Preamplifier 20	EMC INSTRUMENT	EMC051845	980084	11/16/2021	11/16/2022
Rad. Above 1GHz	Microwave Cable 11	HUBER SUHNER	SUCOFLEX 106	78034/6	03/09/2022	03/09/2023
Rad. Above 1GHz	Microwave Cable 26	EMCI	EMC104-NM-S M-800	141112	03/09/2022	03/09/2023

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
EN61K-4-2	ESD Gun 12	EM TEST	Dito	P1650188689	05/05/2021	05/05/2022
EN61K-4-3	Broadband Log-Periodic Antenna	AR	AT1080	310698	N/A	N/A
EN61K-4-3	Horn Antenna RF-01	AR	ATS700M11G	0335864	N/A	N/A
EN61K-4-3	Amplifier 80Mz~1GHz 250W	AR	250W1000A	312494	N/A	N/A
EN61K-4-3	Amplifier 800MHz~4.2GHz 50W	AR	50S1G4M1	312762	N/A	N/A
EN61K-4-3	Amplifier 4.0~8.0GHz 35W	AR	35S4G8AM1	0335752	N/A	N/A
EN61K-4-3	Broadband Coupler 80M~1GHz	Amplifier Research	DC6180A	0341805	N/A	N/A
EN61K-4-3	Coaxial Cable	INSULATED	NPS-4806-2360-NP3	108599.003.01.03	N/A	N/A
EN61K-4-3	Broadband Coupler 0.8G~4.26GHz	AR	DC7144A	0335226	N/A	N/A
EN61K-4-3	Broadband Coupler 4G~8GHz	AR	DC7350A	0335817	N/A	N/A
EN61K-4-3	Signal Generator 08	ROHDE&SCHWARZ	SMB100A	106541	05/12/2021	05/12/2022
EN61K-4-4	Signal Generator 10	EMC Partner	IMU3000	1547	09/01/2021	09/01/2022
EN61K-4-5	CDN-UTP8 03	EMC-PARTNER	CDN-UPT8ESD3	1546	03/29/2022	03/29/2023
EN61K-4-5	Surge Tester	EMC Partner	MIG0603IN3	523	06/10/2021	06/10/2022
EN61K-4-6	CDN M2+M3 04	TESEQ	CDN M016	43257	09/01/2021	09/01/2022
EN61K-4-6	Coaxial Cable 4-6 02-1			4-6 02-1	N/A	N/A
EN61K-4-6	Conducted Immunity Test System 03	Frankonia	CIT-10-75	126B1151	01/14/2022	01/14/2023
EN61K-4-8	Magnetic Field Immunity Loop	FCC	F-1000-4-8-L-1M	01037	05/31/2021	05/31/2022
EN61K-4-8	Magnetic Field Test Generator	FCC	F-1000-4-8-G-12 5A	01038	05/31/2021	05/31/2022
EN61K-4-11	Voltage Dip and UP Simulator 01	NoiseKen	VDS-2002	VDS1750439	09/17/2021	09/17/2022
EN61K-3-2/3, EN61K-3-11-12	(Harmonic/Flicker) MX Series CTS Compliance Test System	California Instruments	MX60T04GH104 00	72793	08/05/2021	08/05/2022

PS: N/A => The equipment does not need calibration.

****Software for Controlling Spectrum/Receiver and Calculating Test Data**

Test Item	Filename	Version
EN IEC 61000-3-2	California Instruments	CTSMXL V2.20.0
EN 61000-3-3	California Instruments	CTSMXL V2.20.0
EN 61000-4-2	N/A	2.0
EN 61000-4-3	i2	529b
EN 61000-4-4	TEM A3000	v4.6.1
EN 61000-4-5	EMC Partner	1.69
EN 61000-4-6	i2	529b
EN 61000-4-8	N/A	
EN 61000-4-11(<16A)	NOISE KEN	2.0

Site	Filename	Version
Conduction/Radiation	EZ EMC	ISL-03A2

16.7 Appendix B: Uncertainty of Measurement

The laboratory measurement uncertainty accordance with refers to CISPR 16-4-2. If U_{lab} is less than or equal to U_{cisp} in Table 1, then the test report may either state the value of U_{lab} or state that U_{lab} is less than U_{cisp} .

The coverage factor $k = 2$ yields approximately a 95 % level of confidence.

<Conduction 02>

AMN: $\pm 2.90\text{dB}$

<Chamber 02 (10m)>

Horizontal

30MHz~200MHz: $\pm 4.42\text{dB}$

200MHz~1000MHz: $\pm 3.83\text{dB}$

Vertical

30MHz~200MHz: $\pm 4.57\text{dB}$

200MHz~1000MHz: $\pm 3.97\text{dB}$

<Chamber 14 (3m)>

1GHz~6GHz: $\pm 5.06\text{dB}$

<Immunity 02>

Test item	Uncertainty	Test item	Uncertainty
EN 61000-4-2 (ESD)		EN 61000-4-6 (CS)	
Rise time t_r	$\leq 9.81\%$	CDN	1.73 dB
Peak current I_p	$\leq 4.83\%$	EM Clamp	3.37 dB
current at 30 ns	$\leq 4.84\%$	EN 61000-4-8 (Magnetic)	5.49 %
current at 60 ns	$\leq 4.84\%$	EN 61000-4-11 (Dips)	2.04 %
EN 61000-4-3 (RS)	2.66 dB	EN IEC 61000-3-2 (Harmonics)	0.43 %
EN 61000-4-4 (EFT)		EN 61000-3-3 (Fluctuations and Flicker)	8 %
voltage rise time (t_r)	5.4 %		
peak voltage value (VP)	6.34 %		
voltage pulse width (t)	3.5 %		
EN 61000-4-5 (Surge)			
open-circuit voltage front time	10.5 %		
open-circuit voltage peak value	7.5 %		
open-circuit voltage duration (T)	53.33 μs		

16.8 Appendix C: Photographs of EUT

Please refer to the File of **ISL-22LE0256P-MD**

--- END ---