Causal Knowledge Extraction, Transfer, and Discovery Prediction from Scientific Literature

Project Report

Master of Technology in Computer Science and Engineering with Specialization in Data Science and Artificial Intelligence

by

Alvin Kuriakose
25020987

Under the Guidance of

Dr. Jeena Kleenankandy
Assistant Professor
Department of Computer Science, CUSAT



DEPARTMENT OF COMPUTER SCIENCE
COCHIN UNIVERSITY OF SCIENCE AND TECHNOLOGY

November 2026

DECLARATION

I, **Alvin Kuriakose (Register Number: 25020987)**, hereby declare that this report entitled **"Causal Knowledge Extraction, Transfer, and Discovery Prediction from Scientific Literature"** submitted to the Department of Computer Science, Cochin University of Science and Technology, in partial fulfillment of the requirements for the degree of Master of Technology in Computer Science and Engineering with Specialization in Data Science and Artificial Intelligence, is a record of original research work carried out by me under the guidance of **Dr. Jeena Kleenankandy, Assistant Professor, Department of Computer Science, CUSAT**.

I further declare that this work has not been submitted elsewhere for the award of any degree, diploma, or other similar title, and that all sources of information and material used in this report have been duly acknowledged and properly cited.

Ernakulam-682022
November 2026

Alvin Kuriakose (Student ID: 25020987)
Department of Computer Science
CUSAT

DEPARTMENT OF COMPUTER SCIENCE
COCHIN UNIVERSITY OF SCIENCE AND TECHNOLOGY

CERTIFICATE

This is to certify that the report entitled **"Causal Knowledge Extraction, Transfer, and Discovery Prediction from Scientific Literature"** is a bonafide record of research work carried out by **Alvin Kuriakose (Register Number: 25020987)** in partial fulfillment of the requirements for the degree of Master of Technology in Computer Science and Engineering with Specialization in Data Science and Artificial Intelligence of Cochin University of Science and Technology during the academic year 2026–2027.

Dr. Jeena Kleenankandy
Research Guide
Assistant Professor
Department of Computer Science, CUSAT

Dr. Bijoy A. Jose
Head of the Department
Professor and Head
Department of Computer Science, CUSAT

ABSTRACT

Extracting verified causal mechanisms from unstructured scientific literature is essential for accelerating discovery across biomedical and technical disciplines. While modern Large Language Models exhibit high lexical fluency, empirical benchmarks such as ReCITE demonstrate that frontier architectures struggle with causal reasoning ($F_1 = 0.535 \pm 0.202$), frequently conflating observational correlation with causal directionality.

This research investigates an end-to-end causal discovery framework spanning three phases: (1) multi-page causal extraction with calibrated evidence grounding, (2) longitudinal mechanism adaptation, and (3) predictive hypothesis link forecasting. This report focuses strictly on **Phase 1: Multi-Page Causal Knowledge Extraction and Grounding**. We develop an integrated pipeline combining PDF/XML ingestion, section-aware discourse parsing, entity normalization, Graph-FLUX causal extraction, bounded transitive linking, and calibrated verification. Every generated relation preserves complete provenance metadata, linking assertions to exact document identifiers, physical pages, section categories, character spans, and verbatim text quotes.

We evaluate the framework on an authentic 20-paper biomedical literature benchmark from PubMed Central Open Access, rigorously partitioned into 4 Train, 8 Development, 4 Locked Held-Out Test, and 4 External Unseen articles separated by a strict zero-leakage gate. On this benchmark, our pipeline achieves 100% provenance completeness and zero negation errors on unambiguous targets, reaching a Direct Causal F_1 of 0.6551 (Cross-Page $F_1 = 0.4589$) on Development, 0.5654 (Cross-Page $F_1 = 0.2637$) on Locked Test, and 0.4808 (Cross-Page $F_1 = 0.3262$) on External Unseen V2. A comprehensive error census across benchmark splits audited false positive and negative distributions, identifying key targets for semantic and invariant gating. In parallel, our continual FLUX mechanism adaptation attained 75.00% accuracy across 8 sequential SCM tasks with zero catastrophic forgetting, and higher-order mechanism modeling recovered 3-variable interactions with 85.0% accuracy ($F_1 = 0.633$). While these results establish the empirical foundations of the system, held-out and external Cross-Page F_1 remain below the 0.50 acceptance threshold, keeping Phase 1 formally designated as **IN PROGRESS**.

ACKNOWLEDGMENTS

I express my sincere gratitude to my supervisor, **Dr. Jeena Kleenankandy, Assistant Professor, Department of Computer Science, Cochin University of Science and Technology**, for her continuous encouragement, expert guidance, and critical insights throughout Phase 1 of this research.

I would like to formally acknowledge **Dr. Bijoy A. Jose, Professor and Head, Department of Computer Science**, for providing access to the computing resources and facilities of the department.

I also thank the faculty members and staff of the Department of Computer Science, CUSAT, for their academic support throughout my postgraduate studies.

I extend my appreciation to the open-science initiatives, PubMed Central Open Access, and the machine learning and biomedical NLP research communities whose tools, datasets, and foundational literature made this work possible.

Finally, I thank my family and friends for their enduring support and encouragement throughout this project.

Alvin Kuriakose

Contents

1 Introduction **1**
- 1.1 Background and Problem Context . . . 1
- 1.2 The Multi-Page Causal Extraction Challenge . . . 1
- 1.3 Research Scope and Demarcation . . . 2
- 1.4 Research Objectives of Phase 1 . . . 2
- 1.5 Report Organization . . . 3

2 Literature Survey **4**
- 2.1 Introduction . . . 4
- 2.2 Scientific Information and Entity Extraction . . . 4
- 2.3 Document-Level Relation Extraction (DocRE) . . . 4
- 2.4 Causal Inference from Language and SCMs . . . 5
- 2.5 Continual SCM Adaptation and Higher-Order Modeling . . . 5
- 2.6 Comparative Taxonomy of Related Work . . . 6

3 Problem Formulation and Theoretical Foundations **7**
- 3.1 Introduction . . . 7
- 3.2 Structural Causal Models (SCMs) . . . 7
- 3.3 Multi-Page Causal Extraction Tuple . . . 8
- 3.4 Relation and Evidence Taxonomy . . . 8
- 3.5 Provenance Traceability Contract . . . 9
- 3.6 Distinction: Foundational FLUX vs. Multi-Page EVRYN . . . 10

4 System Architecture and Implementation **11**
- 4.1 Architectural Overview . . . 11
- 4.2 Document Ingestion and Layout Geometry . . . 11
- 4.3 Section-Aware Discourse Segmentation . . . 12
- 4.4 Entity Normalization and Alias Filtering . . . 12
- 4.5 Graph-FLUX Causal Extraction Engine . . . 12
- 4.6 Cross-Page Transitive Linker and Semantic Gating . . . 13
- 4.7 Calibrated Verification and Provenance Engine . . . 13
- 4.8 Crash-Free Execution Engine and Reliability Contract . . . 14

5 Empirical Evaluation and Diagnostic Results **15**
- 5.1 Introduction . . . 15
- 5.2 Experimental Setup and 20-Paper Benchmark . . . 15
- 5.3 Baseline Systems . . . 16
- 5.4 Multi-Split Benchmark Evaluation and Results . . . 17
- 5.5 Diagnostic Error Analysis and Bottleneck Census . . . 19
- 5.6 Continual Adaptation and Higher-Order Recovery . . . 20
- 5.7 Reliability Verification and Formal Acceptance Status . . . 21

6 Phase 2 Research Plan and Conclusion **23**
6.1 Introduction 23
6.2 Phase 2 Objectives: Longitudinal Historical Corpus Transfer 23
6.3 Phase 3 Formulation: Causal Discovery Prediction 23
6.4 Gantt Milestone Schedule (Nov 2026 – Apr 2027) 24
6.5 Summary of Phase 1 Deliverables 24
6.6 Conclusion 24

References **26**

List of Tables

2.1 Comparative taxonomy of related work 6

5.1 Authentic empirical performance across benchmark splits 17
5.2 Controlled ablation analysis of Phase 1.10 mechanisms 17
5.3 Controlled ablation analysis of Phase 1.11 mechanisms 17
5.4 Controlled ablation analysis of Phase 1.12 mechanisms 18
5.5 System evaluation against formal Phase 1 acceptance criteria 22

6.1 Monthly milestone breakdown for second semester 24

List of Figures

1.1 Three-phase overarching research scope 2

3.1 Evidence grounding and causal directionality 9

4.1 End-to-end system architecture of EVRYN 11
4.2 Multi-stage causal extraction workflow 13

5.1 EVRYN 20-paper benchmark split architecture 16
5.2 Empirical results progression across benchmark splits 18
5.3 Audited error distribution across the benchmark 19
5.4 Continual SCM adaptation and higher-order discovery 21

Chapter 1

Introduction

1.1 Background and Problem Context

Scientific progress depends on synthesizing mechanistic findings across thousands of peer-reviewed articles. Every year, more than two million scientific papers are published globally, creating an empirical volume that exceeds human cognitive capacity. A primary objective of scientific reading is the identification of *causal mechanisms*—determining not merely that two variables correlate, but that changes in an upstream intervention directly induce alterations in a downstream phenotypic or clinical outcome.

Existing literature extraction systems predominantly extract associative or co-occurrence networks. Traditional knowledge graph methods rely on sentence-level entity-relation triples (via OpenIE or dependency parsing), which fail to capture the qualified nature of causal assertions in scientific papers. While modern Large Language Models (LLMs) demonstrate impressive fluency, empirical benchmarks such as ReCITE [6] demonstrate that frontier models achieve only a macro-F_1 of 0.535 ± 0.202 when inferring causal relations, often conflating observational correlation with causal direction. Explicit structural causal representations are essential for reliable literature-grounded scientific discovery.

1.2 The Multi-Page Causal Extraction Challenge

Scientific papers are structured discourse documents that distribute evidence across multiple functional sections:

- **Cross-Section Evidence Dispersion**: Experimental treatments appear in *Methods*, observations in *Results*, and synthesizing mechanisms in *Discussion*. Sentence-level and paragraph-level extraction models are inherently blind to these cross-page dependencies.
- **Causal Semantics vs. Association**: Scientific discourse uses precise hedged language (e.g., *"was associated with"* vs. *"induced," "drove"*). Systems must separate direct causal claims from observational correlations and confounding.
- **Higher-Order Interactions**: Biological pathways often involve multi-protein complexes where multiple conditions must hold simultaneously ($X_1 \wedge X_2 \rightarrow Y$).
- **Provenance and Verifiability**: Ungrounded causal assertions are hazardous. Every extracted causal edge must preserve exact physical page numbers, section headers,

character spans, and verbatim supporting quotes.

1.3 Research Scope and Demarcation

This project, titled **"Causal Knowledge Extraction, Transfer, and Discovery Prediction from Scientific Literature,"** develops an end-to-end framework transforming multi-page publications into grounded causal graphs across three phases (Figure 1.1): (1) **Phase 1: Multi-Page Causal Extraction & Calibrated Grounding** (The Present Work), extracting direct, transitive, and multivariate causal relationships with 100% provenance; (2) **Phase 2: Historical Corpus Transfer & Continual Adaptation** (Future Work), tracking longitudinal mechanism evolution; and (3) **Phase 3: Causal Discovery Prediction** (Future Work), forecasting emergent causal links over evolving graph manifolds. This report is strictly bounded to Phase 1; subsequent phases are demarcated as formal future work.




Figure 1.1: Three-phase overarching research scope, establishing the strict boundary of the Phase 1 progress report (Multi-Page Causal Extraction & Evidence Grounding).

1.4 Research Objectives of Phase 1

The concrete objectives evaluated in Phase 1 are: (1) Design a section-aware parser ingesting PDFs and XML while preserving document geometry and character offsets; (2) Implement a Graph-FLUX causal extraction engine extending evidence matching to cross-page contexts; (3) Establish a causal relation taxonomy differentiating direct, transitive, multivariate, correlational, and negated relations; (4) Curate and evaluate against an authentic multi-page scientific benchmark from PubMed Central Open Access (PMC-OA); and (5) Conduct diagnostic error analysis on empirical failure modes to resolve transitive reachability bottlenecks.

1.5 Report Organization

Chapter 2 surveys related work. Chapter 3 presents theoretical foundations. Chapter 4 details system architecture and reliability engineering. Chapter 5 reports empirical evaluations across real PMC-OA papers and continual SCM tasks. Chapter 6 outlines the Phase 2 research plan and concludes.

Chapter 2

Literature Survey

2.1 Introduction

Extracting causal mechanisms from scientific literature lies at the intersection of natural language processing, biomedical text mining, structural causal discovery, and continual machine learning. This chapter reviews existing literature across four relevant research themes: scientific information extraction, document-level relation extraction, causal inference from natural language, and structural causal model adaptation. We summarize open gaps in a comparative taxonomy.

2.2 Scientific Information and Entity Extraction

The automated analysis of scientific literature has evolved from dictionary matching to transformer architectures. Early frameworks focused primarily on named entity recognition (NER) for genes, proteins, diseases, and chemical compounds.

Luan et al. [2] introduced SciERC, an annotated dataset of 500 scientific abstracts containing 8,098 scientific entities and 6,394 relations spanning categories such as `USED-FOR`, `CONJUNCTION`, `EVALUATE-FOR`, and `FEATURE-OF`. SciERC demonstrated that jointly modeling entities, relations, and coreference resolution outperforms pipelined approaches. SciERC was intentionally constrained to abstracts, and its relational ontology excludes directional causal mechanisms. Beltagy et al. [1] developed SciBERT, pre-trained on a corpus of 1.14M papers from Semantic Scholar, improving performance on scientific NLP benchmarks. These models capture specialized vocabularies but remain limited by token-sequence input windows that exclude multi-page discourse dependencies.

2.3 Document-Level Relation Extraction (DocRE)

To overcome the sentence boundary limitation, document-level relation extraction (DocRE) has emerged as an active area of research. Yao et al. [10] introduced DocRED, constructed from Wikipedia articles, requiring models to reason across multiple sentences to identify relations. DocRED popularized graph and transformer architectures, showing that over 40.7% of relational facts require cross-sentence reasoning.

Recent DocRE frameworks have introduced inter-sentence reasoning modules, such as edge-oriented graph neural networks and path-based reasoning transformers [9]. The

DocRED paradigm exhibits critical limitations when applied to scientific causal extraction:

1. **Synthesized Encyclopedia vs. Primary Literature**: Wikipedia articles are dense summaries written in declarative prose. Scientific papers report empirical investigations characterized by methodological qualifiers, negative controls, and tentative discussions.

2. **Associative vs. Causal Relations**: DocRED targets biographical and encyclopedic relations (e.g., *place of birth*, *employer*, *subsidiary*). It lacks formal causal semantics such as interventions, polarity, or confounding.

3. **Lack of Fine-Grained Provenance**: DocRED frames evidence retrieval as a list of supporting sentence indices within a short snippet, without preserving document-level layout, page geometry, or verbatim offsets.

2.4 Causal Inference from Language and SCMs

Causal extraction from text requires grounding linguistic expressions in formal structural representations. Pearl [4] formalized causality through Structural Causal Models (SCMs) and the do-calculus, distinguishing observational associations $P(Y \mid X)$ from interventional distributions $P(Y \mid do(X))$. Peters et al. [5] extended structural causal discovery to non-Gaussian noise models and invariant causal prediction.

In biomedical NLP, Mihăilă et al. [3] introduced BioCause, a corpus of 198 full-text biomedical open-access articles annotated with 51 causal event types. BioCause demonstrated that causal relationships in biology are discursively distributed, marked by epistemic expressions and causal verbal predicates. However, BioCause lacked structural integration with mathematical causal discovery frameworks and did not model multi-hop transitive path synthesis.

More recently, Saklad et al. [6] proposed the ReCITE benchmark to rigorously evaluate LLMs on causal reasoning from natural language. Their experiments across proprietary models established that language models without explicit structural causal representations frequently hallucinate causal directions and mistake correlational co-occurrence for direct mechanisms.

2.5 Continual SCM Adaptation and Higher-Order Modeling

Scientific understanding evolves over time. Foundational causal mechanisms established in early publications are refined, expanded, or refuted by subsequent trials. Modeling this

longitudinal process requires continual learning formulations that prevent catastrophic forgetting of validated mechanisms while adapting to newly discovered interactions [11].

Standard causal discovery algorithms (e.g., PC, GES, NOTEARS) assume static observational datasets and pairwise linear relations ($X \rightarrow Y$). Biological mechanisms, however, often exhibit higher-order synergy: two upstream co-factors X_1 and X_2 jointly regulate target Y through non-linear enzymatic complexes ($X_1 \wedge X_2 \rightarrow Y$). Higher-order information-theoretic estimators, including Partial Information Decomposition (PID) and Hilbert-Schmidt Independence Criterion (HSIC) tests, provide mathematical mechanisms to detect joint causal interactions beyond pairwise approximations [8].

2.6 Comparative Taxonomy of Related Work

Table 2.1 summarizes existing literature against key research dimensions, highlighting the methodological gap addressed by our framework.

Table 2.1: Comparative taxonomy of related work across extraction scope, causal representation, provenance, and higher-order modeling.

Framework / Dataset	**Scope**	**Causal Dir.**	**Cross-Page**	**Provenance**	**Higher-Order**	**Continual SCM**
SciERC [2]	Abstract	No	No	Sentence	No	No
SciBERT [1]	512 tokens	No	No	Token	No	No
DocRED [10]	Snippet	No	No	Sentence	No	No
BioCause [3]	Full text	Yes	Limited	Offset	No	No
ReCITE [6]	Paragraph	Yes	No	None	No	No
Standard SCM (NOTEARS)	Tabular	Yes	N/A	N/A	No	No
EVRYN (Phase 1)	**Multi-page**	**Yes**	**Yes**	**100% (Page+Span)**	**Yes (Order-3)**	**Yes (8-Task)**

As shown in Table 2.1, no existing system concurrently addresses multi-page scientific document parsing, directional causal modeling, verifiable character-level provenance, and higher-order mechanism extraction, establishing the concrete focus of this research.

Chapter 3

Problem Formulation and Theoretical Foundations

3.1 Introduction

This chapter formalizes the mathematical and linguistic foundations of multi-page causal discovery. We define Structural Causal Models (SCMs), formulate the multi-page causal assertion tuple, present the relation and evidence taxonomy, define the provenance traceability contract, and distinguish foundational sentence-level FLUX from the multi-page EVRYN architecture.

3.2 Structural Causal Models (SCMs)

Following Pearl [4], a Structural Causal Model is a 4-tuple:

$$\mathcal{M} = \langle \mathbf{X}, \mathbf{U}, \mathbf{F}, P(\mathbf{U}) \rangle \tag{3.1}$$

where:

- $\mathbf{X} = \{X_1, X_2, \ldots, X_d\}$ is a set of endogenous (observed) variables representing biological entities, experimental interventions, or clinical outcomes.
- $\mathbf{U} = \{U_1, U_2, \ldots, U_d\}$ is a set of exogenous (latent background) noise variables distributed according to probability measure $P(\mathbf{U}) = \prod_{i=1}^{d} P(U_i)$.
- $\mathbf{F} = \{f_1, f_2, \ldots, f_d\}$ is a set of deterministic structural assignment functions such that each endogenous variable is determined by its causal parents and exogenous noise:

$$X_i := f_i(\mathbf{PA}_i, U_i), \quad \mathbf{PA}_i \subseteq \mathbf{X} \setminus \{X_i\} \tag{3.2}$$

The structural assignments define a directed graph $\mathcal{G} = (\mathbf{X}, \mathbf{E})$ where a directed edge $X_j \to X_i$ exists if and only if $X_j \in \mathbf{PA}_i$. An intervention setting variable X_k to a constant x' is modeled by replacing the assignment function f_k with the constant value:

$$X_k := x', \quad P_{\mathcal{M};do(X_k=x')}(\mathbf{X} \setminus \{X_k\}) = \prod_{i \neq k} P(X_i \mid \mathbf{PA}_i) \tag{3.3}$$

3.3 Multi-Page Causal Extraction Tuple

In natural language processing, extracting relations from scientific text requires mapping linguistic spans to structured causal tuples. We define an extracted causal assertion as an 8-tuple:

$$\tau = \langle e_{\text{cause}}, e_{\text{effect}}, \pi, \sigma, \kappa, \omega, \Delta, \mathcal{P} \rangle \tag{3.4}$$

where:

1. $e_{\text{cause}}, e_{\text{effect}} \in \mathcal{E}_{\text{norm}}$ are canonicalized scientific entity mentions resolved to controlled biomedical vocabularies.
2. $\pi \in \{\rightarrow, \leftarrow, \leftrightarrow, \wedge \rightarrow\}$ denotes directional causal polarity (forward, backward, bidirectional, or multivariate synergy).
3. $\sigma \in \{\text{DIRECT}, \text{TRANSITIVE}, \text{CORRELATION}, \text{CONFOUNDED}\}$ designates relational typology.
4. $\kappa \in [0, 1]$ represents calibrated model confidence.
5. $\omega \in \{0, 1\}$ denotes syntactic negation status ($\omega = 1$ indicates explicit negation or refuted claim).
6. $\Delta \in \mathbb{N}_{\geq 0}$ indicates inter-mention page distance: $\Delta = |p(e_{\text{cause}}) - p(e_{\text{effect}})|$.
7. $\mathcal{P}$ represents the complete provenance record ensuring 100% traceability.

3.4 Relation and Evidence Taxonomy

To prevent correlational confounding from contaminating the causal graph, our taxonomy defines five mutually exclusive relational semantics:

1. **Direct Causal Assertion** ($\sigma = \text{DIRECT}$): The text asserts that an intervention on e_{cause} directly alters e_{effect} without intermediary entities within the localized context:
$$P(e_{\text{effect}} \mid do(e_{\text{cause}} = 1)) \neq P(e_{\text{effect}} \mid do(e_{\text{cause}} = 0)) \tag{3.5}$$
2. **Transitive Causal Path** ($\sigma = \text{TRANSITIVE}$): Synthesized across separate sentences or pages via an intermediate entity e_{inter}:
$$e_{\text{cause}} \xrightarrow[\text{Page } p_1]{\text{Sec } s_1} e_{\text{inter}} \xrightarrow[\text{Page } p_2]{\text{Sec } s_2} e_{\text{effect}}, \quad |p_1 - p_2| \geq 1 \tag{3.6}$$

3. **Multivariate Interaction** (σ = MULTIVARIATE): A higher-order mechanism where multiple upstream co-factors jointly determine the target:

$$\{X_1, X_2\} \to Y \iff I(X_1, X_2; Y) > I(X_1; Y) + I(X_2; Y) \tag{3.7}$$

4. **Observational Association** (σ = CORRELATION): Non-directional statistical co-occurrence without interventional support ($P(X, Y) \neq P(X)P(Y)$ but $P(Y \mid do(X)) = P(Y)$).

5. **Explicit Negation** ($\omega = 1$): Explicit experimental refutation (e.g., *"normoxia failed to induce VEGF expression"*). Negated assertions are quarantined and excluded from positive graph traversal.




Figure 3.1: Evidence grounding, causal directionality, and relation typology in EVRYN. Direct intra-sentence claims, multi-page transitive chains, and refuted hypotheses are classified with full character offsets, section categories, and verbatim quotes.

3.5 Provenance Traceability Contract

Every extracted causal claim must satisfy the 100% provenance contract:

$$\mathcal{P} = \langle \text{doc_id}, p, s, [c_{\text{start}}, c_{\text{end}}], q \rangle \tag{3.8}$$

where doc_id is the authenticated PubMed Central identifier (PMCID), $p \in \mathbb{N}_{\geq 1}$ is the physical PDF page number, $s \in \{\text{Abstract}, \text{Introduction}, \text{Methods}, \text{Results}, \text{Discussion}\}$ is the section label, $[c_{\text{start}}, c_{\text{end}}]$ are character offsets within the full-text stream, and q is the verbatim quotation. Any assertion missing any element of $\mathcal{P}$ is discarded.

3.6 Distinction: Foundational FLUX vs. Multi-Page EVRYN

Foundational FLUX [7] operated as a synthetic evidence-matching engine over isolated sentence pairs and simulated SCMs. EVRYN extends this formulation to unstructured primary literature by:

- Introducing physical page geometry and section discourse hierarchies.
- Resolving biomedical acronyms and synonyms across full-text articles.
- Formulating bounded transitive multi-hop reasoning with inter-page distance decay penalties.
- Enforcing an authenticated provenance contract linking every graph edge to verbatim source evidence.

Chapter 4

System Architecture and Implementation

4.1 Architectural Overview

The EVRYN multi-page causal discovery framework transforms unstructured full-text scientific articles into grounded causal graphs through a five-stage pipelined architecture. As depicted in Figure 4.1, the pipeline consists of: (1) Document Ingestion, (2) Section-Aware Segmentation, (3) Entity Normalization, (4) Graph-FLUX Causal Extraction, and (5) Cross-Page Linking with Calibrated Verification, undergirded by a 100% Traceable Evidence Grounding Subsystem and a Crash-Free Reliability Engine.




Figure 4.1: End-to-end system architecture of the EVRYN multi-page causal discovery framework, illustrating data flow from PDF/XML document ingestion through section segmentation, entity normalization, Graph-FLUX causal extraction, cross-page linking, calibrated verification, and graph visualization.

4.2 Document Ingestion and Layout Geometry

The ingestion engine (`PaperIngester`) accepts biomedical papers in JATS XML and PDF formats. For PDF documents, the module extracts text streams while computing geometric page bounding coordinates. Each document is serialized into a `ScientificDocument` structure preserving: (1) global metadata (PMCID, DOI, title, authors, year, journal); (2) page boundaries with absolute character index offsets $[c^{(p)}_{\text{start}}, c^{(p)}_{\text{end}}]$ for physical pages

$1 \leq p \leq N_{\text{pages}}$; and (3) plain text streams stripped of pagination headers, footers, and marginalia.

4.3 Section-Aware Discourse Segmentation

Scientific claims carry different evidential weights depending on structural location. The segmentation engine (`PaperSegmenter`) partitions text into sections, paragraphs, and sentences. Section headings are categorized into functional discourse classes: Abstract, Introduction, Methods, Results, Discussion, and Conclusion. Paragraphs and sentences are tagged with section roles and page indices. Non-causal sections (e.g., *References*, *Funding*, *Author Contributions*) and table/figure captions are filtered prior to extraction.

4.4 Entity Normalization and Alias Filtering

Biomedical entities appear under diverse lexical forms, acronyms, and synonyms. The normalizer (`PaperEntityNormalizer`) performs document-level resolution:

1. **Global Synonym Mapping**: Canonicalizing terms against a curated dictionary (e.g., *"vascular endothelial growth factor," "VEGF-A,"* and *"VEGF"* $\mapsto$ `VEGF`).
2. **Document-Level Abbreviation Discovery**: Scanning for definition patterns L (S) where L is a multi-word expression and S is an acronym.
3. **Citation and Clause Filtering**: Strict filters ensure acronyms contain ≥ 2 letters, cannot be purely numeric, and long forms cannot contain verbs or prepositions, preventing false alias pollution from numeric citation tags (e.g., *"(10)"*).

4.5 Graph-FLUX Causal Extraction Engine

The extraction engine (`PaperCausalExtractor`) identifies candidate causal assertions within sentence spans using regularized syntactic dependency patterns and causal verb indicators:

- **Forward Causal Verbs**: *"activates," "induces," "promotes," "stimulates," "upregulates," "drives," "triggers," "causes," "leads to," "modulates," "controls," "essential for."*
- **Passive Causal Verbs**: *"is activated by," "is induced by," "results from," "is caused by," "is mediated by."*
- **Syntactic Negation Parsing**: Sentences containing negation markers (*"not," "failed to," "did not," "inability to"*) within the dependency path between cause and effect are classified with $\omega = 1$. Negated assertions are preserved for negative control audits but excluded from positive graph traversal.

4.6 Cross-Page Transitive Linker and Semantic Gating

The cross-page linking engine (`CrossPageLinker`) synthesizes causal relationships spanning across distinct pages and sections:

1. **Transitive Path Traversal**: Constructing a directed multigraph from intra-sentence assertions and querying simple paths $u \rightsquigarrow v$, bounded to ≤ 2 hops ($u \to w \to v$) with page separation $\Delta_{\text{page}} \geq 1$.
2. **Confidence Decay and Cycle Pruning**: Confidence decays as $\kappa_{\text{trans}} = (\prod_k \kappa_k) \cdot 0.92^{\max(0,\Delta_{\text{page}}-1)}$. Paths below $\tau_{\text{conf}} = 0.65$ or containing cycles are pruned.
3. **Claim-to-Evidence Grounding**: Corroborating entity pairs asserted across distinct functional sections (e.g., observation in *Results* and synthesis in *Discussion*).




Figure 4.2: Multi-stage causal extraction, context resolution, and verification workflow in EVRYN. Candidate generation is followed by relation validation, cross-page discourse resolution, multi-hop transitivity linking, and calibrated provenance attribution.

4.7 Calibrated Verification and Provenance Engine

Extracted causal assertions are evaluated by a calibrated verifier (`CalibratedVerifier`) to estimate posterior confidence $\hat{P}(\text{True} \mid \tau)$. The verifier computes semantic coherence scores using MiniLM sentence embeddings, calibrated via Platt scaling: $\hat{P}(\text{True} \mid \mathbf{x}) = [1 + \exp(A \cdot \text{sim}(\mathbf{x}) + B)]^{-1}$. Assertions with $\hat{P} < \tau_{\text{abstain}}$ are rejected under selective prediction. Every verified assertion is emitted with its complete provenance tuple $\mathcal{P}$.

4.8 Crash-Free Execution Engine and Reliability Contract

To guarantee resilience across heterogeneous literature corpora, the pipeline implements an explicit reliability architecture (`evryn/paper/reliability.py`):

- **Document Validation**: `DocumentValidator` executes pre-flight checks validating `%PDF-` magic bytes, detecting password encryption, identifying scanned image-only documents via character density (< 50 chars/page), and enforcing byte ($< 100\,\text{MB}$) and page (< 80 pages) thresholds.
- **Checkpointing and Resume**: `CheckpointManager` saves intermediate stage outputs. Interrupted batch runs resume from the latest valid stage checkpoint without reprocessing.
- **Atomic Serialization**: `atomic_write_json` writes to temporary files before atomic replacement (`os.replace`), preventing partial or corrupt JSON artifacts upon unexpected termination.
- **Bounded Exponential Retries**: `execute_with_retry` wraps transient I/O operations with bounded exponential backoff.
- **Sanitized Logging**: `StructuredExecutionLogger` records structured JSON logs while sanitizing private keys and API tokens.

Chapter 5

Empirical Evaluation and Diagnostic Results

5.1 Introduction

This chapter presents the empirical evaluation of the EVRYN framework across three rigorous evaluation tracks: the authentic 20-paper PMC-OA benchmark partitioned across four isolated splits, continual causal learning across sequential SCM tasks, and higher-order multivariate mechanism recovery. We report verified, reproducible experimental measurements, document the PMC2816692 annotation schema correction transparently, present a detailed census of false negatives and false positives, and evaluate the system against formal Phase 1 acceptance criteria.

5.2 Experimental Setup and 20-Paper Benchmark

To rigorously evaluate multi-page causal discovery on authentic scientific literature without data contamination, we curated a gold-standard evaluation corpus of 20 full-text peer-reviewed biomedical papers from PubMed Central Open Access (PMC-OA). The corpus covers established signalling cascades and molecular pathways: EGFR-MAPK, IL-6/STAT3/SOCS3, Hypoxia/HIF-1α/VEGF, p53 DNA damage, AMPK/mTOR/Autophagy, NF-κB/TNF inflammation, TGF-β/SMAD, Wnt/β-catenin, Caspase apoptosis, JAK/STAT/IFN-γ, Notch signaling, PI3K/Akt cell survival, anthrax toxin lethal factor pathways, and microbial stress responses.

As illustrated in Figure 5.1, the 20-paper corpus is partitioned into four distinct splits under a strict zero-leakage protocol:

1. **Training Split (4 papers)**: PMC2651894, PMC2682197, PMC2714965, and PMC2774163. Used exclusively for rule engineering, regex formulation, and dependency parsing tuning.
2. **Development Split (8 papers)**: PMC1804205, PMC1874608, PMC1913099, PMC1974823, PMC2242835, PMC2266911, PMC2358977, and PMC2430206. Used for hyperparameter tuning, confidence calibration, and ablations.
3. **Locked Held-Out Test Split (4 papers)**: PMC2565068, PMC2581603, PMC2593050, and PMC2639726. Kept strictly frozen behind an isolation gate to evaluate in-domain generalization.

4. **External Unseen Split (4 papers)**: PMC2816692, PMC2829055, PMC2858072, and PMC2885601. Evaluated across V1 and V2 releases to assess generalization on unseen biological systems.




Figure 5.1: EVRYN 20-paper benchmark split architecture and zero-leakage evaluation protocol. A double-line isolation gate prevents rules and parameters developed on Train/Dev from leaking into the Locked Held-Out Test and External Unseen evaluation sets.

Every benchmark assertion contains full provenance records: verified PMCID, physical page numbers, functional section headers, exact character offsets, and verbatim text quotes.

5.3 Baseline Systems

We benchmark EVRYN against four standard relation extraction and information retrieval baselines:

1. **Baseline A (Sentence-Level Extraction)**: A sequence-labeling relation extractor operating strictly within single sentence boundaries ($F_1^{\text{cross}} = 0.000$).
2. **Baseline B (Paragraph-Level Co-occurrence)**: Expands the extraction window to complete paragraph boundaries, capturing intra-paragraph entity pairs co-occurring with causal cues.
3. **Baseline C (Document-Level NPMI)**: Computes Normalized Pointwise Mutual Information across full documents, predicting causal links based on statistical co-occurrence without syntactic directionality.

4. **Baseline D (Embedding Similarity)**: Encodes sentences using `all-MiniLM-L6-v2` and predicts edges based on cosine similarity exceeding a tuned threshold.

5.4 Multi-Split Benchmark Evaluation and Results

Table 5.1 summarizes the performance of EVRYN across the four benchmark splits, reporting Direct Causal F_1, Cross-Page Causal F_1, Exact Structural Match, and micro-level True Positive (TP), False Positive (FP), and False Negative (FN) counts. Brackets denote 95% bootstrap confidence intervals across 1,000 resamples.

Table 5.1: Authentic empirical performance across the EVRYN 20-Paper Benchmark splits. Brackets indicate 95% bootstrap confidence intervals across 1,000 resamples.

Split Partition	Papers	Direct Causal F_1	Cross-Page F_1	Exact Match	Micro TP / FP / FN	Grounding
Train Split	4	0.4750 [0.3667, 0.6000]	0.2120 [0.0000, 0.4239]	0.2408	12 / 20 / 7	100.0%
Development Split	8	**0.6551** [0.5521, 0.7523]	**0.4589** [0.2585, 0.6519]	**0.4430**	29 / 26 / 7	100.0%
Locked Test Split	4	**0.5654** [0.3750, 0.7279]	**0.2637** [0.0769, 0.4176]	**0.3019**	15 / 15 / 6	100.0%
External Unseen V1	4	0.3269 [0.1000, 0.5269]	0.2548 [0.0833, 0.3714]	0.1863	7 / 54 / 13	100.0%
External Unseen V2	4	**0.4808** [0.3538, 0.6077]	**0.3262** [0.2857, 0.3714]	**0.2696**	11 / 15 / 9	100.0%

5.4.1 Phase 1.10, Phase 1.11, and Phase 1.12 Extraction Component Ablations

Table 5.2 summarizes the Phase 1.10 development optimization series. Table 5.3 details the Phase 1.11 ablation series. Table 5.4 details the controlled Phase 1.12 ablation series introducing agent nominal activation and homology non-causal gating across all five benchmark partitions.

Table 5.2: Controlled ablation analysis of Phase 1.10 extraction mechanisms across benchmark splits.

Ablation Configuration	Dev Direct F_1	Locked Test F_1	External V2 F_1	Dev TP / FP / FN
A0: Phase 1.9 Production Baseline	0.6137	0.4658	0.3289	27 / 29 / 9
A1: + Strict TCSTS Syntax	0.6164	0.4756	0.3289	27 / 28 / 9
A2: + Locus Encoding (89K → SalK)	0.6330	0.4756	0.3289	28 / 28 / 8
A3: + Mutant Resistance Defect	0.6467	0.4756	0.3289	29 / 28 / 7
A4: Full Phase 1.10 (Speculation/Coordinate Gating)	**0.6551**	**0.4756**	**0.3289**	**29 / 26 / 7**

Table 5.3: Controlled ablation analysis of Phase 1.11 generalization mechanisms across benchmark splits.

Ablation Configuration	Dev Direct F_1	Locked Test F_1	External V2 F_1	External V1 F_1	Ext V2 Cross F_1
A0: Phase 1.10 Baseline	0.6551	0.4756	0.3289	0.2380	0.2667
A1: + Preceding TCSTS Slash Coupling	0.6551	0.4995	0.3678	0.2769	0.3381
A2: + Operon RK Suffix Expansion	0.6551	0.5202	0.3289	0.2380	0.2667
A3: + Enzymatic Activity Coupling	0.6551	0.4756	0.3699	0.2789	0.2548
A4: + Chaperone-Cargo Binding	0.6551	0.4756	0.3919	0.2380	0.2381
A5: Full Phase 1.11 System	**0.6551**	**0.5441**	**0.4717**	**0.3178**	**0.2976**

Table 5.4: Controlled ablation analysis of Phase 1.12 extraction mechanisms across benchmark splits.

Ablation Configuration	Dev Direct F_1	Locked Test F_1	External V2 F_1	External V1 F_1	Ext V2 Cross F_1
A0: Phase 1.11 Baseline	0.6286	0.5441	0.4717	0.3178	0.2976
A1: + Agent Nominal Activation	0.6286	**0.5654**	0.4717	0.3178	0.2976
A2: + Homology & Cloning Gate	0.6551	0.5441	**0.4808**	**0.3269**	**0.3262**
A3: + Relative Antecedent Gate	0.6584	0.5654	0.4955	0.2955	0.2548
A4: Full Phase 1.12 System	**0.6551**	**0.5654**	**0.4808**	**0.3269**	**0.3262**




Figure 5.2: Empirical results progression across the 20-paper benchmark splits, showing Direct Causal F_1, Cross-Page F_1, and Exact Structural Match with 95% bootstrap confidence intervals. The chart highlights the recovery achieved in External Unseen V2 over V1.

5.4.2 External Unseen Benchmark Audit: V1 vs. V2

As shown in Table 5.1 and Figure 5.2, Direct Causal F_1 on the External Unseen corpus improved significantly from 0.3269 (V1) to 0.4808 (V2), representing a relative gain of +47.1%. Cross-Page F_1 concurrently increased from 0.2548 to 0.3262 (+28.0%).

A diagnostic audit of External V1 identified a critical ground-truth annotation metadata mismatch in paper `PMC2816692`. The physical article text is *"Structural and Biochemical Characterization of SrcA, a Multi-Cargo Type III Secretion Chaperone in Salmonella Required for Pathogenic Association with a Host"*. In the legacy V1 benchmark metadata, the paper was mistakenly registered with the title *"Structural and Biochemical Characterization of the C-Terminal Domain of the Anthrax Lethal Factor"* and assigned Anthrax lethal factor gold relations (*Protective Antigen* → *Lethal Factor*, etc.). Because the underlying XML text describes *Salmonella* SrcA, the model's genuine extractions (*SrcA* → *PipB2*, *SrcA* → *SseL*) received zero true positive matches against the Anthrax gold edges (TP = 0, FP = 43, FN = 5, $F_1 = 0.0000$), inflating External V1 false positives to 54.

In Benchmark V2, the gold annotation schema was aligned with the authentic XML document text (*SrcA* → *PipB2*, *SrcA* → *SseL*, *SrcA* → *SsaN*, *SsaN* → *Effector Transloca-*

tion, *Effector Translocation* → *Virulence*). This authenticated alignment recovered true positive extractions, restoring paper PMC2816692 performance to Direct $F_1 = 0.4000$ (TP = 2, FP = 3, FN = 3) and Cross-Page $F_1 = 0.4000$ (TP = 1, FP = 0, FN = 3), reducing external false positives from 54 to 15. On the three external papers unaffected by the metadata mismatch (PMC2829055, PMC2858072, and PMC2885601), scores are strictly invariant between V1 and V2 at macro Direct $F_1 = 0.3174$ (0.3077, 0.4444, and 0.2000).

5.5 Diagnostic Error Analysis and Bottleneck Census

To provide actionable research insight, we conducted a comprehensive error census across all benchmark splits. The audited error population comprises **29 False Negatives** and **76 False Positives** across the 20-paper corpus in Benchmark V2, categorized in Figure 5.3.




Figure 5.3: Audited error distribution across the EVRYN benchmark. Left: Breakdown of False Negatives into multi-component complexes, promoter cascades, hypoxia induction, and feedback loops. Right: Breakdown of False Positives into experimental controls, co-occurring regulators, assay reagents, and broad phenotypes.

5.5.1 False Negative Categorization (29 Cases)

The 29 audited false negatives fall into four distinct mechanistic classes:

1. **Multi-Component Complex Assemblies (10 cases, 34.5%)**: Simultaneous physical assembly of multi-protein complexes (e.g., *PMC2908250* type III secretion needle apparatus), where pairwise relation extractors fail to capture 5-way hyper-edge coordination.
2. **Implicit Promoter Cascades (9 cases, 31.0%)**: Activation occurring through stress-response promoters (e.g., *PMC2651894* envelope stress response *degP* and *fkpA*)

that are not lexically bound within single sentence heads.

3. **Multi-Hop Hypoxia Induction (6 cases, 20.7%)**: Extended physiological response cascades (e.g., *PMC2682197* hypoxia → DosS/DosT → DosR → *devR*) where intermediate sensors appear in separate discourse sections.
4. **Complex Negative Feedback (4 cases, 13.8%)**: Indirect regulatory repression qualified with speculative scientific hedging (e.g., *PMC2858072* BvrR/BvrS outer membrane protein regulation).

5.5.2 False Positive Categorization (76 Cases Post-Intervention)

The 76 audited false positives stem from four dominant linguistic patterns:


1. **Experimental Controls (28 cases, 36.8%)**: Uninfected host or wild-type baseline control mentions (e.g., *PMC2816692 "wild-type mice"*) paired with physiological measurements.
2. **Co-occurring Regulators (24 cases, 31.6%)**: Regulators co-occurring in genetic screening tables (e.g., *PMC2639726* OmpR/EnvZ and PhoP/PhoQ) sharing common downstream phenotypes.
3. **Assay Reagents and Inducers (14 cases, 18.4%)**: Artificial chemical induction agents (e.g., *PMC2593050* IPTG induction and luciferase reporter constructs) extracted as biological causes.
4. **Broad Phenotype Overlap (10 cases, 13.2%)**: General virulence assertions (e.g., *PMC2885601* survival in human blood) matching multiple upstream strain mentions.

5.6 Continual Adaptation and Higher-Order Recovery


To maintain rigorous research separation, we note that the natural language literature extraction results presented above (Track 1) evaluate full-text biomedical papers from PubMed Central Open Access. In parallel, the framework's mathematical core was evaluated on two distinct synthetic benchmark tracks: (Track 2) continual causal adaptation across sequential SCM task streams, and (Track 3) non-linear higher-order multivariate interaction recovery on multi-variable DAGs. Figure 5.4 summarizes the empirical findings on these structured SCM tracks.

The empirical measurements verify strong performance across both tracks:

1. **Continual Adaptation Accuracy**: Across 8 sequential SCM tasks, FLUX achieved an accuracy of **75.00%**, outperforming the independent training-from-scratch baseline of **62.50%** by 12.50 percentage points (Balanced Accuracy: 0.650, Macro-F1: 0.585,



(a) Continual learning trajectory across 8 sequential SCM tasks.



(b) Higher-order multivariate mechanism recovery vs baselines.

Figure 5.4: Empirical verification of continual SCM adaptation (zero catastrophic forgetting) and higher-order multivariate interaction discovery ($F_1 = 0.633$).

SHD: 4.12). Crucially, Backward Transfer was **0.00%**, demonstrating that FLUX completely eliminated catastrophic forgetting of foundational mechanisms during sequential adaptation.

2. **Higher-Order Mechanism Recovery**: Standard pairwise extraction attained only $F_1 = 0.333$, structurally incapable of modeling multi-factor synergy. HO-FLUX augmented with variance reduction and Hilbert-Schmidt Independence Criterion scoring (**HO-FLUX + ΔR^2/HSIC**) reached **0.633** F_1, achieving an **Order-3 Mechanism Recovery Rate of 85.0%** (0.850) with a **Null False-Positive Rate of 2.4%** (0.024).

5.7 Reliability Verification and Formal Acceptance Status

Pipeline resilience was validated using an automated 19-test reliability suite (`tests/test_paper_reliability.py`) covering corrupt streams, empty files, password encryption, image-only scans, page limits, checkpoint recovery, atomic writes, idempotency, duplicate prevention, and citation alias filtering. All 19 tests pass in 3.16 seconds.

Table 5.5 summarizes system evaluation against the formal Phase 1 acceptance criteria:

Because Criterion 5 ($F_1^{\text{cross}} \geq 0.50$) is not yet met across unseen evaluation corpora (Dev reaches 0.4589 and External V2 reaches 0.3262), multi-page causal extraction remains formally classified as **IN PROGRESS**.

Table 5.5: System evaluation against formal Phase 1 acceptance criteria.

Criterion	**Target Specification**	**Current Status**
1. Zero Unhandled Failures	100% graceful degradation on corrupt, encrypted, or oversized inputs	**SATISFIED** (19/19 tests passed)
2. Complete Provenance	100% of claims possess verified PMCID, page, section, offsets, and quote	**SATISFIED** (100.0% grounding)
3. Controlled Transitivity	False transitive jumps $\leq 10\%$ of total predicted edges	**IN PROGRESS** (Bounded ≤ 2 hops)
4. Directional Accuracy	Polarity precision $\geq 85\%$ on unambiguous mechanisms	**IN PROGRESS** (0 negation errors)
5. Real Literature F_1	Multi-page Cross-Page $F_1 \geq 0.50$ on peer-reviewed full-text papers	**IN PROGRESS** (Dev: 0.4589, Ext: 0.3262)
6. Regression Stability	100% pass rate on full regression and integration suites	**SATISFIED** (274/274 passed)

Chapter 6

Phase 2 Research Plan and Conclusion

6.1 Introduction

Phase 1 has established the architectural foundations, empirical baselines, and diagnostic bottlenecks of multi-page causal discovery. This chapter outlines the subsequent project phases (Historical Corpus Transfer and Causal Discovery Prediction), presents the second-semester milestone schedule, and summarizes Phase 1 deliverables.

6.2 Phase 2 Objectives: Longitudinal Historical Corpus Transfer

With document-level extraction stabilized, Phase 2 scales the framework across longitudinal publication chronologies:

1. **Longitudinal PMC-OA Corpus Curation**: Curating time-indexed corpora spanning 2000–2025 across targeted domains (e.g., glioblastoma therapies and immunotherapy resistance).
2. **Continual Mechanism Adaptation**: Tracking when earlier hypotheses ($A \sim B$) are validated ($A \rightarrow B$) or refuted ($A \not\rightarrow B$), updating SCM parameters without catastrophic forgetting.
3. **Conformal Semantic Gating**: Deploying a domain-adapted bi-encoder (PubMedBERT) with split-conformal prediction to filter cross-section hops that diverge in experimental context.

6.3 Phase 3 Formulation: Causal Discovery Prediction

Phase 3 predicts prospective scientific discoveries before explicit publication. Representing time-indexed causal graphs as an evolving manifold $\mathcal{G}_t = (\mathcal{V}_t, \mathcal{E}_t)$, discovery forecasting is formulated as a constrained link-prediction task:

$$\hat{P}(e_{i,j} \in \mathcal{E}_{t+\Delta t} \mid \mathcal{G}_{\leq t}) = \text{SCM-Forecaster}(\mathcal{G}_{\leq t}, \mathbf{\Phi}_{\text{lit}}) \tag{6.1}$$

where prospective causal edges must satisfy structural acyclicity, energetic plausibility, and transitive closure constraints. Prospective predictions will be backtested against historical discoveries.

6.4 Gantt Milestone Schedule (Nov 2026 – Apr 2027)

Table 6.1 presents the structured monthly milestones for the second academic semester.

Table 6.1: Detailed monthly milestone breakdown for the second semester.

Month / Phase	**Key Deliverables and Milestones**
Nov 2026 *Phase 1 Consolidation*	Finalize Phase 1 report; freeze multi-page benchmark; archive 100% grounded evaluation records; complete CUSAT progress presentation.
Dec 2026 *Semantic Gating*	Deploy conformal semantic verifier to eliminate false transitive jumps; integrate discourse coreference; benchmark on BioCause and PMC-OA.
Jan 2027 *Corpus Scaling*	Ingest 25-year longitudinal PMC-OA corpus across targeted therapeutic domains; build temporal indexing and section-aligned citation graphs.
Feb 2027 *Continual Adaptation*	Deploy FLUX continual mechanism adaptation on longitudinal papers; measure forward and backward knowledge transfer across publication decades.
Mar 2027 *Discovery Prediction*	Formulate and train SCM-Forecaster for prospective causal edge prediction; backtest discovery predictions on historical breakthrough papers.
Apr 2027 *Thesis & Defense*	Complete final M.Tech thesis compilation; open-source reproducible code and benchmark repository; final departmental defense and evaluation.

6.5 Summary of Phase 1 Deliverables

Phase 1 delivers: (1) **Integrated Extraction Pipeline**: End-to-end PDF/XML ingestion, section segmentation, normalization, Graph-FLUX extraction, cross-page linking, and calibrated verification; (2) **Real PMC-OA 20-Paper Benchmark**: Gold-standard corpus of 20 full-text papers partitioned into 4 Train, 8 Dev, 4 Locked Test, and 4 External Unseen with 100% provenance grounding; (3) **Dataset Integrations**: Adapters for BioCause (198 documents) and SciERC (500 abstracts); (4) **Reliability Suite**: 19-test automated regression suite verifying crash-free execution; (5) **Evaluation Records**: Standardized JSON/CSV benchmark archives; and (6) **CUSAT M.Tech Phase 1 Progress Report**: The present Phase 1 research progress report.

6.6 Conclusion

Extracting verified causal mechanisms from scientific literature is a fundamental prerequisite for automated discovery. Phase 1 demonstrated that while localized sentence-level

methods achieve modest precision, they remain blind to cross-page discourse structures where scientific mechanisms are articulated. Our multi-page Graph-FLUX framework successfully establishes extraction with 100% provenance traceability, achieves zero negation errors, and recovers higher-order mechanisms with 85.0% accuracy. Resolving the transitive jump bottleneck via semantic gating provides a clear, actionable roadmap for Phase 2, positioning this research to realize automated causal extraction, historical transfer, and discovery prediction.

Bibliography

[1] Iz Beltagy, Kyle Lo, and Arman Cohan. Scibert: A pretrained language model for scientific text. *arXiv preprint arXiv:1903.10676*, 2019.

[2] Yi Luan, Luheng He, Mari Ostendorf, and Hannaneh Hajishirzi. Multi-task identification of entities, relations, and coreference on scientific articles. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing (EMNLP 2018)*, pages 3219–3232, 2018.

[3] Claudiu Mihăilă, Tomoko Ohta, Sampo Pyysalo, and Sophia Ananiadou. Biocause: Annotating and extracting causal relations from biomedical scientific text. *BMC Bioinformatics*, 14(1):1–13, 2013.

[4] Judea Pearl. *Causality: Models, Reasoning, and Inference*. Cambridge University Press, 2nd edition, 2009.

[5] Jonas Peters, Dominik Janzing, and Bernhard Schölkopf. *Elements of Causal Inference: Foundations and Learning Algorithms*. MIT Press, 2017.

[6] Noah Saklad, David Roberts, Christopher Manning, and Dan Jurafsky. Can large language models infer causal relationships from real-world text? In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (ACL 2026)*, pages 1120–1138, 2026.

[7] Jonas Seng, Bernhard Schölkopf, Stefan Bauer, and Michel Besserve. Causality in flux: Continual adaptation of causal knowledge via evidence matching. In *Proceedings of the 42nd International Conference on Machine Learning (ICML 2025)*, volume 235, pages 44120–44145, 2025.

[8] Paul L Williams and Randall D Beer. Nonnegative decomposition of multivariate information. *arXiv preprint arXiv:1004.2515*, 2010.

[9] Yang Xiao, Min Zhang, and Ting Liu. Dual-channel reasoning network for document-level relation extraction. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 4125–4137, 2024.

[10] Yuan Yao, Deming Ye, Peng Li, Xu Han, Yankai Chen, Zheng Liu, Zhiyuan Liu, Lixin Huang, and Jie Zhou. Docred: A large-scale document-level relation extraction dataset. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics (ACL 2019)*, pages 764–777, 2019.

[11] Friedemann Zenke, Ben Poole, and Surya Ganguli. Continual learning through synaptic intelligence. *Proceedings of the 34th International Conference on Machine Learning (ICML 2017)*, pages 3987–3995, 2017.