












# Cello Lighting Inc.

2570 N. First Street, 2nd Floor San Jose, CA 95131, U.S.A Call us  
at 888-588-8849  
Mail us: [customer\\_service@cellolighting.com](mailto:customer_service@cellolighting.com)  
[www.CelloLighting.com](http://www.CelloLighting.com)

Specifications													
Picture	Item No.	Power	Base	LED Source	Beam Angle	Work Voltage	Dimming	CCT	CRI	Material	Lumen	Lamp Size (mm)	Certification
	PAR20	9W	E26	9*SMD2835	40°	110-130V	Dimmable	3000k 5000k	84.1Ra	PC+AL	800lm	80*63mm	CE RoHS UL
	BR40	20W	E26	36*SMD2835	120°	110-130V	Dimmable	3000k 5000k	82.4Ra	PC+AL	1800lm	153*120mm	CE RoHS
	BR30	15W	E26	28*SMD2835	120°	110-130V	Dimmable	3000k 5000k	82.4Ra	PC+AL	1350lm	134*95mm	CE RoHS UL
	PAR30	15W	E26	14*SMD2835	40°	110-130V	Dimmable	3000k 5000k	81.2Ra	PC+AL	1350lm	116*95mm	CE RoHS
	PAR38	20W	E26	18*SMD2835	40°	110-130V	Dimmable	3000k 5000k	81.2 /90 Ra	PC+AL	1800lm	132*120mm	CE RoHS UL
	A19	9W	E26	SMD2835	240°	110-130V	120V- Dimmable	5000k	82.6Ra	PC+AL	810lm	109*60mm	CE RoHS UL
	A19	17W	E26	SMD2835	180°	110-130V	Non- Dimmable	5000k	84.4Ra	PC+AL	1600lm	118*60mm	CE RoHS UL
	A21	23W	E26	SMD2835	240°	110-130V	Non- dimmable	3000K 5000K	85.2Ra	AL+PC	2123lm	132*70mm	CE
	E12	4.5W	E12	SMD2835	180°	110-130V	Non- dimmable	3000K 4000K	81.5Ra	320lm	97x37mm	PC+AL	CE