



Specification Details

Model NO.:	CL-A19-6W-DIM
Input Power	6W
Input Voltage:	120V
Luminous Flux:	450lm
Power Factor:	>0.9
Light Source:	Epistar
Driver:	Dimmable UL&cUL approved
Dust and Moistue:	IP45
Enviroment Temperature:	-20℃ to 40 ℃
Demensions(L*W):	105mm*60mm
Package method:	Factory standard/Customized
Beam angle	>230°
Base:	E26
CCT:	2700K-5700K
Lifespan	25000hours
Warranty:	3 years
Certification:	ETL/cETL/UL/cUL





Specification Details

Model NO.:	CL-A19-9W-DIM
Input Power	9W
Input Voltage:	120V
Luminous Flux:	800lm
Power Factor:	>0.9
Light Source:	Epistar
Driver:	Dimmable UL&cUL approved
Dust and Moistue:	IP45
Enviroment Temperature:	-20°C to 40 °C
Demensions(L*W):	105mm*60mm
Package method:	Factory standard/Customized
Beam angle	>230°
Base:	E26
CCT:	2700K-5700K
Lifespan	25000hours
Warranty:	3years
Certification:	ETL/cETL/UL/cUL/ES





Specification Details

Model NO.:	CL-A19-11W-DIM
Input Power	11W
Input Voltage:	120V
Luminous Flux:	1180lm
Power Factor:	>0.9
Light Source:	Epistar
Driver:	Dimmable UL&cUL approved
Dust and Moistue:	IP45
Enviroment Temperature:	-20℃ to 40 ℃
Demensions(L*W):	118mm*60mm
Package method:	Factory standard/Customized
Beam angle	>230°
Base:	E26
CCT:	2700K-5700K
Lifespan	25000hours
Warranty:	3years
Certification:	ETL/cETL/UL/cUL





Specification Details

Model NO.:	CL-A21-21W-DIM
Input Power	21W
Input Voltage:	120V
Luminous Flux:	2600lm
Power Factor:	>0.9
Light Source:	Epistar
Driver:	Dimmable UL&cUL approved
Dust and Moistue:	IP45
Enviroment Temperature:	-20℃ to 40 ℃
Demensions(L*W):	132mm*70mm
Package method:	Factory standard/Customized
Beam angle	>230°
Base:	E26
CCT:	2700K-5700K
Lifespan	25000hours
Warranty:	3 years
Certification:	ETL/cETL/UL/cUL





Specification Details

Model NO.:	CL-PAR20-7W-DIM
Input Power	7W
Input Voltage:	120V
Luminous Flux:	523lm
Power Factor:	>0.9
Light Source:	Epistar
Driver:	Dimmable UL&cUL approved
Dust and Moistue:	IP45
Enviroment Temperature:	-20°C to 40 °C
Demensions(L*W):	83mm*63mm
Package method:	Factory standard/Customized
Beam angle	40°
Base:	E26
CCT:	2700K-5700K
Lifespan	25000hours
Warranty:	5 years
Certification:	ETL/cETL/UL/cUL



ICES-005





Specification Details

Model NO.:	CL-B10-4W-DIM
Input Power	4W
Input Voltage:	85-265V
Luminous Flux:	400lm
CRI:	>90
Driver:	Dimmable UL&cUL approved
Dust and Moistue:	IP45
Enviroment Temperature:	-20℃ to 40 ℃
Demensions(L*W):	35*35*100mm
Package method:	Factory standard/Customized
Base:	Candelabra
CCT:	2700K-5700K
Lifespan	15000hours
Warranty:	3 years
Certification:	UL/cUL

