

21	WITH PAB Logo
12 JOB NUMBER	SSS/0005/26
21 COMPANY NAME	Jolibee
12 COMPANY ADDRESS	
12 ATTENTION	Juan Dela Cruz
INSTRUMENT NAME	Weighing Balance
BRAND	brand
MODEL	model
SERIAL	serial
DATE REC	2026-07-29
DATE CAL	2026-07-29
DATE DUE	2027-07-29
PROCEDURE NUMBER	SSS-CP-020
	ASSET NAME
ASSET 1	System Multimeter
ASSET 2	-
ASSET 3	-
ASSET 4	-
ASSET 5	-
ASSET 6	-
ASSET 7	-
ASSET 8	-
ASSET 9	-
ASSET 10	-
ASSET 11	-
ASSET 12	-
ASSET 13	-
ASSET 14	-
ASSET 15	-
ASSET 16	-

SERIAL NO
6305012(M044)

CERT NO
SSS/LAB/044/24

DUE DATE
2026-10-10

TRACEABILITY

company
brand
model
serial
ex at
ratio
OIC
SIGN

Jolibee
brand
model
serial
electrical and temperature

date rec
date cal
date due
type
range

2026-07-29
2026-07-29
2027-07-29
ANALOG
to x /div.

job no
temp
rh
inst
W/LOGO

SSS/0005/26

Weighing Balance

5A : A

JJP

STANDARD		SERIAL NO.	CERTIFICATE NO.	DUE DATE
THERMOHYGROMETER		0	0	0

lower	upper	rsln	read	unit of measure	uut decimal

0

1.0 AC CURRENT @ 60Hz:

decimal	APPLIED VALUE	EXPECTED VALUE		INDICATED VALUE	CORRECTION	CMC
	(A) (STD)	(A) (STD)		(A) (UUT)	(A)	
2		0.00	0	0	0	0.06
2		0.00	0	2	-2	0.06
2		0.00	0	4	-4	0.06
2		0.00	0	6	-6	0.06
2		0.00	0	8	-8	0.06
2		0.00	0	10	-10	0.06

SSS/0005/26

(This Certificate shall not be reproduced without the written approval of the laboratory)

Submitted By : **Jolibee**

Attention : Juan Dela Cruz
Instrument : Weighing Balance
Manufacturer : brand
Model : model
Serial Number : serial
Ambient Temperature : 23°C ± 2°C
Relative Humidity : CONTACT ADMIN
Date Calibrated : 2026-07-29
Recommended Due Date : 2027-07-29
Date Received : 2026-07-29

The Scientific Standards Services certifies that this instrument was calibrated under the environmental conditions above using reference standard traceable to SI Units as maintained by NIM (China) thru SCM (Hongkong), NM (Singapore) , NIST (USA), and NML ITDI (Philippines), NPL (UK) thru SONJU Engineering Services (Philippines).

Method of Calibration

The instrument was calibrated according to the established SSS Standard Calibration Procedure SSS-CP-C comparison to the range stated on the calibration data at the time of calibration.

Reference Standard(s) Used During Calibration

	Standard	Serial No.	Certificate No.	Date
1.		0	0	

Results of Calibration

The results of calibration are given on the attached calibration data. The estimated uncertainty of measurement in this calibration was determined in accordance with ISO Guide to the expression of uncertainty in measurement and is within 95% level of confidence.

#N/A

#N/A

litions stated
IC@A*STAR
ippines) and

120 by direct

le Date
0

it associated
ment (GUM)

SSS/0005/26

CALIBRATION DATA

Temperature : °C
Relative Humidity : % RH
Examined At : electrical and temperature
Range : to x /div.
Type : ANALOG
Ratio : : 5A

1.0 AC CURRENT @ 60Hz:

APPLIED VALUE (STD) (A)	EXPECTED VALUE (STD) ()	INDICATED VALUE (UUT) ()	CORRECTION ()	UNCERTAINTY OF MEASUREMENT (± A)	C
0.00	0.00	0	0	#DIV/0!	
0.00	0.00	2	-2	#DIV/0!	
0.00	0.00	4	-4	#DIV/0!	
0.00	0.00	6	-6	#DIV/0!	
0.00	0.00	8	-8	#DIV/0!	
0.00	0.00	10	-10	#DIV/0!	

REMARKS:

1. The user should determine the suitability of the instrument for its intended use.
2. Certain factors may cause the calibration item to drift out of calibration before the recommended expired.
3. The calibration results in this certificate refer to the date of calibration and should the instrument be damaged in anyway, or develop inconsistent readings, the results may not be valid and the uni recalibration.
4. A positive correction is to be added to the unit under test (UUT) reading and a negative correc subtracted to the UUT reading to give the true value.
5. The results of this certificate refers only to the instrument calibrated.




#N/A


#N/A

**OVERAGE
FACTOR**

(k)

#DIV/0!
#DIV/0!
#DIV/0!
#DIV/0!
#DIV/0!
#DIV/0!

interval has

modified or
t will require

tion is to be

UNCERTAINTY COMPUTATION

INSTRUMENT Weighing Balance
 PARAMETER DC CURRENT
 RANGE to x /div.
 PRIMARY INSTRUMENT 0
 PERSONEL ---
 DATE ---

TYPE A UNCERTAINTY	Uncert		Sens	Dist	Deg
--------------------	--------	--	------	------	-----

TYPE B UNCERTAINTY	Uncert		Sens	Dist	Deg
calibrator	1.20E-01	A	1	95%	45
read uut	0.00E+00	A	1	RECT	12.5

Results

Uncertainty Type	Combination	Uncertainty	Standard Uncertainty
Type A	RSS	0.00E+00	0.00E+00
Type B	RSS	1.20E-01	5.97E-02
Type AB	RSS	1.20E-01	5.97E-02

UC	5.97E-02			
U1	0.00E+00	V1	=	12.5

1.27E-05
0.00E+00
12.5

1.27E-05
0.00E+00

1.27E-05
0.00E+00

#DIV/0!

Remarks:

As per internal agreement, if the V eff falls below 11, k factor will be 2

In the event that the bmc (0.06A) is greater than the computed uncertainty, the bmc will be reported.

expanded uncertainty	±	#DIV/0! A
coverage factor (k)		#DIV/0!

SSS/0005/26

STD Uncert

Div	STD Uncert
2.01	5.97E-02
1.732	0.00E+00

interpolation	
0	0
	0.06
10 A	5
0	0.060000
10	5
0.6	0
	5
0.6	
0.12	
0.12	

UNCERTAINTY COMPUTATION

INSTRUMENT Weighing Balance
 PARAMETER DC CURRENT
 RANGE to x /div.
 PRIMARY INSTRUMENT 0
 PERSONEL ---
 DATE ---

TYPE A UNCERTAINTY	Uncert		Sens	Dist	Deg
--------------------	--------	--	------	------	-----

TYPE B UNCERTAINTY	Uncert		Sens	Dist	Deg
calibrator	1.20E-01	A	1	95%	45
read uut	0.00E+00	A	1	RECT	12.5

Results

Uncertainty Type	Combination	Uncertainty	Standard Uncertainty
Type A	RSS	0.00E+00	0.00E+00
Type B	RSS	1.20E-01	5.97E-02
Type AB	RSS	1.20E-01	5.97E-02

UC	5.97E-02			
U1	0.00E+00	V1	=	12.5

1.27E-05
0.00E+00
12.5

1.27E-05
0.00E+00

1.27E-05
0.00E+00

#DIV/0!

Remarks:

As per internal agreement, if the V eff falls below 11, k factor will be 2

In the event that the bmc (0.06A) is greater than the computed uncertainty, the bmc will be reported.

expanded uncertainty	±	#DIV/0! A
coverage factor (k)		#DIV/0!

UNCERTAINTY COMPUTATION

SSS/0005/26

Div STD Uncert

Div	STD Uncert
2.01	5.97E-02
1.732	0.00E+00

interpolation	
0	0
	0.06
10 A	5
0	0.060000
10	5
0.6	0
	5
0.6	
0.12	
0.12	

UNCERTAINTY COMPUTATION

INSTRUMENT Weighing Balance
 PARAMETER DC CURRENT
 RANGE to x /div.
 PRIMARY INSTRUMENT 0
 PERSONEL ---
 DATE ---

TYPE A UNCERTAINTY	Uncert		Sens	Dist	Deg
--------------------	--------	--	------	------	-----

TYPE B UNCERTAINTY	Uncert		Sens	Dist	Deg
calibrator	0.00E+00	A	1	95%	45
read uut	0.00E+00	A	1	RECT	12.5

Results

Uncertainty Type	Combination	Uncertainty	Standard Uncertainty
Type A	RSS	0.00E+00	0.00E+00
Type B	RSS	0.00E+00	0.00E+00
Type AB	RSS	0.00E+00	0.00E+00

UC	0.00E+00			
U1	0.00E+00	V1	=	12.5

0.00E+00
0.00E+00
12.5

0.00E+00
0.00E+00

0.00E+00
0.00E+00

#DIV/0!

Remarks:

As per internal agreement, if the V eff falls below 11, k factor will be 2

In the event that the bmc (0.06A) is greater than the computed uncertainty, the bmc will be reported.

expanded uncertainty	±	#DIV/0! A
coverage factor (k)		#DIV/0!

UNCERTAINTY COMPUTATION

SSS/0005/26

Div STD Uncert

Div	STD Uncert
2.01	0.00E+00
1.732	0.00E+00

interpolation	
0	0
	0.06
0 A	5
0	0.060000
0	5
0	0
	5
0	
0.00	
0	

UNCERTAINTY COMPUTATION

INSTRUMENT Weighing Balance
 PARAMETER DC CURRENT
 RANGE to x /div.
 PRIMARY INSTRUMENT 0
 PERSONEL ---
 DATE ---

TYPE A UNCERTAINTY	Uncert		Sens	Dist	Deg
--------------------	--------	--	------	------	-----

TYPE B UNCERTAINTY	Uncert		Sens	Dist	Deg
calibrator	0.00E+00	A	1	95%	45
read uut	0.00E+00	A	1	RECT	12.5

Results

Uncertainty Type	Combination	Uncertainty	Standard Uncertainty
Type A	RSS	0.00E+00	0.00E+00
Type B	RSS	0.00E+00	0.00E+00
Type AB	RSS	0.00E+00	0.00E+00

UC	0.00E+00			
U1	0.00E+00	V1	=	12.5

0.00E+00
0.00E+00
12.5

0.00E+00
0.00E+00

0.00E+00
0.00E+00

#DIV/0!

Remarks:

As per internal agreement, if the V eff falls below 11, k factor will be 2

In the event that the bmc (0.06A) is greater than the computed uncertainty, the bmc will be reported.

expanded uncertainty	±	#DIV/0! A
coverage factor (k)		#DIV/0!

UNCERTAINTY COMPUTATION

SSS/0005/26

Div STD Uncert

Div	STD Uncert
2.01	0.00E+00
1.732	0.00E+00

interpolation	
0	0
	0.06
0 A	5
0	0.060000
0	5
0	0
	5
0	
0.00	
0	

UNCERTAINTY COMPUTATION

INSTRUMENT Weighing Balance
 PARAMETER DC CURRENT
 RANGE to x /div.
 PRIMARY INSTRUMENT 0
 PERSONEL ---
 DATE ---

TYPE A UNCERTAINTY	Uncert		Sens	Dist	Deg
--------------------	--------	--	------	------	-----

TYPE B UNCERTAINTY	Uncert		Sens	Dist	Deg
calibrator	0.00E+00	A	1	95%	45
read uut	0.00E+00	A	1	RECT	12.5

Results

Uncertainty Type	Combination	Uncertainty	Standard Uncertainty
Type A	RSS	0.00E+00	0.00E+00
Type B	RSS	0.00E+00	0.00E+00
Type AB	RSS	0.00E+00	0.00E+00

UC	0.00E+00			
U1	0.00E+00	V1	=	12.5

0.00E+00
0.00E+00
12.5

0.00E+00
0.00E+00

0.00E+00
0.00E+00

#DIV/0!

Remarks:

As per internal agreement, if the V eff falls below 11, k factor will be 2

In the event that the bmc (0.06A) is greater than the computed uncertainty, the bmc will be reported.

expanded uncertainty	±	#DIV/0! A
coverage factor (k)		#DIV/0!

UNCERTAINTY COMPUTATION

SSS/0005/26

Div STD Uncert

Div	STD Uncert
2.01	0.00E+00
1.732	0.00E+00

interpolation	
0	0
	0.06
0 A	5
0	0.060000
0	5
0	0
	5
0	
0.00	
0	

UNCERTAINTY COMPUTATION

INSTRUMENT Weighing Balance
 PARAMETER DC CURRENT
 RANGE to x /div.
 PRIMARY INSTRUMENT 0
 PERSONEL ---
 DATE ---

TYPE A UNCERTAINTY	Uncert		Sens	Dist	Deg
--------------------	--------	--	------	------	-----

TYPE B UNCERTAINTY	Uncert		Sens	Dist	Deg
calibrator	0.00E+00	A	1	95%	45
read uut	0.00E+00	A	1	RECT	12.5

Results

Uncertainty Type	Combination	Uncertainty	Standard Uncertainty
Type A	RSS	0.00E+00	0.00E+00
Type B	RSS	0.00E+00	0.00E+00
Type AB	RSS	0.00E+00	0.00E+00

UC	0.00E+00			
U1	0.00E+00	V1	=	12.5

0.00E+00
0.00E+00
12.5

0.00E+00
0.00E+00

0.00E+00
0.00E+00

#DIV/0!

Remarks:

As per internal agreement, if the V eff falls below 11, k factor will be 2

In the event that the bmc (0.06A) is greater than the computed uncertainty, the bmc will be reported.

expanded uncertainty	±	#DIV/0! A
coverage factor (k)		#DIV/0!

UNCERTAINTY COMPUTATION

SSS/0005/26

Div STD Uncert

Div	STD Uncert
2.01	0.00E+00
1.732	0.00E+00

interpolation	
0	0
	0.06
0 A	5
0	0.060000
0	5
0	0
	5
0	
0.00	
0	

interpolation

1		2	
0	0	0	0
	0		0
0	5	0	5
0	0	0	0
0	5	0	5
0	0	0	0
	5		5
0		0	
0		0	

STD


		0.00
load	0	7 0.0000000
decimal	2	6 0.0000000
		0.00
load	0	7 0.0000000
decimal	2	6 0.0000000
		0.00
load	0	7 0.0000000
decimal	2	6 0.0000000
		0.00
load	0	7 0.0000000
decimal	2	6 0.0000000
		0.00
load	0	7 0.0000000
decimal	2	6 0.0000000

#N/A

converted value

load	0	7
decimal	2	6
load	0	7
decimal	2	6
load	0	7
decimal	2	6
load	0	7
decimal	2	6
load	0	7
decimal	2	6

ALP	ARSEMAR L. POBLETE
MGJ	MARIO G. JULIAN
RMP	ROWELL M. POBLETE
COT	CELSO O. TAMAYO JR.
SPE	SUNNY P. EVANGELISTA
FSO	FREDIRICK S. ORTEGA
HAS	HERMINIO A. SANTOS III
RCL	RAMEL C. LUNA



UUT

0.00
0.0000000
0.000000

		0
load	0	7 0.0000000
decimal	0	6 0.000000

0.00
0.0000000
0.000000

		2
load	2	7 20
decimal	0	6 2

0.00
0.0000000
0.000000

		4
load	4	7 40
decimal	0	6 4

0.00
0.0000000
0.000000

		6
load	6	7 6.0000000
decimal	0	6 6.000000

0.00
0.0000000
0.000000

		8
load	8	7 80
decimal	0	6 8

0.00
0.0000000
0.000000

		10
load	10	7 100
decimal	0	6 10



correction

		0
load	0	7 0.0000000
decimal	0	6 0.000000

		-2
load	-2	7 -20
decimal	0	6 -2

		-4
load	-4	7 -40
decimal	0	6 -4

		-6
load	-6	7 -6.0000000
decimal	0	6 -6.000000

		-8
load	-8	7 -80
decimal	0	6 -8

		-10
load	-10	7 -100
decimal	0	6 -10