

N-Channel Enhancement Mode MOSFET

GENERAL DESCRIPTION


The PW2320 uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 2.5V. This device is suitable for use as a Battery protection or in other Switching application..

FEATURES

$V_{DS} = 20V$ $I_D = 8A$

$R_{DS(ON)} < 12m\Omega$ @ $V_{GS}=4.5V$

Available in a 3-Pin SOT23-3 Package



Absolute Maximum Ratings (TA=25°C unless otherwise noted)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	20	V
Gate-Source Voltage	V_{GS}	± 12	V
Continuous Drain Current	I_D	8	A
Continuous Drain Current	$I_D@T_A=100^\circ C$	4.5	A
Pulsed Drain Current	I_{DM}	75	A
Maximum Power Dissipation	$P_D@T_A=25^\circ C$	12	W
Storage Temperature Range	T_{STG}	-55 To 175	°C
Operating Junction Temperature Range	T_J	-55 To 175	°C
Single pulse avalanche energy	E_{AS}	1	mJ
Thermal Resistance Junction-Case	$R_{\theta JC}$	3.8	°C/W



ELECTRICAL CHARACTERISTICS

(TA = 25°C, unless otherwise noted.)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV _{DSS}	VGS=0V ID=250μA	20	22		V
Zero Gate Voltage Drain Current	I _{DSS}	VDS=20V, VGS=0V			1	μA
Gate-Body Leakage Current	I _{GSS}	VGS=±12V, VDS=0V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	VDS=VGS, ID=250μA	0.5	0.65	1.2	V
Drain-Source On-State Resistance	R _{D(S)ON}	VGS=4.5V, ID=6A		8.5	12	mΩ
Drain-Source On-State Resistance	R _{D(S)ON}	VGS=2.5V, ID=3A		10	15	mΩ
Forward Transconductance	g _{FS}	VDS=5V, ID=20A	10			S
Total Gate Charge	Q _g	VGS=10V, VDS=10V, ID=20A		15		nC
Gate-Source Charge	Q _{gs}			1.8		nC
Gate-Drain Charge	Q _{gd}			2.8		nC
Turn-on Delay Time	t _{d(on)}	VGS=10V, VDS=10V RL=0.5Ω, RGEN=3Ω		4.5		nS
Turn-on Rise Time	t _r			9.2		nS
Turn-Off Delay Time	t _{d(off)}			18.7		nS
Turn-Off Fall Time	t _f			3.3		nS
Diode Forward Voltage (Note 3)	V _{SD}	VGS=0V, IS=25A			1.2	V
Diode Forward Current (Note 2)	I _S				25	A
Reverse Recovery Time	t _{rr}	T _J = 25°C, IF = 20A di/dt = 100A/μs (Note 3)		18		nS
Reverse Recovery Charge	Q _{rr}			9.5		nC
Input Capacitance	C _{lss}	VDS=10V, VGS=0V, F=1.0MHz		625		PF
Output Capacitance	C _{oss}			162		PF
Reverse Transfer Capacitance	C _{rss}			105		PF

Note :

- 1、 Repetitive Rating: Pulse width limited by maximum junction temperature.
- 2、 Surface Mounted on FR4 Board, t ≤ 10 sec.
- 3、 Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
- 4、 Guaranteed by design, not subject to production

Typical Characteristics




Fig.1 Typical Output Characteristics




Fig.2 Transfer Characteristics




Fig.3 RDSON-Current




Fig.4 RDSON- Junction Temperature




Fig.5 Gate-Charge










Fig.6 Source-Drain Diode Forward


Fig.7 Capacitance vs Vds

Fig.8 Safe Operating Area

Fig.9 Power De-rating

Fig.10 Current De rating

Fig.11 Normalized Maximum Transient Thermal Impedance

PACKAGE DESCRIPTION

SOT23-3L



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E1	1.500	1.700	0.059	0.067
E	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

Notes

1. All dimensions are in millimeters.
2. Tolerance $\pm 0.10\text{mm}$ (4 mil) unless otherwise specified
3. Package body sizes exclude mold flash and gate burrs. Mold flash at the non-lead sides should be less than 5 mils.
4. Dimension L is measured in gauge plane.
5. Controlling dimension is millimeter, converted inch dimensions are not necessarily exact.



IMPORTANT NOTICE

Wuxi PWChip Semi Technology CO., LTD (PW) reserves the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any products or services. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

PW assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using PW components.

PW products are not authorized for use in safety-critical applications (such as life support devices or systems) where a failure of the PW product would reasonably be expected to affect the safety or effectiveness of that devices or systems.

The information included herein is believed to be accurate and reliable. However, PW assumes no responsibility for its use; nor for any infringement of patents or other rights of third parties which may result from its use.