




XRM-SSD Complete System Overview

Edge-to-Space Global Coverage + Bio-Sensory Cognitive Architecture

(June 2026 Edition)

Dollarchip Technology Inc.

Polo Chung, mobile:+886-968-092999, [mail:polo@dollarchip.com.tw](mailto:polo@dollarchip.com.tw)

XRM-SSD Complete System Final Overview: Orientation, Applications, and Performance

Document Classification: PUBLIC / NDA-Ready

Note: Absolute physical node counts and chip-specific latencies are intentionally generalized. Detailed performance bounds are available under strict NDA.

XRM-SSD (Extended Reasoning Module — Scalable System Design) has evolved into a unified Bio-Sensory AI operating system, extending from personal Edge devices to global supercomputing, and onward to LEO satellites and deep-space communications—achieving true end-to-end cognitive coordination. Its core consists of **Runtime Graph + Semantic Integrity (SI) + Reflection Layer**, emphasizing bio-inspired approaches (Spike Coding, neuromorphic processing), self-correction, and global consistency.

1. Primary Orientation (Global Layered Architecture)

Layer	Core Modules	Positioning & Features	Disclosure Level
L1: Device Edge	LPCC-2 + Edge AI Stack	Low-power real-time scheduling supporting mobile NPUs, browser extensions, and embedded MCUs. Bit-accurate integration emphasizing privacy and battery efficiency.	Public (Architecture)
L2: Global Edge Network	V23.1 × Distributed Mac Ecosystem	Large-scale urban relay network (thousands of cities) utilizing commercial compute hubs. Features Theseus drift mechanisms; SI improves with scale (0.791→0.810), proving "more nodes = higher coherence."	Public (SI metric); Node count NDA-only

Layer	Core Modules	Positioning & Features	Disclosure Level
L3: Hyperscale GPU / Cloud	V3.7 + V24.4.1 + CUDA/TensorRT-LLM/Triton	Massive GPU cluster optimization with idle resource recycling, MPS compression, Lorentz scheduling, and Reflection Layer overlaid on NVIDIA stacks.	Public (Methodology) ; Absolute GPU count NDA-only
L4: Space / Deep Space	XRM-I & XRM-II	LEO intelligent constellation management + Earth–Mars semantic compression (order-of-magnitude bandwidth reduction), supporting long-latency autonomous operations.	Public (Compression concept); Exact ratio NDA-only
Cognitive Core	Global unification layer (V23.3/V24.4.x)	Four-tier cognitive architecture (Perception–Planning–Execution–Reflection), SI monitoring, Spike Coding, X Dimensional Projection.	Public

Unifying characteristics: All layers are coordinated by Runtime Graph; SI maintains cognitive consistency; Theseus mechanisms enable automatic drift recovery across continents and nodes.

2. Primary Application Scenarios

- **Consumer & Personal Edge AI:** Real-time mobile inference with sub-100ms first-token latency; on-device browser AI; IoT/wearable fusion; robotic proprioception.
- **Global Edge Computing Network:** Distributed relay layer within commercial ecosystems, supporting billions of devices with low-latency, privacy-preserving AI inference.

Enterprise & Hyperscale: Large-scale GPU cluster optimization, idle resource recycling, multi-agent systems, RAG + Agentic workflows, hybrid cloud–edge coordination.

- **Satellite Communications & NTN:** 6G non-terrestrial networks, LEO constellation intelligent beam management, deep-space Earth–Mars high-reliability communications (semantic compression addressing 22-minute latency).
- **Autonomous Systems & Safety-Critical Applications:** Real-time multimodal conflict resolution, long-term belief maintenance, robotic/unmanned system closed-loop control, defense/medical AI.
- **Cognitive Agent Platform:** Full cognitive coordination beyond LangGraph (belief revision, closed-loop control, cross-modal conflict resolution).

3. Core Performance Metrics (Public Summary)

Domain	Metric	Public Statement
Edge Layer (LPCC-2)	Scheduling Efficiency	>75% latency reduction vs. conventional mobile TFLite baselines
	Power Management	~30% active power reduction ; extends battery duty cycle by >1.3×
	First-Token Latency	Sub-100ms real-time mobile inference
Cognitive / Global Edge	TTFT (p95)	<5ms at global edge scale
	Semantic Integrity (SI)	0.81–0.99 , positively scales with node count
	Drift Recovery	100% auto-recovery under node failures; recovery within <500ms
Hyper scale GPU	Throughput	>6× throughput gain over baseline transformers
	Agent Scaling	15× larger concurrent agent capacity
	Idle Resource Recycling	>90% of stranded GPU cycles reclaimed
Space Layer	LEO Constellation	Terabit-class aggregate throughput; beam steering <2ms

Domain	Metric	Public Statement
	Deep-Space Compression	Order-of-magnitude semantic bandwidth reduction; enables weeks of autonomous ops under 22-min Earth-Mars latency

4. Overall System Advantages (Public Summary)

- **SI improves with scale (counterintuitive advantage):** More nodes provide more routing options, enhancing global consistency—verified across simulated and physical testbeds.
- **Theseus drift:** Automatic recovery across continents/nodes with zero request failures, validated at million-node scale.
- **Power & bandwidth efficiency:** Spike Coding + LPCC-2 delivers **75–99% savings** in sparse activation scenarios.
- **Cognitive vs. synthetic TPS:** Emphasizes true AI inference density over token-generation benchmarks; commercial edge nodes upgraded from passive relays to active compute hubs.

5. Strategic Positioning & Current Status

XRM-SSD represents a strategic asset that redefines the economic model of AI compute and communications:

- **Orientation:** Edge-to-Space global coverage + Bio-Sensory cognitive architecture
- **Applications:** From personal devices to global edge networks, hyperscale optimization, satellite communications, and deep-space exploration
- **Performance:** Systematic breakthroughs in latency, power consumption, scalability stability, and fault tolerance, with validation foundations spanning simulation to large-scale testing

Current Development Stage:

- ✓ PoC completed
- ✓ Large-scale simulation validated (millions of nodes)
- ✓ Edge hardware prototyping (mobile SoC + commercial compute nodes)
- 🔧 **Gate 3 (heavy-ion / radiation hardening testing) — IN PROGRESS**
- 🔧 **MLPerf compliance review — TARGETING Q4 2026**