

Full Project Code Export

Project folder: bkc-store

Generated on: 2026-07-18 13:30:52

Total files included: 47

Note

- This PDF contains readable source/configuration files from the project.
- Large generated folders such as node_modules, .git, dist, build, and .next are skipped.
- .env files are skipped to avoid leaking secrets such as API keys and passwords.

File Index

1. .gitignore
2. AGENTS.md
3. CLAUDE.md
4. eslint.config.mjs
5. jsconfig.json
6. next.config.mjs
7. package.json
8. postcss.config.mjs
9. README.md
10. sanity.cli.js
11. sanity.config.js
12. src\actions\telegram.js
13. src\app\api\razorpay\route.js
14. src\app\collections\[slug]\page.js
15. src\app\contact\page.js
16. src\app\globals.css
17. src\app\layout.js
18. src\app\page.js
19. src\app\privacy\page.js
20. src\app\product\[slug]\page.js
21. src\app\product\[slug]\ProductClientUI.js
22. src\app\refund-policy\page.js
23. src\app\request\page.js
24. src\app\search\page.js
25. src\app\search\SearchClientUI.js
26. src\app\shipping\page.js
27. src\app\studio\[[...tool]]\page.jsx
28. src\app\success\page.js
29. src\app\terms\page.js
30. src\app\track\page.js
31. src\components\home\CollectionRow.js
32. src\components\layout\Footer.js
33. src\components\layout\Navbar.js
34. src\components\product\BuyDrawer.js
35. src\components\shared\InstaBrowserWarning.js
36. src\components\shared\ProductCard.js
37. src\lib\supabase.js
38. src\sanity\env.js
39. src\sanity\lib\client.js
40. src\sanity\lib\image.js
41. src\sanity\lib\live.js
42. src\sanity\lib\sanity.js
43. src\sanity\schemaTypes\collection.js
44. src\sanity\schemaTypes\index.js
45. src\sanity\schemaTypes\product.js
46. src\sanity\structure.js
47. tailwind.config.js

FILE: .gitignore

```
1 | # See https://help.github.com/articles/ignoring-files/ for more about ignoring files.
2 |
3 | # dependencies
4 | /node_modules
5 | /.pnp
6 | .pnp.*
7 | .yarn/*
8 | !.yarn/patches
9 | !.yarn/plugins
10 | !.yarn/releases
11 | !.yarn/versions
12 |
13 | # testing
14 | /coverage
15 |
16 | # next.js
17 | /.next/
18 | /out/
19 |
20 | # production
21 | /build
22 |
23 | # misc
24 | .DS_Store
25 | *.pem
26 |
27 | # debug
28 | npm-debug.log*
29 | yarn-debug.log*
30 | yarn-error.log*
31 | .pnpm-debug.log*
32 |
33 | # env files (can opt-in for committing if needed)
34 | .env*
35 |
36 | # vercel
37 | .vercel
38 |
39 | # typescript
40 | *.tsbuildinfo
41 | next-env.d.ts
```

FILE: AGENTS.md

```
1 | <!-- BEGIN:nextjs-agent-rules -->
2 | # This is NOT the Next.js you know
3 |
4 | This version has breaking changes – APIs, conventions, and file structure may all differ from your training data. R
  | ead the relevant guide in `node_modules/next/dist/docs/` before writing any code. Heed deprecation notices.
5 | <!-- END:nextjs-agent-rules -->
```


FILE: eslint.config.mjs

```
1 | import { defineConfig, globalIgnores } from "eslint/config";
2 | import nextVitals from "eslint-config-next/core-web-vitals";
3 |
4 | const eslintConfig = defineConfig([
5 |   ...nextVitals,
6 |   // Override default ignores of eslint-config-next.
7 |   globalIgnores([
8 |     // Default ignores of eslint-config-next:
9 |     ".next/**",
10 |    "out/**",
11 |    "build/**",
12 |    "next-env.d.ts",
13 |   ]),
14 | ]);
15 |
16 | export default eslintConfig;
```

FILE: jsconfig.json

```
1 | {  
2 |   "compilerOptions": {  
3 |     "paths": {  
4 |       "@/*": [".src/*"]  
5 |     }  
6 |   }  
7 | }
```

FILE: next.config.mjs

```
1 | /** @type {import('next').NextConfig} */
2 | const nextConfig = {
3 |   /* config options here */
4 | };
5 |
6 | export default nextConfig;
```

FILE: package.json

```
1 | {
2 |   "name": "bkc-store",
3 |   "version": "0.1.0",
4 |   "private": true,
5 |   "scripts": {
6 |     "dev": "next dev",
7 |     "build": "next build",
8 |     "start": "next start",
9 |     "lint": "eslint"
10 |   },
11 |   "dependencies": {
12 |     "@sanity/client": "^7.23.1",
13 |     "@sanity/image-url": "^2.1.1",
14 |     "@sanity/vision": "^5.31.1",
15 |     "@supabase/supabase-js": "^2.110.7",
16 |     "framer-motion": "^12.42.2",
17 |     "lucide-react": "^1.24.0",
18 |     "next": "16.2.10",
19 |     "next-sanity": "^13.1.1",
20 |     "razorpay": "^2.9.8",
21 |     "react": "19.2.4",
22 |     "react-dom": "19.2.4",
23 |     "react-medium-image-zoom": "^5.4.8",
24 |     "sanity": "^5.31.1",
25 |     "styled-components": "^6.4.3"
26 |   },
27 |   "devDependencies": {
28 |     "@tailwindcss/postcss": "^4",
29 |     "eslint": "^9",
30 |     "eslint-config-next": "16.2.10",
31 |     "tailwindcss": "^4"
32 |   }
33 | }
```

FILE: postcss.config.mjs

```
1 | const config = {  
2 |   plugins: {  
3 |     "@tailwindcss/postcss": {},  
4 |   },  
5 | };  
6 |  
7 | export default config;
```

FILE: README.md

```
1 | This is a [Next.js](https://nextjs.org) project bootstrapped with [create-next-app](https://github.com/vercel/next.js/tree/canary/packages/create-next-app).
2 |
3 | ## Getting Started
4 |
5 | First, run the development server:
6 |
7 | ```bash
8 | npm run dev
9 | # or
10 | yarn dev
11 | # or
12 | pnpm dev
13 | # or
14 | bun dev
15 | ```
16 |
17 | Open [http://localhost:3000](http://localhost:3000) with your browser to see the result.
18 |
19 | You can start editing the page by modifying app/page.js. The page auto-updates as you edit the file.
20 |
21 | This project uses [next/font](https://nextjs.org/docs/app/building-your-application/optimizing/fonts) to automatically optimize and load [Geist](https://vercel.com/font), a new font family for Vercel.
22 |
23 | ## Learn More
24 |
25 | To learn more about Next.js, take a look at the following resources:
26 |
27 | - [Next.js Documentation](https://nextjs.org/docs) - learn about Next.js features and API.
28 | - [Learn Next.js](https://nextjs.org/learn) - an interactive Next.js tutorial.
29 |
30 | You can check out [the Next.js GitHub repository](https://github.com/vercel/next.js) - your feedback and contributions are welcome!
31 |
32 | ## Deploy on Vercel
33 |
34 | The easiest way to deploy your Next.js app is to use the [Vercel Platform](https://vercel.com/new?utm_medium=default-template&filter=next.js&utm_source=create-next-app&utm_campaign=create-next-app-readme) from the creators of Next.js.
35 |
36 | Check out our [Next.js deployment documentation](https://nextjs.org/docs/app/building-your-application/deploying) for more details.
```

FILE: sanity.cli.js

```
1 | /**
2 |  * This configuration file lets you run `$ sanity [command]` in this folder
3 |  * Go to https://www.sanity.io/docs/cli to learn more.
4 |  */
5 | import { defineCliConfig } from 'sanity/cli'
6 |
7 | const projectId = process.env.NEXT_PUBLIC_SANITY_PROJECT_ID
8 | const dataset = process.env.NEXT_PUBLIC_SANITY_DATASET
9 |
10 | export default defineCliConfig({ api: { projectId, dataset } })
```

FILE: sanity.config.js

```
1 | 'use client'
2 |
3 | /**
4 |  * This configuration is used to for the Sanity Studio that's mounted on the ``src\app\studio\[...tool]\page.jsx`
5 |  */
6 |
7 | import {visionTool} from '@sanity/vision'
8 | import {defineConfig} from 'sanity'
9 | import {structureTool} from 'sanity/structure'
10 |
11 | // Go to https://www.sanity.io/docs/api-versioning to learn how API versioning works
12 | import {apiVersion, dataset, projectId} from './src/sanity/env'
13 | import {schema} from './src/sanity/schemaTypes'
14 | import {structure} from './src/sanity/structure'
15 |
16 | export default defineConfig({
17 |   basePath: '/studio',
18 |   projectId,
19 |   dataset,
20 |   // Add and edit the content schema in the './sanity/schemaTypes' folder
21 |   schema,
22 |   plugins: [
23 |     structureTool({structure}),
24 |     // Vision is for querying with GROQ from inside the Studio
25 |     // https://www.sanity.io/docs/the-vision-plugin
26 |     visionTool({defaultApiVersion: apiVersion}),
27 |   ],
28 | })
```

FILE: srclactions\telegram.js

```
1 | "use server"
2 |
3 | export async function sendOrderAlert(order) {
4 |   const token = process.env.TELEGRAM_BOT_TOKEN
5 |   const chatId = process.env.TELEGRAM_CHAT_ID
6 |
7 |   if (!token || !chatId) return
8 |
9 |   // Format a beautiful receipt for your phone
10 |   const message = `
11 |   ■ <b>NEW ORDER RECEIVED!</b> ■
12 |
13 |   ■ <b>Product:</b> ${order.product_name}
14 |   ■ <b>Payment:</b> ${order.payment_mode === 'prepaid' ? '■ ONLINE PREPAID' : '■ CASH ON DELIVERY'}
15 |   ■ <b>Amount:</b> ■${order.total_amount}
16 |
17 |   ■ <b>Customer:</b> ${order.customer_name}
18 |   ■ <b>Phone:</b> ${order.customer_phone}
19 |   ■ <b>Address:</b>
20 |   ${order.delivery_address}
21 |   ${order.city}, ${order.state} - ${order.pincodes}
22 |
23 |   ■ <b>Order ID:</b> ${order.order_id}
24 |   `
25 |
26 |   try {
27 |     await fetch(`https://api.telegram.org/bot${token}/sendMessage`, {
28 |       method: 'POST',
29 |       headers: { 'Content-Type': 'application/json' },
30 |       body: JSON.stringify({
31 |         chat_id: chatId,
32 |         text: message,
33 |         parse_mode: 'HTML'
34 |       })
35 |     })
36 |   } catch (error) {
37 |     console.error("Telegram error:", error)
38 |   }
39 | }
40 |
41 | export async function sendRequestAlert(request) {
42 |   const token = process.env.TELEGRAM_BOT_TOKEN
43 |   const chatId = process.env.TELEGRAM_CHAT_ID
44 |
45 |   if (!token || !chatId) return
46 |
47 |   const message = `
48 |   ■ <b>NEW PRODUCT REQUEST!</b>
49 |
50 |   ■ <b>Looking for:</b>
51 |   ${request.item_query}
52 |
53 |   ■ <b>Contact:</b> ${request.contact_info}
54 |   `
55 |
56 |   try {
57 |     await fetch(`https://api.telegram.org/bot${token}/sendMessage`, {
58 |       method: 'POST',
59 |       headers: { 'Content-Type': 'application/json' },
60 |       body: JSON.stringify({
61 |         chat_id: chatId,
62 |         text: message,
63 |         parse_mode: 'HTML'
64 |       })
65 |     })
66 |   } catch (error) {
67 |     console.error("Telegram error:", error)
68 |   }
69 | }
```

FILE: src\app\api\razorpay\route.js

```
1 | import { NextResponse } from "next/server";
2 | import Razorpay from "razorpay";
3 | import { client } from '@sanity/lib/client';
4 |
5 | const razorpay = new Razorpay({
6 |   key_id: process.env.NEXT_PUBLIC_RAZORPAY_KEY_ID,
7 |   key_secret: process.env.RAZORPAY_KEY_SECRET,
8 | });
9 |
10 | export async function POST(request) {
11 |   try {
12 |     const { slug } = await request.json();
13 |
14 |     // 1. SECURE FETCH: Look up the real price in Sanity! Never trust the frontend.
15 |     const product = await client.fetch(`*[_type == "product" && slug.current == $slug][0]`, { slug });
16 |
17 |     if (!product) {
18 |       return NextResponse.json({ error: "Product not found" }, { status: 404 });
19 |     }
20 |
21 |     const realPrice = product.prepaidPrice;
22 |
23 |     // 2. Generate Razorpay order using the REAL price
24 |     const options = {
25 |       amount: realPrice * 100, // Amount in paise
26 |       currency: "INR",
27 |       receipt: "rcpt_" + Math.random().toString(36).substring(7),
28 |     };
29 |
30 |     const order = await razorpay.orders.create(options);
31 |     return NextResponse.json(order);
32 |   } catch (error) {
33 |     console.error("Razorpay Error:", error);
34 |     return NextResponse.json({ error: "Something went wrong" }, { status: 500 });
35 |   }
36 | }
```

FILE: src\app\collections\[slug]\page.js

```
1 | import { client } from '@sanity/lib/client'
2 | import { urlFor } from '@sanity/lib/image'
3 | import ProductCard from '@components/shared/ProductCard'
4 | import Link from 'next/link'
5 | import { ChevronLeft } from 'lucide-react'
6 |
7 | export const revalidate = 10
8 |
9 | export default async function CollectionPage({ params }) {
10 |   const { slug } = await params
11 |
12 |   // 1. Fetch the Collection details
13 |   const collectionQuery = `[_type == "collection" && slug.current == $slug][0]`
14 |   const collection = await client.fetch(collectionQuery, { slug })
15 |
16 |   if (!collection) {
17 |     return <div className="text-center py-20 font-bold text-xl">Collection not found</div>
18 |   }
19 |
20 |   // 2. FIXED QUERY: Fetch all active products that reference this Collection
21 |   const productsQuery = `[_type == "product" && isActive == true && references($collectionId)] | order(_createdAt desc)`
22 |   const rawProducts = await client.fetch(productsQuery, { collectionId: collection._id })
23 |
24 |   const products = rawProducts.map(p => ({
25 |     slug: p.slug?.current || '',
26 |     title: p.title || 'Untitled',
27 |     prepaidPrice: p.prepaidPrice || 0,
28 |     codPrice: p.codPrice || 0,
29 |     isCodAvailable: p.isCodAvailable || false,
30 |     discountBadge: p.discountBadge || null,
31 |     imageUrl: p.gallery?.length > 0 ? urlFor(p.gallery[0]).url() : ''
32 |   }))
33 |
34 |   return (
35 |     <div className="min-h-screen bg-surface px-4 md:px-8 py-6">
36 |
37 |       {/* Back Button & Title */}
38 |       <div className="mb-8">
39 |         <Link href="/" className="inline-flex items-center gap-1 text-sm font-bold text-secondary hover:text-primary transition-colors mb-6">
40 |           <ChevronLeft size={18} />
41 |           Back to Home
42 |         </Link>
43 |         <h1 className="text-3xl font-black tracking-tight text-primary">
44 |           {collection.title}
45 |         </h1>
46 |         {collection.shortDescription && (
47 |           <p className="text-sm font-medium text-secondary mt-2">
48 |             {collection.shortDescription}
49 |           </p>
50 |         )}
51 |       </div>
52 |
53 |       {/* Product Grid */}
54 |       {products.length > 0 ? (
55 |         <div className="grid grid-cols-2 md:grid-cols-3 lg:grid-cols-4 gap-x-3 md:gap-x-6 gap-y-6 md:gap-y-10 pb-16">
56 |           {products.map((product) => (
57 |             <ProductCard key={product.slug} product={product} />
58 |           ))}
59 |         </div>
60 |       ) : (
61 |         <div className="py-20 text-center bg-[#F3F4F6] rounded-3xl border border-border">
62 |           <h3 className="text-lg font-bold text-primary mb-2">No products yet!</h3>
63 |           <p className="text-sm text-secondary font-medium">
64 |             We are curating new items for this collection. Check back soon.
65 |           </p>
66 |         </div>
67 |       )}
68 |     </div>
69 |   )
70 | }
71 | }
```

FILE: src\app\contact\page.js

```
1 | import Link from 'next/link'
2 | import { ChevronLeft, Mail, MessageCircle } from 'lucide-react'
3 |
4 | export default function ContactPage() {
5 |   return (
6 |     <div className="px-5 py-8 max-w-2xl mx-auto min-h-screen">
7 |
8 |       <Link href="/" className="inline-flex items-center gap-1 text-sm font-bold text-secondary hover:text-primary
9 | transition-colors mb-8">
10 |         <ChevronLeft size={18} />
11 |         Back to store
12 |       </Link>
13 |
14 |       <h1 className="text-3xl font-black tracking-tight mb-2">Get in touch.</h1>
15 |       <p className="text-sm text-secondary font-medium mb-10">
16 |         Have a question about your order or want to suggest a product? We are here to help.
17 |       </p>
18 |
19 |       <div className="flex flex-col gap-4">
20 |
21 |         {/* Email Support */}
22 |         <a
23 |           href="mailto:support@bigkidfinds.online"
24 |           className="flex items-center p-5 bg-[#F3F4F6] rounded-3xl border border-border hover:border-primary trans
25 | ition-colors group"
26 |         >
27 |           <div className="h-12 w-12 bg-surface rounded-full flex items-center justify-center text-primary shrink-0
28 | shadow-sm group-hover:scale-110 transition-transform">
29 |             <Mail size={20} />
30 |           </div>
31 |           <div className="ml-4">
32 |             <h3 className="text-base font-bold text-primary">Email Support</h3>
33 |             <p className="text-sm font-medium text-secondary">support@bigkidfinds.online</p>
34 |           </div>
35 |         </a>
36 |
37 |         {/* Store Instagram */}
38 |         <a
39 |           href="https://instagram.com/bkc.finds"
40 |           target="_blank"
41 |           rel="noopener noreferrer"
42 |           className="flex items-center p-5 bg-[#F3F4F6] rounded-3xl border border-border hover:border-primary trans
43 | ition-colors group"
44 |         >
45 |           <div className="h-12 w-12 bg-surface rounded-full flex items-center justify-center text-primary shrink-0
46 | shadow-sm group-hover:scale-110 transition-transform">
47 |             {/* Native SVG for Instagram to avoid library errors */}
48 |             <svg xmlns="http://www.w3.org/2000/svg" width="20" height="20" viewBox="0 0 24 24" fill="none" stroke="
49 | currentColor" strokeWidth="2" strokeLinecap="round" strokeLinejoin="round"><rect width="20" height="20" x="2" y="2"
50 | rx="5" ry="5"/><path d="M16 11.37A4 4 0 1 1 12.63 8 4 4 0 0 1 16 11.37z"/><line x1="17.5" x2="17.51" y1="6.5" y2="
51 | 6.5"/></svg>
52 |           </div>
53 |           <div className="ml-4 flex-1">
54 |             <h3 className="text-base font-bold text-primary">Instagram</h3>
55 |             <p className="text-sm font-medium text-secondary">@bkc.finds</p>
56 |           </div>
57 |         </a>
58 |
59 |         {/* Business / Collab Instagram */}
60 |         <a
61 |           href="https://instagram.com/bkc.finds"
62 |           target="_blank"
63 |           rel="noopener noreferrer"
64 |           className="flex items-center p-5 bg-[#F3F4F6] rounded-3xl border border-border hover:border-primary trans
65 | ition-colors group"
66 |         >
67 |           <div className="h-12 w-12 bg-surface rounded-full flex items-center justify-center text-primary shrink-0
68 | shadow-sm group-hover:scale-110 transition-transform">
69 |             <MessageCircle size={20} />
70 |           </div>
71 |           <div className="ml-4 flex-1">
72 |             <h3 className="text-base font-bold text-primary">Business & Collabs</h3>
73 |             <p className="text-sm font-medium text-secondary">DM us for partnerships</p>
74 |           </div>
75 |         </a>
76 |
77 |       </div>
78 |
79 |       <p className="text-xs text-secondary/60 font-medium text-center mt-12">
```

FILE CONTINUED: src\applcontact\page.js

```
70 |         We typically reply within 24 hours.  
71 |     </p>  
72 | </div>  
73 | )  
74 | }
```

FILE: src\app\globals.css

```
1 | @import "tailwindcss";
2 |
3 | @theme {
4 |   --color-background: #FAFAFA;
5 |   --color-surface: #FFFFFF;
6 |   --color-primary: #111827;
7 |   --color-secondary: #4B5563;
8 |   --color-border: #E5E7EB;
9 |   --color-accent: #3B82F6;
10 | }
11 |
12 | body {
13 |   background-color: var(--color-background);
14 |   color: var(--color-primary);
15 |   overflow-x: hidden;
16 |   -webkit-tap-highlight-color: transparent;
17 | }
18 |
19 | /* Hide scrollbar for clean horizontal scrolling in collections */
20 | .hide-scrollbar::-webkit-scrollbar {
21 |   display: none;
22 | }
23 | .hide-scrollbar {
24 |   -ms-overflow-style: none;
25 |   scrollbar-width: none;
26 | }
```

FILE: src\app\layout.js

```
1 | import { Inter } from "next/font/google";
2 | import "../globals.css";
3 | import Navbar from "@components/layout/Navbar";
4 | import Footer from "@components/layout/Footer";
5 | import InstaBrowserWarning from "@components/shared/InstaBrowserWarning";
6 |
7 | const inter = Inter({ subsets: ["latin"] });
8 |
9 | export const metadata = {
10 |   title: "BigKidFinds | Premium Curated Finds",
11 |   description: "Curated aesthetic finds and impulse-worthy products.",
12 | };
13 |
14 | export const viewport = {
15 |   width: 'device-width',
16 |   initialScale: 1,
17 |   maximumScale: 1,
18 |   userScalable: false,
19 | };
20 |
21 | export default function RootLayout({ children }) {
22 |   return (
23 |     <html lang="en">
24 |       <body className={` ${inter.className} bg-surface text-primary antialiased min-h-screen flex flex-col`} >
25 |         <InstaBrowserWarning />
26 |         <Navbar />
27 |
28 |         { /* Changed max-w-md to max-w-7xl for full desktop support */ }
29 |         <main className="flex-1 w-full max-w-7xl mx-auto relative">
30 |           {children}
31 |         </main>
32 |
33 |         <Footer />
34 |       </body>
35 |     </html>
36 |   );
37 | }
```

FILE: src\app\page.js

```
1 | import { Search } from 'lucide-react'
2 | import Link from 'next/link'
3 | import CollectionRow from '@components/home/CollectionRow'
4 | import ProductCard from '@components/shared/ProductCard'
5 |
6 | // FIXED: Changed urlForImage to urlFor
7 | import { client } from '@sanity/lib/client'
8 | import { urlFor } from '@sanity/lib/image'
9 |
10 | export const revalidate = 10
11 |
12 | export default async function Home() {
13 |   const rawProducts = await client.fetch(`*[_type == "product" && isActive == true] | order(_createdAt desc)`)
14 |   const rawCollections = await client.fetch(`*[_type == "collection"]`)
15 |
16 |   const products = rawProducts.map(p => ({
17 |     slug: p.slug?.current || '',
18 |     title: p.title || 'Untitled',
19 |     prepaidPrice: p.prepaidPrice || 0,
20 |     codPrice: p.codPrice || 0,
21 |     isCodAvailable: p.isCodAvailable || false,
22 |     discountBadge: p.discountBadge || null,
23 |     // FIXED here too
24 |     imageUrl: p.gallery?.length > 0 ? urlFor(p.gallery[0]).url() : ''
25 |   }))
26 |
27 |   const collections = rawCollections.map(c => ({
28 |     slug: c.slug?.current || '',
29 |     title: c.title || 'Untitled',
30 |     // FIXED here too
31 |     imageUrl: c.image ? urlFor(c.image).url() : ''
32 |   }))
33 |
34 |   return (
35 |     <div className="pb-10 min-h-screen">
36 |       <div className="px-4 md:px-8 pt-6 pb-2">
37 |         <h1 className="text-3xl font-bold tracking-tight mb-2">
38 |           Things you didn't know you needed.
39 |         </h1>
40 |         <p className="text-sm text-secondary">Premium aesthetic finds, delivered.</p>
41 |       </div>
42 |
43 |       <div className="px-4 md:px-8 py-3">
44 |         <Link href="/search" className="flex items-center gap-3 w-full bg-[#F3F4F6] border border-border rounded-xl
45 | px-4 py-3 text-secondary transition-opacity hover:opacity-80">
46 |           <Search size={18} />
47 |           <span className="text-sm font-medium">Search for products...</span>
48 |         </Link>
49 |       </div>
50 |
51 |       {collections.length > 0 && <CollectionRow collections={collections} />}
52 |
53 |       <div className="px-4 md:px-8 pt-6 md:pt-10">
54 |         <h2 className="text-lg md:text-2xl font-bold tracking-tight mb-4 md:mb-6">Just Dropped</h2>
55 |
56 |         {products.length > 0 ? (
57 |           <div className="grid grid-cols-2 md:grid-cols-3 lg:grid-cols-4 gap-x-3 md:gap-x-6 gap-y-6 md:gap-y-10">
58 |             {products.map((product) => (
59 |               <ProductCard key={product.slug} product={product} />
60 |             ))}
61 |           </div>
62 |         ) : (
63 |           <div className="py-10 text-center text-secondary font-medium bg-[#F3F4F6] rounded-2xl mx-4">
64 |             No products found. Add your first product in Sanity Studio!
65 |           </div>
66 |         )}
67 |       </div>
68 |     )
69 |   }
```

```

1 | import Link from 'next/link'
2 | import { ChevronLeft } from 'lucide-react'
3 |
4 | export default function PrivacyPage() {
5 |   return (
6 |     <div className="px-5 py-10 max-w-3xl mx-auto min-h-screen">
7 |       <Link href="/" className="inline-flex items-center gap-1 text-sm font-bold text-secondary hover:text-primary
8 |         <ChevronLeft size={18} /> Back to store
9 |       </Link>
10 |
11 |       <p className="text-xs font-bold uppercase tracking-widest text-secondary mb-2">Your Data, Respected</p>
12 |       <h1 className="text-3xl font-black tracking-tight mb-6">Privacy Policy</h1>
13 |
14 |       <p className="text-base font-medium text-secondary leading-relaxed mb-10">
15 |         Your privacy is critically important to us. We believe in radical transparency and collect only the absolut
16 | e minimum data required to run our store and deliver your order. This policy explains what we collect and why.
17 |       </p>
18 |       <div className="prose prose-sm md:prose-base prose-neutral max-w-none text-primary/90">
19 |         <h3 className="text-lg font-bold text-primary mt-8 mb-3">1. What We Collect</h3>
20 |         <p className="font-medium mb-3">To successfully deliver your order, we collect the following essential info
21 | rmation at checkout:</p>
22 |         <ul className="font-medium list-disc pl-5 mb-6 space-y-2">
23 |           <li><strong>Contact Information:</strong> Your full name, email address, and mobile phone number.</li>
24 |           <li><strong>Delivery Information:</strong> Your full shipping address, including house number, street, ci
25 | ty, state, and PIN code.</li>
26 |         </ul>
27 |         <p className="font-medium mb-6">We do not collect, see, or store any of your payment information (like cred
28 | it card numbers or UPI details). All payments are handled securely by our payment partners.</p>
29 |
30 |         <h3 className="text-lg font-bold text-primary mt-8 mb-3">2. How We Use Your Data</h3>
31 |         <p className="font-medium mb-3">Your data has one purpose and one purpose only: to get your product to you.
32 |
33 |         <ul className="font-medium list-disc pl-5 mb-6 space-y-2">
34 |           <li><strong>Fulfillment:</strong> Your name, address, and phone number are shared securely and programmat
35 | ically with our network of trusted fulfillment partners and courier services (such as Delhivery, Ecom Express, Shad
36 | owfax, or Meesho-backed logistics) for the sole purpose of dispatching and delivering your package.</li>
37 |           <li><strong>Communications:</strong> Your email address is used to send you automated transactional email
38 | s: your order confirmation and shipping updates. We will never send you marketing spam.</li>
39 |           <li><strong>Support:</strong> If you contact us with a query, we will use your provided details to look u
40 | p your order and resolve your issue.</li>
41 |         </ul>
42 |
43 |         <h3 className="text-lg font-bold text-primary mt-8 mb-3">3. What We Will NEVER Do</h3>
44 |         <ul className="font-medium list-disc pl-5 mb-6 space-y-2">
45 |           <li>We will never sell your data to third-party marketers.</li>
46 |           <li>We will never send you unsolicited marketing emails or SMS messages.</li>
47 |           <li>We will never ask for sensitive personal information beyond what is required for delivery.</li>
48 |         </ul>
49 |
50 |         <h3 className="text-lg font-bold text-primary mt-8 mb-3">4. Cookies & Device Memory</h3>
51 |         <p className="font-medium mb-3">To enhance your experience, we use minimal, privacy-focused "localStorage"
52 | on your device.</p>
53 |         <ul className="font-medium list-disc pl-5 mb-6 space-y-2">
54 |           <li><strong>Ghost Cart:</strong> We temporarily save your checkout form details on your device so if you
55 | accidentally close the page, you don't have to type everything again. This data never leaves your device until you
56 | submit the order.</li>
57 |           <li><strong>Order Tracking:</strong> After you place an order, we save your Order ID on your device so yo
58 | u can easily track it later without having to search your emails.</li>
59 |         </ul>
60 |         <p className="font-medium text-secondary">You can clear this data at any time from your browser's settings.
61 |       </p>
62 |     </div>
63 |   )
64 | }

```

FILE: src\app\product\[slug]\page.js

```
1 | // FIXED: Changed urlForImage to urlFor
2 | import { client } from '@sanity/lib/client'
3 | import { urlFor } from '@sanity/lib/image'
4 | import ProductClientUI from './ProductClientUI'
5 |
6 | export const revalidate = 10
7 |
8 | export default async function ProductPage({ params }) {
9 |   const { slug } = await params
10 |
11 |   const query = `*[_type == "product" && slug.current == $slug][0]`
12 |   const rawProduct = await client.fetch(query, { slug })
13 |
14 |   if (!rawProduct) {
15 |     return <div className="text-center py-20 font-bold text-xl">Product not found ■</div>
16 |   }
17 |
18 |   const product = {
19 |     slug: rawProduct.slug.current,
20 |     title: rawProduct.title,
21 |     originalPrice: rawProduct.prepaidPrice + Math.floor(rawProduct.prepaidPrice * 0.4),
22 |     prepaidPrice: rawProduct.prepaidPrice,
23 |     codPrice: rawProduct.codPrice || rawProduct.prepaidPrice,
24 |     isCodAvailable: rawProduct.isCodAvailable,
25 |     discountBadge: rawProduct.discountBadge,
26 |     tagline: rawProduct.tagline,
27 |     deliveryEstimate: rawProduct.deliveryEstimate || '5-7 Days',
28 |     highlights: rawProduct.highlights || [],
29 |     // FIXED here too
30 |     gallery: rawProduct.gallery ? rawProduct.gallery.map(img => urlFor(img).url()) : []
31 |   }
32 |
33 |   return <ProductClientUI product={product} />
34 | }
```

FILE: src\app\product\[slug]\ProductClientUI.js

```
1 | "use client"
2 | import { useState, useRef } from 'react'
3 | import { Truck, ShieldCheck } from 'lucide-react'
4 | import { motion } from 'framer-motion'
5 | import BuyDrawer from '@components/product/BuyDrawer'
6 |
7 | // Premium Zoom features
8 | import Zoom from 'react-medium-image-zoom'
9 | import 'react-medium-image-zoom/dist/styles.css'
10 |
11 | export default function ProductClientUI({ product }) {
12 |   const [isDrawerOpen, setIsDrawerOpen] = useState(false)
13 |   const [activeImage, setActiveImage] = useState(0)
14 |   const scrollContainerRef = useRef(null)
15 |
16 |   const handleScroll = (e) => {
17 |     if (!scrollContainerRef.current) return
18 |     const scrollPosition = e.target.scrollLeft
19 |     const width = e.target.clientWidth
20 |     const index = Math.round(scrollPosition / width)
21 |     if (index !== activeImage) setActiveImage(index)
22 |   }
23 |
24 |   const hasImages = product.gallery && product.gallery.length > 0
25 |   const activeImageUrl = hasImages ? product.gallery[activeImage] : ''
26 |
27 |   return (
28 |     <div className="relative bg-surface min-h-screen">
29 |       <div className="max-w-5xl mx-auto md:flex md:items-start md:gap-10 md:px-8 pt-4 md:pt-10 pb-28 md:pb-16">
30 |
31 |         {/* --- LEFT COLUMN: Images --- */}
32 |         <div className="w-full md:w-[50%] flex flex-col gap-4">
33 |
34 |           {/* MOBILE GALLERY: Now with Strict Snapping */}
35 |           <div className="md:hidden w-full aspect-square relative bg-[#F3F4F6] overflow-hidden">
36 |             <div ref={scrollContainerRef} onScroll={handleScroll} className="flex h-full w-full overflow-x-auto snap-x snap-mandatory hide-scrollbar scroll-smooth">
37 |               {hasImages && product.gallery.map((img, i) => (
38 |                 <div key={i} className="h-full w-full shrink-0 snap-always snap-center flex items-center justify-center p-4">
39 |                   <Zoom>
40 |                     <img src={img} alt={`View ${i + 1}`} className="max-h-full max-w-full object-contain drop-shadow-w-sm" />
41 |                   </Zoom>
42 |                 </div>
43 |               ))}
44 |             </div>
45 |
46 |             {hasImages && product.gallery.length > 1 && (
47 |               <div className="absolute bottom-4 left-0 right-0 flex justify-center gap-2 items-center z-10 pointer-events-none">
48 |                 {product.gallery.map((_, i) => (
49 |                   <motion.div key={i} layout transition={{ type: "spring", stiffness: 300, damping: 20 }} className={`h-1.5 rounded-full bg-primary ${activeImage === i ? 'w-5' : 'w-1.5 opacity-30'}`} />
50 |                 ))}
51 |               </div>
52 |             )}
53 |             </div>
54 |
55 |           {/* DESKTOP GALLERY: Fixed Height & Width */}
56 |           {hasImages && (
57 |             <div className="hidden md:flex flex-col gap-3">
58 |
59 |               {/* Locked height and width to prevent Zoom overflow */}
60 |               <div className="w-full h-[450px] bg-[#F3F4F6] rounded-3xl border border-border flex items-center justify-center p-6 overflow-hidden">
61 |                 <Zoom>
62 |                   <img
63 |                     src={activeImageUrl}
64 |                     style={{ maxHeight: '400px', width: '100%', objectFit: 'contain' }}
65 |                     className="drop-shadow-md transition-opacity duration-300"
66 |                     alt="Main"
67 |                   />
68 |                 </Zoom>
69 |               </div>
70 |
71 |               {/* Clickable Thumbnails */}
72 |               <div className="flex gap-3 overflow-x-auto hide-scrollbar">
73 |                 {product.gallery.map((img, i) => (
```

```

74 |         <button
75 |             key={i}
76 |             onClick={() => setActiveImage(i)}
77 |             className={`relative h-20 w-20 shrink-0 rounded-2xl bg-[#F3F4F6] border-2 transition-all p-2 fl
| ex items-center justify-center ${activeImage === i ? 'border-primary opacity-100' : 'border-transparent opacity-50
| hover:opacity-100'}`}
78 |         >
79 |             <img src={img} className="max-h-full max-w-full object-contain" alt={`Thumb ${i+1}`} />
80 |         </button>
81 |     )}}
82 | </div>
83 | </div>
84 | ))
85 | </div>
86 |
87 | /* --- RIGHT COLUMN: Info --- */
88 | <div className="w-full md:w-[50%] px-4 md:px-0">
89 |     <div className="flex flex-col gap-5 md:gap-6 mt-6 md:mt-0 h-full">
90 |         <div>
91 |             {product.discountBadge && (
92 |                 <span className="inline-block bg-primary text-surface text-[10px] font-bold px-2.5 py-1 rounded-ful
| l uppercase tracking-wider mb-2">
93 |                     {product.discountBadge}
94 |                 </span>
95 |             )}
96 |             <h1 className="text-2xl md:text-3xl font-bold tracking-tight text-primary leading-tight mb-2">
97 |                 {product.title}
98 |             </h1>
99 |
100 |             <div className="flex items-baseline gap-3 mt-2">
101 |                 <span className="text-2xl md:text-3xl font-black tracking-tight">■{product.prepaidPrice}</span>
102 |                 <span className="text-sm text-secondary line-through">■{product.originalPrice}</span>
103 |                 <span className="text-xs font-bold text-emerald-600 bg-emerald-50 px-2 py-0.5 rounded-md">
104 |                     Save ■{product.originalPrice - product.prepaidPrice}
105 |                 </span>
106 |             </div>
107 |         </div>
108 |
109 |         {product.tagline && (
110 |             <
111 |                 <p className="text-base font-medium text-secondary leading-relaxed italic">{product.tagline}</p>
112 |                 <hr className="border-border" />
113 |             </>
114 |         )}
115 |
116 |         {product.highlights && product.highlights.length > 0 && (
117 |             <div>
118 |                 <h3 className="text-xs font-bold uppercase tracking-wider text-secondary mb-3">Why you'll love it</
| h3>
119 |                 <ul className="flex flex-col gap-2.5">
120 |                     {product.highlights.map((point, i) => (
121 |                         <li key={i} className="flex items-start gap-3 text-sm font-medium text-primary/90">
122 |                             <span className="text-primary mt-0.5 leading-none select-none text-base">•</span>
123 |                             <span>{point}</span>
124 |                         </li>
125 |                     )}}
126 |                 </ul>
127 |             </div>
128 |         )}
129 |
130 |         <div className="flex flex-col gap-2.5 rounded-2xl bg-[#F3F4F6] border border-border p-4">
131 |             <div className="flex items-center gap-3 text-xs md:text-sm font-semibold text-secondary">
132 |                 <Truck size={16} className="text-primary shrink-0" />
133 |                 <span>Estimated Delivery: <span className="font-bold text-primary">{product.deliveryEstimate}</span>
| ></span>
134 |             </div>
135 |             <div className="flex items-center gap-3 text-xs md:text-sm font-semibold text-secondary">
136 |                 <ShieldCheck size={16} className="text-primary shrink-0" />
137 |                 <span>Fulfilled safely via verified partners.</span>
138 |             </div>
139 |         </div>
140 |
141 |         <div className="hidden md:block mt-2">
142 |             <motion.button whileTap={{ scale: 0.98 }} onClick={() => setIsDrawerOpen(true)} className="w-full rou
| nded-2xl bg-primary h-14 flex items-center justify-center text-base font-bold text-surface shadow-lg hover:opacity-
| 90 transition-all">
143 |                 Buy Now · ■{product.prepaidPrice}
144 |             </motion.button>
145 |         </div>
146 |     </div>

```

FILE CONTINUED: src\app\product\[slug]\ProductClientUI.js

```
147 |         </div>
148 |     </div>
149 |
150 |     <div className="md:hidden fixed bottom-0 left-0 right-0 z-40 bg-surface/90 backdrop-blur-md border-t border-b
| order p-4 pb-safe pointer-events-none">
151 |         <div className="pointer-events-auto">
152 |             <motion.button whileTap={{ scale: 0.96 }} transition={{ type: "spring", stiffness: 400, damping: 15 }} on
| Click={() => setIsDrawerOpen(true)} className="w-full rounded-2xl bg-primary h-14 flex items-center justify-center
| text-base font-bold text-surface shadow-xl">
153 |                 Buy Now · ■{product.prepaidPrice}
154 |             </motion.button>
155 |         </div>
156 |     </div>
157 |
158 |     <BuyDrawer isOpen={isDrawerOpen} onClose={() => setIsDrawerOpen(false)} product={product} />
159 | </div>
160 | )
161 | }
```

```

1 | import Link from 'next/link'
2 | import { ChevronLeft } from 'lucide-react'
3 |
4 | export default function RefundPage() {
5 |   return (
6 |     <div className="px-5 py-10 max-w-3xl mx-auto min-h-screen">
7 |       <Link href="/" className="inline-flex items-center gap-1 text-sm font-bold text-secondary hover:text-primary
8 |         <ChevronLeft size={18} /> Back to store
9 |       </Link>
10 |
11 |       <p className="text-xs font-bold uppercase tracking-widest text-secondary mb-2">Fair & Transparent</p>
12 |       <h1 className="text-3xl font-black tracking-tight mb-6">Refund & Issue Policy</h1>
13 |
14 |       <p className="text-base font-medium text-secondary leading-relaxed mb-10">
15 |         We want every order to feel right. Our products are curated for quality, and we stand behind them. To prote
16 | ct both you, our valued customer, and our small business from fraud, we have a strict, clear, and transparent polic
17 | y for handling issues.
18 |       </p>
19 |       <div className="prose prose-sm md:prose-base prose-neutral max-w-none text-primary/90">
20 |         <h3 className="text-lg font-bold text-primary mt-8 mb-3">1. When Claims Are Accepted (Our Promise)</h3>
21 |         <p className="font-medium mb-3">We will provide a full refund or a free replacement under the following con
22 | ditions only:</p>
23 |         <ul className="font-medium list-disc pl-5 mb-6 space-y-3">
24 |           <li><strong>Wrong Item Received:</strong> The product that arrived is not the product you ordered. <br/><
25 | span className="text-red-600 font-bold">BUT MANDATORY RECORDING OF UNBOXING OF FULL PRODUCT IS REQUIRED WITH SHOWIN
26 | G LABEL CLEARLY FIRST BEFORE OPENING.</span></li>
27 |           <li><strong>Item Unavailable Post-Payment:</strong> You prepaid for an item, but it became out of stock b
28 | efore we could dispatch it. In this rare case, we will proactively contact you and issue an instant full refund.</li>
29 |         </ul>
30 |         <h3 className="text-lg font-bold text-primary mt-8 mb-3">2. The Unboxing Video (Your Responsibility & Prote
31 | ction)</h3>
32 |         <p className="font-medium mb-3">This is the most important part of our policy. No exceptions will be made.<
33 | /p>
34 |         <ul className="font-medium list-disc pl-5 mb-6 space-y-3">
35 |           <li>The video must start before you open the outer package and clearly show the shipping label is intact
36 | while recording. <span className="text-red-600 font-bold">MANDATORY RECORDING OF UNBOXING OF FULL PRODUCT IS REQUIR
37 | ED WITH SHOWING LABEL CLEARLY FIRST BEFORE OPENING.</span></li>
38 |           <li>The video must continue without any cuts or edits, showing you opening the package and revealing the
39 | product for the first time.</li>
40 |         </ul>
41 |         <p className="font-medium mb-6">This policy is in place to protect against fraudulent claims and allows us
42 | to quickly process legitimate issues with our fulfillment partners. Without a valid unboxing video, your claim will
43 | be rejected.</p>
44 |         <h3 className="text-lg font-bold text-primary mt-8 mb-3">3. What Is Not Covered?</h3>
45 |         <p className="font-medium mb-3">We do not accept returns or refunds for the following reasons:</p>
46 |         <ul className="font-medium list-disc pl-5 mb-6 space-y-2">
47 |           <li>"Change of mind" or if you simply do not like the product. Please order thoughtfully.</li>
48 |           <li>Slight variations in color or texture. The products are shot under professional lighting, and slight
49 | differences can occur depending on your screen.</li>
50 |           <li>Claims submitted more than 48 hours after the delivery date recorded by the courier.</li>
51 |         </ul>
52 |         <h3 className="text-lg font-bold text-primary mt-8 mb-3">4. How to Raise a Claim</h3>
53 |         <p className="font-medium mb-6">If your issue meets our criteria, please send a DM to our Instagram (@bkc.f
54 | inds) or use our Contact page within 48 hours of delivery. Include your Order ID, and we will guide you on how to e
55 | mail us your unboxing video. Once verified, we resolve all claims within 5-7 business days.</p>
56 |       </div>
57 |     </div>
58 |   )
59 | }

```

FILE: src\app\request\page.js

```
1 | "use client"
2 | import { useState, useEffect } from 'react'
3 | import { motion } from 'framer-motion'
4 | import { PackageSearch, ArrowRight, CheckCircle2, Loader2 } from 'lucide-react'
5 | import { supabase } from '@lib/supabase' // <--- Added Supabase
6 | import { sendRequestAlert } from '@actions/telegram'
7 |
8 | export default function RequestPage() {
9 |   const [itemQuery, setItemQuery] = useState('')
10 |   const [contact, setContact] = useState('')
11 |   const [isSubmitted, setIsSubmitted] = useState(false)
12 |   const [isSubmitting, setIsSubmitting] = useState(false)
13 |   const [errorMsg, setErrorMsg] = useState('')
14 |
15 |   useEffect(() => {
16 |     const urlParams = new URLSearchParams(window.location.search)
17 |     const item = urlParams.get('item')
18 |     if (item) setItemQuery(item)
19 |   }, [])
20 |
21 |   const handleSubmit = async (e) => {
22 |     e.preventDefault()
23 |     setIsSubmitting(true)
24 |     setErrorMsg('')
25 |
26 |     const requestData = {
27 |       item_query: itemQuery,
28 |       contact_info: contact
29 |     }
30 |
31 |     // Save request to Supabase
32 |     const { error } = await supabase.from('product_requests').insert([requestData])
33 |
34 |     if (error) {
35 |       setErrorMsg("Something went wrong. Please try again.")
36 |       setIsSubmitting(false)
37 |     } else {
38 |       // SEND TELEGRAM ALERT
39 |       await sendRequestAlert(requestData)
40 |
41 |       setIsSubmitting(false)
42 |       setIsSubmitted(true)
43 |     }
44 |   }
45 |
46 |   if (isSubmitted) {
47 |     return (
48 |       <div className="flex flex-col items-center justify-center min-h-[60vh] px-6 text-center">
49 |         <CheckCircle2 size={64} className="text-emerald-500 mb-4" />
50 |         <h1 className="text-2xl font-black tracking-tight mb-2">Request Sent!</h1>
51 |         <p className="text-sm font-medium text-secondary mb-8">
52 |           Our sourcing team is on it. If we can find a high-quality version of this, we'll text you the secret link
53 |         </p>
54 |         <button onClick={() => window.location.href = '/'} className="w-full max-w-xs bg-primary text-surface rounded-
55 |           ed-2xl h-14 font-bold text-sm">
56 |           Return to Store
57 |         </button>
58 |       </div>
59 |     )
60 |   }
61 |
62 |   return (
63 |     <div className="px-5 py-8 max-w-md mx-auto min-h-[75vh]">
64 |       <div className="mb-8">
65 |         <div className="h-12 w-12 bg-[#F3F4F6] rounded-full flex items-center justify-center text-primary mb-4">
66 |           <PackageSearch size={24} />
67 |         </div>
68 |         <h1 className="text-2xl font-black tracking-tight mb-2">Can't find it?</h1>
69 |         <p className="text-sm font-medium text-secondary">
70 |           Saw a cool gadget on Reels? Paste the link or describe it, and we will source it for you at the best price.
71 |         </p>
72 |       </div>
73 |       <form onSubmit={handleSubmit} className="flex flex-col gap-5">
74 |         <div className="flex flex-col gap-1.5">
75 |           <label className="text-xs font-bold uppercase tracking-wider text-secondary">What are you looking for?</label>
76 |           <input type="text" value={itemQuery} onChange={e => setItemQuery(e.target.value)} />
77 |         </div>
78 |         <div className="flex flex-col gap-1.5">
79 |           <label className="text-xs font-bold uppercase tracking-wider text-secondary">Contact info</label>
80 |           <input type="text" value={contact} onChange={e => setContact(e.target.value)} />
81 |         </div>
82 |         <button type="submit" className="w-full max-w-xs bg-primary text-surface rounded-ed-2xl h-14 font-bold text-sm">
83 |           Submit Request
84 |         </button>
85 |       </form>
86 |     </div>
87 |   )
88 | }
```

FILE CONTINUED: src\applrequest\page.js

```
76 |         <textarea required rows="3" placeholder="Paste an Instagram Reel link, or describe the product..." value=
    | {itemQuery} onChange={(e) => setItemQuery(e.target.value)} className="w-full rounded-2xl border border-border px-4
    | py-3.5 text-sm font-medium bg-surface focus:outline-none focus:border-primary transition-colors resize-none" />
77 |     </div>
78 |
79 |     <div className="flex flex-col gap-1.5">
80 |         <label className="text-xs font-bold uppercase tracking-wider text-secondary">Your Phone or Email</label>
81 |         <input type="text" required placeholder="So we can send you the link when we find it" value={contact} onC
    | hange={(e) => setContact(e.target.value)} className="w-full rounded-2xl border border-border px-4 py-3.5 text-sm fo
    | nt-medium bg-surface focus:outline-none focus:border-primary transition-colors" />
82 |     </div>
83 |
84 |     {errorMsg && <p className="text-xs text-red-500 font-bold">{errorMsg}</p>}
85 |
86 |     <motion.button disabled={isSubmitting} whileTap={!isSubmitting ? { scale: 0.98 } : {}} type="submit" classN
    | ame="w-full mt-2 rounded-2xl bg-primary text-surface h-14 flex items-center justify-center font-bold text-sm gap-2
    | shadow-lg disabled:opacity-80">
87 |         {isSubmitting ? <Loader2 size={18} className="animate-spin" /> : <><ArrowRight size={18} /> Send Request<
    | />}
88 |     </motion.button>
89 | </form>
90 | </div>
91 | )
92 | }
```

FILE: src\app\search\page.js

```
1 | import { client } from '@sanity/lib/client'
2 | import { urlFor } from '@sanity/lib/image'
3 | import SearchClientUI from './SearchClientUI'
4 |
5 | export const revalidate = 10
6 |
7 | export default async function SearchPage() {
8 |   // Fetch ALL active products from your real Sanity database
9 |   const rawProducts = await client.fetch(`*[_type == "product" && isActive == true] | order(_createdAt desc)`)
10 |
11 |   const products = rawProducts.map(p => ({
12 |     slug: p.slug?.current || '',
13 |     title: p.title || 'Untitled',
14 |     prepaidPrice: p.prepaidPrice || 0,
15 |     codPrice: p.codPrice || 0,
16 |     isCodAvailable: p.isCodAvailable || false,
17 |     discountBadge: p.discountBadge || null,
18 |     imageUrl: p.gallery?.length > 0 ? urlFor(p.gallery[0]).url() : ''
19 |   }))
20 |
21 |   // Pass them to the client UI
22 |   return <SearchClientUI products={products} />
23 | }
```

FILE: src\app\search\SearchClientUI.js

```
1 | "use client"
2 | import { useState } from 'react'
3 | import { Search, X, PackageSearch } from 'lucide-react'
4 | import Link from 'next/link'
5 | import ProductCard from '@components/shared/ProductCard'
6 |
7 | export default function SearchClientUI({ products }) {
8 |   const [query, setQuery] = useState('')
9 |
10 |   // Live filter logic (as-you-type) against REAL products
11 |   const results = query.length > 0
12 |     ? products.filter(p => p.title.toLowerCase().includes(query.toLowerCase()))
13 |     : []
14 |
15 |   // Get 4 random products to show if search fails
16 |   const fallbackProducts = products.slice(0, 4)
17 |
18 |   return (
19 |     <div className="min-h-screen bg-surface">
20 |
21 |       {/* Sticky Search Header */}
22 |       <div className="sticky top-14 md:top-16 z-40 bg-surface border-b border-border px-4 py-4 md:px-8">
23 |         <div className="relative max-w-2xl mx-auto">
24 |           <Search size={18} className="absolute left-4 top-1/2 -translate-y-1/2 text-secondary" />
25 |           <input
26 |             autoFocus
27 |             type="text"
28 |             placeholder="Search for toys, gadgets, decor..."
29 |             value={query}
30 |             onChange={(e) => setQuery(e.target.value)}
31 |             className="w-full h-12 bg-[#F3F4F6] rounded-2xl pl-11 pr-10 text-sm font-bold text-primary focus:outline-none focus:ring-2 focus:ring-primary/20 transition-all"
32 |           />
33 |           {query.length > 0 && (
34 |             <button
35 |               onClick={() => setQuery('')}
36 |               className="absolute right-3 top-1/2 -translate-y-1/2 text-secondary hover:text-primary p-1"
37 |             >
38 |               <X size={16} strokeWidth={3} />
39 |             </button>
40 |           )}
41 |         </div>
42 |       </div>
43 |
44 |       <div className="px-4 py-6 md:px-8 max-w-5xl mx-auto">
45 |
46 |         {/* STATE 1: Typing but NO results found */}
47 |         {query.length > 0 && results.length === 0 && (
48 |           <div className="flex flex-col items-center justify-center py-10 text-center px-4">
49 |             <div className="h-16 w-16 bg-[#F3F4F6] rounded-full flex items-center justify-center text-secondary mb-4">
50 |               <PackageSearch size={28} />
51 |             </div>
52 |             <h2 className="text-xl font-bold tracking-tight mb-2">No results for "{query}"</h2>
53 |             <p className="text-sm text-secondary font-medium mb-6 max-w-sm">
54 |               We might not have this right now, but we can source it for you!
55 |             </p>
56 |             <Link
57 |               href={` /request?item=${encodeURIComponent(query)} `}
58 |               className="bg-primary text-surface px-6 py-3 rounded-xl font-bold text-sm shadow-md active:scale-95 transition-transform mb-12"
59 |             >
60 |               Request this product
61 |             </Link>
62 |
63 |             {/* FALLBACK PRODUCTS - As you requested! */}
64 |             <div className="w-full text-left">
65 |               <h3 className="text-sm font-bold uppercase tracking-widest text-secondary mb-4">Suggested Products</h3>
66 |               <div className="grid grid-cols-2 md:grid-cols-3 lg:grid-cols-4 gap-x-3 gap-y-6 md:gap-x-6 md:gap-y-10">
67 |                 {fallbackProducts.map(product => (
68 |                   <ProductCard key={product.slug} product={product} />
69 |                 ))}
70 |               </div>
71 |             </div>
72 |           </div>
73 |         )}
74 |       </div>

```

FILE CONTINUED: src\app\search\SearchClientUI.js

```
75 |         {/* STATE 2: Results found */}
76 |         {query.length > 0 && results.length > 0 && (
77 |           <div className="grid grid-cols-2 md:grid-cols-3 lg:grid-cols-4 gap-x-3 gap-y-6 md:gap-x-6 md:gap-y-10">
78 |             {results.map(product => (
79 |               <ProductCard key={product.slug} product={product} />
80 |             ))}
81 |           </div>
82 |         )}
83 |
84 |         {/* STATE 3: Empty State (Haven't typed yet) */}
85 |         {query.length === 0 && (
86 |           <div className="pt-2">
87 |             <h3 className="text-xs font-bold uppercase tracking-widest text-secondary mb-4">All Products</h3>
88 |             <div className="grid grid-cols-2 md:grid-cols-3 lg:grid-cols-4 gap-x-3 gap-y-6 md:gap-x-6 md:gap-y-10">
89 |               {products.map(product => (
90 |                 <ProductCard key={product.slug} product={product} />
91 |               ))}
92 |             </div>
93 |           </div>
94 |         )}
95 |
96 |       </div>
97 |     </div>
98 |   )
99 | }
```

```

1 | import Link from 'next/link'
2 | import { ChevronLeft } from 'lucide-react'
3 |
4 | export default function ShippingPage() {
5 |   return (
6 |     <div className="px-5 py-10 max-w-3xl mx-auto min-h-screen">
7 |       <Link href="/" className="inline-flex items-center gap-1 text-sm font-bold text-secondary hover:text-primary
8 |       <ChevronLeft size={18} /> Back to store
9 |     </Link>
10 |
11 |     <p className="text-xs font-bold uppercase tracking-widest text-secondary mb-2">Fast & Reliable</p>
12 |     <h1 className="text-3xl font-black tracking-tight mb-6">Shipping & Delivery</h1>
13 |
14 |     <div className="bg-[#F3F4F6] border border-border rounded-2xl p-5 mb-8">
15 |       <p className="text-sm font-bold text-primary leading-relaxed">
16 |         REMEMBER, WE DON'T HAVE OUR OWN PRODUCTS, WE JUST CURATE THE PRODUCTS. THEREFORE WHILE DELIVERY TIME YOU
17 |         MAY GET A CALL FROM DELIVERY PARTNERS OF MEESHO, AMAZON, FLIPKART OR ANY OTHER WEBSITE. Our mission is to get your
18 |         curated find into your hands as quickly and reliably as possible. We ship free of charge, all across India as we ne
19 |         ed to pay for shipment too.
20 |       </p>
21 |     </div>
22 |
23 |     <div className="prose prose-sm md:prose-base prose-neutral max-w-none text-primary/90">
24 |       <h3 className="text-lg font-bold text-primary mt-8 mb-3">1. Our 24-Hour Dispatch Rule</h3>
25 |       <p className="font-medium mb-3">We are not a mega-corporation with slow processing times. We are a fast-mov
26 |       ing studio. Our internal target is to process and dispatch every single order within 24 hours of confirmation. Orde
27 |       rs placed before 11 AM IST are typically dispatched the very same day.</p>
28 |
29 |       <h3 className="text-lg font-bold text-primary mt-8 mb-3">2. Our Fulfillment Network</h3>
30 |       <p className="font-medium mb-3">To provide a seamless delivery experience across all pin codes in India, we
31 |       work with a hybrid network of trusted partners. Depending on your location and the product's warehouse, your order
32 |       will be shipped via:</p>
33 |       <ul className="font-medium list-disc pl-5 mb-6 space-y-3">
34 |         <li><strong>Important note:</strong> REMEMBER, WE DON'T HAVE OUR OWN PRODUCTS, WE JUST CURATE THE PRODUCT
35 |         S. THEREFORE WHILE DELIVERY TIME YOU MAY GET A CALL FROM DELIVERY PARTNERS OF MEESHO, AMAZON, FLIPKART OR ANY OTHER
36 |         WEBSITE. Our mission is to get your curated find into your hands as quickly and reliably as possible.</li>
37 |         <li><strong>Courier Partners may include:</strong> Delhivery, Ecom Express, Shadowfax, Meesho partners, A
38 |         mazon partners and many more. Kindly don't raise complaints regarding getting different calls from delivery partner
39 |         s.</li>
40 |         <li><strong>Curated Supplier Networks:</strong> Including the robust and reliable Meesho fulfillment netw
41 |         ork, ensuring deep reach into Tier-2 and Tier-3 cities.</li>
42 |       </ul>
43 |       <p className="font-medium mb-6">Your checkout details are shared securely and only with the partner respons
44 |       ible for delivering your specific order.</p>
45 |
46 |       <h3 className="text-lg font-bold text-primary mt-8 mb-3">3. Estimated Delivery Timelines</h3>
47 |       <ul className="font-medium list-disc pl-5 mb-6 space-y-2">
48 |         <li><strong>Metro & Tier-1 Cities:</strong> 3-5 Business Days after dispatch.</li>
49 |         <li><strong>Rest of India:</strong> 5-7 Business Days after dispatch.</li>
50 |         <li><strong>Note:</strong> Remote pin codes may occasionally take longer.</li>
51 |       </ul>
52 |
53 |       <h3 className="text-lg font-bold text-primary mt-8 mb-3">4. Live, On-Site Tracking</h3>
54 |       <p className="font-medium mb-6">You do not need to hunt for tracking links or visit third-party courier web
55 |       sites. Simply use our on-site Track Order page. Enter the Order ID from your confirmation email and the phone numbe
56 |       r you used at checkout to see a live, visual timeline of your order's journey.</p>
57 |     </div>
58 |   )
59 | }

```

FILE: src\app\studio\[...tool]\page.jsx

```
1 | /**
2 |  * This route is responsible for the built-in authoring environment using Sanity Studio.
3 |  * All routes under your studio path is handled by this file using Next.js' catch-all routes:
4 |  * https://nextjs.org/docs/routing/dynamic-routes#catch-all-routes
5 |  *
6 |  * You can learn more about the next-sanity package here:
7 |  * https://github.com/sanity-io/next-sanity
8 |  */
9 |
10 | import { NextStudio } from 'next-sanity/studio'
11 | import config from '../../../../sanity.config'
12 |
13 | export const dynamic = 'force-static'
14 |
15 | export { metadata, viewport } from 'next-sanity/studio'
16 |
17 | export default function StudioPage() {
18 |   return <NextStudio config={config} />
19 | }
```

FILE: src\app\success\page.js

```
1 | "use client"
2 | import Link from 'next/link'
3 | import { motion } from 'framer-motion'
4 | import { CheckCircle2, Copy, ArrowRight, Package } from 'lucide-react'
5 | import { useState, useEffect } from 'react'
6 |
7 | export default function SuccessPage() {
8 |   const [copied, setCopied] = useState(false)
9 |   const [orderId, setOrderId] = useState('Loading...')
10 |
11 |   // Fetch the saved order ID when the page loads
12 |   useEffect(() => {
13 |     const saved = localStorage.getItem('bkc_recent_order')
14 |     if (saved) setOrderId(saved)
15 |   }, [])
16 |
17 |   const copyToClipboard = () => {
18 |     navigator.clipboard.writeText(orderId)
19 |     setCopied(true)
20 |     setTimeout(() => setCopied(false), 2000)
21 |   }
22 |
23 |   return (
24 |     <div className="flex flex-col items-center justify-center min-h-[75vh] px-6 text-center pt-8">
25 |
26 |       <motion.div
27 |         initial={{ scale: 0, opacity: 0 }}
28 |         animate={{ scale: 1, opacity: 1 }}
29 |         transition={{ type: "spring", damping: 20, stiffness: 200, delay: 0.1 }}
30 |         className="text-emerald-500 mb-6"
31 |       >
32 |         <CheckCircle2 size={80} strokeWidth={1.5} />
33 |       </motion.div>
34 |
35 |       <motion.h1
36 |         initial={{ y: 20, opacity: 0 }}
37 |         animate={{ y: 0, opacity: 1 }}
38 |         transition={{ delay: 0.2 }}
39 |         className="text-3xl font-black tracking-tight text-primary mb-2"
40 |       >
41 |         Order Confirmed!
42 |       </motion.h1>
43 |
44 |       <motion.p
45 |         initial={{ y: 20, opacity: 0 }}
46 |         animate={{ y: 0, opacity: 1 }}
47 |         transition={{ delay: 0.3 }}
48 |         className="text-base font-medium text-secondary mb-8 max-w-sm"
49 |       >
50 |         Your premium finds are being prepared. We've sent a confirmation to your phone.
51 |       </motion.p>
52 |
53 |       <motion.div
54 |         initial={{ y: 20, opacity: 0 }}
55 |         animate={{ y: 0, opacity: 1 }}
56 |         transition={{ delay: 0.4 }}
57 |         className="w-full max-w-sm bg-[#F3F4F6] rounded-3xl p-6 flex flex-col gap-4 border border-border"
58 |       >
59 |         <div className="flex flex-col items-center gap-1">
60 |           <p className="text-xs font-bold uppercase tracking-widest text-secondary">Order Reference</p>
61 |           <div
62 |             onClick={copyToClipboard}
63 |             className="flex items-center gap-2 bg-surface px-4 py-2 rounded-xl cursor-pointer shadow-sm active:scale-95 transition-transform"
64 |           >
65 |             <span className="text-lg font-black tracking-widest">{orderId}</span>
66 |             <Copy size={16} className={copied ? "text-emerald-500" : "text-secondary"} />
67 |           </div>
68 |           {copied && <span className="text-[10px] font-bold text-emerald-600 mt-1">Copied!</span>}
69 |         </div>
70 |
71 |         <hr className="border-border" />
72 |
73 |         <div className="flex justify-between items-center text-sm font-medium">
74 |           <span className="text-secondary">Expected Delivery</span>
75 |           <span className="font-bold text-primary">5-7 Business Days</span>
76 |         </div>
77 |       </motion.div>
78 |     </div>

```

FILE CONTINUED: src\app\success\page.js

```
79 |         <motion.div
80 |             initial={{ y: 20, opacity: 0 }}
81 |             animate={{ y: 0, opacity: 1 }}
82 |             transition={{ delay: 0.5 }}
83 |             className="mt-8 flex flex-col gap-3 w-full max-w-sm"
84 |         >
85 |             <Link href="/track" className="w-full bg-primary text-surface rounded-2xl h-14 flex items-center justify-ce
| nter font-bold text-sm gap-2 shadow-lg active:scale-[0.98] transition-transform">
86 |                 <Package size={18} />
87 |                 Track Order
88 |             </Link>
89 |             <Link href="/" className="w-full bg-surface text-primary border-2 border-border rounded-2xl h-14 flex items
| -center justify-center font-bold text-sm gap-2 active:scale-[0.98] transition-transform">
90 |                 Continue Shopping
91 |                 <ArrowRight size={18} />
92 |             </Link>
93 |         </motion.div>
94 |     }
95 | </div>
96 | )
97 | }
```

```

1 | import Link from 'next/link'
2 | import { ChevronLeft } from 'lucide-react'
3 |
4 | export default function TermsPage() {
5 |   return (
6 |     <div className="px-5 py-10 max-w-3xl mx-auto min-h-screen">
7 |       <Link href="/" className="inline-flex items-center gap-1 text-sm font-bold text-secondary hover:text-primary
8 |         <ChevronLeft size={18} /> Back to store
9 |       </Link>
10 |
11 |       <p className="text-xs font-bold uppercase tracking-widest text-secondary mb-2">The Fine Print, Made Clear</p>
12 |       <h1 className="text-3xl font-black tracking-tight mb-6">Terms of Service</h1>
13 |
14 |       <p className="text-base font-medium text-secondary leading-relaxed mb-10">
15 |         Welcome to BigKidFinds. By browsing our site and placing an order, you agree to the terms below. We have kept them short and simple because we believe in clarity.
16 |       </p>
17 |
18 |       <div className="prose prose-sm md:prose-base prose-neutral max-w-none text-primary/90">
19 |         <h3 className="text-lg font-bold text-primary mt-8 mb-3">1. Our Business Model</h3>
20 |         <p className="font-medium mb-6">BigKidFinds is a curated e-commerce marketplace. We are not the manufacturer of the products. We source unique, high-quality items from a network of domestic and international suppliers, makers, and fulfillment platforms.</p>
21 |
22 |         <h3 className="text-lg font-bold text-primary mt-8 mb-3">2. Order Acceptance</h3>
23 |         <p className="font-medium mb-6">Your placement of an order does not constitute our acceptance of that order. We reserve the right to accept, decline, or cancel your order for any reason. Common reasons for cancellation include (but are not limited to): the item becoming unavailable, a clear pricing error on the website, or if our fraud-detection system flags the order as suspicious. If we cancel an order you have already paid for, we will issue an immediate and full refund.</p>
24 |
25 |         <h3 className="text-lg font-bold text-primary mt-8 mb-3">3. Payment</h3>
26 |         <p className="font-medium mb-6">All prices are listed in Indian Rupees (INR). Prices are subject to change without notice. We offer Prepaid (UPI) and Cash on Delivery (COD) payment methods. COD is available only on select products and pin codes, at our discretion.</p>
27 |
28 |         <h3 className="text-lg font-bold text-primary mt-8 mb-3">4. User Conduct</h3>
29 |         <p className="font-medium mb-6">You agree not to copy, reproduce, or resell any part of our website's design, photography, or written copy. Our brand and its assets are our intellectual property.</p>
30 |
31 |         <h3 className="text-lg font-bold text-primary mt-8 mb-3">5. Governing Law</h3>
32 |         <p className="font-medium mb-6">By using our service, you agree that any disputes will be governed by the laws of India.</p>
33 |
34 |         <hr className="border-border my-8" />
35 |         <p className="font-medium text-secondary">For more specific rules, please refer to our dedicated Privacy, Refund, and Shipping policies.</p>
36 |       </div>
37 |     </div>
38 |   )
39 | }

```

FILE: src\app\track\page.js

```
1 | "use client"
2 | import { useState, useEffect } from 'react' // FIXED: Added useEffect here
3 | import { Search, Package, CheckCircle2, Truck, Clock } from 'lucide-react'
4 | import { motion, AnimatePresence } from 'framer-motion'
5 | import { supabase } from '@/lib/supabase'
6 |
7 | export default function TrackPage() {
8 |   const [orderId, setOrderId] = useState('')
9 |   const [phone, setPhone] = useState('')
10 |   const [isSearching, setIsSearching] = useState(false)
11 |   const [trackingResult, setTrackingResult] = useState(null)
12 |
13 |   // Auto-fill Logic: Magic Links + Local Storage
14 |   useEffect(() => {
15 |     // 1. Check if they clicked a link from their email (e.g., site.com/track?id=BKC-123)
16 |     const urlParams = new URLSearchParams(window.location.search)
17 |     const emailOrderId = urlParams.get('id')
18 |
19 |     // 2. Check if they just bought something right now
20 |     const savedOrder = localStorage.getItem('bkc_recent_order')
21 |     const savedPhone = localStorage.getItem('bkc_recent_phone')
22 |
23 |     // Apply whichever one exists!
24 |     if (emailOrderId) {
25 |       setOrderId(emailOrderId.toUpperCase())
26 |     } else if (savedOrder) {
27 |       setOrderId(savedOrder)
28 |     }
29 |
30 |     if (savedPhone) setPhone(savedPhone)
31 |   }, [])
32 |
33 |   // Replace your handleTrack function with this:
34 |   const handleTrack = async (e) => {
35 |     e.preventDefault()
36 |     setIsSearching(true)
37 |     setTrackingResult(null)
38 |
39 |     // 1. Query Supabase for the exact order
40 |     const { data, error } = await supabase
41 |       .from('orders')
42 |       .select('*')
43 |       .eq('order_id', orderId)
44 |       .eq('customer_phone', phone)
45 |       .single()
46 |
47 |     setIsSearching(false)
48 |
49 |     if (error || !data) {
50 |       alert("Order not found. Please check your Order ID and Phone Number.")
51 |       return
52 |     }
53 |
54 |     // 2. Map Supabase status to our visual timeline
55 |     // Supabase status can be: 'Order Received', 'Processing', 'Shipped', 'Out for Delivery', 'Delivered'
56 |     let mappedStatus = 'processing'
57 |     const dbStatus = data.status.toLowerCase()
58 |
59 |     if (dbStatus.includes('shipped')) mappedStatus = 'shipped'
60 |     if (dbStatus.includes('out')) mappedStatus = 'out_for_delivery'
61 |     if (dbStatus.includes('delivered')) mappedStatus = 'delivered'
62 |
63 |     setTrackingResult({
64 |       id: data.order_id,
65 |       status: mappedStatus,
66 |       expectedDate: '5-7 Days from order date',
67 |       items: data.product_name
68 |     })
69 |   }
70 |
71 |   const timeline = [
72 |     { key: 'processing', label: 'Processing', icon: Clock },
73 |     { key: 'shipped', label: 'Shipped', icon: Package },
74 |     { key: 'out_for_delivery', label: 'Out for Delivery', icon: Truck },
75 |     { key: 'delivered', label: 'Delivered', icon: CheckCircle2 }
76 |   ]
77 |
78 |   const getStatusIndex = (status) => timeline.findIndex(t => t.key === status)
79 | }
```

FILE CONTINUED: src\appl\track\page.js

```

80 |     return (
81 |       <div className="px-5 py-8 max-w-md mx-auto min-h-[70vh]">
82 |
83 |         <div className="mb-8">
84 |           <h1 className="text-2xl font-black tracking-tight mb-2">Track Your Order</h1>
85 |           <p className="text-sm font-medium text-secondary">Enter your details below to get real-time delivery update
s.</p>
86 |         </div>
87 |
88 |         <form onSubmit={handleTrack} className="flex flex-col gap-4 mb-10">
89 |           <div className="flex flex-col gap-1.5">
90 |             <label className="text-xs font-bold uppercase tracking-wider text-secondary">Order ID</label>
91 |             <input
92 |               type="text"
93 |               required
94 |               placeholder="e.g. BKC-123456"
95 |               value={orderId}
96 |               onChange={(e) => setOrderId(e.target.value.toUpperCase())}
97 |               className="w-full rounded-2xl border border-border px-4 py-3.5 text-sm font-bold bg-surface focus:outli
ne-none focus:border-primary transition-colors uppercase"
98 |             />
99 |           </div>
100 |
101 |           <div className="flex flex-col gap-1.5">
102 |             <label className="text-xs font-bold uppercase tracking-wider text-secondary">Phone Number</label>
103 |             <input
104 |               type="tel"
105 |               required
106 |               placeholder="10-digit number used during checkout"
107 |               value={phone}
108 |               onChange={(e) => setPhone(e.target.value.replace(/\D/g, '').slice(0, 10))}
109 |               className="w-full rounded-2xl border border-border px-4 py-3.5 text-sm font-bold bg-surface focus:outli
ne-none focus:border-primary transition-colors"
110 |             />
111 |           </div>
112 |
113 |           <button
114 |             type="submit"
115 |             disabled={isSearching}
116 |             className="w-full mt-2 rounded-2xl bg-primary text-surface h-14 flex items-center justify-center font-bol
d text-sm gap-2 shadow-lg active:scale-[0.98] transition-all disabled:opacity-80"
117 |           >
118 |             {isSearching ? 'Searching...' : (
119 |               <>
120 |                 <Search size={18} />
121 |                 Track Package
122 |               </>
123 |             )}
124 |           </button>
125 |         </form>
126 |
127 |         <AnimatePresence>
128 |           {trackingResult && (
129 |             <motion.div
130 |               initial={{ opacity: 0, y: 20 }}
131 |               animate={{ opacity: 1, y: 0 }}
132 |               className="rounded-3xl border border-border bg-[#F3F4F6] p-6 flex flex-col gap-6"
133 |             >
134 |               <div>
135 |                 <p className="text-xs font-bold uppercase tracking-widest text-secondary mb-1">Status</p>
136 |                 <h2 className="text-xl font-black tracking-tight text-primary capitalize">
137 |                   {trackingResult.status.replace(/_/g, ' ')}
138 |                 </h2>
139 |                 <p className="text-sm font-medium text-secondary mt-1">Expected: {trackingResult.expectedDate}</p>
140 |               </div>
141 |
142 |               <div className="relative flex justify-between items-center mt-2">
143 |                 <div className="absolute top-1/2 left-0 right-0 h-1 bg-border -translate-y-1/2 rounded-full" />
144 |                 <div
145 |                   className="absolute top-1/2 left-0 h-1 bg-primary -translate-y-1/2 rounded-full transition-all dura
tion-1000"
146 |                   style={{ width: `${(getStatusIndex(trackingResult.status) / 3) * 100}%` }}
147 |                 />
148 |
149 |                 {timeline.map((item, i) => {
150 |                   const isActive = getStatusIndex(trackingResult.status) >= i
151 |                   const Icon = item.icon
152 |                   return (
153 |                     <div key={item.key} className="relative z-10 flex flex-col items-center gap-2">
154 |                       <div className={`h-10 w-10 rounded-full flex items-center justify-center border-4 border-[#F3F4

```

FILE CONTINUED: src\appltrack\page.js

```
155 | | F6] transition-colors duration-500
156 | |     ${isActive ? 'bg-primary text-surface' : 'bg-surface text-border'}``>
157 | |     <Icon size={18} strokeWidth={isActive ? 2.5 : 2} />
158 | |   </div>
159 | | )
160 | |   }}
161 | | </div>
162 | |
163 | |   <hr className="border-border my-2" />
164 | |
165 | |   <div>
166 | |     <p className="text-xs font-bold uppercase tracking-widest text-secondary mb-1">Items</p>
167 | |     <p className="text-sm font-bold">{trackingResult.items}</p>
168 | |   </div>
169 | | </motion.div>
170 | |   )}
171 | | </AnimatePresence>
172 | | </div>
173 | | )
174 | | }
```

FILE: src\components\home\CollectionRow.js

```
1 | import Link from 'next/link'
2 |
3 | export default function CollectionRow({ collections }) {
4 |   return (
5 |     <div className="w-full py-4">
6 |       { /* hide-scrollbar is from our globals.css */ }
7 |       <div className="flex w-full gap-3 overflow-x-auto hide-scrollbar px-4 pb-2">
8 |         {collections.map((collection) => (
9 |           <Link
10 |             key={collection.slug}
11 |             href={` /collections/${collection.slug}`}
12 |             className="flex-shrink-0 relative overflow-hidden rounded-xl bg-border h-24 w-32 border border-border"
13 |           >
14 |             {collection.imageUrl && (
15 |               <img
16 |                 src={collection.imageUrl}
17 |                 alt={collection.title}
18 |                 className="absolute inset-0 h-full w-full object-cover brightness-[0.70]"
19 |               />
20 |             )}
21 |             <div className="absolute inset-0 flex items-center justify-center p-2 text-center">
22 |               <span className="text-sm font-bold text-white tracking-tight drop-shadow-md">
23 |                 {collection.title}
24 |               </span>
25 |             </div>
26 |           </Link>
27 |         ))}
28 |       </div>
29 |     </div>
30 |   )
31 | }
```

FILE: src\components\layout\Footer.js

```
1 | import Link from 'next/link'
2 |
3 | export default function Footer() {
4 |   return (
5 |     <footer className="border-t border-border bg-surface mt-auto py-10">
6 |       <div className="max-w-7xl mx-auto px-4 flex flex-col items-center text-center">
7 |
8 |         <p className="text-base md:text-lg font-bold tracking-tight mb-6">BigKidFinds.</p>
9 |
10 |        <div className="flex flex-wrap justify-center gap-x-8 gap-y-3 text-sm font-medium text-secondary mb-8">
11 |          <Link href="/track" className="hover:text-primary transition-colors">Track Order</Link>
12 |          <Link href="/request" className="hover:text-primary transition-colors">Request a Product</Link>
13 |          <Link href="/contact" className="hover:text-primary transition-colors">Contact Support</Link>
14 |        </div>
15 |
16 |        <div className="flex flex-wrap justify-center gap-x-6 gap-y-2 text-xs text-secondary/60 mb-6">
17 |          <Link href="/terms" className="hover:text-primary transition-colors">Terms</Link>
18 |          <Link href="/privacy" className="hover:text-primary transition-colors">Privacy</Link>
19 |          <Link href="/shipping" className="hover:text-primary transition-colors">Shipping</Link>
20 |          <Link href="/refund-policy" className="hover:text-primary transition-colors">Refunds</Link>
21 |        </div>
22 |
23 |        <p className="text-xs text-secondary/40">
24 |          © {new Date().getFullYear()} BigKidFinds. All rights reserved.
25 |        </p>
26 |      </div>
27 |    </footer>
28 |  )
29 | }
```

FILE: src\components\layout\Navbar.js

```
1 | import Link from 'next/link'
2 | import { Search, Package } from 'lucide-react'
3 |
4 | export default function Navbar() {
5 |   return (
6 |     <header className="sticky top-0 z-50 w-full border-b border-border bg-surface/80 backdrop-blur-md">
7 |       <div className="flex h-16 items-center justify-between px-4 md:px-8 max-w-7xl mx-auto w-full">
8 |
9 |         <Link href="/" className="font-bold text-xl md:text-2xl tracking-tight">
10 |           BigKidFinds.
11 |         </Link>
12 |
13 |         <div className="flex items-center gap-4">
14 |           <Link href="/track" className="p-2 text-secondary hover:text-primary transition-colors" aria-label="Track
15 | Order">
16 |             <Package size={22} strokeWidth={2} />
17 |           </Link>
18 |           <Link href="/search" className="p-2 -mr-2 text-primary transition-opacity hover:opacity-70" aria-label="S
19 | earch">
20 |             <Search size={24} strokeWidth={2} />
21 |           </Link>
22 |         </div>
23 |       </header>
24 |     )
25 |   }
```

FILE: src\components\product\BuyDrawer.js

```
1 | "use client"
2 | import { motion, AnimatePresence } from 'framer-motion'
3 | import { X, ShieldCheck, CreditCard, Landmark, ArrowRight, Loader2, ChevronLeft } from 'lucide-react'
4 | import { useState, useEffect } from 'react'
5 | import { useRouter } from 'next/navigation'
6 | import { supabase } from '@lib/supabase'
7 | import { sendOrderAlert } from '@actions/telegram'
8 |
9 | // Helper to load Razorpay script
10 | const loadRazorpayScript = () => {
11 |   return new Promise((resolve) => {
12 |     const script = document.createElement("script")
13 |     script.src = "https://checkout.razorpay.com/v1/checkout.js"
14 |     script.onload = () => resolve(true)
15 |     script.onerror = () => resolve(false)
16 |     document.body.appendChild(script)
17 |   })
18 | }
19 |
20 | function FormField({ label, id, type = "text", value, onChange, placeholder, readOnly = false, optional = false })
21 | {
22 |   return (
23 |     <div className="flex flex-col gap-1.5">
24 |       <label htmlFor={id} className="text-xs font-bold uppercase tracking-wider text-secondary">
25 |         {label}{optional && <span className="font-normal normal-case tracking-normal text-secondary/40 ml-1">(Option
26 |         al)</span>}
27 |       </label>
28 |       <input id={id} type={type} value={value} onChange={onChange} placeholder={placeholder} readOnly={readOnly} cl
29 |       assName={`w-full rounded-xl border border-border px-4 py-3 text-sm font-medium outline-none transition-all ${readOnly ? 'bg-[#F3F4F6] text-secondary cursor-not-allowed' : 'bg-surface text-primary focus:border-primary focus:ring-2 focus:ring-primary/10'}`} />
30 |     </div>
31 |   )
32 | }
33 |
34 | export default function BuyDrawer({ isOpen, onClose, product }) {
35 |   const router = useRouter()
36 |   const [step, setStep] = useState(1)
37 |   const [paymentMode, setPaymentMode] = useState('prepaid')
38 |
39 |   const [phone, setPhone] = useState('')
40 |   const [name, setName] = useState('')
41 |   const [pincode, setPincode] = useState('')
42 |   const [city, setCity] = useState('')
43 |   const [state, setState] = useState('')
44 |   const [house, setHouse] = useState('')
45 |   const [area, setArea] = useState('')
46 |   const [landmark, setLandmark] = useState('')
47 |
48 |   const [isLoadingPin, setIsLoadingPin] = useState(false)
49 |   const [isSubmitting, setIsSubmitting] = useState(false)
50 |   const [pinError, setPinError] = useState('')
51 |   const [formError, setFormError] = useState('')
52 |
53 |   const slideSpring = { type: "spring", damping: 30, stiffness: 350 }
54 |
55 |   useEffect(() => { setFormError('') }, [step])
56 |
57 |   const handlePincodeChange = async (e) => {
58 |     const value = e.target.value.replace(/\D/g, '').slice(0, 6)
59 |     setPincode(value)
60 |     setPinError('')
61 |     if (value.length === 6) {
62 |       setIsLoadingPin(true)
63 |       try {
64 |         const res = await fetch(`https://api.postalpincode.in/pincode/${value}`)
65 |         const data = await res.json()
66 |         if (data && data[0]?.Status === "Success") {
67 |           const po = data[0].PostOffice[0]
68 |           setCity(po.District || po.Block || '')
69 |           setState(po.State || '')
70 |         } else {
71 |           setPinError('Could not find pincode. Please enter City/State manually.')
72 |         }
73 |       } catch (err) {
74 |         setPinError('Network error. Please enter City/State manually.')
75 |       } finally {
76 |         setIsLoadingPin(false)
77 |       }
78 |     }
79 |   }
```

FILE CONTINUED: src\components\product\BuyDrawer.js

```
75 |     }
76 |   }
77 |
78 |   const validateStep2 = () => {
79 |     if (!phone || phone.length < 10) return "Valid 10-digit phone required."
80 |     if (!name) return "Full name is required."
81 |     if (!pincode || pincode.length < 6) return "Valid 6-digit Pincode required."
82 |     if (!city || !state) return "City and State required."
83 |     if (!house) return "House/Flat number required."
84 |     if (!area) return "Street/Area required."
85 |     return ""
86 |   }
87 |
88 |   const handleNextStep = () => {
89 |     if (step === 1) setStep(2)
90 |     else if (step === 2) {
91 |       const error = validateStep2()
92 |       if (error) setFormError(error)
93 |       else setStep(3)
94 |     }
95 |   }
96 |
97 |   // Finalizer function runs AFTER successful payment or immediately for COD
98 |   const finalizeOrder = async (orderData) => {
99 |     const { error } = await supabase.from('orders').insert([orderData])
100 |     if (error) {
101 |       setFormError("Database error. If money was deducted, please contact support.")
102 |       setIsSubmitting(false)
103 |       return
104 |     }
105 |
106 |     await sendOrderAlert(orderData)
107 |
108 |     localStorage.setItem('bkc_recent_order', orderData.order_id)
109 |     localStorage.setItem('bkc_recent_phone', orderData.customer_phone)
110 |
111 |     onClose()
112 |     setTimeout(() => {
113 |       router.push('/success')
114 |       setIsSubmitting(false)
115 |       setStep(1)
116 |       setPaymentMode('prepaid')
117 |     }, 300)
118 |   }
119 |
120 |   const handleOrderSubmit = async () => {
121 |     setIsSubmitting(true)
122 |     setFormError('')
123 |
124 |     const generatedOrderId = 'BKC-' + Math.floor(100000 + Math.random() * 900000)
125 |     const finalPrice = paymentMode === 'prepaid' ? product.prepaidPrice : product.codPrice
126 |     const fullAddress = `${house}, ${area}${landmark ? `, Near ${landmark}` : ''}`
127 |
128 |     const orderData = {
129 |       order_id: generatedOrderId,
130 |       product_name: product.title,
131 |       payment_mode: paymentMode,
132 |       total_amount: finalPrice,
133 |       customer_name: name,
134 |       customer_phone: phone,
135 |       delivery_address: fullAddress,
136 |       city: city,
137 |       state: state,
138 |       pincode: pincode,
139 |       status: 'Order Received'
140 |     }
141 |
142 |     if (paymentMode === 'cod') {
143 |       // Direct to finalize for COD
144 |       await finalizeOrder(orderData)
145 |     } else {
146 |       // RAZORPAY FLOW
147 |       const res = await loadRazorpayScript()
148 |       if (!res) {
149 |         setFormError("Failed to load payment gateway. Check your connection.")
150 |         setIsSubmitting(false)
151 |         return
152 |       }
153 |
154 |       // SECURE: Send product slug instead of amount to prevent tampering
```

FILE CONTINUED: src\components\product\BuyDrawer.js

```
155 |     const data = await fetch('/api/razorpay', {
156 |       method: 'POST',
157 |       headers: { 'Content-Type': 'application/json' },
158 |       body: JSON.stringify({ slug: product.slug }),
159 |     }).then((t) => t.json())
160 |
161 |     if (!data.id) {
162 |       setFormError("Server error. Please try again.")
163 |       setIsSubmitting(false)
164 |       return
165 |     }
166 |
167 |     const options = {
168 |       key: process.env.NEXT_PUBLIC_RAZORPAY_KEY_ID,
169 |       amount: data.amount,
170 |       currency: data.currency,
171 |       name: "BigKidFinds",
172 |       description: product.title,
173 |       order_id: data.id,
174 |       prefill: { name: name, contact: phone },
175 |       theme: { color: "#111827" },
176 |       handler: async function (response) {
177 |         // Success! Mark as Paid and finalize
178 |         orderData.status = `Paid - ${response.razorpay_payment_id}`
179 |         await finalizeOrder(orderData)
180 |       },
181 |     }
182 |
183 |     const paymentObject = new window.Razorpay(options)
184 |     paymentObject.on('payment.failed', function (response) {
185 |       setFormError("Payment failed or cancelled.")
186 |       setIsSubmitting(false)
187 |     })
188 |
189 |     // If user closes window without paying
190 |     paymentObject.on('modal.closed', function() {
191 |       setIsSubmitting(false)
192 |     })
193 |
194 |     paymentObject.open()
195 |   }
196 | }
197 |
198 | const codFee = product.codPrice - product.prepaidPrice
199 | const finalPrice = paymentMode === 'prepaid' ? product.prepaidPrice : product.codPrice
200 |
201 | return (
202 |   <AnimatePresence>
203 |     {isOpen && (
204 |       <>
205 |         <motion.div initial={{ opacity: 0 }} animate={{ opacity: 1 }} exit={{ opacity: 0 }} onClick={onClose} className="fixed inset-0 z-[60] bg-primary/40 backdrop-blur-sm" />
206 |         <motion.div initial={{ y: "100%" }} animate={{ y: 0 }} exit={{ y: "100%" }} transition={slideSpring} className="fixed bottom-0 left-0 right-0 z-[70] mx-auto w-full max-w-md overflow-hidden rounded-t-[2.5rem] bg-surface shadow-2xl flex flex-col max-h-[90vh] pb-safe">
207 |
208 |           <div className="flex items-center justify-between border-b border-border p-5 shrink-0">
209 |             <button onClick={step === 1 ? onClose : () => setStep(step - 1)} className="flex items-center gap-1 text-secondary hover:text-primary transition-colors">
210 |               <ChevronLeft size={18} strokeWidth={2.5} />
211 |               <span className="text-sm font-medium">{step === 1 ? 'Close' : 'Back'}</span>
212 |             </button>
213 |             <div className="text-center">
214 |               <span className="text-[10px] font-bold text-secondary uppercase tracking-widest">Step {step} of 3</span>
215 |             <h3 className="font-bold tracking-tight text-base text-primary">{step === 1 ? 'Payment' : step === 2 ? 'Address' : 'Review'}</h3>
216 |           </div>
217 |           <button onClick={onClose} className="rounded-full bg-background p-2 text-primary hover:bg-border transition-colors">
218 |             <X size={18} strokeWidth={2.5} />
219 |           </button>
220 |         </div>
221 |
222 |         <div className="flex-1 overflow-y-auto p-5 hide-scrollbar">
223 |           {step === 1 && (
224 |             <div className="flex flex-col gap-4">
225 |               <label className="relative flex cursor-pointer flex-col gap-1 rounded-2xl border-2 p-4 transition-all ${paymentMode === 'prepaid' ? 'border-primary bg-primary/5' : 'border-border bg-surface'}">
226 |                 <input type="radio" name="payment" value="prepaid" checked={paymentMode === 'prepaid'} onChange
```

FILE CONTINUED: src\components\product\BuyDrawer.js

```

    =({}) => setPaymentMode('prepaid')) className="sr-only" />
227 |         <div className="flex items-center justify-between">
228 |             <span className="font-bold text-primary flex items-center gap-2"><CreditCard size={18} /> Pay
    Online</span>
229 |             <span className="text-lg font-black text-primary">■{product.prepaidPrice}</span>
230 |         </div>
231 |         <p className="text-xs text-secondary mt-1">UPI, Cards, NetBanking. Dispatched instantly.</p>
232 |         <div className="absolute -top-3 right-4 bg-primary text-surface text-[9px] font-black px-2.5 py
-0.5 rounded-full uppercase tracking-wider">Save ■{codFee}</div>
233 |     </label>
234 |
235 |     {product.isCodAvailable && (
236 |         <label className={`flex cursor-pointer flex-col gap-1 rounded-2xl border-2 p-4 transition-all $
{paymentMode === 'cod' ? 'border-primary bg-primary/5' : 'border-border bg-surface opacity-80'}`}>
237 |             <input type="radio" name="payment" value="cod" checked={paymentMode === 'cod'} onChange={() =
> setPaymentMode('cod')} className="sr-only" />
238 |             <div className="flex items-center justify-between">
239 |                 <span className="font-bold text-primary flex items-center gap-2"><Landmark size={18} /> Cas
h on Delivery</span>
240 |                 <span className="text-lg font-bold text-primary">■{product.codPrice}</span>
241 |             </div>
242 |             <p className="text-xs text-secondary mt-1">Pay with cash when package arrives.</p>
243 |             <div className="mt-2 text-[10px] font-medium text-secondary bg-background border border-borde
r p-2.5 rounded-xl flex gap-2">
244 |                 <ShieldCheck size={14} className="shrink-0 text-primary" /> Includes ■{codFee} extra COD c
onvenience fee.
245 |             </div>
246 |         </label>
247 |     )}
248 | </div>
249 | )}
250 |
251 | {step === 2 && (
252 |     <div className="flex flex-col gap-4">
253 |         <FormField label="Phone Number" id="phone" type="tel" value={phone} onChange={(e) => setPhone(e.t
arget.value.replace(/\D/g, '').slice(0, 10))} placeholder="10-digit mobile number" />
254 |         <FormField label="Full Name" id="name" value={name} onChange={(e) => setName(e.target.value)} pla
ceholder="Your first and last name" />
255 |         <div className="grid grid-cols-2 gap-3 relative">
256 |             <FormField label="Pincode" id="pincode" type="tel" value={pincode} onChange={handlePincodeChang
e} placeholder="6-digit Pincode" />
257 |             {isLoadingPin && <Loader2 size={16} className="animate-spin absolute left-1/2 -ml-6 top-10 text
-secondary" />}
258 |             <FormField label="City / District" id="city" value={city} onChange={(e) => setCity(e.target.val
ue)} placeholder="City" />
259 |         </div>
260 |         {pinError && <span className="text-xs font-bold text-red-500">{pinError}</span>}
261 |         <FormField label="State" id="state" value={state} onChange={(e) => setState(e.target.value)} plac
eholder="State" />
262 |         <FormField label="House / Flat No, Building" id="house" value={house} onChange={(e) => setHouse(e
.target.value)} placeholder="e.g., Flat 402, Royal Enclave" />
263 |         <FormField label="Street / Area / Locality" id="area" value={area} onChange={(e) => setArea(e.tar
get.value)} placeholder="e.g., MG Road" />
264 |         <FormField label="Landmark" id="landmark" value={landmark} onChange={(e) => setLandmark(e.target.
value)} placeholder="e.g., Opp. Metro" optional />
265 |     </div>
266 | )}
267 |
268 | {step === 3 && (
269 |     <div className="flex flex-col gap-4">
270 |         <div className="rounded-2xl border border-border p-4 bg-background flex flex-col gap-2">
271 |             <h5 className="text-xs font-bold uppercase tracking-wider text-secondary">Ship To</h5>
272 |             <p className="text-sm font-bold">{name}</p>
273 |             <p className="text-xs text-secondary leading-relaxed font-medium">{house}, {area}, {landmark} &&
`$${landmark},` {city}, {state} - {pincode}</p>
274 |             <p className="text-xs font-semibold text-secondary mt-1">Contact: {phone}</p>
275 |         </div>
276 |         <div className="flex flex-col gap-2 p-1">
277 |             <div className="flex justify-between text-sm font-medium text-secondary"><span>Items</span><spa
n>■{product.prepaidPrice}</span></div>
278 |             <div className="flex justify-between text-sm font-medium text-secondary"><span>Shipping Fee</sp
an><span><span className="text-emerald-600 font-bold">FREE</span></span></div>
279 |             {paymentMode === 'cod' && (
280 |                 <div className="flex justify-between text-sm font-medium text-secondary"><span>COD Fee</span>
<span>■{codFee}</span></div>
281 |             )}
282 |             <hr className="border-border my-1" />
283 |             <div className="flex justify-between text-base font-black text-primary"><span>Total Amount</spa
n><span>■{finalPrice}</span></div>
284 |         </div>

```

FILE CONTINUED: src\components\product\BuyDrawer.js

```
285 |         <p className="text-[11px] leading-relaxed text-secondary/70 bg-[#F3F4F6] p-3 rounded-xl">
286 |             By clicking below you agree to our Terms and authorize BigKidFinds to fulfill this delivery via
287 |             our verified partners.
288 |         </p>
289 |     </div>
290 |     )}
291 |     {formError && <div className="mt-4 p-3 rounded-xl bg-red-50 border border-red-200 text-xs font-bold t
ext-red-500">{formError}</div>}
292 |     </div>
293 |
294 |     <div className="shrink-0 border-t border-border p-5 bg-surface pb-safe">
295 |         {step < 3 ? (
296 |             <motion.button whileTap={{ scale: 0.97 }} onClick={handleNextStep} className="w-full rounded-2xl bg
-primary h-14 flex items-center justify-center text-sm font-bold text-surface transition-transform gap-2">
297 |                 Continue <ArrowRight size={16} />
298 |             </motion.button>
299 |         ) : (
300 |             <motion.button disabled={isSubmitting} whileTap={!isSubmitting ? { scale: 0.97 } : {}} onClick={han
dleOrderSubmit} className="w-full rounded-2xl bg-primary h-14 flex items-center justify-center text-sm font-bold te
xt-surface transition-transform disabled:opacity-80 disabled:cursor-not-allowed">
301 |                 {isSubmitting ? <Loader2 className="animate-spin" size={20} /> : (paymentMode === 'prepaid' ? `Pa
y Online • 🟦${finalPrice}` : `Place COD Order • 🟦${finalPrice}`)}
302 |             </motion.button>
303 |         )}
304 |     </div>
305 | </motion.div>
306 | </>
307 | )}
308 | </AnimatePresence>
309 | )
310 | }
```

FILE: src\components\shared\InstaBrowserWarning.js

```
1 | "use client"
2 | import { useEffect, useState } from 'react'
3 |
4 | export default function InstaBrowserWarning() {
5 |   const [isInsta, setIsInsta] = useState(false)
6 |
7 |   useEffect(() => {
8 |     // Detects if the user is trapped inside Instagram's internal browser
9 |     if (navigator.userAgent.includes('Instagram')) {
10 |       setIsInsta(true)
11 |     }
12 |   }, [])
13 |
14 |   if (!isInsta) return null
15 |
16 |   return (
17 |     <div className="bg-primary text-surface text-[11px] text-center py-2 px-4 font-medium tracking-wide">
18 |       For faster checkout, tap <span className="font-bold tracking-widest">•••</span> at the top and select <span c
19 |       lassName="font-bold underline">Open in Browser</span>
20 |     </div>
21 |   )
22 | }
```

FILE: src\components\shared\ProductCard.js

```
1 | import Link from 'next/link'
2 |
3 | export default function ProductCard({ product }) {
4 |   return (
5 |     <Link href={`\product/${product.slug}`} className="group flex flex-col gap-2">
6 |       <div className="relative aspect-square w-full overflow-hidden rounded-2xl bg-[#F3F4F6] border border-border">
7 |         {product.discountBadge && (
8 |           <div className="absolute top-2 left-2 z-10 rounded-full bg-primary px-2 py-1 text-[10px] font-bold text-s
9 |             urface uppercase tracking-wider">
10 |               {product.discountBadge}
11 |             </div>
12 |           )}
13 |         <img
14 |           src={product.imageUrl}
15 |           alt={product.title}
16 |           className="h-full w-full object-contain p-2 transition-transform duration-500 group-hover:scale-105"
17 |         />
18 |       </div>
19 |
20 |       <div className="flex flex-col px-1">
21 |         <h3 className="text-sm font-medium leading-tight line-clamp-1">{product.title}</h3>
22 |         <div className="mt-1 flex items-baseline gap-2">
23 |           <span className="text-sm font-bold">■{product.prepaidPrice}</span>
24 |           {product.isCodAvailable && (
25 |             <span className="text-[10px] font-medium text-secondary bg-border/50 px-1.5 py-0.5 rounded-md">
26 |               COD Available
27 |             </span>
28 |           )}
29 |         </div>
30 |       </div>
31 |     </Link>
32 |   )
33 | }
```

FILE: src\lib\supabase.js

```
1 | import { createClient } from '@supabase/supabase-js'
2 |
3 | const supabaseUrl = process.env.NEXT_PUBLIC_SUPABASE_URL
4 | const supabaseAnonKey = process.env.NEXT_PUBLIC_SUPABASE_ANON_KEY
5 |
6 | export const supabase = createClient(supabaseUrl, supabaseAnonKey)
```

FILE: src\sanity\env.js

```
1 | export const apiVersion =  
2 |   process.env.NEXT_PUBLIC_SANITY_API_VERSION || '2026-07-14'  
3 |  
4 | export const dataset = process.env.NEXT_PUBLIC_SANITY_DATASET;  
5 | export const projectId = process.env.NEXT_PUBLIC_SANITY_PROJECT_ID;
```

FILE: src\sanity\lib\client.js

```
1 | import { createClient } from 'next-sanity'
2 |
3 | import { apiVersion, dataset, projectId } from '../env'
4 |
5 | export const client = createClient({
6 |   projectId,
7 |   dataset,
8 |   apiVersion,
9 |   useCdn: false, // Set to false if statically generating pages, using ISR or tag-based revalidation
10 | })
```

FILE: src\sanity\lib\image.js

```
1 | import createImageUrlBuilder from '@sanity/image-url'
2 |
3 | import { dataset, projectId } from '../env'
4 |
5 | // https://www.sanity.io/docs/image-url
6 | const builder = createImageUrlBuilder({ projectId, dataset })
7 |
8 | export const urlFor = (source) => {
9 |   return builder.image(source)
10 | }
```

FILE: src\sanity\liblive.js

```
1 | // Querying with "sanityFetch" will keep content automatically updated
2 | // Before using it, import and render "<SanityLive />" in your layout, see
3 | // https://github.com/sanity-io/next-sanity#live-content-api for more information.
4 | import { defineLive } from "next-sanity/live";
5 | import { client } from './client'
6 |
7 | export const { sanityFetch, SanityLive } = defineLive({
8 |   client,
9 | });
```

FILE: src\sanity\lib\sanity.js

```
1 | import { createClient } from '@sanity/client'
2 | import imageUrlBuilder from '@sanity/image-url'
3 |
4 | export const client = createClient({
5 |   projectId: process.env.NEXT_PUBLIC_SANITY_PROJECT_ID,
6 |   dataset: process.env.NEXT_PUBLIC_SANITY_DATASET,
7 |   apiVersion: '2024-03-01',
8 |   useCdn: true, // This makes loading insanely fast
9 | })
10 |
11 | const builder = imageUrlBuilder(client)
12 |
13 | export function urlFor(source) {
14 |   return builder.image(source)
15 | }
```

FILE: src\sanity\schemaTypes\collection.js

```
1 | export default {
2 |   name: 'collection',
3 |   title: 'Collections',
4 |   type: 'document',
5 |   fields: [
6 |     {
7 |       name: 'title',
8 |       title: 'Collection Title',
9 |       type: 'string',
10 |       validation: (Rule) => Rule.required(),
11 |     },
12 |     {
13 |       name: 'slug',
14 |       title: 'URL Slug',
15 |       type: 'slug',
16 |       options: { source: 'title', maxLength: 96 },
17 |       validation: (Rule) => Rule.required(),
18 |     },
19 |     {
20 |       name: 'shortDescription',
21 |       title: 'Short Description',
22 |       type: 'string',
23 |     },
24 |     {
25 |       name: 'image',
26 |       title: 'Collection Cover Image',
27 |       type: 'image',
28 |       options: { hotspot: true },
29 |     },
30 |   ],
31 | }
```

FILE: src\sanity\schemaTypes\index.js

```
1 | import collection from './collection'
2 | import product from './product'
3 |
4 | export const schema = {
5 |   types: [collection, product],
6 | }
```

FILE: src\sanity\schemaTypes\product.js

```
1 | export default {
2 |   name: 'product',
3 |   title: 'Products',
4 |   type: 'document',
5 |   groups: [
6 |     { name: 'basics', title: 'Basic Info', default: true },
7 |     { name: 'pricing', title: 'Pricing & COD' },
8 |     { name: 'media', title: 'Images & Text' },
9 |   ],
10 |   fields: [
11 |     // --- BASIC INFO TAB ---
12 |     {
13 |       name: 'isActive',
14 |       title: 'Product is Active (Visible on site)',
15 |       type: 'boolean',
16 |       initialValue: true,
17 |       group: 'basics',
18 |     },
19 |     {
20 |       name: 'title',
21 |       title: 'Product Name',
22 |       type: 'string',
23 |       validation: (Rule) => Rule.required(),
24 |       group: 'basics',
25 |     },
26 |     {
27 |       name: 'slug',
28 |       title: 'URL Slug',
29 |       type: 'slug',
30 |       options: { source: 'title', maxLength: 96 },
31 |       validation: (Rule) => Rule.required(),
32 |       group: 'basics',
33 |     },
34 |     {
35 |       name: 'collection',
36 |       title: 'Category / Collection',
37 |       type: 'reference',
38 |       to: [{ type: 'collection' }],
39 |       group: 'basics',
40 |     },
41 |
42 |     // --- PRICING & COD TAB ---
43 |     {
44 |       name: 'prepaidPrice',
45 |       title: 'Prepaid Price (■)',
46 |       type: 'number',
47 |       validation: (Rule) => Rule.required(),
48 |       group: 'pricing',
49 |     },
50 |     {
51 |       name: 'isCodAvailable',
52 |       title: 'Is COD Available?',
53 |       type: 'boolean',
54 |       initialValue: true,
55 |       group: 'pricing',
56 |     },
57 |     {
58 |       name: 'codPrice',
59 |       title: 'COD Price (■)',
60 |       type: 'number',
61 |       hidden: ({ document }) => !document?.isCodAvailable,
62 |       group: 'pricing',
63 |       description: 'Usually Prepaid Price + ■49-■99 for COD fee',
64 |     },
65 |     {
66 |       name: 'discountBadge',
67 |       title: 'Discount Badge Text (Optional)',
68 |       type: 'string',
69 |       group: 'pricing',
70 |       description: 'e.g., "20% OFF" or "Trending"',
71 |     },
72 |     {
73 |       name: 'deliveryEstimate',
74 |       title: 'Delivery Estimate',
75 |       type: 'string',
76 |       initialValue: '5-7 Days',
77 |       group: 'pricing',
78 |     },
79 |   ],
```

FILE CONTINUED: src\sanity\schemaTypes\product.js

```
80 | // --- IMAGES & TEXT TAB ---
81 | {
82 |   name: 'gallery',
83 |   title: 'Product Images (Minimum 3, First is Hero)',
84 |   type: 'array',
85 |   of: [{ type: 'image', options: { hotspot: true } }],
86 |   validation: (Rule) => Rule.required().min(1),
87 |   group: 'media',
88 | },
89 | {
90 |   name: 'tagline',
91 |   title: 'Short Hook / One-Liner',
92 |   type: 'string',
93 |   group: 'media',
94 |   description: 'e.g., "The desk lamp you didn\'t know you needed."',
95 | },
96 | {
97 |   name: 'highlights',
98 |   title: 'Bullet Highlights (Max 4)',
99 |   type: 'array',
100 |   of: [{ type: 'string' }],
101 |   validation: (Rule) => Rule.max(4),
102 |   group: 'media',
103 | },
104 | ],
105 | }
```

FILE: src\sanity\structure.js

```
1 | // https://www.sanity.io/docs/structure-builder-cheat-sheet
2 | export const structure = (S) =>
3 |   S.list()
4 |     .title('Content')
5 |     .items(S.documentTypeListItems())
```

FILE: tailwind.config.js

```
1 | /** @type {import('tailwindcss').Config} */
2 | module.exports = {
3 |   content: [
4 |     "./src/pages/**/*..{js,ts,jsx,tsx,mdx}",
5 |     "./src/components/**/*..{js,ts,jsx,tsx,mdx}",
6 |     "./src/app/**/*..{js,ts,jsx,tsx,mdx}",
7 |   ],
8 |   theme: {
9 |     extend: {
10 |       colors: {
11 |         background: "#FAFAFA", // Premium off-white, reduces eye strain
12 |         surface: "#FFFFFF",
13 |         primary: "#111827", // Deep charcoal instead of cheap pure black
14 |         secondary: "#4B5563",
15 |         border: "#E5E7EB",
16 |         accent: "#3B82F6", // Subtle blue for specific highlights if needed
17 |       },
18 |       animation: {
19 |         'slide-up': 'slideUp 0.4s cubic-bezier(0.16, 1, 0.3, 1)',
20 |         'fade-in': 'fadeIn 0.3s ease-out',
21 |       },
22 |       keyframes: {
23 |         slideUp: {
24 |           '0%': { transform: 'translateY(100%)' },
25 |           '100%': { transform: 'translateY(0)' },
26 |         },
27 |         fadeIn: {
28 |           '0%': { opacity: '0' },
29 |           '100%': { opacity: '1' },
30 |         }
31 |       }
32 |     },
33 |   },
34 |   plugins: [],
35 | };
```