# ARDUINO
# NANO RP2040 CONNECT

STORE.ARDUINO.CC/NANO-RP2040-CONNECT




- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default

⚠ **MAXIMUM** I/O supply voltage is 3.63V

⚠ **MAXIMUM** GPIO input voltage is 3.3V

⚠ **MAXIMUM** sum of all current being sunk into GPIO and QSPI pins is 50mA

**VIN** Input voltage to the board.

ARDUINO.CC

**Last update: 3/11/2021**

This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.

# ARDUINO
# NANO RP2040 CONNECT

STORE.ARDUINO.CC/NANO-RP2040-CONNECT




- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default
- Analog
- Communication
- Timer
- GPIO

⚠ **MAXIMUM** I/O supply voltage is 3.63V

⚠ **MAXIMUM** GPIO input voltage is 3.3V

⚠ **MAXIMUM** sum of all current being sunk into GPIO and QSPI pins is 50mA

**VIN** Input voltage to the board.

ARDUINO.CC

**Last update: 3/11/2021**

This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.

# ARDUINO
# NANO RP2040 CONNECT

STORE.ARDUINO.CC/NANO-RP2040-CONNECT




- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default
- Analog
- Communication
- Timer
- GPIO

**MAXIMUM** I/O supply voltage is 3.63V

**MAXIMUM** GPIO input voltage is 3.3V

**MAXIMUM** sum of all current being sunk into GPIO and QSPI pins is 50mA

**VIN** Input voltage to the board.

ARDUINO.CC

**Last update: 3/11/2021**

This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.




- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default
- Analog
- Communication
- Timer
- GPIO

**MAXIMUM** I/O supply voltage is 3.63V

**MAXIMUM** GPIO input voltage is 3.3V

**MAXIMUM** sum of all current being sunk into GPIO and QSPI pins is 50mA

**VIN** Input voltage to the board.



This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.




- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default
- Analog
- Communication
- Timer
- GPIO

⚠ **MAXIMUM** I/O supply voltage is 3.63V

⚠ **MAXIMUM** GPIO input voltage is 3.3V

⚠ **MAXIMUM** sum of all current being sunk into GPIO and QSPI pins is 50mA

**VIN** Input voltage to the board.



This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.




Ground
Power
LED
Internal Pin
SWD Pin
Digital Pin
Analog Pin
Other Pin
Microcontroller's Port
Default

**MAXIMUM** I/O supply voltage is 3.63V

**MAXIMUM** GPIO input voltage is 3.3V

**MAXIMUM** sum of all current being sunk into GPIO and QSPI pins is 50mA

**VIN** Input voltage to the board.



This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.