【K210开发笔记】#standalone# (1) Kendryte IDE 安装与使用

一、安装


Kendryte IDE 使用手册

1, windows

- 1. 下载 Kendryte IDE (BETA)
- 2. 解压后双击文件夹里面的 KendryteIDE.bat 安装
- 3. 【问题解决】K210 windows下Kendryte IDE安装出错问题解决

2, linux


安装后的界面:



二、使用


1、下载软件包

注意: 软件包不要放在中文路径下



2、安装项目依赖

初次使用直接点击 安装全部项目依赖:




3、编译

点击下面 构建 按钮编译项目:



编译完成:



4. 烧录

点击下面的 点击选择刷写器默认串口设备 按钮选择对应的串口:





点击下面的 构建和刷写 按钮开始烧录:



烧录完成:

```
搜索问题 输出调试控制台 终端 串口
[ INFO] Failed to boot as KD233: Timeout greeting kd233 board
[ INFO] try reboot as other board
[ INFO] - Hello.
[ INFO] Writing boot loader to memory (at 0x80000000)
[ INFO] Writing memory with 1024 chunk size. total bytes = 36224, chunk = 36
[ INFO] - speed: 10.50KB/s
[ INFO] - Complete.
[ INFO] Boot from memory: 0x80000000.
  INFO] boot command sent
[ INFO] - Greeting 1.
[ INFO]
           - got hello.
[ INFO] Select flash: InChip
  INFO] - Complete.
[ INFO] Downloading program to flash
[ INFO] Writing flash with 4096 chunk size. total bytes = 58853, chunk = 15
[ INFO] - speed: 8.90KB/s
[ INFO] - Complete.
[ INFO] finished.
  INFO]
  INFO] Program successfully flashed to the board.https://blog.csdn.net/p1279030826
```