/v3/api-docs

Explore

OpenAPI definition

v0 OAS 3.1

/v3/api-docs

Servers

http://localhost:8082 - Generated server url

hunt-log-controller

GET /api/hunts/

Parameters

Try it out

Name	Description
criminal_id integer($int64) *(query)*	criminal_id

Responses

Code	Description	Links
200	OK Media type */* Controls `Accept` header. **Example Value** Schema {}	*No links*

POST /api/hunts/

Parameters Try it out

No parameters

Request body required application/json

Example Value Schema

```
{
  "criminalId": 0,
  "success": true,
  "notes": "string"
}
```

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. **Example Value** Schema {}	*No links*

GET /api/hunts/{id}

Parameters Try it out

Name	Description
id * required integer($int64) *(path)*	id

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. **Example Value** Schema {}	*No links*

DELETE /api/hunts/{id}

Parameters Try it out

Name	Description
id * required integer($int64) *(path)*	id

Responses

Code	Description	Links
200	OK Media type */* Controls `Accept` header. **Example Value** Schema {}	*No links*

PATCH /api/hunts/{id}

Parameters

Try it out

Name	Description
id * required integer($int64) *(path)*	id

Request body required

application/json

Example Value Schema


```
{
  "criminalId": 0,
  "success": true,
  "notes": "string"
}
```

Responses

Code	Description	Links
200	OK Media type */* Controls `Accept` header. **Example Value** Schema {}	*No links*

criminal-log-controller

GET /api/criminals/

Parameters

Try it out

Name	Description
min_reward integer($int32) *(query)*	min_reward
max_reward integer($int32) *(query)*	max_reward
armed boolean *(query)*	--
has_crew boolean *(query)*	--
escape_master boolean *(query)*	--

Name	Description
sort `string` *(query)*	sort

Responses

Code	Description	Links
200	OK Media type */* Controls `Accept` header. **Example Value** Schema {}	*No links*

POST /api/criminals/

Parameters

Try it out

No parameters

Request body required

application/json

Example Value Schema

```
{
  "name": "string",
  "nickname": "string",
  "reward": 0,
  "lastKnownCoordinate": "string",
  "difficulty": 0,
  "armed": true,
  "hasCrew": true,
  "escapeMaster": true
}
```

Responses

Code	Description	Links
200	OK Media type */* Controls `Accept` header. **Example Value** Schema {}	*No links*

GET /api/criminals/{id}

Parameters

Try it out

Name	Description
id * required integer($int64) *(path)*	id

Responses

Code	Description	Links
200	OK Media type */* Controls `Accept` header. **Example Value** Schema {}	*No links*

Schemas

SaveLogDto ›

Expand all `object`

CriminalDto ›

Expand all `object`