



PROTOCOL SECURITY & MAXIMUM EXTRACTABLE VALUE

Fundamentals of Distributed Trust

Dissecting low-level smart contract vulnerabilities, predatory transaction dynamics in the public mempool, and the architecture of Proposer-Builder Separation (PBS).


THE ADVERSARIAL ENVIRONMENT

Traditional Systems / Web2	Decentralized Systems / Web3
- Closed servers and firewalled databases. - Private transactions with reversible state. - Recourse available via banks or legal intervention.	- Public bytecode and globally transparent state. - Deterministic, strictly immutable execution. - Zero emergency pauses; no legal recourse.

The Dark Forest (Public Mempool)

Thousands of algorithmic bots monitor unconfirmed transactions 24/7. Any logical flaw is exploited in milliseconds without warning and without legal recourse.

VULNERABILITY: REENTRANCY ATTACK



The Mechanism: Occurs when a contract calls an external address before resolving its internal state updates.

The Exploit: Transferring coins hands execution control to the receiver's fallback function. The attacker re-enters the target's function before their balance is set to zero.

Historical Impact: The 2016 DAO Hack. 3.6M ETH drained, resulting in the Ethereum / Ethereum Classic hard fork.

VULNERABILITY: ARITHMETIC & ACCESS

Integer Overflow & Underflow

- **Pre-Solidity 0.8.0:** Integers suffered **silent wraparound**. Subtracting 1 from a zero-value uint256 yielded a massive $2^{256} - 1$. External libraries (SafeMath) were mandatory.
- **Solidity 0.8.0+:** Compilers include native checks that automatically revert transactions on overflow—unless explicitly bypassed using unchecked { ... } blocks for gas optimization.



Access Control Failures

- **The Threat:** Neglecting visibility and access modifiers on critical functions (ownership, minting, initialization).
- **Historical Impact:** The 2017 Parity Multi-Sig hack. An unprotected initialization function allowed an attacker to call `initWallet()`, claim ownership, and execute `selfdestruct()`, permanently freezing 513,774 ETH.



SMART CONTRACT DEFENSE ARCHITECTURE

1

Checks-Effects-Interactions (CEI)

The absolute standard for state updates.
Checks: Validate inputs (require).
Effects: Update internal state variables.
Interactions: Call external addresses last.

2

Mutex Guards

Semaphore locks (e.g., OpenZeppelin `nonReentrant`). Flags a boolean before execution and reverts if a second call attempts entry before the first resolves.

3

Invariant Fuzzing

Tools (Foundry, Echidna) bombard contracts with millions of randomized transaction combinations to break defined absolute mathematical states (invariants).

4

Formal Verification

Tools (Certora, Halmos) convert contract logic into mathematical propositions, using theorem provers to cryptographically guarantee code contains no hidden logical flaws.

MAXIMUM EXTRACTABLE VALUE (MEV)

Formalized in Flash Boys 2.0 (Daian et al., 2019). The maximum value extractable from block production beyond standard block rewards and gas fees, achieved by including, excluding, or **altering the chronological order** of transactions.

Front-Running

Searcher bots detect highly profitable pending transactions and broadcast copies with a higher priority gas fee to be mined first.

Back-Running

Bots detect massive AMM trades that alter price ratios, placing their transaction directly behind the victim to capture instant arbitrage.

Automated Liquidations

Bots monitor lending protocols (Aave, Compound) 24/7, engaging in Priority Gas Auctions (PGAs) to execute liquidations the millisecond collateral drops.

PREDATORY EXTRACTION: THE SANDWICH ATTACK



The Target:

Retail traders executing DEX swaps with overly loose slippage tolerance.

The Execution:

A searcher bot identifies the pending buy order. The bot crafts a three-part bundle executed sequentially within the exact same block.

The Result:

The attacker extracts risk-free market margins. The victim suffers direct financial loss, receiving significantly fewer tokens than intended.

THE MEV CENTRALIZATION THREAT


Solo Home Stakers	Institutional Cartels
- Lack algorithmic infrastructure to compete in High-Frequency Trading (HFT). - Yield limited strictly to base issuance (e.g., ~4% APR). - Highly vulnerable to capital flight.	- Data centers partnered with specialized HFT firms. - Yield boosted massively by sophisticated MEV extraction (e.g., 10-15% APR). - Attracts global staking capital through superior returns.

The Systemic Risk

Rational market dynamics dictate capital flows to the highest yield. Unchecked MEV naturally centralizes the validator set into a coordinated oligarchy, destroying consensus decentralization.

PROTOCOL DEFENSE: PROPOSER-BUILDER SEPARATION (PBS)

The architectural solution to democratize MEV and protect solo stakers by unbundling block construction.



1. Searchers: Algorithms that find arbitrage, package transactions into bundles, and route them.

2. Block Builders: High-power specialized servers that assemble bundles and mempool transactions into the most profitable blocks, bidding for inclusion.

3. Relays: Neutral escrow intermediaries that validate block contents and prevent fraud before signatures.

4. Block Proposers (Validators): Solo stakers simply select and sign the highest-bidding blind header, receiving massive MEV rewards without running HFT infrastructure.

USER DEFENSE: ROUTING AROUND THE MEMPOOL

1.

Private RPC Endpoints (Flashbots Protect)



- Users bypass the public mempool **entirely** by pointing their wallet to a private RPC endpoint.
- Transactions are routed through encrypted tunnels directly to trusted Block Builders.
- **Completely neutralizes Sandwich Attacks and Front-Running**, as predator bots cannot see the pending state.

2.

Order Flow Auctions (MEV-Share, MEV-Blocker)



- If a user's transaction naturally creates unavoidable arbitrage value, the protocol auctions that right to registered searchers in a controlled environment.
- Up to **90%** of the extracted arbitrage profit is routed automatically back to the original user's wallet as **MEV Cashback**, transforming a predatory threat into user yield.