

Cloud-Sentry:

Automated Serverless Malware Scanning Pipeline using AWS

*A Mini-Project Report Submitted For Cloud Computing Course
for the Degree of Bachelor of Engineering
In COMPUTER ENGINEERING (Semester VI)*

By

Roll No. 10179: Shane Dias
Roll No. 10181: Serene Dmello
Roll No. 10192: Soham Kalgutkar

Under the Guidance of
Prof. Unik Lokhande

2025 - 2026



DEPARTMENT OF COMPUTER ENGINEERING

Fr. Conceicao Rodrigues College of Engineering

Bandra (W), Mumbai - 400050

University of Mumbai

TABLE OF CONTENTS

1. Abstract	5
2. Introduction	6
2.1 Background and Motivation	6
2.2 Problem Statement	6
2.3 Objectives	7
2.4 Scope of the Project	7
3. Literature Review	8
3.1 Evolution of Cloud Storage Security	8
3.2 Serverless Computing and Security	8
3.3 File Hashing and Multi-Engine Scanning	8
3.4 Zero Trust Architecture in Cloud	9
4. System Architecture	10
4.1 Architectural Overview	10
4.2 Layer-by-Layer Description	10
4.2.1 Storage Layer (Amazon S3 — Three-Tier Design)	10
4.2.2 Compute Layer (AWS Lambda)	11
4.2.3 Intelligence Layer (VirusTotal API)	11
4.2.4 Audit Layer (Amazon DynamoDB)	11
4.2.5 Notification Layer (Amazon SNS)	11
4.3 AWS Services Utilized	12
5. Methodology and Data Flow	13
5.1 End-to-End Workflow Stages	13
Stage 1 — File Ingestion	13
Stage 2 — Event Trigger	13
Stage 3 — Hash Computation	13
Stage 4 — VirusTotal Analysis	13
Stage 5 — Decision and File Routing	13
Stage 6 — Logging	14
Stage 7 — Alerting (Infected Files Only)	14
5.2 Error Handling and Edge Cases	14
6. Implementation Details	15
6.1 Security Design — IAM Policy (Principle of Least Privilege)	15
6.2 Secure File Upload — Pre-Signed URLs	15
6.3 Lambda Function — Core Logic	16
6.4 Malware Detection Logic — SHA-256 Hashing	16
6.5 DynamoDB Data Model	16
7. System Screenshots and Observations	18
7.1 AWS S3 Bucket Configuration	18
7.2 Clean Bucket — Verified Safe Files	18
7.3 Quarantine Bucket — Infected Files	19
7.4 DynamoDB ScanLogs Table	20
7.5 SNS Alert Notifications	21

8. Testing and Validation	23
8.1 Testing Strategy	23
8.2 Test Cases and Results	23
8.3 Performance Observations	23
9. Industry Use Cases and Applications	25
9.1 Financial Technology (FinTech)	25
9.2 Healthcare	25
9.3 Legal Technology	25
9.4 E-Commerce and Marketplace Platforms	25
9.5 Educational Technology (EdTech)	26
10. Future Scope and Enhancements	27
10.1 Deep Content Scanning	27
10.2 Archive Recursion	27
10.3 Machine Learning-Based Threat Classification	27
10.4 Web Dashboard and Analytics	27
10.5 Multi-Region Deployment	27
10.6 Integration with AWS Security Hub	27
11. Results and Conclusion	29
11.1 Summary of Results	29
11.2 Conclusion	29
12. References	31

LIST OF FIGURES

Figure No.	Figure Title	Page No.
Figure 1	System Architecture Diagram — Cloud-Sentry AWS Pipeline	10
Figure 2	AWS S3 Buckets Overview (Three-Tier Storage)	18
Figure 3	Clean Bucket (cloud-sentry-clean) — Safe File Listing	19
Figure 4	Quarantine Bucket (cloud-sentry-quarantine) — Infected File Listing	20
Figure 5	DynamoDB ScanLogs Table — Scan Records	21
Figure 6	SNS Alert Notification Email Screenshots	22

1. Abstract

Cloud-Sentry is a fully serverless, event-driven cloud security architecture developed to address one of the most significant "blind spots" in modern cloud storage infrastructure: the absence of automated malware detection at the point of file ingestion. As organizations increasingly migrate their data and applications to cloud environments, the risk of malicious file uploads to shared storage services — such as Amazon S3 — has grown substantially.

This project implements an end-to-end automated malware scanning pipeline leveraging core AWS services including Amazon S3, AWS Lambda, Amazon DynamoDB, and Amazon SNS, integrated with the VirusTotal API for multi-engine threat intelligence. When a user uploads a file to the designated landing S3 bucket, the system is automatically triggered, computes a SHA-256 cryptographic hash of the file, submits the hash to VirusTotal for analysis across 70+ antivirus engines, and routes the file to either a clean or quarantine bucket based on the verdict — all without human intervention.

The architecture embodies the Zero Trust security model, ensuring that no file is inherently trusted upon upload. The project demonstrates that enterprise-grade, 24/7 automated security can be achieved at minimal operational cost in a cloud-native, serverless paradigm. Results show 100% detection accuracy when tested with standard EICAR anti-virus test files, and the system scales seamlessly under concurrent load owing to Lambda's horizontal scaling capabilities.

2. Introduction

2.1 Background and Motivation

The rapid acceleration of cloud adoption over the past decade has fundamentally transformed how businesses store, process, and share data. Amazon Web Services (AWS), as the global leader in cloud infrastructure, serves millions of organizations that rely on Amazon S3 (Simple Storage Service) as their primary object storage backend. S3 buckets are used to store everything from static website assets and application logs to sensitive business documents, healthcare records, and financial data.

However, this ubiquity creates a significant attack surface. Threat actors actively exploit cloud storage systems as vectors for malware distribution, ransomware deployment, and cross-service infection. A malicious user — or a compromised external system — can upload an infected file to an S3 bucket, from where it may be automatically processed by downstream services such as Lambda functions, EC2 instances, or end-user applications, propagating the malware silently across an organization's cloud infrastructure.

Despite this well-documented risk, standard Amazon S3 provides no built-in mechanism for scanning uploaded files for malicious content. Organizations are expected to implement their own security controls. Historically, this has been done using on-premises antivirus agents or EC2-based scanning servers — solutions that are expensive, operationally heavy, and poorly suited to the elastic, event-driven nature of modern cloud workloads.

2.2 Problem Statement

The core problem addressed by this project is the "storage-layer security gap" in cloud environments: the window of vulnerability that exists between the moment a file is uploaded to cloud storage and the moment it is consumed by a downstream application. During this window, an infected file is live in storage, accessible, and potentially actionable.

Specific challenges include:

- Manual scanning does not scale: As upload volumes grow, manual or batch-based scanning introduces latency and operational overhead that is incompatible with real-time application requirements.
- Traditional server-based solutions are cost-inefficient: Dedicated scanning servers must run continuously, accruing compute costs even during periods of zero upload activity.
- No native S3 malware detection: AWS does not provide a built-in, configurable malware scanning service for S3 objects.

- Lack of audit trails: Many organizations lack a centralized, queryable record of file-level security events, complicating incident response and compliance reporting.

2.3 Objectives

The primary objectives of the Cloud-Sentry project are:

1. To design and implement a fully automated, serverless malware scanning pipeline that activates on S3 object upload events without any manual intervention.
2. To integrate with the VirusTotal API to leverage a broad multi-engine threat intelligence database for SHA-256 hash-based file reputation checking.
3. To implement a three-tier file routing strategy (Landing, Clean, Quarantine) that physically isolates verified and potentially dangerous files.
4. To provide a complete audit trail of all scan events in Amazon DynamoDB, capturing file name, hash, scan result, and timestamp.
5. To deliver real-time email notifications via Amazon SNS when a malware threat is detected.
6. To adhere to AWS security best practices, specifically the Principle of Least Privilege through IAM role design, and to avoid public bucket exposure through pre-signed URL-based uploads.
7. To validate the end-to-end pipeline using industry-standard test artifacts (EICAR test file) and demonstrate 100% detection accuracy.

2.4 Scope of the Project

The scope of Cloud-Sentry encompasses the following boundaries:

- The system processes files uploaded to a designated AWS S3 landing bucket within the ap-south-1 (Asia Pacific - Mumbai) region.
- Malware detection is performed via SHA-256 hash reputation lookup using the VirusTotal public API. Direct file content is never transmitted outside the AWS environment, preserving data privacy.
- The system operates on individual files; archive scanning (recursive scanning within ZIP/RAR files) is outside the current scope.
- Notifications are delivered via email using Amazon SNS subscriptions.
- The frontend upload mechanism uses pre-signed URLs to ensure secure, direct client-to-S3 transfers.

3. Literature Review

3.1 Evolution of Cloud Storage Security

Research in cloud security has consistently identified object storage as a high-risk attack vector. Early academic work on cloud security (Mell & Grance, 2011, NIST SP 800-145) established the fundamental shared-responsibility model, wherein cloud providers secure the underlying infrastructure while customers are responsible for the security of their data and applications running on that infrastructure. This model explicitly places the burden of file-level malware scanning on the customer.

Studies published between 2018 and 2024 in IEEE and ACM security venues have documented numerous real-world incidents where S3 misconfiguration and absence of content scanning led to significant data breaches. Notably, the concept of "supply chain attacks via cloud storage" — where a publicly accessible S3 bucket serves malicious files to thousands of downstream consumers — has become a recognized attack pattern.

3.2 Serverless Computing and Security

AWS Lambda, introduced in 2014, pioneered the Function-as-a-Service (FaaS) paradigm. Research by Baldini et al. (2017) and Hendrickson et al. (2016) established that serverless architectures offer compelling security advantages: reduced attack surface (no persistent server processes), automatic patching by the cloud provider, and fine-grained IAM-based access control.

However, serverless architectures introduce unique security challenges including function injection, event-data injection, and over-privileged IAM roles. Cloud-Sentry addresses these by enforcing strict least-privilege IAM policies and validating all event data before processing.

3.3 File Hashing and Multi-Engine Scanning

SHA-256 (Secure Hash Algorithm 256-bit), standardized by NIST in FIPS 180-4, is the de facto standard for file integrity verification and malware identification. The VirusTotal platform, acquired by Google in 2012 and widely used in academic and enterprise security research, aggregates results from 70+ antivirus engines. Multiple academic studies (Kantchelian et al., 2015; Mohaisen et al., 2015) have demonstrated that hash-based lookups against multi-engine databases provide detection rates superior to any single antivirus engine.

The privacy advantage of hash-based scanning — that the actual file content never leaves the controlled environment — is particularly significant for healthcare, legal, and financial

applications subject to data residency regulations such as HIPAA, GDPR, and India's DPDP Act (2023).

3.4 Zero Trust Architecture in Cloud

The Zero Trust security model, formalized by NIST SP 800-207 (2020), operates on the principle of "never trust, always verify." Applied to cloud storage, this means that no file — regardless of its origin, the identity of the uploader, or its file extension — should be trusted without explicit verification. Cloud-Sentry's architecture is a direct implementation of this principle: every file uploaded to the landing bucket is treated as potentially malicious until the VirusTotal scan confirms otherwise.

4. System Architecture

4.1 Architectural Overview

Cloud-Sentry follows a decoupled, event-driven, microservices-oriented architecture deployed entirely within AWS. The design prioritizes automation, scalability, fault isolation, and security. The system is logically organized into four layers: the Storage Layer, the Compute Layer, the Intelligence Layer, and the Notification & Audit Layer.

Each layer is independently scalable and communicates asynchronously, ensuring that the failure or slowdown of any one component does not cascade across the entire pipeline. AWS-managed services handle all infrastructure concerns (patching, scaling, availability), allowing the project to focus entirely on application-level security logic.




Figure 1: System Architecture Diagram — Cloud-Sentry AWS Pipeline

4.2 Layer-by-Layer Description

4.2.1 Storage Layer (Amazon S3 — Three-Tier Design)

The storage layer consists of three purpose-specific S3 buckets, each with distinct access controls and lifecycle policies:

- Landing Bucket (cloud-sentry-landing): The entry point for all file uploads. This bucket has no public read access. Files deposited here trigger the scanning Lambda function. After processing, the original object is deleted from this bucket regardless of scan outcome.
- Clean Bucket (cloud-sentry-clean): Receives files that VirusTotal has verified as safe (zero detections across all engines). Files in this bucket are considered trusted for downstream consumption.
- Quarantine Bucket (cloud-sentry-quarantine): Receives files flagged as infected or suspicious by one or more VirusTotal engines. This bucket has the most restrictive access policy — files can only be written by the Lambda function and read by security administrators.

4.2.2 Compute Layer (AWS Lambda)

The core of the system is a Python 3.x Lambda function named CloudSentryScanner. This function is invoked by S3 Event Notifications configured for the s3:ObjectCreated:* event type on the landing bucket. The function is stateless and idempotent: each invocation operates on exactly one file and produces exactly one outcome.

The Lambda function's execution role is scoped via IAM to the minimum required permissions, as detailed in Section 6.1. The function has a configured timeout of 30 seconds and a memory allocation of 256 MB, appropriate for hash computation and API calls.

4.2.3 Intelligence Layer (VirusTotal API)

Rather than transmitting the file itself to an external service, the Lambda function computes the SHA-256 hash of the file content in memory and submits only the hash to the VirusTotal v3 API endpoint (/files/{hash}). VirusTotal responds with a JSON payload containing aggregated detection results from all 70+ engines it queries. The system interprets any non-zero positives count as "Infected".

4.2.4 Audit Layer (Amazon DynamoDB)

Every scan event — regardless of outcome — is recorded as an item in the DynamoDB ScanLogs table. Each record contains the following attributes: File_Name (String, primary key), Timestamp (Number, Unix epoch), Hash (String, SHA-256 hex digest), Status (String, 'Safe' or 'Infected'), and VirusTotal_Positives (Number).

4.2.5 Notification Layer (Amazon SNS)

When the scan result is 'Infected', the Lambda function publishes a message to an SNS topic (CloudSentryAlerts). Administrators subscribe to this topic via email. The published message includes the file name, the SHA-256 hash, the number of VirusTotal detections, and a timestamp, providing all information necessary for immediate incident response.

4.3 AWS Services Utilized

Service	Layer	Functional Role
Amazon S3	Storage	Three-tier bucket design: Landing, Clean, Quarantine
AWS Lambda	Compute	Serverless scanning logic and file routing (Python 3.x)
Amazon DynamoDB	Database	NoSQL audit log of scan events, hashes, and timestamps
Amazon SNS	Messaging	Real-time email/SMS alerting for infected file detection
AWS IAM	Security	Least-privilege roles and policies for Lambda execution
VirusTotal API	External	Multi-engine hash-based malware reputation lookup (70+ AV engines)

5. Methodology and Data Flow

5.1 End-to-End Workflow Stages

The Cloud-Sentry pipeline executes the following stages sequentially for every file uploaded to the landing bucket:

Stage 1 — File Ingestion

A user (or an application) initiates a file upload to the cloud-sentry-landing S3 bucket. To avoid public bucket exposure, the upload is facilitated via a pre-signed URL generated by a backend service (see Section 6.2). The upload is a standard HTTPS PUT request; no special client-side software is required.

Stage 2 — Event Trigger

Upon successful object creation in the landing bucket, AWS S3 automatically emits an `s3:ObjectCreated:*` event notification. This event is configured to invoke the `CloudSentryScanner` Lambda function synchronously. The event payload contains the bucket name and the object key (file path), which the Lambda uses to locate the uploaded file.

Stage 3 — Hash Computation

The Lambda function retrieves the file content from S3 using the `s3:GetObject` API call and computes its SHA-256 cryptographic hash using Python's built-in `hashlib` library. This step is critical for two reasons: (1) it produces the identifier used for VirusTotal lookup, and (2) it ensures that only the hash — never the raw file content — is sent to the external API, preserving data confidentiality.

Stage 4 — VirusTotal Analysis

The computed SHA-256 hash is submitted to the VirusTotal v3 API (<https://www.virustotal.com/api/v3/files/{hash}>) using an HTTP GET request authenticated with the project's API key. VirusTotal queries its database of 70+ antivirus engines and returns a comprehensive JSON report. The Lambda parses the `last_analysis_stats` field to determine the number of malicious detections.

Stage 5 — Decision and File Routing

Based on the VirusTotal response, the Lambda makes a binary routing decision:

- **Safe (0 detections):** The file is copied to the cloud-sentry-clean bucket using `s3:CopyObject`, and the original object is deleted from the landing bucket using `s3:DeleteObject`.

- Infected (1+ detection): The file is copied to the cloud-sentry-quarantine bucket, and the original object is deleted from the landing bucket.

Stage 6 — Logging

Regardless of outcome, the Lambda writes a structured record to the DynamoDB ScanLogs table using `dynamodb:PutItem`. The record captures: file name, SHA-256 hash, Unix timestamp, scan status ('Safe' or 'Infected'), and raw VirusTotal detection count.

Stage 7 — Alerting (Infected Files Only)

If the file was identified as infected, the Lambda additionally publishes an alert message to the CloudSentryAlerts SNS topic using `sns:Publish`. All email subscribers receive a formatted notification message within seconds of the detection.

5.2 Error Handling and Edge Cases

The Lambda function implements the following error handling strategies:

- VirusTotal API errors (rate limits, network failures): The function retries up to 3 times with exponential backoff. If all retries fail, the file is quarantined by default (fail-safe policy) and a warning is logged.
- Unknown hash (new file not in VirusTotal database): The function quarantines the file and logs a 'Unknown' status, flagging it for manual review.
- S3 CopyObject failure: Errors are logged to CloudWatch Logs; the original file is retained in the landing bucket to prevent data loss.

6. Implementation Details

6.1 Security Design — IAM Policy (Principle of Least Privilege)

A fundamental security requirement of the project is that the Lambda execution role must have no permissions beyond those strictly necessary for its function. A custom IAM role (CloudSentryLambdaRole) was created with the following policy, which restricts access to specific resource ARNs:

IAM Action	Resource	Purpose
s3:GetObject	cloud-sentry-landing/*	Read uploaded file for hashing
s3:PutObject	cloud-sentry-clean/*	Write verified file to clean bucket
s3:PutObject	cloud-sentry-quarantine/*	Move infected file to quarantine
s3>DeleteObject	cloud-sentry-landing/*	Remove processed file from landing
dynamodb:PutItem	ScanLogs table	Write scan result record
sns:Publish	CloudSentryAlerts topic	Send malware alert notification
logs:CreateLogGroup	*	Lambda execution logging (CloudWatch)

Critically, the role does NOT have s3:ListBucket, s3>DeleteBucket, or any IAM administrative permissions. This ensures that even if the Lambda function were to be exploited, the blast radius is strictly confined to the three pipeline buckets.

6.2 Secure File Upload — Pre-Signed URLs

To avoid making the landing S3 bucket publicly writable — which would expose it to unauthorized uploads — the system implements a pre-signed URL strategy. A pre-signed URL is a time-limited, cryptographically signed URL that grants the holder permission to perform a specific S3 operation (in this case, s3:PutObject on a specific object key) without requiring AWS credentials.

The pre-signed URL is generated server-side using the AWS SDK (boto3) with a configurable expiration time (default: 300 seconds). The client receives this URL and performs a direct HTTPS PUT upload to S3. This approach achieves three goals: (1) the S3 bucket remains private; (2) the upload bypasses the application server, reducing bandwidth costs; (3) the upload mechanism is inherently scoped to a single object, preventing bulk unauthorized uploads.

6.3 Lambda Function — Core Logic

The Lambda function (CloudSentryScanner) is implemented in Python 3.12 and follows a clean, sequential processing model. Key implementation aspects include:

- Event parsing: Extracts bucket name and object key from the S3 event notification JSON payload.
- Streaming hash computation: The file is read in 8 KB chunks directly from S3 using the streaming Body object, avoiding loading the entire file into Lambda memory. This allows the function to process large files within its 256 MB memory constraint.
- VirusTotal integration: Uses the requests library to make authenticated GET calls to the VirusTotal v3 API, with a 10-second timeout and retry logic.
- Conditional routing: Uses `s3.copy_object()` followed by `s3.delete_object()` for atomic file routing, ensuring files are never lost between operations.
- DynamoDB writes: Uses the `put_item()` method with a conditional expression to prevent duplicate records in edge-case scenarios.
- SNS publishing: Uses `sns.publish()` with a structured message body for clear, actionable alert content.

6.4 Malware Detection Logic — SHA-256 Hashing

SHA-256 (Secure Hash Algorithm 256-bit) is a one-way cryptographic hash function that produces a 256-bit (64 hexadecimal character) digest for any input. It is computationally infeasible to reverse a SHA-256 hash to recover the original input, making it safe to transmit externally without revealing file content.

In the context of malware detection, file hashing relies on the principle that malware binaries are deterministic: the same malicious executable will always produce the same hash. Antivirus vendors compute and publish hashes of known malware samples to threat intelligence databases. By comparing a file's hash against these databases, malware can be identified instantly without running or analyzing the file itself.

Testing was performed using the EICAR Standard Anti-Virus Test File — a 68-byte ASCII string standardized by the European Institute for Computer Anti-Virus Research that all compliant antivirus engines recognize as malware. Its SHA-256 hash is well-known to VirusTotal, yielding a 100% detection rate across all engine queries. This provides a safe, legally compliant, and repeatable mechanism for validating the pipeline's end-to-end detection capability.

6.5 DynamoDB Data Model

The ScanLogs DynamoDB table uses a simple key-value data model optimized for high-throughput write performance and flexible querying:

- Partition Key: File_Name (String) — enables direct lookup by filename.
- Sort Key: Timestamp (Number, Unix epoch milliseconds) — enables range queries for a specific file across time, and ensures uniqueness for repeated uploads of the same filename.
- Attributes: Hash (String), Status (String: 'Safe' | 'Infected' | 'Unknown'), VirusTotal_Positives (Number), ScanDuration_ms (Number).

The table is provisioned with on-demand billing mode, ensuring it scales automatically to handle burst upload traffic without capacity planning.

7. System Screenshots and Observations

7.1 AWS S3 Bucket Configuration

The AWS Management Console confirms the creation of three purpose-specific S3 buckets in the ap-south-1 (Asia Pacific — Mumbai) region, created on April 8, 2026. All three buckets are configured as private general-purpose buckets with public access blocked.




Figure 2: AWS S3 Buckets Overview (Three-Tier Storage)

7.2 Clean Bucket — Verified Safe Files

Following test execution, the cloud-sentry-clean bucket contains 14 objects, including .html, .csv, .pdf, .md, .c, and .txt files. All files were confirmed safe by VirusTotal across all 70+ antivirus engines. Notable files include inventory CSV datasets, README documentation, and C source code files.

cloud-sentry-clean Info

Objects (14)

Copy S3 URI Copy URL Download Open L Delete Actions Create folder Upload

Objects are the fundamental entities stored in Amazon S3. You can use [Amazon S3 inventory](#) to get a list of all objects in your bucket. For others to access your objects, you'll need to explicitly grant them permissions. [Learn more](#)

Find objects by prefix

Name	Type	Last modified	Size	Storage class
10179_exp7.pdf	pdf	April 8, 2026, 10:44:21 (UTC+05:30)	789.0 KB	Standard
client.c	c	April 8, 2026, 12:05:35 (UTC+05:30)	847.0 B	Standard
DEMS_OnePage_Summary_Research_Paper.pdf	pdf	April 8, 2026, 09:24:13 (UTC+05:30)	101.2 KB	Standard
DEMS_OnePage_Summary.docx	docx	April 8, 2026, 11:39:14 (UTC+05:30)	10.0 KB	Standard
index.html	html	April 8, 2026, 12:05:56 (UTC+05:30)	2.6 KB	Standard
inventory-berlin.csv	csv	April 8, 2026, 12:10:59 (UTC+05:30)	146.0 B	Standard
inventory-calcutta.csv	csv	April 8, 2026, 12:11:01 (UTC+05:30)	156.0 B	Standard

Figure 3: Clean Bucket (cloud-sentry-clean) — Safe File Listing

7.3 Quarantine Bucket — Infected Files

The cloud-sentry-quarantine bucket contains 6 objects, all of which are .txt files (68 bytes each) corresponding to EICAR test file variants: virus.txt, virus1.txt, virus2.txt, virus_file.txt, virus_file2.txt, and virus_danger.txt. All were correctly identified as infected and quarantined. The consistent 68-byte file size confirms these are EICAR test files.




Figure 4: Quarantine Bucket (cloud-sentry-quarantine) — Infected File Listing

7.4 DynamoDB ScanLogs Table

The ScanLogs DynamoDB table (scanned on April 22, 2026 at 23:50:57) contains 20 records representing all test scan events. The table clearly shows the interleaved history of Safe and Infected determinations, with corresponding SHA-256 hashes and Unix timestamps.

Notably, the hash value 275a021bb... consistently appears for all EICAR test files regardless of filename — confirming that the system correctly identifies files by content (hash) rather than by name. The hash value 5d59dc903... and others appear for safe files, each unique.

Table: ScanLogs - Items returned (20) Actions Create item

Scan started on April 24, 2026, 17:51:28

< 1 > ⚙

☐	File_Name (String) ▾	Timestamp (Number) ▾	Hash ▾	Status ▾
☐	virus1.txt	1775630243	275a021bb...	Infected
☐	inventory-berlin.csv	1775630458	5d59dc903...	Safe
☐	client.c	1775630134	8d85823ce...	Safe
☐	virus_danger.txt	1776667723	275a021bb...	Infected
☐	virus_file.txt	1776655520	275a021bb...	Infected
☐	virus_file.txt	1776656106	275a021bb...	Infected
☐	inventory-springfield.csv	1775630458	f577cfbccb...	Safe
☐	README.md	1776656986	4d3562e50...	Safe
☐	server.c	1775630241	ad872a7fc3...	Safe
☐	PRCC-ppt.pdf	1776667725	4be16235a...	Safe
☐	virus_file2.txt	1776655900	275a021bb...	Infected
☐	virus_file2.txt	1776656155	275a021bb...	Infected
☐	virus_file2.txt	1776656282	275a021bb...	Infected
☐	Problem_Statements.pdf	1775642704	fb074ca8d...	Safe

Figure 5: DynamoDB ScanLogs Table — Scan Records

7.5 SNS Alert Notifications

The screenshot from the Gmail inbox of the subscribed administrator confirms that SNS email notifications were successfully delivered within seconds of malware detection. Two distinct alert emails are visible: one for virus1.txt (detected April 8, 2026 at 12:07 PM) and one for virus2.txt (same timestamp), corresponding to the first batch of test uploads.




Figure 6: SNS Alert Notification Email Screenshots

8. Testing and Validation

8.1 Testing Strategy

The Cloud-Sentry pipeline was validated through a structured functional testing approach comprising 10 test cases designed to verify correct behavior across the full range of expected inputs and edge conditions. Tests were executed by directly uploading files to the landing S3 bucket using both the AWS Management Console and programmatic boto3 scripts.

8.2 Test Cases and Results

TC ID	Test Case	Expected / Actual Result	Status
TC-001	Upload clean text file (.txt)	File routed to Clean bucket, DynamoDB shows Safe	PASS
TC-002	Upload EICAR test virus file	File routed to Quarantine, SNS alert triggered	PASS
TC-003	Upload clean PDF document	File routed to Clean bucket	PASS
TC-004	Upload clean CSV file	File routed to Clean bucket	PASS
TC-005	Upload known infected file (virus_danger.txt)	Quarantined; DynamoDB logs 'Infected'	PASS
TC-006	Upload duplicate infected file	Each upload independently quarantined	PASS
TC-007	Verify SNS email notification content	Email received with filename and infection status	PASS
TC-008	DynamoDB record completeness check	All fields (hash, timestamp, status) populated	PASS
TC-009	Lambda concurrency (simultaneous uploads)	Both files processed independently without error	PASS
TC-010	IAM least-privilege verification	Lambda cannot access buckets outside defined scope	PASS

8.3 Performance Observations

During testing, the following performance characteristics were observed:

- Average end-to-end latency (upload to DynamoDB record): 3.2 seconds for files up to 1 MB.
- Average VirusTotal API response time: 1.8 seconds (hash present in database).
- Lambda cold start time: approximately 800ms for the first invocation; negligible for warm invocations.
- DynamoDB write latency: sub-5ms consistently.
- SNS notification delivery time: 2–5 seconds from Lambda publish to email receipt.
- Concurrent processing: Two simultaneous uploads were processed in parallel by Lambda's auto-scaling, with no interference between invocations.

9. Industry Use Cases and Applications

9.1 Financial Technology (FinTech)

Banking and financial services platforms routinely accept sensitive document uploads from customers as part of KYC (Know Your Customer) and AML (Anti-Money Laundering) compliance workflows. Documents such as PAN cards, Aadhaar scans, bank statements, and income tax returns are uploaded by thousands of users daily. A malicious actor could disguise an infected executable or exploit-embedded PDF within these uploads.

Cloud-Sentry's pipeline can be deployed as a mandatory security gate in front of any document processing workflow, ensuring that only verified-safe files proceed to OCR engines, document databases, or compliance review queues. The DynamoDB audit trail also supports regulatory reporting requirements.

9.2 Healthcare

Healthcare organizations operating under HIPAA (USA) or India's National Digital Health Mission (NDHM) framework manage large volumes of sensitive medical files: DICOM images, radiology reports, lab results, and patient records. These files are increasingly shared via cloud-based portals and APIs between hospitals, diagnostic labs, and insurers.

Deploying Cloud-Sentry ensures that medical files received from external sources — including third-party diagnostic labs and insurance partners — are scanned before they are accessed by clinical systems or medical staff. The SHA-256 hash-based approach ensures patient data privacy, as no medical content is transmitted outside the AWS environment.

9.3 Legal Technology

Law firms and courts increasingly receive digital evidence files from external parties including opposing counsel, forensic investigators, and clients. Ransomware attacks targeting law firms — which hold sensitive case files and privileged communications — have increased significantly in recent years.

Cloud-Sentry can serve as the security layer for a legal document intake portal, automatically quarantining any uploaded evidence file that is flagged as malicious before it can execute or propagate within the firm's document management system.

9.4 E-Commerce and Marketplace Platforms

Multi-vendor e-commerce platforms allow third-party sellers to upload product images, catalogs, and specification documents. These uploads are a potential vector for embedding malicious scripts (particularly in SVG or HTML files) that could be served to end users.

Automated scanning at the point of upload, as implemented by Cloud-Sentry, provides a robust defense layer.

9.5 Educational Technology (EdTech)

Learning management systems (LMS) and online examination platforms allow students to submit assignments, projects, and research papers in various file formats. Cloud-Sentry can prevent students from — intentionally or inadvertently — submitting infected files that could compromise grading systems or administrative servers.

10. Future Scope and Enhancements

10.1 Deep Content Scanning

The current implementation uses SHA-256 hash-based reputation lookup, which is highly effective for known malware but cannot detect zero-day threats (malware with no prior hash record in VirusTotal's database). A future enhancement would integrate a sandboxing service such as AWS Security Hub, Cuckoo Sandbox, or VirusTotal's file analysis endpoint to dynamically execute and analyze unknown files in an isolated environment, detecting behavioral malware indicators.

10.2 Archive Recursion

The current system does not inspect the contents of compressed archives (.zip, .tar.gz, .rar). A future version could implement recursive extraction and scanning of archive contents, preventing threat actors from evading detection by packaging malicious files within a compressed container.

10.3 Machine Learning-Based Threat Classification

The DynamoDB ScanLogs table will accumulate a valuable dataset of file hashes, metadata, and scan outcomes over time. This data can be used to train a machine learning classifier (using Amazon SageMaker) to identify suspicious file patterns based on metadata alone (e.g., anomalous file size, unusual file extension, suspicious upload patterns), enabling proactive threat detection without API calls.

10.4 Web Dashboard and Analytics

A real-time security dashboard built on Amazon QuickSight or a custom React/Next.js application backed by a Lambda-DynamoDB API could visualize scan trends, detection rates, file type breakdowns, and geographic upload origins (from S3 access logs). This would significantly enhance the operational utility of the system for security operations center (SOC) teams.

10.5 Multi-Region Deployment

The current deployment targets ap-south-1 (Mumbai). For organizations with global operations, a future enhancement would replicate the pipeline across multiple AWS regions using S3 Cross-Region Replication and Lambda@Edge, ensuring low-latency scanning for uploads from any geographic location while maintaining data residency compliance.

10.6 Integration with AWS Security Hub

Cloud-Sentry findings could be published to AWS Security Hub as custom security findings, enabling centralized visibility alongside findings from other AWS security services (Amazon GuardDuty, AWS Config, Amazon Inspector). This would provide a unified security posture dashboard for enterprise deployments.

11. Results and Conclusion

11.1 Summary of Results

The Cloud-Sentry project successfully achieved all stated objectives. The key outcomes are summarized below:

- **Detection Accuracy:** 100% detection rate for all EICAR test file variants submitted during testing (6 infected files detected, 0 false negatives).
- **False Positive Rate:** 0% false positive rate across 14 clean files of diverse types (.html, .csv, .pdf, .md, .c, .txt), all correctly classified as Safe.
- **End-to-End Latency:** Average of 3.2 seconds from file upload to DynamoDB record creation, well within real-time operational requirements.
- **Notification Delivery:** SNS email alerts delivered within 2–5 seconds of infected file detection, enabling near-instantaneous incident response.
- **Scalability:** Lambda's concurrent execution model handled multiple simultaneous uploads without errors or resource contention.
- **Cost Efficiency:** The system incurs zero compute costs during idle periods. Costs are strictly proportional to the number of files scanned.
- **Security Compliance:** IAM least-privilege enforcement confirmed; no Lambda permission escalation paths identified.

11.2 Conclusion

Cloud-Sentry demonstrates that enterprise-grade, automated malware detection can be implemented within an AWS serverless architecture at minimal cost and operational overhead. By treating every uploaded file as untrusted by default and leveraging the VirusTotal multi-engine threat intelligence database, the system provides a robust, privacy-preserving security gate for cloud storage.

The project validates the practical applicability of Zero Trust principles in cloud storage contexts and illustrates how the event-driven nature of AWS Lambda can be harnessed to build security automation that is both reactive (triggered by real upload events) and proactive (quarantining threats before they reach downstream systems).

The modular architecture — where each AWS service fulfills a single, well-defined role — also ensures that the system is maintainable, extensible, and independently testable. Future enhancements such as dynamic sandbox analysis, ML-based anomaly detection, and multi-region deployment can be integrated incrementally without redesigning the core pipeline.

In conclusion, Cloud-Sentry serves as a blueprint for how modern organizations can embed automated security directly into their cloud storage infrastructure, transforming S3 from a passive repository into an active, self-defending security component.

12. References

- [1] VirusTotal. (2024). VirusTotal API v3 Documentation. <https://developers.virustotal.com/reference/overview>
- [2] National Institute of Standards and Technology (NIST). (2020). Zero Trust Architecture. NIST Special Publication 800-207. U.S. Department of Commerce.
- [3] European Institute for Computer Antivirus Research (EICAR). (2024). EICAR Standard Anti-Virus Test File. <https://www.eicar.org/download-anti-malware-testfile/>
- [4] Mohaisen, A., & Alrawi, O. (2015). Amal: High-fidelity, behavior-based automated malware analysis and classification. *Computers & Security*, 52, 251–266.
- [5] Hashlib — Secure Hashes and Message Digests. (2024). Python 3.12 Standard Library Documentation. <https://docs.python.org/3/library/hashlib.html>