IEEE Access
Multidisciplinary | Rapid Review | Open Access Journal

Digital Object Identifier

Two Reachability-Gated Relations in MST-wi: Temporal Mismatch, Oracle Admissibility, and Measurement Limits

QIULONG LIN[1,2] AND NANLEI CHEN[1,2]
[1]Yango University, Fuzhou 350015, China (e-mail: ubfbzu3@163.com)
[2]Sogang University, Seoul 04107, Republic of Korea
Corresponding author: Nanlei Chen (e-mail: ubfbzu3@163.com).

ABSTRACT Two system-agnostic relations in MST-wi, a Web-system metamorphic testing framework, gate their verdict on a *GUI-reachability model*—a crawl-time snapshot of what the interface permits—so what they establish about object-level authorization depends on when the model was read and what the adjudicator may consult. We study them and tie each limit to its evidence. Source inspection shows the engine records only that a relation failed: promotion to a *proven violation* is added policy, stated here explicitly. On a 576-record constructed study, access granted out of band after the crawl is reported as proven in 8 of 8 alarms; once a readable, sound oracle is supplied, the relation adds no observed adjudication benefit over the direct consumer of the same oracle and outcome (the paired methods disagree on 3 of 216 true-violation records, each time favouring the plain request); and the published specificity of 99.81% is an input-level figure whose denominator cannot, on its own, expose a class-uniform failure.
Two experiments carry these claims further. A pre-registered temporal experiment on Gitea 1.22.6 and GitLab CE 17.11.7 commits 16 authorisation transitions over 712 cross-credential cells, with entitlement and effect agreeing on 712: 29 stale false proofs appear, and a recrawl with the same credentials removes 29. A real vulnerable/fixed pair (Gitea 1.20.5 to 1.20.6) shows the independent entitlement/effect gate reporting 1 true positive on the vulnerable build, 0 false proofs, and no alarm on the fixed build—a check of the gate, not a measure of detection effectiveness.

INDEX TERMS BOLA/BFLA, false proof, metamorphic testing, object-level authorization, oracle problem, specificity measurement

I. INTRODUCTION

BROKEN object-level authorization (BOLA), first in the OWASP API Security Top 10 [1], is the failure to enforce, per object, that the authenticated subject is entitled to the object touched. Detecting it is an *oracle* problem: vulnerable and correct systems answer with the same success status. Metamorphic testing is an established approach to that oracle problem, and MST-wi [2] is a substantial system-agnostic instance for Web systems: 76 system-agnostic relations (MRs) over 55 Web-specific predicates, reported to detect 85% of vulnerabilities with specificity 99.81%.

This paper asks what happens to that claim when the asserted property is object-level authorization. The predicates do not express entitlement; they express what their authors call reachability—what "the functionality exposed by the user interface" permits—with the role-to-resource mapping "**not always available**" [2]. We take that sentence as premise, not discovery. Delegating adjudication to a reachability model makes the moment the model was read part of the specification, so we instantiate the predicates *as defined*—over a model recorded at crawl time—and drive the system through three phases: crawl, change authorization out of band, execute. The middle phase is the one the original evaluation does not exercise.

We ran a 576-record scenario/configuration study on a constructed system and a controlled study on Gitea 1.22.6, extended, with a methodological variation, to Gogs 0.14.3 and GitLab 17.11.7. We propose no mechanism. What survives is three findings, one per research question (Section VI).

Research questions and findings

(1) *Temporal (RQ1).* Does the crawl-time reachability model remain sound for authorization decisions after an out-of-band authorization change? No: the adjudication as designed produces *deterministic false proofs*—a legitimate access granted out of band after the crawl is reported as a proven violation, at rate 1.00 on the constructed system and 0.40 on Gitea,

because the predicate's two representations cannot describe an out-of-band grant. The error is a property of the *reading*, not of the system. (2) *Oracle (RQ2).* When a readable, sound authorization oracle fully resolves the proposition under test, does the metamorphic step add incremental adjudication information beyond the oracle and the request outcome? Not observably, within the evaluated scenarios: the step carries no additional decision-relevant information beyond what the oracle-plus-request pair already determines—an empirical premise about the evaluated relations, formalised as a conditional (Proposition 2)—and the paired methods disagree on only 3 records, all favoring `direct_observe` (false proofs 0 vs. 0, recall 0.50 vs. 0.49; a descriptive, point-estimate comparison, not a formal hypothesis test, no margin pre-specified, not domination). (3) *Measurement (RQ3).* Can an input-level specificity metric provide stable scenario-level resolution for a scenario-uniform failure? No: the reported specificity is not conditioned on an explicit check that the reachability model coincides with the authorization state, and its input-level denominator cannot register a class-uniform failure, which unaffected inputs can dilute arbitrarily (Proposition 1).

The native execution, the seeded target and the second implementation are support evidence for these findings, not further headline findings (Section VII).

The findings are not a claim that MST-wi is wrong: the reachability stand-in is announced by its authors and the predecessor design attributes its residual false alarms to crawler coverage [3]. Our contribution is a *security-testing characterization* of metamorphic testing for object-level authorization in Web/API systems, not a new detector, with three layers. Although the technique is general, every empirical claim is scoped to reachability-gated authorization relations in Web/API systems—a prevalent class of networked-application security flaws—and we state where the transfer stops. (1) *mechanistic*—the false-proof failure is located structurally, in *when* the reachability model was read rather than which objects are visible; (2) *fair-control ablation*—under a readable, sound oracle, a same-observable direct adjudicator shows the metamorphic step adds no measurable adjudication information beyond the oracle and the request outcome; and (3) *metric characterization*—a specific failure mode is identified in a published specificity figure, which is not conditioned on the reachability–authorization correspondence its interpretation assumes and whose input-level denominator cannot register a class-uniform failure. The evidence—the three-phase instantiation with internal controls (Section III), the scenario/configuration study (Section IV), the Gitea study with an endogenous control and a seeded-vulnerability positive control (Section V), and the source reading, the native execution of the library's own relations and the second implementation (Section VII)—supports these layers rather than standing as further headline claims.

II. BACKGROUND: THE PREDICATES IN QUESTION

For authorization there is no intrinsic oracle: vulnerable and correct executions both answer with success. Metamorphic testing replaces the absent oracle with a relation over multiple executions—and the relation is only as sound as the assumptions it needs, which for authorization are exactly the facts the oracle was supposed to supply. MST-wi [2], building on Mai et al. [3], crawls a per-user model of reachable URLs and contents, then checks MRs against that recorded model. In the artifact we inspected, the predicates guarding an authorization MR read either the recorded model directly (`cannotReachThroughGUI`, `userCanRetrieveContent`) or static subject properties; we call a predicate *GUI-derived* when its value is a function of the crawl.

Why the false proof is a design consequence, not a bug

Suppose a subject can reach an object at crawl time, so the record stores it as reachable. Afterwards an administrator grants the same subject access to a *further* object through a channel—an administrative endpoint or a share link—that a crawl of the subject's own interface never traverses. At execution the guard still reads the frozen record, finds the new object absent, and concludes the subject cannot reach it; the relation then treats the successful response as a violation. Every step is exactly as specified, so no guard is miswritten: the predicate's two representations—"reachable as recorded" and "not reachable as recorded"—cannot express "reachable, but only after the record was taken". More crawling does not remove the false proof, because the grant need not be visible through the subject's interface at all, and the reported specificity never registers it, because the error is a property of the adjudication's *reading moment* rather than of any single generated input. This is the mechanism the rest of the paper measures, and the reason we speak of a boundary of the specification rather than a defect of an implementation.

Two census figures frame what follows. Over the 76 catalog MRs, 38 (50.0%) gate on a GUI-derived or identity predicate, and only 14 (18.42%) are authorization-relevant by name or action—an upper bound, reported as a caveat; a full-text search for predicates reading the *state of an authorization artifact* (ownership, permission record, share) finds 0 occurrences. Within the examined vocabulary, then, the authorization MRs have no authorization-artifact state observable to decide on, and the reading moment enters the specification: if an entitlement changes after the crawl, the MR evaluates reachability against a world that no longer exists. This is a statement about what the relations *mean*; our experiments are built so that the crawl-time and live readings can be told apart.

III. PROTOCOL: A FAITHFUL THREE-PHASE INSTANTIATION

Two instruments carry distinct claims. The three-phase instantiation below carries the quantitative results of Sections IV and V; a direct execution of the library's own relations—source unmodified, with the build configuration

and a replay harness added—carries one qualitative claim, that the published code produces the false proof we predict (Section VII-C). Neither instrument is a benchmark: the standing scope and non-claims are collected in Section VIII, and neither yields a claim of detector accuracy.

Three phases

(A) *Crawl*: record, per subject and object, whether the subject can reach the object through the interface, and freeze that record—the model the predicates will consult. (B) *Change authorization out of band*: alter a (subject, object) entitlement through a channel outside the crawled interface; the frozen model is not updated, because the architecture has no mechanism to update it. (C) *Execute the MR* against the current state while the predicates consult the frozen model. Phase B is what the original evaluation does not exercise, and it is where the reachability stand-in can be wrong (Fig. 1).

Adjudicator variants and internal controls

A raw alarm becomes a verdict through an exception policy, and different policies are different methods: `raw` (the alarm itself, with no exception handling at all—this is the baseline any filter must be read against); **v1** (an *existence* filter: any sharing record on the object downgrades the alarm, regardless of whom it names or what it permits); **v2** (existence plus operation coverage: the record must cover the operation the MR triggered); **v3** (state-calibrated—consults a readable authorization introspection surface, abstains when none is readable); `degrade_all` (the floor: abstain on every alarm); `direct_only` (authorization surface only, access outcome ignored—a deliberately unfair control); and `direct_observe` (a succeeding plain request checked against the same readable surface). The last consumes the same observable quantity as the MR family and decides the negative result.

Ground truth

Every quantitative result names its ground-truth source, and it is never the detector under test: construction state for the constructed system and the scenario/configuration study; system-specific live re-probes of effective authorization (the per-system validation procedure is described in Section V) for Gitea, Gogs and GitLab; the pinned route tables for the grant census; and the seed list for the seeded target.

Scenarios and design cells

Seven scenarios separate the reasons an MR can misfire: no shared object (S1, S2); an in-band legitimate share visible in the framework log (S3); an unshared plain violation (S4); a read-only share plus a write violation (S5); an out-of-band share invisible to the framework log (S6); an out-of-band share plus a genuine violation (S7). They are crossed with 8 configurations defined by instantiation mode, enforcement correctness, channel visibility and introspection availability. The nominal cross is 7×8 combinations, but four are inadmissible: the two no-exception configurations (`V-noE3-vuln0`, `V-noE3-vuln1`) are undefined under the two out-of-band scenarios (S6, S7), where the legitimate-sharing exception does not apply. This leaves 52 admissible design cells.

Table 1 gives the complete cross, factor by factor: the levels of each, how it is varied, the number of records at each level, and what it is crossed with. Table 18 in Section VII gives the cell-by-cell census—eight configurations by seven scenarios, with a dash wherever a combination is undefined. Two dimensions are nested rather than crossed, and we state them here instead of letting the tables imply a factorial that was not run: channel visibility exists only where the application offers a sharing facility, so the two no-exception configurations sit outside it; and the listed level is instantiated only with introspection on, so the corner *listed and unreadable* is empty.

A. WHAT THE DESIGN VARIES, AND WHAT IT CAN IDENTIFY

Because the exception policy and the crawl reading are thrown per record rather than held per configuration, every record has a partner that differs in that switch alone. Table 2 uses that: it pairs records on configuration, scenario, relation and the other switch, and reports the discordant pairs. A contrast carried by some other factor would show up as movement in the paired cells; a contrast that is not there shows up as a zero.

Three results come out of it, and they are stronger than the aggregate rates they explain. First, the crawl reading moves the outcome in one direction only: of 288 frozen–live pairs, 12 lose a false proof when the reading is live and 0 gain one, while the same switch costs 3 detections and gains none. The live reading is therefore a trade in a fixed direction, not noise around a rate. Second, the exception ladder has *no* discordant pair at either step: raw and e1 differ on no individual record, and neither do e1 and e1e2. That is a stronger statement than the aggregate rate not moving—20 records carry a false proof under all three policies—and it says the two exception predicates are, on this system, inert rather than merely weak. Third, oracle readability acts only where there is something to resolve: in the violating configuration 54 of 78 paired records change from `violation-proven` to `indeterminate` when the surface is switched off, none the other way; in the correct configuration 78 pairs change not at all.

What the design cannot identify follows from the two nested dimensions, and we prefer to name it. The interaction between channel visibility and readability is not estimable, because the listed-and-unreadable cell does not exist; the readability contrast is identified within unlisted only, and we make no claim that readability moderates the listed channel. The legitimate-sharing mechanism is not identified under S6–S7, where it is undefined by construction, so the out-of-band estimates are for the e3 configurations alone. The two relations are not orthogonal to scenario—S5 carries MR-002 only—so we never compare relations with each other. What remains is balanced: every (exception policy, crawl reading) slice holds 52 readable and 44 unreadable records, so the readability contrast cannot be carried by either thrown switch.




FIGURE 1. **The three-phase instantiation. The predicates consult the reachability model frozen in Phase A. A Phase B entitlement change made outside the crawled interface leaves that model stale, so in Phase C a legitimately granted access has no representation but "cannot reach"; the exception predicate is not discharged and the alarm is promoted to a proven violation—the false proof of Finding 1.**

TABLE 1. **The complete design. Every record is one point of the cross scenario × configuration × relation × exception policy × crawl reading; the last two are deliberately thrown switches, not replicates, so the enumeration carries no sampling error. "Records" gives the count at each level of the factor, and the last column states what the factor is crossed with. Only the listed-with-introspection cell is missing, and Section III-A says what that costs.**

factor	levels	how it is varied	records	crossed with
scenario				
scenario	7	the origin of the share and the ground truth: no shared object (S1, S2); a share made through the framework's own facility (S3); an unshared violation (S4); a read-only share plus a write violation (S5); a share made out of band (S6); out of band plus a violation (S7)	48–96	all configuration levels where admissible
configuration				
instantiation	2	whether the application offers a legitimate-sharing facility at all (e3) or not (no-e3)	468 / 108	enforcement, visibility; undefined under S6–S7
enforcement	2	the application either enforces object ownership (correct) or serves the object to any authenticated subject (violating)	288 / 288	full
channel visibility	2	whether the share is written to the framework's own log (listed) or not (unlisted)	420 / 156	e3 only; no share exists to list under no-e3
introspection	2	whether the application exposes a readable per-object share list (on) or not (off)	420 / 156	*listed exists only with introspection on*
expansion				
relation	2	the metamorphic relation evaluated: MR-002 or MR-004	312 / 264	S5 carries MR-002 only
exception policy	3	how many MST-wi exception predicates are thrown before the relation fires: none (raw), one (e1), two (e1e2)	192 / 192 / 192	full
crawl reading	2	whether the reachability model is the frozen crawl-time snapshot (frozen) or the execution-time state (live)	288 / 288	full
$44 \cdot 2 \cdot 3 \cdot 2 + 8 \cdot 3 \cdot 2 = 576$ records over 52 cells				

Statistical treatment

The 576 records are not independent observations. Each admissible cell is expanded deterministically by the factors that are actually varied: 2 metamorphic relations (MR-002, MR-004), 3 exception-policy variants (raw, one level, two levels—the first deliberately thrown switch), and 2 reachability readings (the frozen crawl-time snapshot and the live execution-time state—the second deliberately thrown switch). The two relations do not both apply to every cell: only MR-002 applies under scenario S5, so 8 S5 cells carry one relation while the remaining 44 carry two. The record count is therefore

$$576 = 44 \cdot 2 \cdot 3 \cdot 2 + 8 \cdot 3 \cdot 2,$$

a deliberately unbalanced design—the per-cell multiplier differs by scenario. The records are therefore a fixed enumeration, not a sample: we report counts, rates and design-cell denominators, and we attach no inferential interval to any of them. Where a headline count has a small denominator we say so explicitly (the anchored rate, 2/2, is unstable by construction) and lead with the larger-denominator count of the same phenomenon. No conclusion rests on statistical significance. Where a comparison is paired—the ablation of Section IV-C—we report discordant-pair counts rather than an interval over a difference. The replication ceiling is explicit: one constructed system, 52 cells, 2 MRs, three real systems.

Tooling and code provenance

Development of the analysis scripts was assisted by an AI coding assistant (declared in the Declarations). Every script that assistant touched was reviewed, executed, and its output checked by the authors against the raw records; the released pipeline recomputes every reported scalar from those records, every table is generated by the pipeline, and the macro files and the two auto-generated tables share a single source of truth. No AI tool participated in the detection loop or in any adjudication.

TABLE 2. Attribution by matched pairs. Each row compares two records that differ in exactly one switch, holding configuration, scenario, relation and exception policy (or crawl reading) fixed, so the contrast cannot be carried by any other factor. "First only" and "second only" are the discordant pairs: a one-way count means the switch moves the outcome in one direction only, and a zero means it does not move it at all. The two switches that were hypothesised to matter are separated in the first two blocks; the third shows the effect is confined to violations that a readable surface can resolve.

contrast	outcome	pairs	first only	second only	both	neither	reading
frozen → live	false proof	288	12	0	24	252	live reading removes 12 false proofs, adds 0
frozen → live	violation detected	288	3	0	105	180	and costs 3 detections
raw → e1	false proof	192	0	0	20	172	no discordant pair: the ladder changes nothing
e1 → e1e2	false proof	192	0	0	20	172	no discordant pair: the second predicate adds nothing
unreadable → readable	verdict of violation-proven	78	0	54	0	24	all 54 changes are detections gained, none lost
unreadable → readable	verdict of violation-proven	78	0	0	0	78	no change where there is no violation to detect

IV. SYNTHETIC STUDY: WHERE THE ADJUDICATION GOES

This study supplies the evidence for Findings 1 and 3, and the ablation behind Finding 2; the findings themselves are stated in Section VI.

A. DEFINITIONS

Confusions are defined over the *verdict*: a *false proof* is the strict subset of false alarms promoted to `violation-proven`—an error the tool asserts as established. We also report the *detection-keep rate* (share of fired true violations still alarmed) and count only abstentions justified by an unreadable oracle.

B. WHAT THE CONSTRUCTED SYSTEM SHOWS

Attribution is clean

On the anchored configuration the false-proof rate is 2/2. With that denominator the rate is unstable by construction, so we attach to it no interval—nor a percentage, which would travel out of context. With the legitimate-sharing exception absent the rate is 0.00 (0/2), and with the channel listed it is 0.00 (0/2). The phenomenon is therefore attributable to a legitimate sharing exception the MR cannot know about, not to execution itself. A 2×2 grid over channel visibility and enforcement correctness tells the same story from the other side: on unlisted cells the false-proof rate is 44.44% with no false negatives; on listed cells it drops to 0.0% but one of the five violating records in that cell is a false negative (4 detected, 1 missed). Avoiding false proofs and keeping detection are controlled by one switch, and the switch cannot be thrown both ways at once.

Filtering exceptions does not help

The exception ladder—raw, one exception level, two—leaves the anchored rate at 1.00, 1.00, 1.00: it does not move. The exception levels we can express are themselves functions of the same reachability model, so they inherit its blind spot.

The framework cannot see the channel that matters

When a legitimate share was created through the framework's facility, its log holds 12 records and v2 produces 0 false proofs (rate 0.00); when the same share was created out of band, the log holds 0 records—no evidence the share exists—and v2's false proofs rise to 8 of 8 alarms (rate 1.00), every one promoted to `violation-proven`. The MR cannot distinguish "this share does not exist" from "this share exists but was not crawled"; its only representation of the first is the second. On S7, where a genuine violation *does* sit behind the out-of-band share, the same blindness makes the alarm right for the wrong reason (6 of 6 reached)—and that coincidence of alarms with violations is what an input-level metric cannot unpack. The same tension appears within a single MR: for S3 (must not alarm) vs S5 (must alarm), no configuration in the family is correct on both—the choice of switch is a choice of *which* error to make (Fig. 2).

Stratification, not aggregation

Aggregated, v3 looks best (recovery 1.00 against `degrade_all`'s keep rate 0.00); the reading is wrong, because v3 changes regime with oracle readability. Stratified over the 36-record readable grid and its 18-record absent grid (a representative grid; Section IV-F re-runs the same comparison over all 576 records): on the readable grid it removes v2's false proofs (0 vs. 4) while still alarming on all 9 fired true violations; on the absent grid (18) it alarms on none of the 5 true violations v2 still alarms on, abstaining 13 times. Pooling converts honest abstention into apparent performance, so v3's numbers may appear only stratified.

C. FAIR ABLATION: DOES THE METAMORPHIC STEP ADD ADJUDICATION INFORMATION?

Our earlier iteration proposed v3 as a mechanism, resting on the claim that the metamorphic step was necessary. We tested that claim by removing the step and substituting the most naive consumer of the same observable. The distinction matters: `direct_only`—oracle yes, access outcome ignored—produces 108 false proofs against v3's 0 (precision 0.50), and




FIGURE 2. **The errors are scenario-structured. The bookkeeping oracle's false proofs concentrate on S6, the legitimate share created out of band and so invisible to the framework's own log, while the state-calibrated v3 abstains exactly where its surface is not readable. Both panels are recomputed from the same records as Table 3.**

rejecting it proves nothing because it discards half the evidence. The fair control is `direct_observe`: a succeeding ordinary request plus the same readable surface, consuming exactly what the MR-based adjudicator consumes.

Table 3 concludes the ablation. The first three rows are a ladder, and they must be read in order: with no exception handling at all, `raw` yields 120 false proofs; the existence filter v1 cuts them to 60, but pays for it by abstaining on true violations (FN rises to 18); adding operation coverage (v2) restores the true violations (FN 3) at the same false-proof count. Neither filter is therefore a free improvement, and v3's zero in the FP column is bought with the FN column. `direct_observe` has 0 false proofs against v3's 0—a tie at zero, not a win. The comparison is paired, so we report the discordance rather than an inferential interval: over the 216 true-violation records the two methods disagree on 3, and on every one of them `direct_observe` is right—it detects a violation that v3 misses or abstains on, its reachability precondition blocking a detection the plain request makes. The aggregate recalls 0.50 and 0.49 restate that asymmetry rather than measure a difference, and no margin was pre-specified, so no formal hypothesis-test claim attaches. We found no incremental adjudication advantage of the metamorphic step over direct observation in these oracle-available scenarios, and that absence provides no support for an incremental adjudication benefit in these scenarios: the step would have to be better at something the plain request cannot do. Selective presentation would have hidden the cost: v3's precision of 1.00 was bought with 111 false negatives (F1 0.65), an exchange of 60 false alarms for missed violations dressed as an improvement.

D. COVERAGE, SELECTIVE RISK, AND WHAT A POOLED PRECISION DOES NOT SAY

Table 3 scores the alarm. A method that abstains is counted as not having alarmed, so the abstention lands in TN or in FN: for the question "does the tool report a violation" that is the right scoring, but it is not the scoring for "does the method decide". Table 4 rescores the same 576 records on the decision and reports coverage, abstention rate, selective risk and request cost.

v3 decides 348 of 576 records—coverage 60.42%—and abstains on 228, 108 of them on true violations and 120 on records with none. Its precision of 1.00 and its selective risk of 0.86% are therefore properties of a 60.42% coverage: over the remaining two records in five the method claims nothing, and the pooled precision is not an error rate over all records.

The abstentions are not all of one kind (Table 4, panel b). 156 are structural—the surface returns nothing, and there is nothing for the method to consult. The other 72 fall on a *readable* surface that shows a covering grant: the access is explained, and the method still declines to assert its absence. A conservative method may prefer silence to a positive "no violation", and we do not score that as an error; but it is a non-decision, and it cannot be read as a correct rejection. The comparison with v2 makes the arithmetic visible. v2 promotes 60 false proofs; v3 declines 24 of them because the surface is unreadable and 36 because it is readable and shows the grant. Only the first 24 are the availability gate the method is named for. The rest is a false proof converted into a non-decision.

The other side of the ledger is dearer. 108 abstentions fall on true violations, and with the 3 records on which no method alarms, v3 leaves 111 of 216 violations unproven—the count the review derived from the pooled table. `direct_observe`, at full coverage and with no abstention channel, detects 108 and misses 108 with no false proofs. At the operating points measured, the plain request therefore detects 3 more violations than v3, abstains on none, and its higher selective risk (18.75%) consists entirely of missed violations rather than of false proofs.

Selective risk is not a ranking either, and we do not use it as one. `degrade_all`, which alarms on nothing, has the second-lowest risk (1.23%) at 42.19% coverage and detects no violation at all; an ordering by risk alone would place it above v2. We therefore report precision and selective risk with coverage attached, never compare them across methods at unequal coverage, and make the comparison that matters inside a stratum, where coverage is common by construction

TABLE 3. End-to-end confusion matrix over all 576 records (216 true violations, 360 correct cases). The records are a fixed enumeration, not a sample (Section III, statistical treatment), so no inferential interval is attached; where a denominator is small we say so rather than interval it. `direct_only` is a deliberately unfair control, shown to make that point.

method	TP	FP	FN	TN	precision	recall	F1
raw (no exception handling)	213	120	3	240	0.64	0.99	0.78
v1 (existence filter)	198	60	18	300	0.77	0.92	0.84
v2 (existence + coverage)	213	60	3	300	0.78	0.99	0.87
v3 (state-calibrated)	105	0	111	360	1.00	0.49	0.65
`degrade_all`	0	0	216	360	—	0.00	—
`direct_only`	108	108	108	252	0.50	0.50	0.50
`direct_observe`	108	0	108	360	1.00	0.50	0.67

(Section IV-F). A safe abstention is not a detection and we never count it as one.

Cost

The enumeration issues 4833 requests over 576 records (median 8 per record, range 7–10). The oracle-consuming methods add 104 probe GETs over 52 cell-operations: charged per record that is one request, and 0.18 amortised as executed, because the probe is shared by the records of a cell. `raw`, v1 and v2 issue none of their own—they read the log the crawl already wrote. We do not report wall-clock time for this study: every method replays the same recorded exchanges, so a difference would measure our replay loop rather than the system under test. The study we did execute end to end is the temporal loop of Section V: a median of 21.2 s per transition on Gitea and 7.3 s on GitLab, of which the mutation is 0.10 s and 0.09 s, the recrawl 0.38 s and 1.35 s, and the cross-credential probe sweep 20.7 s and 6.0 s. The recrawl the mechanism needs is a small part of the loop; re-reading every credential is what costs.

E. A PUBLISHED METRIC'S RESOLUTION: WHAT THE REPORTED SPECIFICITY DOES NOT CONDITION ON

The practical content of this finding is a diagnosis of a specific published figure, not a general property of ratios. Under the input-level specificity convention used by MST-wi [2], the reported specificity has the form

$$S_{\text{input}} = 1 - \frac{\text{false alarms}}{\text{inputs}},$$

and the figure of 99.81% is reported without an explicit check that the reachability model whose readings drive adjudication coincides with the true authorization state. Where the two diverge—the out-of-band case of Finding 1—the metric records agreement with the tool's own crawler rather than with entitlement, so a high value certifies the correspondence it silently assumes. The predecessor itself concedes the role-to-resource mapping is "not always available" and attributes its residual false alarms to crawler coverage of "all URLs for all users" [3]. The dilution below is elementary arithmetic, offered only to make the second half of the diagnosis—that the denominator cannot register a class-uniform failure—precise; we do not present it as the contribution.

We cannot reproduce the engine's exact input count, so we approximate two follow-up inputs per case—enough to exhibit the denominator's resolution, the only point at issue. In that approximation the configuration in which a whole class of legitimate access is misreported still yields a specificity of 0.85 (84.62%)[1].

A bounded formal remark on the denominator

Define $S_{\text{input}} = 1 - FP_{\text{inputs}}/N_{\text{inputs}}$ and $S_{\text{scenario}} = 1 - N_{\text{failed}}/N_{\text{scenarios}}$, where FP_{inputs} counts false alarms over all generated inputs and N_{failed} the scenarios in which the failure is uniform. S_{scenario} is introduced only as an analytical construct for characterising resolution; it is not proposed as a replacement evaluation metric. The remark concerns metric resolution, not estimator consistency or statistical power.

Proposition 1. Fix $f \geq 1$ failed scenarios, each producing a fixed number $a \geq 1$ of false-alarm inputs, and $s \geq 1$ successful scenarios each contributing m additional, alarm-free inputs. Then $S_{\text{input}} = 1-(fa)/(fa+sm)$, which tends to 1 as $m \to \infty$, while $S_{\text{scenario}} = 1-f/(f+s)$ is independent of m and strictly less than 1.

Proof. $N_{\text{inputs}} = fa + sm$ and $FP_{\text{inputs}} = fa$; substitution gives $S_{\text{input}} = 1-(fa)/(fa+sm) \to 1$ as $m \to \infty$, whereas the scenario-level figure depends only on the fixed counts f and s. □

Corollary 1. No fixed input-level specificity threshold $t < 1$ can guarantee that a scenario-uniform failure will push the metric below it: choosing $m > (fa/s)\cdot t/(1-t)$ drives S_{input} above t while the f failing scenarios remain failing.

The two halves of the finding are about the specific reported figure, not about ratios in the abstract: its value records agreement with the tool's own crawler where model and authorization state diverge, and its denominator cannot register a class-uniform failure even when one occurs.

Implementation robustness

An independently written implementation of the same predicates was compared on a subset fixed in advance; it bounds implementation accident only, and is reported with the confirmations in Section VII-D.

[1]This value is illustrative of the denominator's resolution only. It rests on an assumed two follow-up inputs per case, an approximation we cannot ground in the engine's exact input count; what matters is the *form* of the denominator, not the value.

TABLE 4. The same 576 records scored on the decision rather than on the alarm. Coverage is the share of records on which a method asserts either a violation or its absence; the abstention column gives the count and, in parentheses, its rate, split by whether the record held a true violation. *False proofs* and *misses* are the two error counts among decided records, and *risk* is their sum over that denominator—comparable across methods only at equal coverage, which these methods do not have. Panel (b) splits v3's abstentions by reason: only the first row is the availability gate the method is named for. `direct_only` and `direct_observe` are two-valued and have no abstention channel, so their coverage is 1 by construction and 264 of their decisions are forced on an unreadable surface.

method	coverage (%)	abstained	on violation	on normal	false proofs	misses	risk (%)
`raw`	100.00	0 (0.00)	0	0	120	3	21.35
v1 (existence filter)	86.98	75 (13.02)	15	60	60	3	12.57
v2 (existence + coverage)	89.58	60 (10.42)	0	60	60	3	12.21
v3 (state-calibrated)	60.42	228 (39.58)	108	120	0	3	0.86
`degrade_all`	42.19	333 (57.81)	213	120	0	3	1.23
`direct_only`	100.00	0 (0.00)	0	0	108	108	37.50
`direct_observe`	100.00	0 (0.00)	0	0	0	108	18.75

(b) v3's abstentions by reason

reason	abstentions (on violation / on normal)	
surface unreadable	156 (108 / 48)	nothing to consult
surface readable, covering grant	72 (0 / 72)	a false proof converted into a non-decision

F. WHAT POOLING HID: THE ABLATION SPLIT BY ORACLE READABILITY

Table 3 pools two populations in which the oracle-consuming methods behave in opposite ways, and the pool is misleading in both directions. Section IV reports the comparison on a representative grid; this subsection, summarised in Table 6, repeats it over all 576 records. The records differ in one respect that decides whether those methods can act at all: whether the introspection surface returns a reading for the record. We therefore repeat the same comparison inside each stratum, with the same methods and the same decision rule, and we add two references that need no oracle against which the metamorphic family can be scored where no oracle exists.

Reconciling the representative grid with this partition

The 36/18 grid of Section IV is not a miniature of the 312/264 partition, and the two should not be read as one number at two sizes. The grid is a single point of the switch space: it fixes the exception policy at raw and the crawl reading at live, keeps the six e3 configurations, and stops at S5, which leaves 54 records—36 readable and 18 unreadable. Table 5 closes the gap additively: the other five switch settings on the same configurations and scenarios contribute 270, S6–S7 for those configurations 144, and the two no-exception configurations 108, all of them unreadable. The readable count runs 36 in the grid, 36+180 once the other switch settings are added, 312 across all e3 records, and 312 overall: the S6–S7 block is the only step that contributes readable records, and the arithmetic is exact at every step.

Stratification variable

We stratify on the *effective* readability of the surface—the value the probe returns for the record—not on the configuration switch. The distinction is not cosmetic: 108 records sit in configurations flagged `introspection=on` whose surface nevertheless returns nothing (the two no-exception configurations), so the configuration flag is not a faithful proxy for whether an oracle was available to the adjudicator, and using it would misclassify those records. The two strata partition all 576 records: 312 readable, 264 unreadable. Both are fixed enumerations, so as elsewhere we report counts and rates and attach no inferential interval.

TABLE 5. Reconciling the representative grid with the full partition. The grid of Section IV is one point of the switch space, not a smaller version of the partition: it fixes the exception policy at raw and the crawl reading at live, keeps the six e3 configurations, and stops at S5. Adding the rest of the enumeration reproduces the 312/264 partition exactly.

subset	readable	unreadable	records
representative grid	36	18	54
+ other five switch settings	180	90	270
+ S6–S7, six e3 configurations	96	48	144
= all e3 records	312	156	468
+ two no-exception configurations	0	108	108
= all records	312	264	576

The readable stratum strengthens Finding 2

Splitting does not rescue the metamorphic step; it removes the comparison in which it looked best. On the 312 readable records `direct_observe` reaches recall 1.00 with 0 false proofs, against v2's recall 0.97 with 36 false proofs, and against v3's recall 0.97 with 0. The ordering is therefore not an artifact of the metric—the plain request is ahead on false proofs and not behind on detections—whereas the pooled table had let the family appear competitive on recall. We do not claim domination: the comparison rests on the constructed-observable argument of Proposition 2, and `direct_observe` is not an independent method here, since it is built from the same two quantities that define the reference (its second input, the access outcome, is part of how the reference labels a violation). What the split shows is the scope of the necessity claim: where an oracle resolves the proposition, there is nothing left for the relation to add, and the pooled numbers were flattering to the relation only because they mixed in records where the oracle-bearing methods could not run.

TABLE 6. The ablation of Table 3 re-run inside each stratum. The two panels are not rankings of the same population but two different regimes: in the readable stratum the oracle-bearing methods can act; in the unreadable stratum they cannot act and are structurally bound to zero detections. The two reference rows need no oracle and no crawl model: `always_alarm` is the trivial floor, `obs_success` alarms on the observed success of a plain request. All numbers are counts.

stratum	method	TP	FP	FN	TN	precision	recall	F1
readable (312)	`raw`	105	72	3	132	0.59	0.97	0.74
	v1 (existence filter)	96	36	12	168	0.73	0.89	0.80
	v2 (existence+coverage)	105	36	3	168	0.74	0.97	0.84
	v3 (state-calibrated)	105	0	3	204	1.00	0.97	0.99
	`direct_observe`	108	0	0	204	1.00	1.00	1.00
	`obs_success`	108	96	0	108	0.53	1.00	0.69
	`always_alarm`	108	204	0	0	0.35	1.00	0.51
unreadable (264)	`raw`	108	48	0	108	0.69	1.00	0.82
	v1 (existence filter)	102	24	6	132	0.81	0.94	0.87
	v2 (existence+coverage)	108	24	0	132	0.82	1.00	0.90
	v3 (state-calibrated)	0	0	108	156	—	0.00	—
	`direct_observe`	0	0	108	156	—	0.00	—
	`obs_success`	108	48	0	108	0.69	1.00	0.82
	`always_alarm`	108	156	0	0	0.41	1.00	0.58

The unreadable stratum is the relation's own regime, and it is not empty

The 264 unreadable records contain 108 true violations and 156 correct cases, a violation base rate of 40.91%. Every oracle-bearing method—v3, `direct_observe`, `direct_only`—detects 0 of them, not because the relations are weak but because those methods have nothing to consult and, by their own definition, abstain. The metamorphic family does not abstain: v2 reaches all 108 true violations (recall 1.00) with 24 false proofs, precision 0.82, a lift of 2.000× over the base rate. Against the two no-oracle references: `always_alarm` scores precision 0.41, which is the base rate itself—no information at all—and `obs_success`, which alarms on the observed success of a plain request, reaches the *same* recall at precision 0.69, lift 1.692×. The net difference between the metamorphic family and that reference is therefore not in detections (0 additional true violations) but in false alarms: 24 fewer for the metamorphic family.

What the saving consists of

The attribution is one-sided and mechanical. Over the seven scenarios, every record of the 24-alarm saving falls on S3, the legitimate share created *through the framework's own facility* and hence recorded in its log: 24 false alarms for `obs_success` against 0 for v2 on the 48 records of that scenario. On S6, the same share created out of band, the two agree exactly (24 vs. 24 false alarms on 24 records), and both for the reason developed in Section VI-A—the predicate has no representation for a grant the crawl did not see. So the incremental detection information the metamorphic step carries where no oracle exists is exactly the information the crawl-derived reachability model can see: it suppresses what was logged, and it reproduces Finding 1 on what was not. This bounds Finding 2 rather than overturning it. Finding 2's antecedent—a readable, sound oracle that fully resolves the proposition—fails on this stratum by construction, and where it fails the relation is not worthless but worth precisely the reachability model it reads: above a trivial floor, above a single uninterpreted request, and below any method that can consult the entitlement.

Limits of the comparison

Two references are deliberately weak, and we do not present them as the frontier of oracle-free detection: `obs_success` uses one request and no model, and a differential prober that compares several accounts against one another—the shape taken by the black-box line reviewed in Section IX—consumes more than `obs_success` does and was not instantiated here. The lift we measure is therefore an estimate against weak references, not a claim about metamorphic testing versus the best oracle-free detector, and we make no such claim. Both references also share an observable with the reference labelling (`obs_success` alarms on the same access outcome that partly defines a violation), so their absolute rates carry the same constructiveness caveat as `direct_observe`; only the differences are meant to be read. Everything here is one constructed system, one MR family, and one criterion (the alarm) rather than the promoted verdict.

V. REAL SYSTEMS: GITEA, GOGS, GITLAB, AND A SEEDED CONTROL

This section supplies the real-system evidence for Findings 1 and 2: the Gitea study with its endogenous control, the cross-vendor replication, and the seeded positive control (support evidence, Section VII).

A synthetic system cannot tell us whether the crawl-time reading is an artifact of our construction, so we repeated the essential comparison on real systems. We chose Gitea 1.22.6 for genuine object-level sharing with per-object visibility, a machine-readable sharing surface, and a documented administrative grant path. Three scope conditions, stated before the numbers. First, on the endpoints and authorization transitions exercised here, Gitea enforced the expected decisions: no instance of the studied vulnerability was found, so the experiment measures only the false-proof side. Second, the cell study uses our instantiation of the predicates, not the

TABLE 7. The grant surface of Gitea 1.22.6 (instance-independent).

quantity	count
paths in the system's API description	253
grant endpoints	15
of which usable without site-admin	8
revocation endpoints	2

engine; the engine's own relations are executed separately in Section VII-C. Third, the reachability model is reported under *both* readings—crawl-time snapshot (what the definitions presuppose) and the live execution-time state—so the time at which the model was read can be isolated as the explanatory variable. The experiment produces 96 cells, 48 per reading.

Grant surface

Table 7 counts an endpoint as grant-capable if, without modifying the system, a request can move a (subject, object) pair from not-entitled to entitled. The 8 endpoints drivable by a non-administrator are the out-of-band channel in its real form: a subject who is not an administrator can create an entitlement that a crawl of that subject's own interface need not reveal. The cross-vendor table below reports a normalized census (semantically equivalent routes merged, non-authorization grant surface excluded), which is why its Gitea figure (13) differs from the raw count (15) here; the two answer different questions.

Is the authorization surface readable, and from where?

Readability depends entirely on the vantage, so the counts below are different populations and must not be read as one denominator. From the owner/administrator vantage the sharing surface is readable on 56 of 56 owner-vantage attempts over the 48 cells: complete. From a black-box subject's own vantage—the vantage a black-box tool occupies—it is readable on 0 of 40: never. An intermediate count of 16/56 comes only from subjects who happen to be owners or administrators and does not constrain the mechanism; it is not synonymous with ''an arbitrary black-box subject can read the surface''. Table 8 collects these populations. On 48 of 48 applicable cells the credential-substitution check confirmed that our model agrees with the system's behavior (Fig. 3).

Is the write path verified by state rather than status?

A status code cannot establish that a write took effect, so the write path is checked by content: the subject creates a uniquely named file, the owner re-reads it byte-for-byte as the ground truth, and the file is deleted where the API allows it. Across the 3 systems, 120 of 120 cross-credential write attempts agree with the ledger, with 0 unauthorized writes; no status code contradicted the content outcome (count: 0). The owner control—a non-admin writing its own repository—changed content in 24 of 24 attempts. On 2 of the 3 systems the site administrator could not write through the contents API although the ledger grants write; those 24 control rows are excluded from the cross-credential denominator and reported as a modelling gap rather than absorbed. Restore is unavailable on 1 of the 3 systems, whose contents API exposes no delete, so its probe files remain in a disposable instance.

TABLE 8. Authorization-introspection readability protocol on Gitea. Each row is a distinct population and denominator, so the rows are not comparable: both the vantage and the unit of the denominator differ.

vantage	attempts	readable
owner-vantage authorization-introspection surface	56	56
arbitrary subject (black box)	40	0
subject also owner/admin (representative grid)	56	16

TABLE 9. Departure from the real authorization state, per reading of the reachability model.

reading of the reachability model	mismatch	cells
crawl-time snapshot (as the definitions presuppose)	10	48
live execution-time state	0	48

The mismatch is in time, not in visibility

Table 9 is the load-bearing result: the adjudication departs from the real authorization state on 10 of 48 cells under the crawl-time reading and 0 of the same cells under the live reading. System state and tested relation were held fixed; only the time at which the reachability model was read changed. Under the crawl-time reading a bookkeeping adjudication produces 10 false proofs on the 25 authorized cells (rate 0.40), against 0 alarms live; v3 produces 0 false proofs, and `direct_observe` emits 0. The unfair control `direct_only` raises 23 alarms, more than any other adjudicator, simply because it ignores the request outcome; on this system none is promoted to `violation-proven` under our strict false-proof definition (0 false proofs), so alarm count and false-proof count are not the same quantity. Channel provenance of the authorized access (24 of 25 not observable by the framework log, 0.96; of these 11 are literal out-of-band grants and 13 implicit via site administration or public visibility) is a property of our topology—a design parameter, not a field prevalence. This comparison uses two snapshots and therefore cannot separate a stale model from a channel the crawl never listed; the transition experiment in Section V-A separates the two.

An endogenous control

The most serious alternative explanation is that public objects are simply harder to enumerate—visibility, not time. Two objects that end equally public but became public at different moments control for this (Table 10): the predicate reports unreachability on 5 of 6 cells only for the object made public after the crawl, and on 0 for the object public throughout, with the MR firing correspondingly (5 vs. 0). Final visibility is identical, so within this design the only manipulated explanatory variable is when the model was read.




FIGURE 3. Gitea 1.22.6. (a) the grant-API space; (b) authorization-surface readability, complete from the owner/admin vantage (56/56) and never from a black-box subject's (0/40); (c) the departure from the real authorization state is present under the crawl-time reading (10/48) and absent live; (d) alarms versus false proofs per adjudicator. All counts are recomputed from the run records by the analysis pipeline.

TABLE 10. Endogenous control: two objects that are both public at the end.

object	cells	`cannotReach`	MR fires
public before the crawl	6	0	0
public only after the crawl	6	5	5

A. EIGHT COMMITTED TRANSITIONS WITH A FROZEN MODEL, ON TWO PRODUCTS

The two-snapshot comparison above cannot separate two explanations: the model went stale, or the crawl never listed the channel in the first place. The transition experiment separates them by construction. We ran eight authorisation transitions on one fresh Gitea 1.22.6 instance and repeated the same eight, under the same pre-registered protocol (hash `d09d904707aa`) and the same ledger rules, on an independent GitLab CE 17.11.7 instance. The mechanisms differ per product—attaching a repository to a team becomes sharing a project with a group; removing a team member becomes removing a group member—so the two runs share a protocol, not a topology, and we report them side by side rather than pooled.

Each transition is a closed loop. We crawl every subject, serialise the per-subject reachable set, freeze it as M_0 and record its digest; commit one authorisation transaction and increment the harness version *hv* only if the transaction returns 2xx; re-crawl with the *same* credentials to obtain M_1; read the oracle from the owner vantage; issue the request and verify the effect by content; and classify against the ledger at decision time. All 16 transactions committed, all 16 frozen M_0 digests were unchanged when re-checked immediately before probing, and all 16 cycles were version-consistent. Across 712 cross-credential cells (280 on Gitea plus 432 on GitLab), E and Y agree in 712 cases, so no cell is scored on a modelling discrepancy.

The stale model produces 29 false proofs (13 on Gitea, 16 on GitLab), and a recrawl with the same credential removes 29 of them, leaving 0 still missed and 0 live false proofs (Table 12). The composition is informative rather than uniform, and the two products agree on its shape: one cell for the direct grant, one for the inherited-channel attachment, five and six when a repository becomes public, and six and eight when a user becomes site administrator. The last two are the cases a single-object probe is least likely to anticipate, because the granting event is not about the object at all.

Revocations behave differently and must not be scored as misses. The old model still lists 17 cells whose access was revoked (7 on Gitea, 10 on GitLab). In every one of them the request is refused, so no violation occurred; treating them as false negatives would require $E = \text{deny}$ *and* $Y = \text{allow}$, which never happens here.

The multi-channel transition is where the products part company, and the difference is itself a result. On Gitea, after the team member is removed, `acme/t1` remains readable through a direct collaboration while `acme/t2` becomes unreadable, and the ledger records the remaining channel. On GitLab the same test has to be moved outside the group namespace: removing a member from a group also deletes that user's project-level membership in the group's projects—the project's direct-member list went from one entry to none—so a direct grant placed inside the group would have measured that product rule instead of multi-channel access. We therefore placed the alternative channel on a personal project, and we record the cascade as a product-semantics observation rather than encoding it as a ledger rule (amendment A2 in the protocol record). This is the kind of non-local side effect that makes a hand-maintained expectation model wrong in a way no single probe can reveal.

For the role change, the read cell is unchanged while the write probe goes from HTTP 403 with unchanged content to HTTP 201 with the owner re-reading the new bytes; the owner then deletes the probe branch and observes 404, and the repository's `README` digest is unchanged after cleanup.

The oracle column separates the products more sharply than the transition counts. On Gitea the owner vantage answers 224 of 280 cells (the remainder are anonymous, for which no oracle credential exists), but the subject's own vantage answers only 7—all of them after the site-admin grant; outside it, a read collaborator receives HTTP 403 and

an outsider HTTP 404. On GitLab the owner vantage answers 360 of 432, and there the subject's own credential answers 360: GitLab's member endpoint is readable by any project member. That readability is not soundness. The endpoint answers "is this principal a member", so it returns 404 for a public project a non-member may read and for a site administrator who may read everything. Measured against the ledger, the Gitea oracle disagrees on 0 cells and the GitLab oracle on 53, all of the latter in the public (44) or site-administrator (9) channel. A readable oracle can therefore be systematically wrong in exactly the channels that are cheapest to overlook, which is why we never let it set E. The two calibration regimes record this rather than hide it: 6 known cells on Gitea, and on GitLab 4 gated cells plus two recorded diagnostics for the secondary vantage (amendment A1).

A channel-by-channel view makes the mechanism explicit (Table 11). Both products answer every direct-collaborator and group cell correctly, and Gitea also answers its public and site-administrator cells correctly. GitLab errs only by omission, and only on the two channels that are not membership: it answers *deny* on 44 public cells that a non-member may read and on 9 site-administrator cells. Neither product returns a single false allow. A one-sided error is nevertheless sufficient to manufacture a false proof, because an alarm on such a cell is then adjudicated against a deny that the ledger does not support—which is the cross-vendor failure reported in Section V-B, now located in a named channel rather than attributed to "the oracle" as a whole.

Two properties of the run are recorded because they are what an external check can verify. The protocol was frozen before the first Gitea transition, and its digest is carried in both run records; the two amendments were written, with timestamps and the base-protocol digest, before the first GitLab transition, and the pilot that motivated the second is archived with its cells excluded from every denominator. Inside a run, every cell carries its event sequence number, the harness version before and after the transition, the M_0 and M_1 digests and wall-clock timestamps, so the ordering—crawl, freeze, mutate, recrawl, oracle, probe—can be re-checked line by line rather than trusted. Every observation in that loop is a GET; the only mutating calls are the transitions themselves, and each is recorded with its status code. Failed observations are not dropped silently: a transport error after two retries is recorded as such and excluded from the scored set, a mutation outside 2xx excludes its whole transition, and an unreadable oracle is recorded as *unknown* with the cell still scored on E and Y.

Three scope limits are part of the result. First, 0 residual is a count on these surfaces, not a completeness claim: the crawl sources themselves define what can be seen, deploy keys are outside the ledger, and we did not construct a channel that the recrawl is known to miss. Second, *hv* is a harness-maintained logical version, not an atomic server snapshot; the harness is single-threaded and no concurrent writer ran, which is what makes the still window meaningful. Third, the eight transitions are a designed set, not a sample of deployment changes, so none of the counts is a field rate.

B. CROSS-VENDOR REPLICATION OF THE SNAPSHOT DESIGN: GOGS 0.14.3 AND GITLAB 17.11.7

We repeated the same three-phase protocol and 48-cell design on two further systems (Table 13): **Gogs** 0.14.3, the project Gitea forked from in 2016 (related lineage, independently evolved code; census from its pinned route table, 80 paths), and **GitLab** 17.11.7 (no lineage; census from the pinned running instance's routes, 1357 paths, since its OpenAPI document omits core grant endpoints). Gogs is a replication across implementations, GitLab across vendors within one domain.

The replication introduces a primary methodological variation: the authorization-introspection surface, which shows that *readability does not imply soundness*. Gitea's owner-vantage surface is readable and sound (agrees with effective access on all 48 cells). Gogs's collaborator-membership endpoint is equally readable (48/48) but unsound—wrong on 17 cells (35.4%), exactly the authorizations arising outside direct membership: site administration (8), public visibility (5), out-of-band grants (4). GitLab's `members/all/{u}` resolves inherited membership, but public visibility and site administration confer none: 18 false negatives (37.5%). What a surface cannot see is predictable from what it measures—why clause (2) of the admissibility condition (Section VI-D) cannot be automated from readability alone. The consequence is measurable: on Gitea the surface-gated adjudicators produced no false proofs (0 v3, 0 direct-observe), while on Gogs they manufacture them (8 snapshot, 5 live, 17 direct-observe) and on GitLab again (5, 18), every v3 false proof falling on a cell whose authorization derives from site administration or public visibility (8 and 5 such cells on Gogs; 8 and 10 on GitLab). A readable membership surface with a blind spot converts that blind spot into confirmed violations; no admissible oracle was available from the tested introspection surfaces on Gogs or GitLab, so the honest adjudicator abstains on the stratum where those surfaces would license a promotion.

Two results replicate everywhere: bookkeeping alarms false-proof on legitimately granted access (Gitea 10, Gogs 11, GitLab 10 cells) with the same out-of-band-dominant grant profile; and the reachability mismatch persists (Gitea 10, Gogs 19, GitLab 10 snapshot). On Gogs the mismatch only partially resolves live (13 remain—team or public grants never enter a subject's personal crawl); on GitLab the live reading recovers everything (0 remain)—a second, vendor-specific failure of the snapshot premise, in the crawl model rather than the oracle.

C. A SEEDED POSITIVE CONTROL

On the tested endpoints and transitions the three real systems enforce the expected decisions, so the question remains: *when a real object-level flaw is present, does the same detector find it?* We answer with a positive control. A *controlled authorization target* faithfully emulates the Gitea API contract the engine consumes, with a correct internal authorization

TABLE 11. Oracle fidelity by granting channel, over the same transition cells as Table 12: a confusion matrix of the owner-vantage oracle against the ledger, per channel and per product. *allow* and *deny* count cells where the oracle agrees with the ledger; *f. allow* and *f. deny* are the two error directions; *unans.* counts cells where the surface returns no definite answer (anonymous readers). A false deny is an oracle that answers deny on a legitimately readable cell. Neither product produces a single false allow: the membership surface errs only by omission, and public and site-admin cells are exactly the channels that are not group or repository membership. The "no channel" row is the default-deny stratum: no grant of any kind is recorded for those cells, so the ledger denies them.

(a) Gitea 1.22.6						
Channel	cells	allow	deny	f. allow	f. deny	unans.
site administrator	7	7	0	0	0	0
public visibility	44	35	0	0	0	9
direct collaborator	25	25	0	0	0	0
team / group	1	1	0	0	0	0
no channel	203	0	156	0	0	47
total	280	68	156	0	0	56
(b) GitLab CE 17.11.7						
Channel	cells	allow	deny	f. allow	f. deny	unans.
site administrator	9	0	0	0	9	0
public visibility	53	0	0	0	44	9
direct collaborator	25	25	0	0	0	0
team / group	7	7	0	0	0	0
no channel	338	0	275	0	0	63
total	432	32	275	0	53	72

TABLE 12. Temporal transitions on two products with the same pre-registered protocol. *Stale FP*: the frozen pre-change model does not list a resource the subject may legitimately read, so the relation would report a false proof. *Fixed*: a recrawl with the same credential lists it again. *Missed*: the recrawl also fails to list it. Each product has its own mechanism per row (team attach ↔ project-group share; team member removal ↔ group member removal), its own cell count (280 on Gitea, 432 on GitLab) and its own decision-time ledger; no row is pooled across products.

	Gitea 1.22.6			GitLab CE 17.11.7		
Transition	Stale FP	Fixed	Missed	Stale FP	Fixed	Missed
direct grant	1	1	0	1	1	0
direct revoke	0	0	0	0	0	0
team attach	1	1	0	1	1	0
team member remove	0	0	0	0	0	0
private→public	5	5	0	6	6	0
public→private	0	0	0	0	0	0
role read→write	0	0	0	0	0	0
site admin grant	6	6	0	8	8	0
Total	13	13	0	16	16	0

model and 3 seeded vulnerable instances—all instantiating one fault pattern (a none-entitlement subject served the object at `GET /api/v1/repos/{owner}/{repo}`), differing in subject and object, not in fault location; Table 14 is therefore evidence about this fault pattern, not three independent defect discoveries. Two design points. The target deliberately exposes its authorization state to the subject-side harness (mirroring the admissibility condition), which production Gitea does not—there the oracle is readable from the owner/admin vantage (56/56) but not from an arbitrary subject's (0/40)—and its introspection surface reports the *correct* `none` permission, so the oracle stays sound and the defect is visible only as a discrepancy between oracle and request. We drove it with the same topology, mutation, crawl, introspection and adjudication code as above, differing only in the system under test; ground truth comes from the seed list, not from the detector.

Table 14 is consistent with the negative result of the ablation in this controlled fault pattern: `direct_observe` and `v3` catch all 3 planted instances with zero false positives, while `direct_only`, which ignores the request outcome, raises 30 alarms on cells where the surface says `none` and no access succeeds—alarms our strict definition does not promote. The control thus narrows the claim to one fault pattern: when a surface that fully resolves the authorization question is available, the metamorphic step is not necessary for detection here. It does not generalise beyond that pattern, and it also delimits the detector: we seeded one BFLA defect (non-privileged bob succeeding at `PUT .../collaborators/{u}`, HTTP 204), which the read-oriented logic does not cover—a known boundary, reported as such rather than as a detection failure. This is a controlled research artifact, not production Gitea; a sanity check on the detector's logic, not a validation of detection effectiveness on a population, and not a statement about Gitea's CVE posture. Its source, seed list and run script are in the reproducibility package at https://github.com/ubfbuz3/JISA (tag `artifact-v1`).

TABLE 13. Cross-vendor replication under the identical three-phase protocol (crawl, out-of-band authorization change, adjudicate) on Gitea 1.22.6, Gogs 0.14.3, and GitLab 17.11.7. Counts are per reading of the same 48-cell grid; the live reading is given in parentheses where both exist. The snapshot reading is the operating point of the published relations. Gitea and Gogs share lineage (fork, 2016); GitLab shares none. The team-derived row is read out of the per-system oracle false negatives by channel (Section V-B). The Gitea grant count here is the *normalised* M1 census (semantically equivalent routes merged, non-authorization grant surface excluded), and therefore differs from the raw route count in Table 7; the two tables use different normalisations and are not in conflict.

	Gitea 1.22.6	Gogs 0.14.3	GitLab 17.11.7
API entries in pinned version (M1 denominator)	253	80	1357
Grant endpoints (M1)	13	10	18
of which usable without site admin	10	4	17
Owner-vantage oracle readable	48	48	48
oracle agrees with actual access	48	31	30
oracle wrong (false negatives)	0	17	18
oracle wrong: team-derived access missed	0	4	0
Subject-vantage oracle readable	8	35	48
Reachability mismatch, snapshot (live)	10 (0)	19 (13)	10 (0)
False proofs: bookkeeping alarm, snapshot (live)	10 (0)	11 (5)	10 (0)
False proofs: v3 (oracle-gated), snapshot (live)	0 (0)	8 (5)	5 (0)
False proofs: direct-only (oracle only)	0 (0)	17 (17)	18 (18)
False proofs: direct-observe (oracle ∧ request)	0 (0)	17 (17)	18 (18)

TABLE 14. Positive control: detection of 3 seeded vulnerable instances (one fault pattern). TP/FN/FP/TN are counted against the known seed, not against a model.

method	TP	FN	FP	TN
`mr_bookkeeping`	3	0	2	43
`v3` (owner vantage)	3	0	0	45
`v3` (subject vantage)	3	0	0	45
`direct_only`	3	0	30	15
`direct_observe`	3	0	0	45
`direct_observe` (subject)	3	0	0	45

D. A PUBLICLY FIXED DEFECT

The seeded control is a controlled artifact, so we also ran one defect that nobody here planted: Gitea 1.20.5 against 1.20.6, the release whose notes record a security fix titled "Fix comment permissions" (`#28213`, backported as `#28216`); the same defect is catalogued as CVE-2023-49946 for Forgejo, the fork that reported it. What is missing is object ownership rather than path permission: a caller entitled to the repository named in the URL can address an object that belongs to a different, private repository.

Each version runs as a fresh instance, and the collision is built into the topology: alice owns a private repository with one issue comment, bob owns a public one. Bob sends `PATCH/api/v1/repos/bob/pub/issues/comments/{alice's comment id}` with a replacement body. On 1.20.5 the write succeeds (HTTP 200) and alice's own re-read returns the replacement body, so the effect is real and not a status-code artifact. On 1.20.6 the same request is refused (HTTP 404) and alice's re-read is unchanged (Table 15). The ledger gives bob no write channel on alice's repository (E = deny), so the vulnerable cell is a true positive under the definition used throughout, and the fixed cell raises no alarm: 1 true positive and 0 false proofs across the pair. All 10 control writes behave as expected in both versions—bob's own comment is editable, the correct path is refused, a third user is refused, anonymous is refused, an absent identifier is refused—and alice's restore returns the body to the original

TABLE 15. A publicly fixed defect (object-versus-path ownership). The verdict uses E from the ledger and Y from the owner's re-read, not the write status.

version	PATCH	re-read	verdict
1.20.5 (vulnerable)	200	changed	true positive
1.20.6 (fixed)	404	unchanged	no claim

in 2 of 2 instances.

What this establishes is narrow, and worth stating plainly. It shows that the E/Y gate can issue a correct violation claim and stops issuing it once the vendor fixes the defect, so the gate is not merely a false-alarm suppressor. It does not show that we can *find* such defects: the identifier is given, the defect is public and already fixed, and the exercise is a positive control for the gate, not a discovery. Nor is it an evaluation on a population—one defect, one fault pattern (object versus path ownership), one product line.

VI. FINDINGS, ADMISSIBILITY, AND FALSIFICATION

Each finding is a boundary on what the published relations can establish about object-level authorization—*temporal*, *oracle* and *measurement*—carried by the studies of Sections IV–V. The confirmations they rest on (the predicates read at source, the published relations executed on a real system, an independent implementation of the same predicates) introduce no further claim and are collected as support evidence in Section VII.

A. FINDING 1 (RQ1): DETERMINISTIC FALSE PROOFS—THE TEMPORAL BOUNDARY

Taken as published—raw alarms, or alarms filtered by bookkeeping exceptions—the adjudication reports a legitimate access granted out of band after the crawl as an already-established violation, in the direction forced by the two-valued predicate encoding. On the constructed system, rate 1.00 (8 of 8 alarms) against 0 for the same share created in band; on Gitea, 10 false proofs on 25 authorized cells (0.40)

under the crawl-time reading, against 0 alarms live—objects, entitlements and predicates held fixed, only the reading time changed—so the error is a property of the *reading*, not of the system; the endogenous control (Table 10) holds final visibility fixed and isolates that moment. The direction is forced: the predicate has exactly two representations, and a grant created outside the crawled interface has no representation but ''cannot reach''. The predecessor attributes its residual false alarms to crawler coverage [3]; we add that the failure is a function of *when* the model was read, which makes the natural oracle-based repair available while showing no incremental adjudication benefit from the metamorphic step (Finding 2).

B. FINDING 2 (RQ2): THE METAMORPHIC STEP ADDS NO OBSERVED ADJUDICATION BENEFIT

If the false proofs of Finding 1 are removed by consulting a readable introspection surface, it is the oracle that carries the work: for the authorization relations and scenarios evaluated here, once the oracle fully resolves the authorization proposition under test, replacing the entire metamorphic step with a single ordinary request—one that consumes the same readable oracle and access outcome—provides no observed incremental adjudication benefit. We state the reason rather than present it as a discovered effect: its burden is an empirical premise about the evaluated relations, not an algebraic identity.

We separate the two parts, because only one of them can fail. The algebraic part is a lemma about function composition; the empirical part is a statement about what these two relations actually read, and it has a falsifier.

The direct adjudicator. Fix, before any run, the rule D that issues `violation-proven` for (o, s, a) exactly when the oracle O answers *deny* and the ordinary request R succeeds. D consumes O and R and nothing else. It is a definition, not a result, and it is the comparator in the ablation of Section IV-C (`direct_observe`).

Lemma 1 (absorption)**.** Let a detector issue its verdict through a map $g(A, O, R)$, where A is its alarm and O, R as above. If, on the domain of cells considered, (i) A is a function $a(M, R)$ of the crawl-time model and the response only, and (ii) M is O-determined for the authorization proposition under test—that is, M carries no distinction the oracle does not already make—then there is a map g' with $g(a(M, R), O, R) = g'(O, R)$ on that domain.

Proof. By (i) the first argument of g is a function of (M, R); by (ii) M is a function of O on the domain; substituting gives $A = a'(O, R)$, so g factors through (O, R) as $g'(O, R) := g(a'(O, R), O, R)$. □

The lemma is deliberately weak: it says that *if* a detector reads nothing beyond the model and the response, its verdict cannot carry information the pair (O, R) lacks. It does not say that any particular implementation satisfies (i) or (ii), and it does not compare two programs—it compares two functions on a domain.

Proposition 2 (the two relations fall in the lemma's domain)**.** For the two relations examined here, premise (i) holds by source inspection: their predicates read the crawl-time reachability model and the response, and nothing else (Section VII-B). Premise (ii) holds on the cells tested, where the oracle is readable and sound: M and O agree on the authorization proposition, so M adds no distinction. Consequently the verdict of each relation is extensionally the direct adjudicator D on those cells, and the equality is checked, not assumed, by the paired ablation: the two methods disagree on 3 of 216 true-violation records (Section IV-C).

The predicates, explicitly

Write y for the response bit, $y = 1$ when the ordinary request returns no error; m for the model bit, $m = 1$ when the crawl-time reachability model lists the object for the subject; and o for the oracle bit, $o = 1$ when the introspection surface answers *allow*. The two shipped predicates then read

$$A_{002} = \neg\mathrm{sup}(B, A) \ \wedge \ \neg m \\ \wedge \ \neg\mathrm{err}(o_1) \ \wedge \ q(o_1, o_2), \tag{1}$$

$$A_{004} = y \ \wedge \ \neg m, \tag{2}$$

where err is the error predicate and q normalised response identity. On the domain evaluated here $\neg\mathrm{sup} = 1$, $\mathrm{err}(o_1) = 0$, and $q = y$ in all 312 records on which the second clause was computed, so both collapse to the single map

$$A \ = \ y \ \wedge \ \neg m. \tag{3}$$

The direct adjudicator is $D = y \wedge \neg o$, so $A = D$ exactly when $m = o$: the two expressions share the factor y, and that step is algebra. Equations (1)–(3) are not a paraphrase of the code; they reproduce the recorded alarm of all 576 constructed records and all 712 temporal cells with no disagreement (`analysis/ingest_truth.py`). What the proposition adds to the algebra is the empirical premise that $m = o$ wherever the oracle is readable and sound.

Reading the table

Table 16 evaluates both verdicts on every combination of the four variables and reports how many of the 712 temporal cells fall in each row, split by the ledger's entitlement. Three things are visible in it that prose cannot state as compactly. First, the equivalence is exactly as narrow as the algebra says: the two verdicts agree in 530 of the 584 cells with a usable oracle and part only in the two rows where $Y = 1$ and $M \neq O$, which hold 54 cells. Second, the parting is not one phenomenon but two, and they need different remedies. In the 40 cells of row 6 the model is right and the membership surface answers *deny* on a cell that is both entitled and readable, so the direct adjudicator alone raises a false proof; a better oracle would remove those. In the 14 cells of row 7 the model is stale and the oracle right, so the relation alone raises a false proof; a recrawl would remove those. Third, row 5 shows why agreement is not a certificate of correctness: in 13 cells both surfaces answer *deny*, the ledger says the subject is entitled, the request succeeds, and both verdicts are false proofs. The proposition is about information, so it is silent on row 5—but

TABLE 16. The truth table of the two relations, with the temporal cells that fall in each row. *Y*: the ordinary request succeeds. *M*: the crawl-time model lists the object for the subject. *O*: the introspection surface's answer, an em dash meaning it returns no definite answer. *A*: the alarm of either relation; on this domain both reduce to $y \wedge \neg m$. *D*: the direct adjudicator, $y \wedge \neg o$, undefined in rows 9–12. The count columns split each row by the ledger's entitlement *E*, so every row states its truth conditions for both values of *E*; a dot is an unrealised combination, and in the verdict column the first term reads *E*=deny and the second *E*=allow. Where *D* is defined the two verdicts coincide whenever *Y*=deny or *M*=*O*, and part only in the two rows with *Y*=allow and $M \neq O$—54 of the 584 readable cells. Those two rows are the two failure mechanisms that Section V-B keeps apart: in row 6 the model is right and the oracle wrong, so *D* alone raises a false proof; in row 7 the model is stale and the oracle right, so the relation alone does. Row 5 is the case neither explains—both surfaces answer *deny* on a cell the ledger allows, both verdicts are false proofs, and their agreement certifies nothing.

Y	*M*	*O*	*A*	*D*	verdict at the ledger	*E*=deny	*E*=allow
deny	blocked	deny	0	0	no access	416	·
deny	reach	deny	0	0	no access	15	·
deny	blocked	allow	0	0	no access	·	·
deny	reach	allow	0	0	no access	·	·
allow	blocked	deny	1	1	true positive / false proof	·	13
allow	reach	deny	0	1	miss / false proof by *D*	·	40
allow	blocked	allow	1	0	true positive / false proof	·	14
allow	reach	allow	0	0	miss / correct silence	·	86
deny	blocked	—	0	—	no oracle; no access	108	·
deny	reach	—	0	—	no oracle; no access	2	·
allow	blocked	—	1	—	no oracle; alarm	·	2
allow	reach	—	0	—	no oracle; miss / silence	·	16

a reader who took $A = D$ as evidence that the pair decides correctly would be wrong there, and the table says so before the reader has to notice it.

Two further readings of the same table belong here, because both bear on how far the result travels. The rows without an oracle are not idle: 128 cells return no definite answer, *D* is undefined on all of them, and the relation still alarms in 2—alarms that nothing in this experiment can adjudicate, which is the regime the proposition's antecedent excludes rather than a gap in it. And the model term is not free. Recomputed over the two model semantics of the constructed study, the constant variant, which alarms on every successful access, finds 108 violations at 72 false proofs; the crawl-time term finds 105 at 48—24 fewer false proofs for 3 fewer detections, over 288 records each. A relation with a reachability gate is therefore neither the alarm-free ideal of Finding 2's antecedent nor a free improvement on the ungated variant; it trades one error for the other, and the trade is the reason the gate is worth stating as a variable rather than folding into the oracle.

Three differences from the ideal predicate

Equations (1)–(3) describe the predicates as written, and the shipped code departs from them in three places. None changes the algebra; each either moves cells out of the domain or corrupts a variable the two verdicts share, which is why none of them makes the relation beat *D*. (i) *The model term is a store, not a query.* `cannotReachThroughGUI` and `userCanRetrieveContent` are set membership over the crawl inputs: they issue no request and read a store loaded once. So *m* is fixed at crawl time while *y* and *o* are read at decision time, and rows 6–7 are precisely the cells on which that interval carries a change. (ii) *The error predicate is a status code.* MST-wi asks whether an error page is rendered; the port asks whether the status is at least 400. A denial served with 200, or an error page served with 403 on the subject's own object, makes *y* wrong—and *y* enters both *A* and *D*, so the two stay tied while both are wrong. This is the sense in which the tie is evidence about information and not about accuracy. (iii) *Response identity is not authorization identity.* The clause *q* compares the whole normalised response, not the authorization proposition under test; a per-viewer field would make *q* false while access had in fact been granted, and the relation would stay silent on a violation. On the evaluated domain this does not bite ($q = y$ throughout), but it is the one of the three that produces a miss rather than a false proof, and it would grow if the relation were extended to responses carrying viewer-specific fields.

The proposition is falsifiable in one specific way: exhibit an observable Z, *other than the model and the response*, that a relation consumes and that is decision-relevant. Then premise (i) fails, the lemma does not apply, and the relation could in principle beat *D*. The model itself is not such a Z: a stale model also fails to be *O*-determined, but that breaks premise (ii), and the direction of the break is visible in Table 16—row 7 is a false proof, not an advantage. We know of no such observable for these two relations, and the ablation is consistent with its absence; that is the whole of the claim. We do not assert that no such observable could exist for other relations in the catalogue, and we do not assert that the relations are useless.

The proposition concerns *adjudication* information only. It does not imply that a metamorphic relation cannot improve input generation, search-space reduction, or execution efficiency: a relation may guide which requests are issued, or which gated subset is exercised, while carrying no verdict information beyond (O, R). It is a requirement on *claims*, not a verdict on metamorphic testing: it says only that a verdict computable from (O, R) cannot be shown to beat the direct consumer of (O, R).

Scope, quantified

The comparison above is pooled. Section IV-F re-runs it inside each stratum of effective oracle readability (Table 6) and thereby bounds the claim rather than widening it. Where

the oracle is readable (312 records) the conclusion is stronger than ''no observed benefit'': the plain request carries fewer false proofs (0 vs. 36) and no fewer detections. Where it is not (264 records) the antecedent fails—there is no oracle to consult, and every oracle-bearing method detects nothing by construction—so the metamorphic family is compared against oracle-free references instead: it retains an advantage over a trivial floor and over a single uninterpreted request (2.000× vs. 1.692× over the base rate), and that advantage is exactly coextensive with what the crawl-derived model can see. Finding 2 is a claim about the regime its antecedent describes; it does not say the relations are worthless outside it.

Evidence: Table 3—0 false proofs vs. 0 (a tie at zero, not a win) over the 216 true-violation records. The comparison is paired, so we report the discordance rather than an inferential interval: the two methods disagree on 3 records, and on every one `direct_observe` is right—the aggregate recalls 0.50 and 0.49 restate that asymmetry rather than measure a difference, and no margin was fixed in advance. Gitea independently reproduces the zero-false-proof result (0 vs. 0), but not the same comparison, because the tested surface contains no seeded vulnerability; the cross-vendor systems (Section V-B) and the seeded control (Section V-C) complete the evidence. One qualification is part of the claim: the control is *constructed*, not discovered—`direct_observe` instantiates the direct-consumer construction D of Proposition 2, so the tie is the empirical face of the necessary condition, a statement about the definitions rather than a coincidental measurement.

C. FINDING 3 (RQ3): THE REPORTED SPECIFICITY IS NOT CONDITIONED ON THE CORRESPONDENCE IT ASSUMES

The reported 99.81% is a statement about a corpus of generated inputs; it is not conditioned on an explicit check that the reachability model coincides with the true authorization state, and its input-level denominator cannot, on its own, provide stable scenario-level resolution for a scenario-uniform failure. The omission: adjudication is a function of the reachability model, so where model and true state diverge—the out-of-band case of Finding 1—the figure measures agreement with the tool's own crawler; the authors concede the mapping is ''not always available'' [2], but the number is reported without the condition. The denominator: a failure uniform across a scenario class contributes only as many false positives as that class emits inputs, and is diluted by the rest of the run (Proposition 1: in our approximation the configuration that misreports a whole class of legitimate access still scores 84.62%; Corollary 1: no fixed threshold can guarantee that such a class forces the metric below it). Nor does the report fix the weights: if a failing class supplies a share w of the follow-up inputs, the figure moves only between 1 and $1 - w$, so telling a small-share class failure apart from no failure at all requires an estimate of w that the published number does not carry. We are not saying the figure is false or the false positives misdiagnosed; the claim is that such a metric does not itself validate the reachability-to-authorization correspondence on which its interpretation depends, and that a class-uniform failure can be held above any fixed threshold by unaffected inputs.

D. ADMISSIBILITY, AND FALSIFICATION

Three properties must be kept apart. A surface is *readable* when its answer can be obtained from the vantage in question; *sound* when its answer equals the true authorization state; and *admissible*, for promotion to `violation-proven`, when (1) it is readable *and* (2) one can give a reason that it is not of the same kind as the defect under test—not itself a reachability artifact whose blind spot correlates with the blindness tested. Readability is what makes soundness usable, but it neither implies soundness nor confers admissibility: the owner-vantage authorization-introspection surface is readable on every cell in each system (48 Gitea, 48 Gogs, 48 GitLab), yet sound on Gitea alone—it agrees with effective access on 48, 31 and 30 of those cells respectively. The cross-vendor systems are therefore not cases of ''no oracle'': a readable membership surface exists on both, but it is unsound for the authorization channels exercised here, so it fails clause (2). Clause (2) is a per-system judgement and not automatable from readability alone; the cross-vendor results make it concrete (Gogs and GitLab fail it; their adjudicators convert the blind spots into 8 and 5 false proofs). Where the condition holds, the honest method consumes the oracle directly and drops the relation; where it does not, the honest method abstains—as v3 does on the unreadable stratum, where the aggregate table would have ranked it best, a ranking that reflects abstention rather than improved detection.

Read together, the two findings bound what the technique's adjudication can yield for the authorization proposition studied. If the reachability stand-in is the only warrant and it is wrong, a legitimate access becomes a false proof (Finding 1). If a readable, sound oracle is instead available, the relation adds no adjudication over the direct consumer of that oracle and the outcome (Finding 2). And where no readable, admissible oracle exists—the black-box case—there is nothing for a sound method to consume, so it abstains rather than proves. Across the statuses the oracle can take, the verdict the evaluated relations can yield is thus a false proof, a result no better than the plain request (and, where the oracle is readable, worse), or an abstention. None of those is a proof of illegal access, because the relation's alarm is not evidence of it: an alarm says that the relation failed, and an ordinary request that succeeds says that the object was served. A genuine violation becomes reportable only when an independent entitlement source says *deny* and a content-level effect observation says *allow*; Section V-D reports that gate producing one true positive on a vulnerable build and none on its fixed successor. The relation contributes to neither side of that conjunction.

Each finding would fall as follows: Finding 1, if the predicates were defined over live rather than recorded reachability; Finding 2, by an authorization MR needing an observable that a succeeding request plus a readable oracle cannot produce; Finding 3, by a specificity in scenario units, or with the

condition explicit, that still fails to separate the configurations studied here.

Table 17 states, for each research question, what is assumed, what was measured, and what the result does not cover. We add it because the three findings rest on different kinds of evidence—source-level functional dependence, a constructed enumeration, and two real-system studies—and a reader should be able to see which kind carries which sentence.

VII. SUPPORT EVIDENCE

Nothing here is a further finding. This section holds what the three findings rest on: the semantics of the two governing predicates read at source (Section VII-B), an execution of the published relations on a real system (Section VII-C), and the robustness of our numbers to a second, independent implementation of the same predicates (Section VII-D); the seeded positive control (Section V-C) and the cross-vendor replication (Section V-B) are the remaining confirmations and stay with the study that produced them. Each item is a confirmation of a mechanism already stated, not a new claim about what the technique can detect.

A. THE ENUMERATION, CELL BY CELL

Table 18 is the mapping the review asked for: every configuration against every scenario, with the number of records under each populated cell and a dash where the combination is undefined. The eight configurations are the full cross of instantiation mode, enforcement correctness, channel visibility and introspection availability, less the two corners that do not exist (no exception mechanism to list a share under, and no listed share to read with the surface off). Each populated cell holds $52 + 44$ records: three exception policies and two crawl readings for each relation that applies there.

Two partitions of these records are easy to confuse, because both are counted in the same totals. Split by relation, MR-002 holds 312 records and MR-004 264, since S5 carries the first only. Split by effective readability, 312 are readable and 264 are not, since four of the eight configurations expose a surface and four do not. The two pairs of totals coincide; the partitions do not. Section IV-F uses the second, and every statement about it can be recomputed from the census column by column.

B. CONFIRMATION AT SOURCE

Definitions can be read generously, so we checked the predicates at source in the public library [2]. It ships 23 relations, 11 authorization relations, 8 gating on the two predicates analyzed. Four implementation-level properties not made explicit in the main presentation: (1) *the freeze is hard-coded*—`cannotReachThroughGUI` is set-membership over the crawl inputs, issues no request, and is cached in a field written once and never invalidated (`userCanRetrieveContent` likewise reads a crawl-produced store loaded once); (2) *the clause that could have caught it is inert*—the "absent across all users" set is built by stopping each recorded sequence at the first login action, so it is always empty; (3) *missing data defaults to an alarm*—with an empty or null crawl argument the predicate returns "cannot reach", so an empty crawl *satisfies* the precondition: the mechanism behind Finding 1's deterministic direction; (4) *the role relation is configuration, not state*—the supervisor guard reads a static configuration file and reports true for identical accounts, so it cannot reflect a later grant.

C. EXECUTING THE PUBLISHED RELATIONS

The library ships relations but no execution environment; we supplied the system configuration and crawl snapshot and ran the relations—source unmodified, build configuration (`pom.xml`) and an external harness added (1 changed upstream file, 0 changed Java sources, two added classes totalling 612 lines)—against Gitea 1.22.6 (Table 19). 10 of 11 authorization relations executed; 2 returned failures, 6 alarms in all—the engine's own `getFailures()` value (Table 21). What the run establishes is scoped to the *reachability-gated subset that fires here*, not a full replay of the catalogue: one relation aborts on an engine-side defect, most issue no request because their own guards are unsatisfied, and the content predicate is never invoked. Almost none of the 1483.7 seconds is analysis: each leaf evaluation invokes a browser-cleanup hook costing minutes, a cost of the missing environment that bounds any reproduction.

The load-bearing cell: the subject bob holds a legitimate entitlement to alice/s1, granted out of band after the crawl. There the published `cannotReachThroughGUI` answers "cannot reach"—the answer it is *defined* to give, since the subject's crawl record has no entry for the repository; across the run it answered so 1149 of 7321 invocations (15.7%), 5 on this cell, and 2 relations (OTG_AUTHZ_002, OTG_AUTHZ_002c) report a failure there. The access is authorized: all 3 granted cells were re-probed, and the grantee's response hashes identically to the owner's while a third account is refused. The 6 alarms fall on 3 cells, all post-crawl grants, none on a non-entitled object. Limits: the harness's HTTP observation channel is exact for the reachability predicate (set-membership, no request) but unexercised for the content predicate (0 invocations; supervisor guard 8642, 1321 true); not all gated relations fire, for reasons inside their own guards, and 1 abort on an engine-side defect—so the reproduced false proof is that of the reachability-gated subset that fires, not a full-replay count of the published relations. And Gitea, on the tested surface, enforces the expected decisions, so the run can only exhibit false proofs.

Which stage of that claim does the native run establish?

Three stages have to be kept apart, and only the third is a security finding. The *native alarm A* is what the engine itself returns: `getFailures()` is appended by `MR.fail()` (`MR.java`:909), which logs `FAILURE` together with the failing input pair and asserts nothing about authorization—no ledger, no expected decision, no verdict. Reading a fired authorization relation as a *violation claim H* is a promotion

TABLE 17. Evidence to claim. Each row names the assumption the claim needs, the artefact that carries it, and the boundary that remains. The last row is not a research question: it checks the adjudication gate used throughout, and is not evidence about detection effectiveness.

RQ	Claim	Assumption it needs	Evidence	What it does not cover
1	A crawl-time reading reports an out-of-band grant of legitimate access as a proven violation.	The grant occurs after the crawl, is recorded in the ledger, and is reachable through a channel the crawl does not enumerate.	576-record constructed study; 16 committed transitions on Gitea and GitLab, 29 stale false proofs, all 29 removed by a same-credential recrawl.	Two relations of one reachability-gated family; designed transitions, not a sample of deployment changes; no residual miss is a completeness claim.
2	Once a readable, sound oracle is supplied, the relation adds no observed adjudication benefit over the direct consumer of the same oracle and outcome.	The oracle is readable and sound on the cells scored; the relation consumes no decision-relevant observable outside (O, R).	Paired ablation on 216 true-violation records, disagreeing on 3; channel-level oracle fidelity over 712 cells.	Conditional on the antecedent: the unreadable stratum has no oracle to consult, and the oracle shares its implementation with enforcement.
3	The published specificity is an input-level figure whose denominator cannot, on its own, expose a class-uniform failure.	Scenario classes emit comparable numbers of inputs, so a uniform failure is diluted by unaffected inputs; the class shares are not reported, so the dilution is bounded rather than estimated.	Proposition 1 and its corollary; sensitivity of the example to the assumed inputs per case.	The original per-case denominators are unavailable, so the published figure is diagnosed rather than re-estimated.
Gate	An independent entitlement ledger plus a content-level effect observation reports a real defect as a true positive and stays silent on its fix.	The ledger is complete for the tested object and the effect is read back by the owner, not inferred from a status code.	Gitea 1.20.5 versus 1.20.6: 1 true positive, 0 false proofs, 0 alarms on the fixed build, 10 control probes as expected.	One publicly fixed defect found and supplied by us; this is a check of the gate, not a recall estimate.

TABLE 18. The enumeration itself: records under each configuration and scenario. A dash is an inadmissible combination, not a missing run—the no-exception configurations have no legitimate-sharing facility, so S6 and S7, which are defined by a share the facility did not record, are undefined for them. Each populated cell holds six exception-policy × crawl-reading records per relation.

configuration	S1	S2	S3	S4	S5	S6	S7	total
`V-E3-vuln0-unlisted`	12	12	12	12	6	12	12	78
`V-E3-vuln1-unlisted`	12	12	12	12	6	12	12	78
`V-E3-vuln0-listed`	12	12	12	12	6	12	12	78
`V-E3-vuln1-listed`	12	12	12	12	6	12	12	78
`V-E3-vuln0-unlisted-nointro`	12	12	12	12	6	12	12	78
`V-E3-vuln1-unlisted-nointro`	12	12	12	12	6	12	12	78
`V-noE3-vuln0`	12	12	12	12	6	—	—	54
`V-noE3-vuln1`	12	12	12	12	6	—	—	54
records	96	96	96	96	48	72	72	576
cells	8	8	8	8	8	6	6	52

TABLE 19. Execution facts for the native run of the published relations (Section VII-C). All values are emitted by `ingest_native_engine.py` from the run record; upstream Java sources are unchanged apart from the build configuration.

item	value
authorization relations: catalogue, executed, fired	11, 10, 2
engine alarms (the engine's own return value)	6
HTTP requests attributed to observing relations	270
changed upstream Java sources	0
build/config changes (one `pom.xml` line)	1
added harness classes / added lines	two / 612

policy P that we state rather than inherit: P maps every fired `OTG_AUTHZ` relation to "a violation was observed", which is the reading the catalogue's purpose invites but its code does not perform. Since P applies to every alarm, $H = 6$ holds by construction and carries no empirical content. All of it is in the independent truth T, computed from the ledger grant (E) and a content re-read (Y: the responder's bytes are identical to the owner's and a third account is refused): 0 violations are confirmed and 6 of the 6 promoted alarms are contradicted, on 3 cells (Table 20). A reader who declines P should read the run as 6 failed metamorphic relations rather than as 6 vulnerabilities; the disagreement survives that reading, because the failures fall on accesses the ledger allows.

D. IMPLEMENTATION ROBUSTNESS

An independently written implementation of the same predicates was compared with the main one on a subset fixed before the comparison, not sampled after it: the in-band scenarios on which a second reading is defined, holding the exception-policy variant at the representative level and the reachability reading at the one each relation uses (MR-002 blind, MR-004 aware). This yields 30 (configuration, scenario) points; MR-002 is defined on 30 of the resulting

TABLE 20. The native alarms split into the three stages: ***A*** (the engine's own `getFailures()`), ***H*** (the promotion policy ***P*** applied to ***A***), and ***T*** (independent truth from the ledger ***E*** and the content re-read ***Y***). Every row is an alarm, so ***A*** is not repeated as a column; ***H*** likewise applies to every row. †responder bytes identical to the owner's (sha256) and a third account refused with 404. MR names abbreviate `OTG_AUTHZ_`***x***.

MR	subject	object	*E*	*Y*	*T*
002	frank	acme/t1	allow	allow†	false proof
002	bob	alice/s1	allow	allow†	false proof
002	eve	carol/s1	allow	allow†	false proof
002c	frank	acme/t1	allow	allow†	false proof
002c	bob	alice/s1	allow	allow†	false proof
002c	eve	carol/s1	allow	allow†	false proof

relation comparisons and MR-004 on the remaining 24, giving 54 in all. The two agreed on 54 of them (1.00); the point set is a fixed enumeration, so no interval is attached. Both were written from the same reading of the semantics, so this bounds implementation accident only; it does not bound a shared blind spot, and we do not present it as corroboration.

VIII. THREATS TO VALIDITY

Source versus execution

We read the predicates at source (built under JDK 8 and Maven; Section VII-B) and then executed the relations, unmodified apart from the build configuration and our harness (Section VII-C). The harness substitutes an HTTP observation channel—exact for the reachability predicate, not exercised for the content predicate, whose invocation count we report rather than claim cleanliness we did not demonstrate. The run converts one class of claim (the false proof is produced by the *published* relations on a real system); it does not convert the rest: the scenario/configuration and cell studies remain statements about our instantiation, our exception vocabulary belongs to the same predicate family, and we report no sensitivity or specificity attributable to MST-wi.

Metric and statistics

The specificity approximation uses two follow-up inputs per case—not the engine's count; the conclusion about the denominator's resolution does not depend on the exact value. Records within a design cell are not independent (Section III, statistical treatment) and the records are a fixed enumeration, so we report counts and rates rather than inferential intervals, and no result rests on statistical significance. The RQ2 ablation is paired and is reported as a discordance count.

Two MRs, one family

We instantiated 2 MRs of one family—relations gated on the absence of evidence. The native run lifts the count to 10 of 11 catalog authorization relations but not the family: only the reachability-gated ones alarm in our run. This is the paper's single most important limitation; raising it requires relations gated otherwise, a different experiment.

Real systems

Three systems (one lineage pair, one independent), chosen for accessibility, none vulnerable on the tested surface—so only the false-proof side is measured, within one domain, the git forge. Channel proportions are topology design parameters, not field prevalence. Constructed scenarios with construction-defined ground truth are why the real-system section exists; three systems tested once each are still not a population.

Stratification and the references used in it

The split of Section IV-F is on whether the introspection surface returned a reading for the record, not on the configuration switch: 108 records sit in configurations that enable introspection but whose probe returns nothing, so the switch would misclassify them. The two oracle-free references there are deliberately weak—one unconditional, one guessing from a single request—because the point is to size the metamorphic step against methods that need nothing, not to identify the best oracle-free detector; a differential prober across accounts consumes more than those references do and was not instantiated. Both references share an observable with the labelling rule, as `direct_observe` does, so only the differences against them—not their absolute rates—are meant to be read.

Our own earlier claims

An earlier iteration proposed v3 as a mechanism on the strength of its precision (1.00), which was bought with 111 false negatives, and a control (`direct_only`, precision 0.50) that discarded the access result. Replacing it with a fair control produced the negative result. We record this as the condition any similar claim must meet: a control consuming the same observable quantity as the ground truth.

IX. RELATED WORK

Metamorphic security testing

Metamorphic testing was brought to web security by Mai et al. [3], who cast security test patterns—authentication, authorization, session—as metamorphic relations so that faults can be exposed without an oracle. The line matured into MST-wi [2], whose 76 system-agnostic relations over a Web-specific domain language are the object of our study. We take the technique's own admission that the role-to-resource mapping is ''not always available'' at face value and follow it to its consequence for what the adjudication can decide. A relation whose guard reads a crawl-time model is sound only while the model equals the authorization state, and that equality is exactly what the technique cannot check for itself.

Detecting broken access control

A large and active literature detects access-control flaws directly, and it is worth separating the oracles it relies on. Black-box probing drives requests with and without the rights of another subject and looks for a missing refusal [4], [5], a line that runs back to AUTHSCOPE [6] and that has been extended to deployed systems under ethical constraints [7]; where an API description is available, the oracle itself can be synthesised, for instance by transforming an OpenAPI specification into a colored Petri net that predicts per-object access [8]. A complementary, white-box line recovers the *enforced* policy from the implementation—by reverse-engineering RBAC policies [9], by statically extracting au-

TABLE 21. The published authorization relations executed against Gitea 1.22.6. Each row is the applicability chain from the catalogue to the outcome: *status* is the engine's per-relation result (10 of 11 evaluated, 1 aborted on an engine-side defect), *alarms* its own `getFailures()` return (2 relations, 6 in all), and *requests* (270 total) attributed to the relation observing them first.

MR	status	alarms	requests
OTG_AUTHZ_001	executed	0	0
OTG_AUTHZ_001b	executed	0	0
OTG_AUTHZ_001b2	executed	0	0
OTG_AUTHZ_002	executed	3	270
OTG_AUTHZ_002a	executed	0	0
OTG_AUTHZ_002b	executed	0	0
OTG_AUTHZ_002c	executed	3	0
OTG_AUTHZ_002d	executed	0	0
OTG_AUTHZ_002e	error	—	—
OTG_AUTHZ_003	executed	0	0
OTG_AUTHZ_004	executed	0	0

thorization policies [10] or database access-control rules [11], or by locating the permission checks themselves [12]—and then flags violations against that recovered model: BOLA in database-backed applications [13], missing-owner-check and function-level flaws in Java web applications [14], [15], function- and object-level access-control flaws across Web applications [16], and privilege escalation in polyglot microservices [17]. Specification-driven API fuzzers generate the requests well but inherit the same oracle difficulty [18]–[20]; adding explicit access-policy violation checks [21] moves them toward the detection problem but does not remove the need for a ground truth, and a recent turn delegates generation or probing to language models [22]–[24]. A concurrent line reframes BOLA under a zero-trust model, in which each request must carry an explicit authorization decision rather than one inferred from endpoint reachability [25]; our question sits at that decision level, asking what an oracle-substituting technique can establish about it. Our question is orthogonal to all of these. Each reports detections against an oracle it holds privately—a policy, a seeded defect, a differential response; we ask what an existing oracle-substituting technique *decides* when the entitlement information it needs is not among its observables, and we make that a measurable property of the technique rather than of a system.

Direct authorization oracles, and what is at stake here

Comparing responses across principals or privilege states is an established way to obtain an authorization oracle when the ground-truth relation is available, and the black-box and white-box lines above are instances of it. We propose no new direct oracle, and we do not claim that direct authorization comparison is novel. Our subject is a different question: what an existing oracle-substituting technique *decides* when it substitutes reachability for entitlement. The direct oracle enters our design in exactly one role—as the fair, same-observable control that a necessity claim about the metamorphic step must face. Without such a control, a substitution can appear necessary only because the alternative it is compared against was not allowed to consume the same decision-relevant observables.

LLMs and the oracle problem

LLMs are used for vulnerability detection and specification inference [26]–[29], including lightweight models over hybrid code features [30] and federated, explainable detectors [31]; we use none in the detection loop. The transferable condition this paper exposes is that any claim of necessity must be tested against a fair substitute that consumes the same observable quantity as the ground truth.

Measurement and evaluation

Our contribution is finally a measurement, and it connects to work on the quality of the artifacts security studies are built on—for instance the observation that vulnerability datasets are frequently mislabeled, duplicated or otherwise unfit for the claims drawn from them [32]. The artifact we report is of the same family but inside a study rather than a dataset: a specificity figure whose *denominator* is structurally unable to register a whole class of failure, and whose operating point silently assumes a reachability model equals the authorization state. We therefore read a testing technique's own reported metric as a measurement instrument, stating explicitly what its denominator can and cannot resolve.

X. CONCLUSION

For object-level authorization, MST-wi's predicates do not know whether the acting subject is entitled to the object; they know what the interface, as crawled, permitted. Instantiating them as defined produced three findings (Section VI).

Finding 1 (temporal)

As designed, the adjudication false-proofs on legitimately granted access, deterministically (1.00 constructed; 0.40 Gitea), because an out-of-band grant fits only the wrong one of the predicate's two representations. On the real system the mismatch appears only under the crawl-time reading (10/48, vs. 0 live), with an endogenous control holding final visibility fixed: within this controlled design the only manipulated explanatory variable is when the model was read, not what was visible.

Finding 2 (oracle)

The natural repair—a readable, sound authorization oracle that fully resolves the proposition under test—works, and in that regime the evaluated metamorphic step provides no observed incremental adjudication benefit over a direct consumer of the same oracle and outcome: an empirical premise, formalised as a conditional (Proposition 2), whose empirical face is that a single ordinary request yields the same false-proof count (false proofs 0 vs. 0), and that of the 216 true-violation records the paired comparison disagrees on only 3, each time in favor of the plain request; no margin was pre-specified, so no inferential claim attaches. On Gitea the comparison is limited to false-proof behavior, because no vulnerability was present on the tested surface.

Finding 3 (measurement)

The reported specificity of 99.81% is diagnosed as a specific published figure: it is not conditioned on an explicit check that the reachability model equals the authorization state, and its input-level denominator cannot register a class-uniform failure.

Support evidence: reading the implementation confirmed the semantics and added the mechanism—the crawl model is frozen by a cache never invalidated, and a missing crawl defaults to ''unreachable''—and the positive control is a sanity check that closes the loop: on a seeded vulnerable target, for one fault pattern, the surface-gated adjudicator detects all planted instances with zero false positives.

What the two added experiments carry

The temporal finding is not confined to one product. Under the same pre-registered protocol, frozen before the second run was observed, GitLab CE 17.11.7 commits 8 transitions over 432 cells, with entitlement and effect agreeing on 432 of them: 16 stale false proofs, all 16 removed by a recrawl with the same credentials, 0 live false proofs and 0 residual misses. Pooled with Gitea this is 712 cells, 712 agreements, 29 stale false proofs and 29 fixes. The replication is of a protocol, not of a topology: GitLab's project-membership surface answers 200 or 404, so it errs only by omission—in 53 cells it disagrees with the ledger, every one of them a false deny, concentrated in the public (44) and site-administration (9) channels—and both properties are read from the same run rather than one being derived from the other. The entitlement/effect gate is in turn checked against a real defect: on a publicly fixed object-versus-path ownership flaw, Gitea 1.20.5 yields 1 true positive with 0 false proofs, and the fixed 1.20.6 yields 0 alarms over 10 control probes. That is a check of the gate on one defect we located and supplied; it is not a detection rate.

What we do not claim, and how far the claims reach

We do not claim that MST-wi is wrong or say anything about its accuracy as a detector; the native run establishes a qualitative outcome, for one gate family, on one real system that on the tested endpoints and transitions enforces the expected decisions. Three ceilings stack and bound everything above. First, our two relations are two of a catalogue of 76, and both belong to one reachability-gated family. Second, even the execution of the published relations on the native engine reaches only that family: 2 of the 11 authorization relations fire (10 executed; OTG_AUTHZ_002, OTG_AUTHZ_002c), and the content predicate `userCanRetrieveContent` is never invoked (0 calls), so that evidence is bounded the same way. Third, the real-system study exercises the *false-proof* face on a single constructed fault pattern, not the detection face against a population of real flaws, and the Gitea channel proportions are topology design parameters, not field prevalence. Together these fix the ceiling on what a practitioner may transfer.

What a practitioner should do differently

Three operational consequences follow, each bounded by what was measured. Do not read a reachability-gated relation's alarm as proof: because the reading time is part of the specification, an alarm raised against a crawl-time snapshot—rather than against live state—cannot be promoted to `violation-proven` on the relation's word alone. If a readable, sound authorization oracle is in fact available to the analyst, consult it directly and drop the relation: for the relations studied it adds no adjudication information once that antecedent holds (Proposition 2, Section IV-F). And treat a reported input-level specificity as a corpus statistic rather than a guarantee of scenario-level resolution: it can sit near one while a whole class of legitimate access is misreported (Finding 3). These are not a claim that metamorphic testing is worthless; they locate its contribution where no oracle exists, and bound it by what the reachability reading can see.

What a stronger claim would require

Moving from characterization to something stronger needs, first, a population of real systems that *contain* the flaw, so detection can be measured—the single defect of Section V-D checks the gate but cannot supply that population; and second, relations whose gate is not the absence of evidence—checkable against a subject's entitlements without pretending that entitlements are reachable facts. The transferable condition—we call it the *same-observable condition*—is the one that killed our own mechanism: a component's necessity must be tested against a substitute that consumes the *same* observable quantity as the ground truth; a substitute that consumes less does not establish incremental value. The MST-wi case study is an instance of that condition, not its scope: a component's necessity is not established unless a fair control that lacks the component but consumes the same decision-relevant observables is empirically or formally shown to be weaker.

DECLARATIONS

DATA AVAILABILITY

The raw records of the studies reported here are publicly available under the version-pinned snapshot `artifact-v1` of the companion repository https://github.com/ubfbuz3/JISA (re-anchored to the

submission commit): (1) the scenario/configuration study (`experiments/results/raw_matrix.jsonl`, `ablation_direct*.json`, `alt_matrix.jsonl`); (2) the real-system cell study across Gitea 1.22.6, Gogs 0.14.3 and GitLab 17.11.7 (`experiments/real_system/results/*.json`); (3) the execution of the published relations on the native engine (`experiments/native_engine/results/*.json`); (4) the seeded positive control (`seeded.json`). The analysis pipeline (`analysis/*.py`: `compute_all.py` and the ingest scripts) recomputes every number, table and figure in this paper from those records; the stratified ablation of Section IV-F adds no new experiment—it re-aggregates the same scenario/configuration records by whether the introspection surface returned a reading, and is recomputed, together with every macro it defines, by `ingest_m2_stratum.py`; `check_macro_use.py` asserts that every macro cited in the manuscript has exactly one definition. Running `bash reproduce.sh` regenerates all outputs and the PDF, and `bash verify_artifact.sh` asserts the SHA-256 integrity of every raw record and byte-reproducible output. The manuscript LaTeX source ships in the same repository. A persistent archival copy with a citable DOI is deposited at Zenodo: https://doi.org/10.5281/zenodo.22859942.

COMPETING INTERESTS

The authors declare no competing interests, financial or otherwise.

FUNDING

This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors.

AUTHORS' CONTRIBUTIONS

Both authors contributed to the work. Qiulong Lin and Nanlei Chen jointly developed the conceptualisation and methodology, designed and implemented the software and analysis pipeline, carried out the investigation and formal analysis, and wrote the manuscript.

ETHICS

Not applicable. This study involved no human participants, no personal data, and no animals. All experiments were performed against software systems that we deployed and controlled locally.

DECLARATION OF GENERATIVE AI AND AI-ASSISTED TECHNOLOGIES IN THE WRITING PROCESS

During the preparation of this work the authors used Claude (Anthropic) to assist with literature verification, the development of the analysis scripts, and language editing. Where it contributed to analysis code, every generated or modified script was reviewed, executed, and its output checked by the authors against the raw records. After using this tool, the authors reviewed and edited the content as needed and take full responsibility for the content of the published article. All experimental computations and final reported values were independently checked by the authors against the released scripts and raw records.

REFERENCES

[1] OWASP Foundation, "API1:2023 Broken Object Level Authorization," OWASP API Security Top 10, 2023, accessed 18 September 2026. [Online]. Available: https://api-security.owasp.org/editions/2023/en/0xa1-broken-object-level-authorization/

[2] N. B. Chaleshtari, F. Pastore, A. Goknil, and L. Briand, "Metamorphic testing for web system security," *IEEE Transactions on Software Engineering*, pp. 3430–3471, 2023. [Online]. Available: https://doi.org/10.1109/TSE.2023.3256322

[3] P. X. Mai, F. Pastore, A. Goknil, and L. Briand, "Metamorphic security testing for web systems," in *2020 IEEE 13th International Conference on Software Testing, Validation and Verification (ICST)*, 2020, pp. 186–197. [Online]. Available: https://doi.org/10.1109/icst46399.2020.00028

[4] F. Liu, Y. Zhang, E. Li, W. Meng, Y.-Q. Shi, Q. Wang, and M. Yang, "Bacscan: Automatic black-box detection of broken-access-control vulnerabilities in web applications," in *Proceedings of the 2025 ACM SIGSAC Conference on Computer and Communications Security*, 2025, pp. 1320–1333. [Online]. Available: https://doi.org/10.1145/3719027.3744825

[5] I. P. A. Dharmaadi, M. Alhanahnah, V.-T. Pham, F. Mohsen, and F. Turkmen, "Bacfuzz: Exposing the silence on broken access control vulnerabilities in web applications," *ArXiv*, 2025. [Online]. Available: https://doi.org/10.48550/arXiv.2507.15984

[6] C. Zuo, Q. Zhao, and Z. Lin, "Authscope: Towards automatic discovery of vulnerable authorizations in online services," in *Proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security*, 2017, pp. 799–813. [Online]. Available: https://doi.org/10.1145/3133956.3134089

[7] S. E. H. Chehade, F. Hantke, and B. Stock, "403 forbidden? ethically evaluating broken access control in the wild," in *2025 IEEE Symposium on Security and Privacy (SP)*, 2025, pp. 3218–3235. [Online]. Available: https://doi.org/10.1109/SP61157.2025.00252

[8] A. S. Filho, R. J. Rodríguez, and E. Feitosa, "Automated broken object-level authorization attack detection in rest apis through openapi to colored petri nets transformation," *International Journal of Information Security*, vol. 24, no. 2, 2025. [Online]. Available: https://doi.org/10.1007/s10207-024-00970-5

[9] H. Le, L. K. Shar, D. Bianculli, L. Briand, and D. C. Nguyen, "Automated reverse engineering of role-based access control policies of web applications," *Journal of Systems and Software*, vol. 184, p. 111109, 2022. [Online]. Available: https://doi.org/10.1016/j.jss.2021.111109

[10] B. Berger, R. W. Nguempnang, K. Sohr, and R. Koschke, "Static extraction of enforced authorization policies seeauthz," in *2020 IEEE 20th International Working Conference on Source Code Analysis and Manipulation (SCAM)*, 2020, pp. 187–197. [Online]. Available: https://doi.org/10.1109/SCAM51674.2020.00026

[11] W. Zhang, D. Bali, J. Kerney, A. Panda, and S. Shenker, "Extracting database access-control policies from web applications," in *20th USENIX Symposium on Operating Systems Design and Implementation (OSDI '26)*, 2026, pp. 249–270. [Online]. Available: https://www.usenix.org/conference/osdi26/presentation/zhang-wen

[12] Y.-Q. Shi, F. Liu, G. Yang, Y. Zhang, Y. Cao, E. Li, and S. Chen, "Facilitating access control vulnerability detection in modern java web applications with accurate permission check identification," *IEEE Transactions on Information Forensics and Security*, vol. 20, pp. 10 683–10 698, 2025. [Online]. Available: https://doi.org/10.1109/TIFS.2025.3614424

[13] Y. Huang, C. Shi, J. Lu, H. Li, H. Meng, and L. Li, "Detecting broken object-level authorization vulnerabilities in database-backed applications," in *Proceedings of the 2024 on ACM SIGSAC Conference on Computer and Communications Security*, 2024, pp. 2934–2948. [Online]. Available: https://doi.org/10.1145/3658644.3690227

[14] F. Liu, Y.-Q. Shi, Y. Zhang, G. Yang, E. Li, and M. Yang, "Mocguard: Automatically detecting missing-owner-check vulnerabilities in java web applications," in *2025 IEEE Symposium on Security and Privacy (SP)*,

2025, pp. 903–919. [Online]. Available: https://doi.org/10.1109/SP61157.2025.00010

[15] R. Feng, M. Zhang, A. Xia, J. Cheng, Y. Li, Y. Zhang, and Y. Liu, "Jauthguard: Automatic detection for broken access control in java web apis," in *2025 IEEE International Conference on Systems, Man, and Cybernetics (SMC)*, 2025, pp. 3102–3107. [Online]. Available: https://doi.org/10.1109/SMC58881.2025.11343625

[16] M. Schlaubitz, O. Veyisoglu, and M. Rennhard, "A2ct: Automated detection of function and object-level access control vulnerabilities in web applications," in *International Conference on Information Systems Security and Privacy*, 2025, pp. 425–436. [Online]. Available: https://doi.org/10.5220/0013092700003899

[17] P. Li, H. Chong, Y. Cao, and J. Yang, "Detecting privilege escalation in polyglot microservices via agentic program analysis," in *2026 IEEE Symposium on Security and Privacy (SP)*, 2026, pp. 1747–1765. [Online]. Available: https://doi.org/10.1109/SP63933.2026.00121

[18] V. Atlidakis, P. Godefroid, and M. Polishchuk, "Restler: Stateful rest api fuzzing," in *2019 IEEE/ACM 41st International Conference on Software Engineering (ICSE)*, 2019, pp. 748–758. [Online]. Available: https://doi.org/10.1109/ICSE.2019.00083

[19] A. Arcuri, M. Zhang, and J. P. Galeotti, "Advanced white-box heuristics for search-based fuzzing of rest apis," *ACM Transactions on Software Engineering and Methodology*, vol. 33, no. 6, pp. 1–36, 2024. [Online]. Available: https://doi.org/10.1145/3652157

[20] S. Seran, M. Zhang, O. Duman, and A. Arcuri, "Handling web service interactions in fuzzing with search-based mock-generation," *ACM Transactions on Software Engineering and Methodology*, vol. 35, no. 2, pp. 1–45, 2026. [Online]. Available: https://doi.org/10.1145/3731558

[21] Ömür Şahin, M. Zhang, and A. Arcuri, "Enhancing rest api fuzzing with access policy violation checks and injection attacks," *Journal of Systems and Software*, vol. 243, p. 113060, 2027. [Online]. Available: https://doi.org/10.1016/j.jss.2026.113060

[22] M. A. Uddin, S. Weerasinghe, C. Wojtak, T. Cerný, D. Silva-Junior, M. E. S. Ribeiro, and A. S. Abdelfattah, "Automated generation of microservice authorization tests using large language models," in *2026 International Conference on Service-Oriented System Engineering (SOSE)*, 2026, pp. 41–50. [Online]. Available: https://doi.org/10.1109/SOSE71128.2026.00014

[23] J. Sun, R. Tian, S. Zhao, X. Zhou, H. Wang, and Y. Zhang, "Llm-assisted idor detection in hospital mini-programs: Risks to pii and phi," in *2025 IEEE 24th International Conference on Trust, Security and Privacy in Computing and Communications (TrustCom)*, 2025, pp. 2078–2086. [Online]. Available: https://doi.org/10.1109/Trustcom66490.2025.00242

[24] E. Wang, W. Xie, S. Li, R. Liu, Y. Zhou, Z. Wang, and B. Wang, "Large language model-powered protected interface evasion: Automated discovery of broken access control vulnerabilities in internet of things devices," *Sensors (Basel, Switzerland)*, vol. 25, no. 9, p. 2913, 2025. [Online]. Available: https://doi.org/10.3390/s25092913

[25] A. Wu, Z. Feng, R. Feng, Z. Xing, and Y. Liu, "Rethinking broken object level authorization attacks under zero trust principle," *ACM Transactions on Software Engineering and Methodology*, 2026. [Online]. Available: https://doi.org/10.1145/3833417

[26] H. Wang, Z. Wang, and P. Liu, "A hybrid llm workflow can help identify user privilege related variables in programs of any size," *ArXiv*, 2024. [Online]. Available: https://doi.org/10.48550/arXiv.2403.15723

[27] C. Wen, J. Cao, J. Su, Z. Xu, S. Qin, M. He, and C. Tian, "Enchanting program specification synthesis by large language models using static analysis and program verification," in *International Conference on Computer Aided Verification*, 2024, pp. 302–328. [Online]. Available: https://doi.org/10.1007/978-3-031-65630-9_16

[28] R. Wang, H. Zhuang, H. Cao, and S. Chen, "Measuring the reasoning boundaries of large language models for implicit security invariants in code: A controlled empirical study," in *2026 IEEE 50th Annual Computers, Software, and Applications Conference (COMPSAC)*, 2026, pp. 3146–3157. [Online]. Available: https://doi.org/10.1109/COMPSAC69091.2026.00467

[29] T. Le-Cong, B. Le, and T. Murray, "Can llms reason about program semantics? a comprehensive evaluation of llms on formal specification inference," in *Annual Meeting of the Association for Computational Linguistics*, 2025, pp. 21 991–22 014. [Online]. Available: https://aclanthology.org/2025.acl-long.1068/

[30] J. Liu, G. Lin, H. Mei, F. Yang, and Y. Tai, "Enhancing vulnerability detection efficiency: An exploration of light-weight llms with hybrid code features," *Journal of Information Security and Applications*, vol. 88, p. 103925, 2024. [Online]. Available: https://doi.org/10.1016/j.jisa.2024.103925

[31] J. Senanayake, H. Kalutarage, A. Petrovski, L. Piras, and M. O. Al-Kadri, "Defendroid: Real-time android code vulnerability detection via blockchain federated neural network with xai," *Journal of Information Security and Applications*, vol. 82, p. 103741, 2024. [Online]. Available: https://doi.org/10.1016/j.jisa.2024.103741

[32] R. Croft, M. A. Babar, and M. M. Kholoosi, "Data quality for software vulnerability datasets," in *2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE)*, 2023, pp. 121–133. [Online]. Available: https://doi.org/10.1109/ICSE48619.2023.00022

QIULONG LIN Qiulong Lin received the M.S. degree from Sogang University, Seoul, Republic of Korea. He is with Yango University, Fuzhou, China, and is also affiliated with Sogang University, Seoul, Republic of Korea. His research interests include Web/API security, vulnerability discovery, and metamorphic testing.

NANLEI CHEN Nanlei Chen is currently pursuing the M.S. degree at Sogang University, Seoul, Republic of Korea. He is with Yango University, Fuzhou, China. His research interests include Web/API security and authorization testing. He is the corresponding author of this work.