

# ECE 220 Computer Systems & Programming

## Lecture 19: Linked Lists




# Outline

- Linked List Data Structure
- Chapter 19.5
- Key concepts
  - Search/Add/Delete operations on a linked list
  - Linked Lists vs Arrays

# The Linked List Data Structure


A **linked list** is an ordered collection of **nodes**, each of which contains some data, connected using **pointers**.

- Each node points to the next node in the list.
- The first node in the list is called the head
- The last node in the list is called the tail



# Array vs Linked List


Element 0
Element 1
Element 2



	Array	Linked List
Memory Allocation	Static/Dynamic	Dynamic
Memory Structure	Contiguous	Not necessary consecutive
Order of Access	Random	Sequential
Insertion/Deletion	Create/delete space, then shift all successive elements	Change pointer address

## Example: Student Record


```
typedef struct studentStruct Record;  
struct studentStruct  
{  
    char Name[100];  
    int UIN;  
    float GPA;  
    Record *next;  
};
```



We have a list of 200 student records sorted by UIN

1. Find a particular student record by UIN
2. Delete a student record from the list
3. Add a new student record to the list at the correct place

# Find a Student Record by UIN



```
//print "Student Record Found" if UIN is found, return a pointer to this record
//otherwise print "Record Not Found", return NULL


Record *find_node(Record *head, int UIN)
{
    Record *current = head;

    //keep traversing the list while 1)not at the end of the list AND
    //                2)current record's UIN < UIN we are looking for

}
```


## Adding a Node

Create a new node with the proper info.  
Find the node (if any) with a greater UIN.  
“Splice” the new node into the list:



```
void add_node(Record **list, int new_UIN)
```

```
{  
    Record *current = *list;  
    Record *prev = *list;  
    Record *temp = (Record *)malloc(sizeof(Record)); //allocate memory for the new node  
    //initialize UIN for the new node  
  
    //keep traversing the list until we reach the end  
    while ( )  
    {  
        //the first instance when new_UIN is smaller than current record's UIN  
        //we want to insert new node in front of the current node  
  
        //if the current node is the head, update head pointer  
  
        else //for everything else, update previous node's next pointer  
  
        return; //exit function  
    }  
    //we've reach the last note and its UIN is still smaller than new node's UIN  
    //new node will have to be inserted at the tail  
  
    {  
    }  
    prev = current;  
    current = current ->next;  
}  
}
```





## Deleting a Node

**Find the node that points to the desired node.**

**Redirect that node's pointer to the next node (or NULL).**

**Free the deleted node's memory.**

