

# ECE 220 Computer Systems & Programming

## Lecture 24 –Overloading, Inheritance & Polymorphism



# Review: Pass by Value / Address (Pointer) / Reference

Let's take a look at our most familiar swap example...

Pass by value: `void swap_val(int x, int y);`

Pass by address: `void swap_ptr(int *x, int *y);`

Pass by reference: `void swap_ref(int &x, int &y);`

```
int main(){
    int x = 1;
    int y = 2;
    swap_val(x, y);           //pass by value
    swap_ptr(&x, &y);         //pass by address (pointer)
    swap_ref(x, y);          //pass by reference
}
```

```
void swap_ref(int &x, int &y){
    int temp = x;
    x = y;
    y = temp;
}
```

*\*see the `ref_vs_ptr.cpp` (github)* 3

# More on Reference

- An alias for a variable/object
- Similar to pointer but safer
- No need to dereference, use it just like a variable/object
- Should use “.” instead of “->” to access members

## Copy constructor and **pass by constant reference**

```
class Rectangle{  
    //default access is private  
    int width, height;  
public:  
    //copy constructor  
    Rectangle(const Rectangle &obj){  
        width = obj.width;  
        height = obj.height;}  
    //other methods omitted here for simplicity  
}; copy construct example: copy_constructor2.cpp (github)
```

# Operator Overloading

Redefine built-in operators such as +, -, \*, <, >, = in C++ to do what you want

Example:

```
class Vector {  
    Protected:  
    double angle, length;  
    public:  
    //constructors & other member functions  
    ...  
    vector operator +(const Vector &b) {  
        Vector c;  
        double ax = length*cos(angle);  
        double bx = b.length*cos(b.angle);  
        double ay = length*sin(angle);  
        double by = b.length*sin(b.angle);  
        double cx = ax+bx;  
        double cy = ay+by;  
        c.length = sqrt(cx*cx+cy*cy);  
        c.angle = acos( cx/c.length );  
        return c;  
    }; Example: test_overloading_L24.cpp (github)
```

```
Vector c(1.5,2);  
Vector d(2.6,3);  
  
//before operator overload  
Vector e = c.add(d);  
  
//after operator overload  
Vector e = c + d;
```

# Inheritance & Abstraction

C++ allows us to define a class based on an existing class, and the new class will inherit members of the existing class.

- the **existing** class –
- the **new** class –

A derived class inherits all base class member functions with the following exceptions:

- Constructors, destructors and copy constructors of the base class.
- Overloaded operators of the base class.
- The friend functions of the base class.

```

class orthovector : public vector{
protected:
    int d; //direction can be 0,1,2,3, indicating r, l, u, d
public:
    orthovector(int dir, double l){
        const double halfPI = 1.507963268;
        d = dir;
        angle = d*halfPI;
        length = l;
    }
    orthovector() {d = 0; angle = 0.0; length = 0.0;}
    double hypotenuse(orthovector b){
        if((d+b.d)%2 == 0) return length + b.length;
        return (sqrt(length*length + b.length*b.length));
    }
};

```

Access	public	protected	private
Same Class	Y	Y	Y
Derived Class	Y	Y	N
Outside Class	Y	N	N

# Polymorphism

- The word **polymorphism** means having many forms. Typically, polymorphism occurs when there is a hierarchy of classes and they are related by inheritance.
- a call to a member function will cause a **different function to be executed** depending on the type of the object that invokes the function

## Example:

```
//base class
```

```
class Shape{  
    protected:  
    double width, height;  
    public:  
    Shape() {width = 1; height = 1;}  
    Shape(double a, double b) { width = a; height = b; }  
    double area() { cout << "Base class area unknown" << endl;  
                    return 0; }  
};
```

Example: `polymorphism_simple.cpp` (on github)

```
int main(){  
    Rectangle rec(3,5);  
    Triangle tri(4,5);  
  
    rect.area();  
    tri.area();  
  
    return 0;  
}
```

```
//derived classes
```

```
class Rectangle : public Shape{  
    public:  
    Rectangle(double a, double b) : Shape(a,b){}  
    double area() {  
  
    }  
};
```

```
class Triangle : public Shape{  
    public:  
    Triangle(double a, double b) : Shape(a,b){}  
    double area() {  
  
    }  
};
```



# Declared Type vs. Actual Type

```
int main(){
    Shape *ptr;
    Rectangle rec(10,7);
    Triangle tri(10,5);

    //use ptr to point to rec object
    ptr = &rec;
    ptr->area();

    //use ptr to point to tri object
    ptr = &tri;
    ptr->area();

    return 0;
}
```

What does this program print?

# Virtual Function

- **virtual functions** are member functions in the base class you expect to redefine in the derived classes
- derived class declares instances of that member function

```
//base class
class Shape{
    protected:
        double width, height;
    public:
        Shape() {width = 1; height = 1;}
        Shape(double a, double b) { width = a; height = b; }

};
```