

VALIDATION PLAN

OPERATIONAL QUALIFICATION

STATISTICAL PROCESS CONTROL MODULE

JR Validated Environment — Statistical Process Control Module v2.0

Field	Value
Document Number	JR-VP-SPC-001
Title	Validation Plan — Operational Qualification, Statistical Process Control Module
System	JR Validated Environment — SPC Module
Module Version	2.0
Document Version	3.0
Status	Approved
Effective Date	2026-10-01
Author	Joep Rous
Reviewer	[Name]
Approver	[Name]

Version History

Version	Date	Author	Description
1.0	2026-03-18	Joep Rous	Initial release. Covers all 5 SPC scripts in module v1.0. 55 test cases; 27 user requirements.
2.0	2026-05-18	Joep Rous	Updated for SPC module v2.0. Added 16 numeric correctness test cases (TC-SPC-IMR-012–015, TC-SPC-XBR-013–016, TC-SPC-XBS-012–015, TC-SPC-P-012–013, TC-SPC-C-011–012) with independent Python reference values. Added 12 --report PV report test cases for jrc_spc_imr, jrc_spc_xbar_r, jrc_spc_xbar_s, and jrc_spc_p (TC-SPC-IMR-016–018, TC-SPC-XBR-017–019, TC-SPC-XBS-016–018, TC-SPC-P-014–016). Added UR-SPC-028 (numeric correctness) and UR-SPC-029 (--report PV report). Total: 83 test cases, 29 user requirements.
3.0	2026-10-01	Joep Rous	jrscripsts v5.0.0, code review 2026-10: one shared Nelson-rule engine; added TC-SPC-IMR-019..021, TC-SPC-XBR-020, TC-SPC-P-017 and TC-SPC-C-013 (signal limits, zero variation, unknown option, user limits drive Rule 1); twelve numeric test cases no longer pass an unused argument. Total: 89 test cases, 29 user requirements.

Approval Signatures

Role	Name	Signature	Date
Author	Joep Rous		2026-05-18
Reviewer	[Name]		
Approver (QA)	[Name]		

1. Purpose

This document defines the Validation Plan for the Operational Qualification (OQ) of the Statistical Process Control (SPC) module included in version 2.0 of the JR Validated Environment. It specifies the user requirements, test cases, acceptance criteria, and traceability between requirements and tests needed to demonstrate that each SPC script performs correctly for its intended use in FDA manufacturing process control under 21 CFR 820.70(i) and ISO 13485:2016.

Execution of the tests defined in this plan, together with satisfactory results and documented evidence, constitutes the OQ for the SPC module.

2. Scope

2.1 In Scope

- All 5 R scripts in repos/spc/R/: jrc_spc_imr, jrc_spc_xbar_r, jrc_spc_xbar_s, jrc_spc_p, jrc_spc_c
- Correct computation of control limits and all 8 Western Electric rule violations for valid inputs
- Numeric correctness of control limit values: all key statistics verified against independent Python reference calculations with specified tolerances
- Correct rejection of invalid inputs with informative error messages
- Correct file I/O behaviour (CSV input, PNG output to ~/Downloads/)
- Correct PV report generation (--report flag) for jrc_spc_imr, jrc_spc_xbar_r, jrc_spc_xbar_s, and jrc_spc_p; JSON sidecar content verified
- Verification that all R scripts enforce execution within the jrrun validated environment by checking RENV_PATHS_ROOT at startup
- Balanced-design validation for subgrouped charts (X-bar/R, X-bar/S)
- Subgroup size constraint enforcement (X-bar/R: $n = 2-10$; X-bar/S: $n \geq 2$)
- Defectives-exceed-n validation for P-chart

2.2 Out of Scope

- Infrastructure scripts in bin/ and admin/ (covered by IQ; see JR-VP-001)
- Performance qualification (PQ) — production process monitoring studies are conducted separately under individual process control protocols
- User acceptance testing (UAT)
- Validation of R language interpreter and third-party packages (ggplot2, grid) — package integrity is confirmed at installation via SHA256 (JR-IQ-001)
- Statistical validation of the underlying SPC methods — method references are cited in Section 3

3. Regulatory Basis and References

3.1 Regulations

Reference	Title
21 CFR Part 820, §820.70(i)	Quality System Regulation — Automated Data Processing
21 CFR Part 11	Electronic Records; Electronic Signatures

3.2 FDA Guidance

Reference	Title	Date
FDA GPSV	General Principles of Software Validation; Final Guidance for Industry and FDA Staff	January 2002
FDA CSA	Computer Software Assurance for Production and Quality System Software; Draft Guidance	September 2022

3.3 Standards and Methods

Reference	Title
AIAG SPC, 2nd Ed.	Statistical Process Control Reference Manual, Automotive Industry Action Group, 2005
Montgomery (2020)	Montgomery DC. Introduction to Statistical Quality Control, 8th Ed. Wiley.
Western Electric (1956)	Statistical Quality Control Handbook. Western Electric Company, Indianapolis.
ISO 7870-2:2023	Control charts — Part 2: Shewhart control charts
ISO 7870-3:2012	Control charts — Part 3: Acceptance control charts
ISO 13485:2016	Medical devices — Quality management systems — Requirements for regulatory purposes

3.4 Internal Documents

Document Number	Title
JR-VP-001	Validation Plan — Installation Qualification, JR Validated Environment
JR-IQ-001	IQ Execution Evidence (docs/IQ_validation_*.txt)
JR-VP-002	Validation Plan — OQ, Community Script Suite

4. User Requirements

The following user requirements define the functional behaviour that the SPC module must satisfy. Each requirement is traced to one or more test cases in Section 6.

UR ID	Script(s)	Requirement
UR-SPC-001	jrc_spc_imr	Compute X-bar, MR-bar, UCL and LCL for both the Individuals chart and the Moving Range chart from a valid id/value CSV. Report all values in terminal output.
UR-SPC-002	jrc_spc_imr	Apply all 8 Western Electric rules to the Individuals chart and Rule 1 only to the Moving Range chart. List each out-of-control observation by ID, value, and rule(s) fired.
UR-SPC-003	jrc_spc_imr	Accept optional --ucl and --lcl arguments. When provided, use user-specified limits in place of computed limits and label them as user-specified in output.
UR-SPC-004	jrc_spc_imr	Output a clear IN CONTROL or OUT OF CONTROL verdict based on WE rule results.
UR-SPC-005	jrc_spc_imr	Save a two-panel PNG (Individuals chart + MR chart) to ~/Downloads/ with a datetime prefix.
UR-SPC-006	jrc_spc_imr	Exit non-zero with an informative error message when: no arguments are supplied; the input file is not found; a required column is missing; fewer than 2 observations are present.
UR-SPC-007	jrc_spc_xbar_r	Compute grand mean, R-bar, and X-bar/R control limits using tabulated A2, D3, D4 constants for n = 2–10 from a valid subgroup/value long-format CSV.
UR-SPC-008	jrc_spc_xbar_r	Apply all 8 Western Electric rules to the X-bar chart and Rule 1 only to the R chart. List each out-of-control subgroup by label, value, and rule(s) fired.
UR-SPC-009	jrc_spc_xbar_r	Accept optional --ucl and --lcl arguments for user-specified X-bar limits.
UR-SPC-010	jrc_spc_xbar_r	Output a clear IN CONTROL or OUT OF CONTROL verdict.

UR-SPC-011	jrc_spc_xbar_r	Save a two-panel PNG (X-bar chart + R chart) to ~/Downloads/ with a datetime prefix.
UR-SPC-012	jrc_spc_xbar_r	Reject unbalanced subgroups with a non-zero exit and informative message. Reject subgroup size $n > 10$ with a non-zero exit and suggestion to use X-bar/S.
UR-SPC-013	jrc_spc_xbar_s	Compute grand mean, S-bar, and X-bar/S control limits using the analytical $c_4(n)$ formula (gamma function) for any $n \geq 2$.
UR-SPC-014	jrc_spc_xbar_s	Apply all 8 Western Electric rules to the X-bar chart and Rule 1 only to the S chart. List each out-of-control subgroup by label, value, and rule(s) fired.
UR-SPC-015	jrc_spc_xbar_s	Accept optional --ucl and --lcl arguments for user-specified X-bar limits.
UR-SPC-016	jrc_spc_xbar_s	Output a clear IN CONTROL or OUT OF CONTROL verdict.
UR-SPC-017	jrc_spc_xbar_s	Save a two-panel PNG (X-bar chart + S chart) to ~/Downloads/ with a datetime prefix.
UR-SPC-018	jrc_spc_xbar_s	Reject unbalanced subgroups with a non-zero exit and informative message.
UR-SPC-019	jrc_spc_p	Compute p-bar and per-subgroup UCL/LCL from a subgroup/n/defectives CSV. Apply all 8 Western Electric rules to standardised z-values. List violations.
UR-SPC-020	jrc_spc_p	Output a clear IN CONTROL or OUT OF CONTROL verdict.
UR-SPC-021	jrc_spc_p	Reject any row where defectives $> n$ with a non-zero exit and informative message.
UR-SPC-022	jrc_spc_p	Save a PNG (P-chart with step-line variable control limits) to ~/Downloads/.
UR-SPC-023	jrc_spc_c	Compute c-bar, $\sigma = \sqrt{c\text{-bar}}$, $UCL = c\text{-bar} + 3*\sigma$, $LCL = \max(0, c\text{-bar} - 3*\sigma)$ from a subgroup/defects CSV. Apply all 8 Western Electric rules. List violations.
UR-SPC-024	jrc_spc_c	Output a clear IN CONTROL or OUT OF CONTROL verdict and save a PNG with sigma zone lines to ~/Downloads/.
UR-SPC-025	All scripts	Each script must check for the RENV_PATHS_ROOT environment variable at startup and exit non-zero with an informative message if it is absent, preventing execution outside the jrrun validated environment.
UR-SPC-026	All scripts	Calling any script with no arguments must exit non-zero and print a usage message showing the expected syntax.
UR-SPC-027	All scripts	Supplying a non-existent CSV path must exit non-zero with a message indicating that the file was not found.
UR-SPC-028	All scripts	Key control limit statistics shall match independently computed Python reference values within specified tolerances: all reference values are derived from closed-form Shewhart formulas using tabulated constants, with no R or scipy used in the reference calculations. Tolerance values are stated per test case.
UR-SPC-029	jrc_spc_imr, jrc_spc_xbar_r, jrc_spc_xbar_s, jrc_spc_p	When invoked with the --report flag, the script shall write a PV report to ~/Downloads/. If jr_pack is installed (pv_report_template.html present) the report is generated as a .docx file; otherwise the intermediate .html file remains. A JSON sidecar written alongside the HTML shall contain report_type == "pv" and verdict_pass as a boolean reflecting the overall process stability verdict.

5. Test Environment

The following environment must be in place before executing the OQ tests.

Item	Requirement
Operating system	macOS 15.x (Apple Silicon or Intel) or Windows 10/11 (Git Bash)
R version	4.5.x (as specified in admin/r_version.txt)
Python version	3.11.x (as specified in repos/spc/oq/python_version.txt)

pytest version	8.3.4 (as specified in repos/spc/oq/requirements.txt)
OQ virtual environment	~/.venvs/<PROJECT_ID>_oq/ (created by admin_spc_oq)
jrrun	bin/jrrun present and executable; project integrity check passing
RENV_PATHS_ROOT	Set by jrrun at execution time; must NOT be set in the test shell
Test data	repos/spc/oq/data/ — synthetic CSV files committed to the repo
Test runner	repos/spc/admin_spc_oq

6. Test Cases

Each test case is implemented as a pytest function in repos/spc/oq/. Tests are executed via repos/spc/admin_spc_oq, which activates the OQ virtual environment, runs pytest with -v, and captures the output. Numeric reference values for TC-SPC-*012 onwards are computed independently of the R scripts using pure Python arithmetic — no R or scipy is used in the reference calculations.

6.1 jrc_spc_imr

TC-SPC-IMR-001

Tests: UR-SPC-001, UR-SPC-004

Command: `jrc_spc_imr oq/data/imr_stable.csv`

Rationale: Verifies the script completes successfully for a well-behaved dataset.

Pass criterion: Exit code 0; output contains control limit section, process stability section, and a verdict line.

TC-SPC-IMR-002

Tests: UR-SPC-002, UR-SPC-004

Command: `jrc_spc_imr oq/data/imr_stable.csv`

Rationale: imr_stable.csv is designed so no WE rule fires.

Pass criterion: Exit code 0; 'IN CONTROL' or 'STABLE' present in output.

TC-SPC-IMR-003

Tests: UR-SPC-002, UR-SPC-004

Command: `jrc_spc_imr oq/data/imr_ooc.csv`

Rationale: imr_ooc.csv contains observation 13 = 11.50, clearly beyond 3σ (UCL ≈ 11.27).

Pass criterion: Exit code 0; 'OUT OF CONTROL' or 'SIGNALS' present in output.

TC-SPC-IMR-004

Tests: UR-SPC-002

Command: `jrc_spc_imr oq/data/imr_ooc.csv`

Rationale: Rule 1 (beyond 3σ) must fire for observation 13.

Pass criterion: Output contains '13' and one of '[1]', 'Rule 1', or 'beyond 3' (case-insensitive).

TC-SPC-IMR-005

Tests: UR-SPC-003

Command: `jrc_spc_imr oq/data/imr_stable.csv --ucl 11.0 --lcl 9.0`

Rationale: Confirms --ucl / --lcl flags are parsed and reported.

Pass criterion: Exit code 0; output contains '11.0' or '11.00' or 'user' or 'specified'.

TC-SPC-IMR-006

Tests: UR-SPC-005

Command: `jrc_spc_imr oq/data/imr_stable.csv`

Rationale: A PNG file must appear in ~/Downloads/ with mtime $\geq$ test start time.

Pass criterion: File matching *_jrc_spc_imr.png exists in ~/Downloads/ with recent mtime.

TC-SPC-IMR-007

Tests: UR-SPC-006

Command: `jrc_spc_imr`

Pass criterion: Exit code $\neq 0$; 'Usage' or 'usage' present in output.

TC-SPC-IMR-008

Tests: UR-SPC-006, UR-SPC-027

Command: `jrc_spc_imr /tmp/no_such_file_xyz.csv`

Pass criterion: Exit code $\neq 0$; 'not found' or the filename present in output.

TC-SPC-IMR-009

Tests: UR-SPC-006

Command: `jrc_spc_imr oq/data/imr_missing_col.csv`

Rationale: `imr_missing_col.csv` lacks the 'value' column.

Pass criterion: Exit code $\neq 0$; 'value' present in output.

TC-SPC-IMR-010

Tests: UR-SPC-006

Command: `jrc_spc_imr oq/data/imr_one_obs.csv`

Rationale: Moving range requires at least 2 observations.

Pass criterion: Exit code $\neq 0$.

TC-SPC-IMR-011

Tests: UR-SPC-025

Command: `Rscript repos/spc/R/jrc_spc_imr.R oq/data/imr_stable.csv`
(`RENV_PATHS_ROOT` unset)

Rationale: Script must detect absent `RENV_PATHS_ROOT` and refuse to run.

Pass criterion: Exit code $\neq 0$; 'RENV_PATHS_ROOT' present in `stderr/stdout`.

TC-SPC-IMR-012

Tests: UR-SPC-028

Command: `jrc_spc_imr oq/data/imr_stable.csv`

Rationale: Reference: $\bar{X}$ = arithmetic mean of 25 values = 10.066800. Computed in pure Python, independent of R.

Pass criterion: Exit code 0; $\bar{X}$ = 10.0668 ± 0.0001 .

TC-SPC-IMR-013

Tests: UR-SPC-028

Command: `jrc_spc_imr oq/data/imr_stable.csv`

Rationale: Reference: $UCL_I = \bar{X} + 3*(\bar{MR}/d_2) = 10.0668 + 3*0.28480 = 10.9212$. $d_2 = 1.128$ for $n=2$ pairs; $\bar{MR} = 0.32125$. Computed in pure Python.

Pass criterion: Exit code 0; $UCL_I = 10.9212 \pm 0.001$.

TC-SPC-IMR-014

Tests: UR-SPC-028

Command: `jrc_spc_imr oq/data/imr_stable.csv`

Rationale: Reference: $LCL_I = \bar{X} - 3*(\bar{MR}/d_2) = 10.0668 - 3*0.28480 = 9.2124$. Computed in pure Python.

Pass criterion: Exit code 0; $LCL_I = 9.2124 \pm 0.001$.

TC-SPC-IMR-015

Tests: UR-SPC-028

Command: `jrc_spc_imr oq/data/imr_stable.csv`

Rationale: Reference: $UCL_{MR} = D_4 * \bar{MR} = 3.267 * 0.32125 = 1.04952$. $D_4 = 3.267$ for $n=2$ pairs. Computed in pure Python.

Pass criterion: Exit code 0; $UCL_{MR} = 1.0495 \pm 0.001$.

TC-SPC-IMR-016

Tests: UR-SPC-029

Command: `jrc_spc_imr oq/data/imr_stable.csv --report`

Rationale: --report flag triggers PV report generation. Report is written as .docx (jr_pack full install) or .html (template-only install).

Pass criterion: Exit code 0; file matching *_spc_imr_pv_report.docx or *_spc_imr_pv_report.html found in ~/Downloads/ with recent mtime.

TC-SPC-IMR-017

Tests: UR-SPC-029

Command: `jrc_spc_imr oq/data/imr_stable.csv --report`

Rationale: When jr_pack is fully installed the JSON sidecar is consumed after .docx generation; either the .docx or the JSON is accepted as evidence.

Pass criterion: Exit code 0; file matching *_spc_imr_pv_report.docx or *_spc_imr_pv_report_data.json found in ~/Downloads/ with recent mtime.

TC-SPC-IMR-018

Tests: UR-SPC-029

Command: `jrc_spc_imr oq/data/imr_stable.csv --report`

Rationale: JSON sidecar must carry report_type == "pv" and verdict_pass == True for the stable (IN CONTROL) dataset confirmed by TC-SPC-IMR-002.

Pass criterion: Exit code 0; .docx or JSON found; if JSON present: report_type == "pv" and verdict_pass is True.

TC-SPC-IMR-019

Tests: UR-SPC-002

Command: `jrc_spc_imr oq/data/imr_mr_beyond_ucl.csv`

Rationale: One moving range of 3.5 with MR-bar = 1.0517: $UCL_MR = 3.267 * 1.0517 = 3.436$. The point is above UCL_MR but below the $3.66 * MR\text{-}bar = 3.849$ threshold used before the 2026-10 fix (SPC-02).

Pass criterion: Exit code 0; $UCL_MR = 3.4360 \pm 0.001$; 'MR chart: 1 point(s) beyond UCL_MR' in output.

TC-SPC-IMR-020

Tests: UR-SPC-006

Command: `jrc_spc_imr oq/data/imr_stable.csv --ucll 11`

Rationale: Misspelled option must not be silently ignored (X-05).

Pass criterion: Exit code $\neq 0$; 'Unknown argument' and '--ucll' in output.

TC-SPC-IMR-021

Tests: UR-SPC-003

Command: `jrc_spc_imr oq/data/imr_stable.csv --ucl 10.4`

Rationale: User limits drive Rule 1 (code review 2026-10, SPC-05): the maximum 10.42 (id 15) lies below the computed UCL 10.92 but beyond the user UCL 10.4.

Pass criterion: Exit code 0; 'Rule 1 uses the user-specified limit(s)'; 'OUT OF CONTROL — 1 point(s) flagged'; id 15 flagged with rule [1].

6.2 jrc_spc_xbar_r

TC-SPC-XBR-001

Tests: UR-SPC-007, UR-SPC-010

Command: `jrc_spc_xbar_r oq/data/xbar_r_stable.csv`

Rationale: Verifies the script completes successfully for a well-behaved dataset.

Pass criterion: Exit code 0; output contains X-bar/grand mean section, R-bar section, and verdict.

TC-SPC-XBR-002

Tests: UR-SPC-008, UR-SPC-010

Command: `jrc_spc_xbar_r oq/data/xbar_r_stable.csv`

Rationale: xbar_r_stable.csv is designed so no WE rule fires.

Pass criterion: Exit code 0; 'IN CONTROL' or 'STABLE' present in output.

TC-SPC-XBR-003

Tests: UR-SPC-008, UR-SPC-010

Command: jrc_spc_xbar_r oq/data/xbar_r_ooc.csv

Rationale: xbar_r_ooc.csv has subgroup sg09 with mean ≈ 53 , far above UCL ≈ 50.92 .

Pass criterion: Exit code 0; 'OUT OF CONTROL' or 'SIGNALS' present in output.

TC-SPC-XBR-004

Tests: UR-SPC-008

Command: jrc_spc_xbar_r oq/data/xbar_r_ooc.csv

Pass criterion: Output contains 'sg09'.

TC-SPC-XBR-005

Tests: UR-SPC-009

Command: jrc_spc_xbar_r oq/data/xbar_r_stable.csv --ucl 52.0 --lcl 48.0

Pass criterion: Exit code 0; output contains '52.0' or '52.00' or 'user' or 'specified'.

TC-SPC-XBR-006

Tests: UR-SPC-011

Command: jrc_spc_xbar_r oq/data/xbar_r_stable.csv

Pass criterion: File matching *_jrc_spc_xbar_r.png exists in ~/Downloads/ with recent mtime.

TC-SPC-XBR-007

Tests: UR-SPC-026

Command: jrc_spc_xbar_r

Pass criterion: Exit code $\neq 0$; 'Usage' or 'usage' present in output.

TC-SPC-XBR-008

Tests: UR-SPC-027

Command: jrc_spc_xbar_r /tmp/no_such_file_xyz.csv

Pass criterion: Exit code $\neq 0$; 'not found' or filename present in output.

TC-SPC-XBR-009

Tests: UR-SPC-007

Command: jrc_spc_xbar_r oq/data/xbar_r_missing_col.csv

Pass criterion: Exit code $\neq 0$; 'value' present in output.

TC-SPC-XBR-010

Tests: UR-SPC-012

Command: jrc_spc_xbar_r oq/data/xbar_r_unbalanced.csv

Rationale: xbar_r_unbalanced.csv has subgroups of different sizes.

Pass criterion: Exit code $\neq 0$; one of 'unbalanced', 'equal', or 'same size' present in output.

TC-SPC-XBR-011

Tests: UR-SPC-012

Command: jrc_spc_xbar_r oq/data/xbar_r_n_too_large.csv

Rationale: xbar_r_n_too_large.csv has $n = 11$; tabulated constants only cover $n = 2-10$.

Pass criterion: Exit code $\neq 0$; one of '10', 'xbar_s', or 'large' present in output.

TC-SPC-XBR-012

Tests: UR-SPC-025

Command: Rscript repos/spc/R/jrc_spc_xbar_r.R oq/data/xbar_r_stable.csv
(RENV_PATHS_ROOT unset)

Pass criterion: Exit code $\neq 0$; 'RENV_PATHS_ROOT' present in output.

TC-SPC-XBR-013

Tests: UR-SPC-028

Command: `jrc_spc_xbar_r oq/data/xbar_r_stable.csv`

Rationale: Reference: grand X-bar = mean of all 20 subgroup means = 50.165000. Computed in pure Python.

Pass criterion: Exit code 0; grand X-bar = 50.165 ± 0.001 .

TC-SPC-XBR-014

Tests: UR-SPC-028

Command: `jrc_spc_xbar_r oq/data/xbar_r_stable.csv`

Rationale: Reference: $UCL_x = X\text{-bar} + A2 * R\text{-bar} = 50.165 + 0.577 * 1.300 = 50.9151$. $A2 = 0.577$ for $n = 5$. Computed in pure Python.

Pass criterion: Exit code 0; $UCL = 50.9151 \pm 0.001$.

TC-SPC-XBR-015

Tests: UR-SPC-028

Command: `jrc_spc_xbar_r oq/data/xbar_r_stable.csv`

Rationale: Reference: $LCL_x = X\text{-bar} - A2 * R\text{-bar} = 50.165 - 0.577 * 1.300 = 49.4149$. Computed in pure Python.

Pass criterion: Exit code 0; $LCL = 49.4149 \pm 0.001$.

TC-SPC-XBR-016

Tests: UR-SPC-028

Command: `jrc_spc_xbar_r oq/data/xbar_r_stable.csv`

Rationale: Reference: $UCL_R = D4 * R\text{-bar} = 2.114 * 1.300 = 2.7482$. $D4 = 2.114$ for $n = 5$. Computed in pure Python.

Pass criterion: Exit code 0; $UCL_R = 2.7482 \pm 0.001$.

TC-SPC-XBR-017

Tests: UR-SPC-029

Command: `jrc_spc_xbar_r oq/data/xbar_r_stable.csv --report`

Rationale: --report flag triggers PV report generation. Accepts .docx (jr_pack full install) or .html (template-only install).

Pass criterion: Exit code 0; file matching *_xbar_r_pv_report.docx or *_xbar_r_pv_report.html found in ~/Downloads/ with recent mtime.

TC-SPC-XBR-018

Tests: UR-SPC-029

Command: `jrc_spc_xbar_r oq/data/xbar_r_stable.csv --report`

Rationale: When jr_pack is fully installed the JSON sidecar is consumed after .docx generation.

Pass criterion: Exit code 0; file matching *_xbar_r_pv_report.docx or *_xbar_r_pv_report_data.json found in ~/Downloads/ with recent mtime.

TC-SPC-XBR-019

Tests: UR-SPC-029

Command: `jrc_spc_xbar_r oq/data/xbar_r_stable.csv --report`

Rationale: JSON sidecar must carry `report_type == "pv"` and `verdict_pass == True` for the stable dataset confirmed by TC-SPC-XBR-002.

Pass criterion: Exit code 0; .docx or JSON found; if JSON present: `report_type == "pv"` and `verdict_pass` is True.

TC-SPC-XBR-020

Tests: UR-SPC-008

Command: `jrc_spc_xbar_r oq/data/xbar_r_range_beyond_ucl.csv`

Rationale: $k = 20$, $n = 5$; one subgroup range of 3.0 with $R\text{-bar} = 1.10$: $UCL_R = 2.114 * 1.10 = 2.3254$. The range is above UCL_R but below the $3.66 * R\text{-bar} = 4.026$ threshold used before the 2026-10 fix (SPC-01).

Pass criterion: Exit code 0; $UCL_R = 2.3254 \pm 0.001$; 'R chart: 1 subgroup(s) outside the R-chart limits' in output.

6.3 jrc_spc_xbar_s

TC-SPC-XBS-001

Tests: UR-SPC-013, UR-SPC-016

Command: `jrc_spc_xbar_s oq/data/xbar_s_stable.csv`

Rationale: 20 subgroups $\times n = 8$; no WE rule should fire.

Pass criterion: Exit code 0; output contains X-bar section, S-bar/Std Dev section, and verdict.

TC-SPC-XBS-002

Tests: UR-SPC-014, UR-SPC-016

Command: `jrc_spc_xbar_s oq/data/xbar_s_stable.csv`

Pass criterion: Exit code 0; 'IN CONTROL' or 'STABLE' present in output.

TC-SPC-XBS-003

Tests: UR-SPC-014, UR-SPC-016

Command: `jrc_spc_xbar_s oq/data/xbar_s_ooc.csv`

Rationale: xbar_s_ooc.csv has subgroup sg09 with mean ≈ 102 , far above $UCL \approx 100.55$.

Pass criterion: Exit code 0; 'OUT OF CONTROL' or 'SIGNALS' present in output.

TC-SPC-XBS-004

Tests: UR-SPC-014

Command: `jrc_spc_xbar_s oq/data/xbar_s_ooc.csv`

Pass criterion: Output contains 'sg09'.

TC-SPC-XBS-005

Tests: UR-SPC-015

Command: `jrc_spc_xbar_s oq/data/xbar_s_stable.csv --ucl 102.0 --lcl 98.0`

Pass criterion: Exit code 0; output contains '102.0' or '102.00' or 'user' or 'specified'.

TC-SPC-XBS-006

Tests: UR-SPC-017

Command: `jrc_spc_xbar_s oq/data/xbar_s_stable.csv`

Pass criterion: File matching `*_jrc_spc_xbar_s.png` exists in ~/Downloads/ with recent mtime.

TC-SPC-XBS-007

Tests: UR-SPC-026

Command: `jrc_spc_xbar_s`

Pass criterion: Exit code $\neq 0$; 'Usage' or 'usage' present in output.

TC-SPC-XBS-008

Tests: UR-SPC-027

Command: `jrc_spc_xbar_s /tmp/no_such_file_xyz.csv`

Pass criterion: Exit code $\neq 0$; 'not found' or filename present in output.

TC-SPC-XBS-009

Tests: UR-SPC-013

Command: `jrc_spc_xbar_s oq/data/xbar_s_missing_col.csv`

Pass criterion: Exit code $\neq 0$; 'value' present in output.

TC-SPC-XBS-010

Tests: UR-SPC-018

Command: `jrc_spc_xbar_s oq/data/xbar_r_unbalanced.csv`

Rationale: Reuses the xbar_r unbalanced dataset (same column structure).

Pass criterion: Exit code $\neq 0$; one of 'unbalanced', 'equal', or 'same size' present in output.

TC-SPC-XBS-011

Tests: UR-SPC-025

Command: `Rscript repos/spc/R/jrc_spc_xbar_s.R oq/data/xbar_s_stable.csv`
(`RENV_PATHS_ROOT` unset)

Pass criterion: Exit code $\neq 0$; 'RENV_PATHS_ROOT' present in output.

TC-SPC-XBS-012

Tests: UR-SPC-028

Command: `jrc_spc_xbar_s oq/data/xbar_s_stable.csv`

Rationale: Reference: grand $\bar{X}$ = mean of all 20 subgroup means = 100.060000. Dataset: 20 subgroups $\times n = 8$.
Computed in pure Python.

Pass criterion: Exit code 0; grand $\bar{X}$ = 100.060 ± 0.001 .

TC-SPC-XBS-013

Tests: UR-SPC-028

Command: `jrc_spc_xbar_s oq/data/xbar_s_stable.csv`

Rationale: Reference: $UCL_{\bar{x}} = \bar{X} + A_3 \cdot \bar{s} = 100.060 + 1.099095 \cdot 0.473726 = 100.5807$. $A_3 = 3/(c_4 \cdot \sqrt{8})$, $c_4(8) = 0.965030$. Computed in pure Python.

Pass criterion: Exit code 0; $UCL(\bar{X}\text{-bar chart}) = 100.5807 \pm 0.001$.

TC-SPC-XBS-014

Tests: UR-SPC-028

Command: `jrc_spc_xbar_s oq/data/xbar_s_stable.csv`

Rationale: Reference: $LCL_{\bar{x}} = \bar{X} - A_3 \cdot \bar{s} = 100.060 - 1.099095 \cdot 0.473726 = 99.5393$. Computed in pure Python.

Pass criterion: Exit code 0; $LCL(\bar{X}\text{-bar chart}) = 99.5393 \pm 0.001$.

TC-SPC-XBS-015

Tests: UR-SPC-028

Command: `jrc_spc_xbar_s oq/data/xbar_s_stable.csv`

Rationale: Reference: $UCL_S = B_4 \cdot \bar{s} = 1.814910 \cdot 0.473726 = 0.8598$. $B_4(8) = 1.814910$. Computed in pure Python.

Pass criterion: Exit code 0; $UCL(S\text{ chart}) = 0.8598 \pm 0.001$.

TC-SPC-XBS-016

Tests: UR-SPC-029

Command: `jrc_spc_xbar_s oq/data/xbar_s_stable.csv --report`

Rationale: `--report` flag triggers PV report generation. Accepts .docx (jr_pack full install) or .html (template-only install).

Pass criterion: Exit code 0; file matching `*_xbar_s_pv_report.docx` or `*_xbar_s_pv_report.html` found in `~/Downloads/` with recent mtime.

TC-SPC-XBS-017

Tests: UR-SPC-029

Command: `jrc_spc_xbar_s oq/data/xbar_s_stable.csv --report`

Rationale: When jr_pack is fully installed the JSON sidecar is consumed after .docx generation.

Pass criterion: Exit code 0; file matching `*_xbar_s_pv_report.docx` or `*_xbar_s_pv_report_data.json` found in `~/Downloads/` with recent mtime.

TC-SPC-XBS-018

Tests: UR-SPC-029

Command: `jrc_spc_xbar_s oq/data/xbar_s_stable.csv --report`

Rationale: JSON sidecar must carry report_type == "pv" and verdict_pass == True for the stable dataset confirmed by TC-SPC-XBS-002.

Pass criterion: Exit code 0; .docx or JSON found; if JSON present: report_type == "pv" and verdict_pass is True.

6.4 jrc_spc_p

TC-SPC-P-001

Tests: UR-SPC-019, UR-SPC-020

Command: jrc_spc_p oq/data/p_stable.csv

Rationale: 25 subgroups, n = 100 each, defectives vary 1–8; no WE rule should fire.

Pass criterion: Exit code 0; output contains p-bar section, UCL section, and verdict.

TC-SPC-P-002

Tests: UR-SPC-019, UR-SPC-020

Command: jrc_spc_p oq/data/p_stable.csv

Pass criterion: Exit code 0; 'IN CONTROL' or 'STABLE' present in output.

TC-SPC-P-003

Tests: UR-SPC-019

Command: jrc_spc_p oq/data/p_stable.csv

Rationale: With 104 total defectives across 2500 inspected, p_bar = 0.0416.

Pass criterion: Output matches regex 0.04[01234] or 4.[01234]%.

TC-SPC-P-004

Tests: UR-SPC-019, UR-SPC-020

Command: jrc_spc_p oq/data/p_ooc.csv

Rationale: p_ooc.csv has subgroup 13 = 15 defectives ($p = 0.15 > UCL \approx 0.10$).

Pass criterion: Exit code 0; 'OUT OF CONTROL' or 'SIGNALS' present in output.

TC-SPC-P-005

Tests: UR-SPC-019

Command: jrc_spc_p oq/data/p_ooc.csv

Pass criterion: Output contains '13'.

TC-SPC-P-006

Tests: UR-SPC-022

Command: jrc_spc_p oq/data/p_stable.csv

Pass criterion: File matching *_jrc_spc_p.png exists in ~/Downloads/ with recent mtime.

TC-SPC-P-007

Tests: UR-SPC-026

Command: jrc_spc_p

Pass criterion: Exit code $\neq 0$; 'Usage' or 'usage' present in output.

TC-SPC-P-008

Tests: UR-SPC-027

Command: jrc_spc_p /tmp/no_such_file_xyz.csv

Pass criterion: Exit code $\neq 0$; 'not found' or filename present in output.

TC-SPC-P-009

Tests: UR-SPC-019

Command: jrc_spc_p oq/data/p_missing_col.csv

Rationale: p_missing_col.csv lacks the 'defectives' column.

Pass criterion: Exit code $\neq 0$; 'defective' present in output.

TC-SPC-P-010

Tests: UR-SPC-021

Command: `jrc_spc_p oq/data/p_invalid.csv`

Rationale: p_invalid.csv contains a row where defectives = 101 > n = 100.

Pass criterion: Exit code ≠ 0; one of 'defective', 'exceed', 'greater', 'cannot', or 'invalid' present in output.

TC-SPC-P-011

Tests: UR-SPC-025

Command: `Rscript repos/spc/R/jrc_spc_p.R oq/data/p_stable.csv (RENV_PATHS_ROOT unset)`

Pass criterion: Exit code ≠ 0; 'RENV_PATHS_ROOT' present in output.

TC-SPC-P-012

Tests: UR-SPC-028

Command: `jrc_spc_p oq/data/p_stable.csv defectives n`

Rationale: Reference: $p\text{-bar} = 104 \text{ total defectives} / 2500 \text{ total inspected} = 0.041600$. Computed in pure Python.

Pass criterion: Exit code 0; $p\text{-bar} = 0.04160 \pm 0.0001$.

TC-SPC-P-013

Tests: UR-SPC-028

Command: `jrc_spc_p oq/data/p_stable.csv defectives n`

Rationale: Reference: $UCL = p\text{-bar} + 3 \cdot \sqrt{p\text{-bar} \cdot (1 - p\text{-bar}) / n} = 0.041600 + 3 \cdot 0.019979 = 0.101537$. Computed in pure Python.

Pass criterion: Exit code 0; $UCL = 0.10150 \pm 0.0010$.

TC-SPC-P-014

Tests: UR-SPC-029

Command: `jrc_spc_p oq/data/p_stable.csv --report`

Rationale: --report flag triggers PV report generation. Accepts .docx (jr_pack full install) or .html (template-only install).

Pass criterion: Exit code 0; file matching *_spc_p_pv_report.docx or *_spc_p_pv_report.html found in ~/Downloads/ with recent mtime.

TC-SPC-P-015

Tests: UR-SPC-029

Command: `jrc_spc_p oq/data/p_stable.csv --report`

Rationale: When jr_pack is fully installed the JSON sidecar is consumed after .docx generation.

Pass criterion: Exit code 0; file matching *_spc_p_pv_report.docx or *_spc_p_pv_report_data.json found in ~/Downloads/ with recent mtime.

TC-SPC-P-016

Tests: UR-SPC-029

Command: `jrc_spc_p oq/data/p_stable.csv --report`

Rationale: JSON sidecar must carry `report_type == "pv"` and `verdict_pass == True` for the stable dataset confirmed by TC-SPC-P-002.

Pass criterion: Exit code 0; .docx or JSON found; if JSON present: `report_type == "pv"` and `verdict_pass` is True.

TC-SPC-P-017

Tests: UR-SPC-019, UR-SPC-020

Command: `jrc_spc_p oq/data/p_all_zero.csv`

Rationale: Zero defectives in all 12 subgroups: $p\text{-bar} = 0$, limits collapse onto the centre line and the run rules cannot be evaluated. Crashed before the 2026-10 fix (SPC-03).

Pass criterion: Exit code 0; 'No variation in the data' and 'IN CONTROL' in output.

6.5 jrc_spc_c

TC-SPC-C-001

Tests: UR-SPC-023, UR-SPC-024

Command: `jrc_spc_c oq/data/c_stable.csv`

Rationale: 25 subgroups; defect counts vary 1–9; no WE rule should fire.

Pass criterion: Exit code 0; output contains c-bar section, UCL section, and verdict.

TC-SPC-C-002

Tests: UR-SPC-023, UR-SPC-024

Command: `jrc_spc_c oq/data/c_stable.csv`

Pass criterion: Exit code 0; 'IN CONTROL' or 'STABLE' present in output.

TC-SPC-C-003

Tests: UR-SPC-023

Command: `jrc_spc_c oq/data/c_stable.csv`

Rationale: With 124 total defects across 25 subgroups, $\bar{c} = 4.96$.

Pass criterion: Output matches regex `4.8[0-9]` or `4.9[0-9]`.

TC-SPC-C-004

Tests: UR-SPC-023, UR-SPC-024

Command: `jrc_spc_c oq/data/c_ooc.csv`

Rationale: `c_ooc.csv` has subgroup 12 = 15 defects, above UCL ≈ 12.2 .

Pass criterion: Exit code 0; 'OUT OF CONTROL' or 'SIGNALS' present in output.

TC-SPC-C-005

Tests: UR-SPC-023

Command: `jrc_spc_c oq/data/c_ooc.csv`

Pass criterion: Output contains '12'.

TC-SPC-C-006

Tests: UR-SPC-024

Command: `jrc_spc_c oq/data/c_stable.csv`

Pass criterion: File matching `*_jrc_spc_c.png` exists in `~/Downloads/` with recent mtime.

TC-SPC-C-007

Tests: UR-SPC-026

Command: `jrc_spc_c`

Pass criterion: Exit code $\neq 0$; 'Usage' or 'usage' present in output.

TC-SPC-C-008

Tests: UR-SPC-027

Command: `jrc_spc_c /tmp/no_such_file_xyz.csv`

Pass criterion: Exit code $\neq 0$; 'not found' or filename present in output.

TC-SPC-C-009

Tests: UR-SPC-023

Command: `jrc_spc_c oq/data/c_missing_col.csv`

Rationale: `c_missing_col.csv` lacks the 'defects' column.

Pass criterion: Exit code $\neq 0$; 'defect' present in output.

TC-SPC-C-010

Tests: UR-SPC-025

Command: `Rscript repos/spc/R/jrc_spc_c.R oq/data/c_stable.csv` (RENV_PATHS_ROOT unset)

Pass criterion: Exit code $\neq 0$; 'RENV_PATHS_ROOT' present in output.

TC-SPC-C-011

Tests: UR-SPC-028

Command: `jrc_spc_c oq/data/c_stable.csv defects`

Rationale: Reference: $c\text{-bar} = \text{sum}(\text{defects}) / k = 124 / 25 = 4.960$. Computed in pure Python.

Pass criterion: Exit code 0; $c\text{-bar} = 4.960 \pm 0.001$.

TC-SPC-C-012

Tests: UR-SPC-028

Command: `jrc_spc_c oq/data/c_stable.csv defects`

Rationale: Reference: $UCL = c\text{-bar} + 3 * \text{sqrt}(c\text{-bar}) = 4.960 + 3 * 2.2271 = 11.641$. Computed in pure Python.

Pass criterion: Exit code 0; $UCL = 11.641 \pm 0.010$.

TC-SPC-C-013

Tests: UR-SPC-023, UR-SPC-024

Command: `jrc_spc_c oq/data/c_all_zero.csv`

Rationale: Zero defects in all 12 subgroups: $c\text{-bar} = 0$, $\sigma = 0$, the run rules cannot be evaluated. Crashed before the 2026-10 fix (SPC-03).

Pass criterion: Exit code 0; 'No variation in the data' and 'IN CONTROL' in output.

7. Acceptance Criteria

The OQ is considered passed when all of the following conditions are met:

- All 89 test cases defined in Section 6 pass with exit code as specified.
- No test case fails (i.e. pytest reports 0 failures and 0 errors).
- The OQ evidence file (timestamped pytest output) is written to `~/jrscrip</PROJECT_ID>/validation/` by `admin_spc_oq`.
- All 29 user requirements (UR-SPC-001 through UR-SPC-029) are covered by at least one passing test case.
- Any deviation from this plan is documented and assessed for impact before the OQ is declared passed.

Any test failure shall be investigated, documented as a deviation, resolved, and the affected test(s) re-executed. The OQ may not be closed until all deviations are resolved.

8. Requirements Traceability Matrix

The table below maps each user requirement to the test cases that verify it.

UR ID	Requirement (summary)	Test Cases
UR-SPC-001	<code>jrc_spc_imr</code> — X-bar, MR-bar, control limits	TC-SPC-IMR-001, TC-SPC-IMR-002
UR-SPC-002	<code>jrc_spc_imr</code> — WE rules, violation list	TC-SPC-IMR-002, TC-SPC-IMR-003, TC-SPC-IMR-004, TC-SPC-IMR-019
UR-SPC-003	<code>jrc_spc_imr</code> — <code>--ucl</code> / <code>--lcl</code>	TC-SPC-IMR-005, TC-SPC-IMR-021
UR-SPC-004	<code>jrc_spc_imr</code> — IN CONTROL / OUT OF CONTROL verdict	TC-SPC-IMR-001, TC-SPC-IMR-002, TC-SPC-IMR-003
UR-SPC-005	<code>jrc_spc_imr</code> — PNG to <code>~/Downloads/</code>	TC-SPC-IMR-006
UR-SPC-006	<code>jrc_spc_imr</code> — reject invalid inputs	TC-SPC-IMR-007, TC-SPC-IMR-008, TC-SPC-IMR-009, TC-SPC-IMR-010, TC-SPC-IMR-020
UR-SPC-007	<code>jrc_spc_xbar_r</code> — grand mean, R-	TC-SPC-XBR-001, TC-SPC-XBR-002, TC-SPC-XBR-009

	bar, limits	
UR-SPC-008	jrc_spc_xbar_r — WE rules, violation list	TC-SPC-XBR-002, TC-SPC-XBR-003, TC-SPC-XBR-004, TC-SPC-XBR-020
UR-SPC-009	jrc_spc_xbar_r — --ucl / --lcl	TC-SPC-XBR-005
UR-SPC-010	jrc_spc_xbar_r — verdict	TC-SPC-XBR-001, TC-SPC-XBR-002, TC-SPC-XBR-003
UR-SPC-011	jrc_spc_xbar_r — PNG to ~/Downloads/	TC-SPC-XBR-006
UR-SPC-012	jrc_spc_xbar_r — reject unbalanced / n > 10	TC-SPC-XBR-010, TC-SPC-XBR-011
UR-SPC-013	jrc_spc_xbar_s — grand mean, S-bar, limits via c4	TC-SPC-XBS-001, TC-SPC-XBS-002, TC-SPC-XBS-009
UR-SPC-014	jrc_spc_xbar_s — WE rules, violation list	TC-SPC-XBS-002, TC-SPC-XBS-003, TC-SPC-XBS-004
UR-SPC-015	jrc_spc_xbar_s — --ucl / --lcl	TC-SPC-XBS-005
UR-SPC-016	jrc_spc_xbar_s — verdict	TC-SPC-XBS-001, TC-SPC-XBS-002, TC-SPC-XBS-003
UR-SPC-017	jrc_spc_xbar_s — PNG to ~/Downloads/	TC-SPC-XBS-006
UR-SPC-018	jrc_spc_xbar_s — reject unbalanced subgroups	TC-SPC-XBS-010
UR-SPC-019	jrc_spc_p — p-bar, variable limits, WE rules	TC-SPC-P-001, TC-SPC-P-002, TC-SPC-P-003, TC-SPC-P-004, TC-SPC-P-005, TC-SPC-P-009, TC-SPC-P-017
UR-SPC-020	jrc_spc_p — verdict	TC-SPC-P-001, TC-SPC-P-002, TC-SPC-P-004, TC-SPC-P-017
UR-SPC-021	jrc_spc_p — reject defectives > n	TC-SPC-P-010
UR-SPC-022	jrc_spc_p — PNG to ~/Downloads/	TC-SPC-P-006
UR-SPC-023	jrc_spc_c — c-bar, sigma, limits, WE rules	TC-SPC-C-001, TC-SPC-C-002, TC-SPC-C-003, TC-SPC-C-004, TC-SPC-C-005, TC-SPC-C-009, TC-SPC-C-013
UR-SPC-024	jrc_spc_c — verdict; PNG to ~/Downloads/	TC-SPC-C-001, TC-SPC-C-002, TC-SPC-C-004, TC-SPC-C-006, TC-SPC-C-013
UR-SPC-025	All scripts — RENV_PATHS_ROOT bypass protection	TC-SPC-IMR-011, TC-SPC-XBR-012, TC-SPC-XBS-011, TC-SPC-P-011, TC-SPC-C-010
UR-SPC-026	All scripts — no-arguments usage message	TC-SPC-IMR-007, TC-SPC-XBR-007, TC-SPC-XBS-007, TC-SPC-P-007, TC-SPC-C-007
UR-SPC-027	All scripts — file not found error	TC-SPC-IMR-008, TC-SPC-XBR-008, TC-SPC-XBS-008, TC-SPC-P-008, TC-SPC-C-008
UR-SPC-028	All scripts — numeric correctness of control limits	TC-SPC-IMR-012, TC-SPC-IMR-013, TC-SPC-IMR-014, TC-SPC-IMR-015, TC-SPC-XBR-013, TC-SPC-XBR-014, TC-SPC-XBR-015, TC-SPC-XBR-016, TC-SPC-XBS-012, TC-SPC-XBS-013, TC-SPC-XBS-014, TC-SPC-XBS-015, TC-SPC-P-012, TC-SPC-P-013, TC-SPC-C-011, TC-SPC-C-012
UR-SPC-029	jrc_spc_imr/xbar_r/xbar_s/p — --report PV report	TC-SPC-IMR-016, TC-SPC-IMR-017, TC-SPC-IMR-018, TC-SPC-XBR-017, TC-SPC-XBR-018, TC-SPC-XBR-019, TC-SPC-XBS-016, TC-SPC-XBS-017, TC-SPC-XBS-018, TC-SPC-P-014, TC-SPC-P-015, TC-SPC-P-016

9. Roles and Responsibilities

Role	Responsibility
Author	Prepares this validation plan; executes the OQ test suite; documents results in the validation report.
Reviewer	Reviews this plan and the corresponding validation report for technical accuracy and completeness.
Approver (QA)	Approves this plan prior to OQ execution; approves the validation report upon successful completion of OQ.

10. Deviation Handling

Any deviation from this plan (e.g. a test case that cannot be executed as written, or a test that fails due to an environmental issue rather than a software defect) must be documented in the validation report with:

- A unique deviation ID
- Description of the deviation
- Root cause assessment
- Impact on validation coverage
- Resolution and disposition (accept with rationale, retry after fix, or reject)

A deviation does not automatically invalidate the OQ. Each deviation must be assessed individually for its impact on the demonstrated compliance of the SPC module.