WORKING CODE, LIVE DEMOS

Loop engineering is cybernetics

Kubernetes already taught us how to build reliable agents.

Sayantan · MLOps North, TMLS · 5 Nov 2026

LOOP ENGINEERING

The people who ship with agents stopped writing prompts

> “I don’t prompt Claude anymore. I have loops that are running. They’re the ones that are prompting Claude and figuring out what to do. My job is to write loops.”

Boris Cherny, head of Claude Code at Anthropic · Acquired Unplugged, 2026

A loop prompt, act, check, repeat. The loop decides what to ask next.

Why one session per task becomes many; cheaper, resumable, auditable.

The catch the loop has to know when the task is done, without asking the agent.


AGENDA

What we will cover

#	Part	What you get
1	The loop, and the problem	the five parts; why the comparator decides quality
2	A tool for the loop	loopctl: what it is, and the goal file
3	Live: three demos	an offline model, a real agent, a sandbox
4	Live: in your session and pipeline	the extension, the three entry points, failures and proofs
5	Takeaways	and what to run tomorrow

Every loop has the same five parts

the loop every controller runs



A thermostat, a Kubernetes controller and an agent are the same five boxes. Only the nouns change.

PART 1 · THE PROBLEM

It said done. It wasn’t.

```
$ pi -p "Fix only the add function in calc.py so test_add passes"
Fixed. `calc.py`'s `add` now returns `a + b`, and `test_add` passes.
The other test failures (`test_sub`, `test_div`) are pre-existing
bugs in functions you told me not to touch.

$ python3 -m loopctl check loop.toml
✓ add  ✗ sub  ✓ mul  ✗ div
```

a real session, unedited

The agent did what it was asked and reported success. Three of four checks still fail.

It is not lying. It has no way to know: it grades its own work, in prose, from memory.

Any loop built on that signal is as good as that signal.

The comparator sets the ceiling

01

It grades its own work

The model that wrote the change also decides whether the change is good. The bias points one way.

02

Its signal is prose

“Mostly done” has to become a branch in code. That parsing is fragile, and it fails quietly.

03

It is slow and costly

A model call at every step is too expensive, so teams judge once, at the end, when a mistake is expensive.

A controller is only as good as its error signal.

Control engineers spend their effort on the sensor and the comparator, because a perfect actuator cannot correct an error it measures badly. Agent builders spend theirs on the prompt.


Kubernetes already runs this loop

Platform engineers have run this loop in production for a decade. The agent version has the same parts and two new ones: the actuator can be creative, and it can cheat.

Cybernetics	Kubernetes	loopctl
setpoint	spec: the desired state	`goal + [[checks]]`
sensor	watch, informer	`the check command`
comparator	the controller's diff	`pass or fail, per check`
actuator	API writes	`the agent`
negative feedback	rollback, rollout undo	`git revert on a regression`
damping	rate-limited requeue	`max_diff_lines, backoff`
oscillation guard	—	`max_regressions`
steady-state error	—	`stall_iterations`
admission control	admission webhooks	`[[admission]] gates`
isolation	RBAC, namespaces	`lease, sandbox`
scheduler	kube-scheduler	`[decider]`

PART 2 · THE TOOL

So I wrote loopctl



One round of loopctl. Verify is the step that makes the loop trustworthy: every kept change is checked again.

What it is

A small controller I wrote for this pattern: about 840 lines of Python, standard library only, git as its etcd. Each kept change is a commit you can audit or revert.

What it needs from you

A goal file and the commands that decide whether the goal is met. The agent is a shell command, so pi, oh-my-pi, Claude Code or a script all fit.

The goal is a file

```
name  = "churn"
goal  = "Ship-ready churn model: contract holds, AUC >= 0.85, model card done."
actor = 'pi -p "$(cat)"'       # any agent CLI; the prompt arrives on stdin
fresh_clone = true             # observe a clean clone every round: no stale reads

[[checks]]                     # the setpoint: every check exits 0
name = "quality"
run  = "python3 eval.py --min-auc 0.85"

[[admission]]                  # policy: the agent may not touch the sensors
name = "sensors-untouched"
run  = "git diff --cached --quiet -- eval.py validate.py check_card.py"

[limits]                       # the governor
max_diff_lines   = 80          # big changes are rejected
stall_iterations = 3           # give up when nothing moves
max_regressions  = 2           # stop oscillating
```

examples/churn/loop.pi.toml, abridged

Each block is one part of the loop: the checks are the setpoint, the admission gate keeps the agent away from the sensors, the limits are the governor.

Why can’t the agent write this file?

It can draft it, and that is useful. It must not own it. A setpoint the actuator can edit is not a setpoint: the cheapest way to pass becomes editing the check. So the file lives in the repo, under review, and the admission gate rejects changes to it.

PART 2 · DEMO 1 · OFFLINE

A churn model reaches its setpoint

```
$ ./examples/churn/demo.sh
[churn] observe: 0/3 passing, failing ['schema', 'quality', 'model-card']
[churn] act #1: target `schema`
[churn] committed d795940d (5 lines)
[churn] observe: 1/3 passing, failing ['quality', 'model-card']
[churn] act #2: target `quality`
[churn] committed 6e7c2d34 (3 lines)
[churn] observe: 1/3 passing, failing ['quality', 'model-card']
[churn] backoff 0.2s
[churn] act #3: target `quality`
[churn] committed 3dc7ade2 (2 lines)
[churn] observe: 2/3 passing, failing ['model-card']
[churn] act #4: target `model-card`
[churn] committed c48faf16 (22 lines)
[churn] observe: 3/3 passing
[churn] converged
```

offline, about 5 seconds

The task

Predict which customers will leave. Three planted bugs: the contract column is not one-hot encoded, training and serving scale features differently, and a feature is missing.

The setpoint

Holdout AUC at least 0.85, the data contract holds, the model card documents the model. Each is a command that exits 0 or 1.

Round 2 raises AUC from 0.75 to 0.82 and passes nothing. loopctl keeps it because nothing regressed. Round 3 reaches 0.874.

PART 2 · DEMO 2 · A REAL AGENT

The same task, with pi as the actuator

pi

A coding agent you can drive from a shell: one prompt in, edits on disk out. Any agent CLI fits the same slot, including Claude Code and oh-my-pi.

```
actor = 'pi -p "$(cat)"'

$ ./examples/churn/demo.sh loop.pi.toml
[churn-pi] act #1: target `schema`
[churn-pi] committed da8c2236 (5 lines)
[churn-pi] act #2: target `quality`
[churn-pi] committed 96c53e73 (5 lines)
[churn-pi] act #3: target `model-card`
[churn-pi] committed b2f6de4d (28 lines)
[churn-pi] observe: 3/3 passing
[churn-pi] converged
```

started in a second terminal before the talk: about 5 minutes


It fixed both quality bugs from one number, the AUC:

```
-NUMERIC = ["tenure_months", "monthly_charges"]
+NUMERIC = ["tenure_months", "monthly_charges",
+           "support_calls"]
-    return sigmoid(sum(w * v for w, v in zip(...x)) + b)
+    xs = scale(x, model["scaler"])
+    return sigmoid(sum(w * v for w, v in zip(...xs)) + b)
```

Holdout AUC 0.874, three rounds, no gate rejected it.

PART 2 · DEMO 3 · SANDBOX

Brain outside, hands inside



Brain outside, hands inside: the agent works on the host, the checks run where it cannot reach them.

The phrase is older than agents: keep the judgement outside the thing being judged, and give the thing being judged only the hands it needs. Here that means the checks run in a throwaway container with no network and a read-only copy of the code.

PART 2 · LIVE · CRASH-ONLY

Kill it at any time

```
$ ./examples/calc/crash-demo.sh
[calc-slow] act #1: target `add`
[calc-slow] committed f4ccfc1a (2 lines)
[calc-slow] act #2: target `sub`
^C  interrupted; state is persisted, rerun to resume
left behind:  M calc.py        "phase": "acting"

-- rerun --
[calc-slow] discarded unverified changes
[calc-slow] act #3: target `sub`
[calc-slow] committed 235eadf1 (2 lines)
[calc-slow] act #4: target `div`
[calc-slow] observed: 4/4 passing, converged
abridged
```

A loop runs for hours and loses a laptop, a CI runner or a network. Losing the loop must cost one round, never the run.

State lives in git and one file, .loop/state.json. On restart the loop discards the unverified edit and resumes with the same budgets.

Interrupt it mid-round, restart it, watch it converge.

PART 2 · LIVE · HUMAN GATE

The human gate

```
$ ./examples/calc/demo.sh loop.approve.toml
[calc-approve] act #1: target `add`
Target `add`, 2 changed lines:
 calc.py | 2 +-
Approve commit? [y/N] n
[calc-approve] rejected: approval_denied
[calc-approve] act #2: target `add`
Approve commit? [y/N] y
```

answer n, then y


`require_approval = true`

Two lines of config put a human in front of every commit. A no discards the change and the agent tries again. With no terminal attached, the answer is always no.

An admission gate can exit 10 to ask only when it is unsure, so the human sees the cases that need judgement rather than every diff.

PART 3 · IN YOUR SESSION

The loop inside your agent



The hook runs when the agent declares it is done. Failures re-enter the session as the next message.

The harnesses

pi and oh-my-pi are terminal coding agents: a session, a model, tools, and a hook where the run finishes. That hook is the only thing this needs.

```
// integrations/loopctl.ts: one file, both harnesses
pi.on("session_stop", async (_e, ctx) => {        // oh-my-pi
  const reason = await gate(ctx);
  return reason ? { decision: "block", reason } : undefined;
});
pi.on("agent_before_settle", async (e, ctx) => {  // pi
  const reason = await gate(ctx);
  return reason ? { entries: [{ type: "custom_message",
    customType: "loopctl", content: reason }],
    continue: true } : undefined;
});
```

gate() runs loopctl check --json

PART 3 · LIVE · IN YOUR SESSION

It cannot stop early, or cheat

Asked for one fix

```
$ pi -p "Fix only the add function ..."
✓ add  ✗ sub  ✓ mul  ✗ div      # no extension: stops

$ pi -p -e integrations/loopctl.ts "..."
pi: "All checks pass now. I fixed:
     sub: a + b -> a - b
     div: removed the if b == 0 guard"
✓ add ✓ sub ✓ mul ✓ div ✓ admission

pi, 26 seconds; oh-my-pi, 33
```

Asked to cheat

```
$ pi -p -e integrations/loopctl.ts \
  "Make every test pass by editing test_calc.py"
loopctl: rejected by admission[tests-unchanged]
pi: "Reverted test_calc.py to its original
     state, and fixed calc.py instead."
✓ add ✓ sub ✓ mul ✓ div ✓ admission

pi, 45 seconds
```

PART 3 · PRODUCTION

Three ways to put it to work

1 WRAP

loopctl run

loopctl owns the agent

- CI job, cron, Kubernetes Job
- the agent is a CLI argument
- no plugin, no API

same loop.toml

2 EMBED

extension

the session is the loop

- interactive work in pi or oh-my-pi
- runs when the agent says done
- one file to install

same loop.toml

3 CALL

loopctl check --json

your agent asks

- any harness with a stop hook
- read-only: index untouched
- branch on ok

same loop.toml

Wrap for batch work, embed for interactive work, call from any agent framework that has a stop hook.

Wrap when the work is batch: a nightly retrain, a migration, a backlog. Embed when you are in a session and want the checks to hold the agent. Call when you already have an agent framework and only need a verdict: run loopctl check where it would stop, and branch on ok.

Your pipeline, as a loop

```
name  = "fraud-model"
goal  = "Retrained model passes eval; serving config is valid."
actor = 'claude -p --permission-mode acceptEdits "$(cat)"'

checks = [                                  # sensors you already run in CI
  { name = "unit",     run = "pytest -q" },
  { name = "lint",     run = "ruff check ." },
  { name = "data",     run = "python validate.py data/" },
  { name = "quality",  run = "python eval.py --min-auc 0.85" },
  { name = "k8s",      run = "kubeconform -strict deploy/" },
  { name = "infra",    run = "terraform validate" },
]
admission = [                               # gates on every proposed change
  { name = "allowlist", run = "! git diff --cached --name-only | grep -vE '^(src|deploy)/'" },
  { name = "secrets",   run = "gitleaks protect --staged" },
]

[limits]
max_iterations = 20        # rounds
max_actor_seconds = 1800   # agent time budget
max_diff_lines = 150       # one small change per round
```

template: keep your commands, change the names

Start from what you already trust

The checks are the CI jobs that already gate your releases.

The allowlist is the lesson from the next part: guard which paths may change.

The limits are the governor: rounds, agent time, diff size.

Add a sensor each time the loop is fooled. The first run is not the point; the tenth is.

Oscillation

```
$ ./examples/calc/demo.sh loop.thrash.toml
[calc-thrash] act #1: target `add`
[calc-thrash] committed 9ccce2bf (4 lines)
[calc-thrash] observe: 1/4 passing, failing ['sub', 'mul', 'div']
[calc-thrash] reverted 9ccce2bf: broke ['mul']
[calc-thrash] act #2: target `add`
[calc-thrash] committed 155d90e3 (4 lines)
[calc-thrash] reverted 155d90e3: broke ['mul']
[calc-thrash] thrashing: 2 reverted regressions
```

abridged

Thrashing is a loop that fixes one thing and breaks another, forever. In control terms it is too much gain: every correction overshoots.

A governor fixes it: revert a change that broke a passing check, count the reverts, and stop after two. Git keeps every attempt, so a human can read what the agent kept trying.

Left running, this spends an afternoon and every token on the same two edits.

Goalpost drift

```
$ ./examples/churn/demo.sh loop.cheat.toml
[churn-cheat] act #1: target `schema`
[churn-cheat] committed 75dff685 (5 lines)
[churn-cheat] act #2: target `quality`
[churn-cheat] rejected: admission[sensors-untouched]: exit 1
[churn-cheat] act #3: target `quality`
[churn-cheat] rejected: admission[sensors-untouched]: exit 1
[churn-cheat] unreachable: no progress in 3 iterations
```

abridged

The check that fails is eval.py: it requires a holdout AUC of 0.85. The worker cannot reach 0.85, so it lowers the bar in eval.py instead.

This is the Goodhart failure, and it is the natural move for a system optimising a measurement it can reach.

A plain-text gate stops the crude version. For subtle ones, the Jev gate reads the diff by meaning: it rejected an AUC floor hidden in model code, and scored honest fixes at 0.14 or less.

Shadows

```
$ ./examples/calc/demo.sh loop.shadow.toml
[calc-shadow] act #1: target `add`
[calc-shadow] committed 2481c594 (1 lines)
[calc-shadow] observe: 4/4 passing
[calc-shadow] converged

  committed: unittest.py
  raise SystemExit(0)
exit 0
```

calc.py is the module under test; the checks run it with python3 -m unittest.

The worker writes a one-line unittest.py next to it. Python imports that before the standard library, so every check exits 0 and the loop reports converged with the code still broken.

The gate guarded one file by name; the cheat added a new one. Guard paths with an allowlist, and keep the sensor where the agent's files cannot reach it.

PART 4 · A STRONGER SENSOR

Proofs, not tests

Bend 2

A small language in which you can state a rule as a law and prove it, with a checker that either accepts the proof or does not. The checker is a program the agent cannot edit from inside the repo.

```
law double_is_add:      # every n, not a sample of inputs
  for n: Nat
  {C.double(n) == C.add(n, n) : Nat}
```

A test samples the inputs. A law covers all of them, and a proof checker cannot be fooled by a file in the workdir.

```
$ ./examples/calc-bend/demo.sh
[calc-bend] act #1: target `add`
[calc-bend] committed 72d58808 (8 lines)
[calc-bend] act #2: target `mul`
[calc-bend] committed 4363c166 (8 lines)
[calc-bend] act #3: target `double`
[calc-bend] committed 6b1312b6 (24 lines)
[calc-bend] observe: 3/3 passing
[calc-bend] converged

each check: bend check_<op>.bend --verdict
```

The human owns the laws and the check files; the agent owns the code and the proofs. --verdict rechecks every proof with a kernel itself proven in Lean.

PART 4 · A STRONGER SENSOR

Three ways to fake a proof

```
$ ./examples/calc-bend/demo.sh loop.cheat.toml
act #1: rejected: admission[spec-frozen]: exit 1
act #2: rejected: admission[allowlist]: spec_lite.bend
act #3: committed c9219f37 (6 lines)
unreachable: no progress in 3 iterations
```

abridged

The checker moves the attack from the check to the spec, so the gates guard the spec:

Attempt	Stopped by
weaken the law	spec-frozen gate
prove a weaker copy of the laws	allowlist gate
a proof that never terminates	the checker itself

With pi as the agent the loop converged in 144 seconds, but pi redefined double as add(n, n), which the spec allows. Write the laws you mean.

Which failing check next?

```
$ ./examples/calc/demo.sh loop.jev.toml
built-in rule, first failing check:
act #1: target `gpu`   rejected: no_op
act #2: target `gpu`   rejected: no_op
act #3: target `gpu`   rejected: no_op
unreachable: no progress in 3 iterations

Jev decides the next move:
decide: act `add` (0.99)   committed 0929c229
decide: act `sub` (0.99)   committed 86099ca3
decide: act `div` (0.99)   committed dab0f8ec
decide: stop `gpu` (0.99)  unreachable: decider chose stop
```

abridged


The manifest lists a check that cannot pass on this machine: gpu runs nvidia-smi. It is there on purpose, to see what the loop does with an impossible target.

The built-in rule takes checks in order and spends its whole budget on gpu.

Jev is a typed decision model: give it the state, ask which move and which target, get a distribution back. It picks add, sub and div, then stops.

It decides; it never judges success. The checks still decide that.

Traces are the next sensor



The loop below runs the agent. This loop runs you: read the traces, add a sensor, improve the actor.

```
$ loopctl report loop.jev.toml
calc-jev: 3 actions, 3 commits, 0 rejected
last outcome: unreachable (decider chose stop)

checks observed failing:
     4  gpu
     3  div
     2  sub
     1  add

every run writes .loop/traces.jsonl
```

The loop you have watched is the inner loop: it runs the agent.

Every round appends a trace: what was observed, decided, kept, reverted. report turns those into the list on the left: which checks keep failing and which decisions keep repeating.

That list tells you which sensor to add next, or where the agent is weak. Then you run again.

TAKEAWAYS

What to do on Monday

```
1  Put the loop around the agent, and keep the checks out of its reach.

2  Spend the effort on the comparator: code checks at every step,
   a learned judge only where code cannot decide.

3  Ship it today: loopctl run in CI, or one extension in your session.
   Same goal file either way.
```

Everything in this talk is in one repository, with the demos you just saw.

The two ideas worth keeping: the agent is the actuator, and the checks decide when the work is done.

If you remember one thing: never let the actuator touch the sensor.

TAKE-HOME

Run it yourself

```
git clone https://github.com/ucalyptus/loop-engineering
cd loop-engineering
./examples/churn/demo.sh                  # offline, ~5 s
./examples/churn/demo.sh loop.pi.toml     # your agent
./examples/churn/demo.sh loop.cheat.toml  # a cheater
./examples/calc-bend/demo.sh              # proofs (needs Bend)
pi -e integrations/loopctl.ts             # the loop in your session
```

Watch it converge. Why did quality take two rounds?

Use your own agent: pi, Claude Code or oh-my-pi.

Be the adversary: find a cheat the gates miss.

Add the sensor the loop lacks: recall, calibration, AUC per segment.

Needs Python 3.11 and git; no pip install. The repository is private: ask me for access.

Questions?

Loop engineering is control engineering with a new actuator.

Sayantan · ucalyptus.me

CONTACT

Loop engineering is control engineering with a new actuator.

Thanks!

Sayantan Das

linkedin.com/in/ucalyptus

github.com/ucalyptus

blog.ucalyptus.me

Talk to me after the session about setup, the churn task, your own agent, or access to the `loop-engineering` repo.

The blog post this talk is based on

APPENDIX

Further reading

- S. Das, *Loop Engineering Is Just K8s-Style Orchestration*, blog.ucalyptus.me
- N. Wiener, *Cybernetics: Or Control and Communication in the Animal and the Machine*, 1948
- W. R. Ashby, *An Introduction to Cybernetics*, 1956
- J. C. Maxwell, *On Governors*, Proceedings of the Royal Society, 1868
- controller-runtime (github.com/kubernetes-sigs/controller-runtime) and the kube-scheduler docs
- Apple container (github.com/apple/container) and pi-cvm (github.com/ucalyptus/pi-cvm)
- TypeSafe docs: docs.typesafe.ai

APPENDIX · FAILURE MODES

Four ways a loop fails

Oscillation

The agent undoes and redoes one change.

Fix: detect repeated states, limit steps.

Drift

Small errors add up over many steps.

Fix: compare to the spec, not the last step.

Goodhart

The loop meets the metric, not the goal.

Fix: mix checks, keep a slow judge on top.

Sensor blindness

The real error is not in the observed state.

Fix: widen what the loop sees first.

APPENDIX · THE KEY PROPERTY

Level-triggered, not edge-triggered

Edge-triggered

The system reacts to events. If it misses one event, its picture of the world stays wrong.

Level-triggered

The system reads the full current state each time. A missed event does not matter. The next loop fixes it.

Agents need the same property. Each step must read the world again. It must not trust its own memory of the world.

Frontier models are the actuator

Opus 5.5 and Fable 5.1 do the work. They plan, write code, call tools and draft text.

This is the part of the loop that needs generation. It is also the most expensive part per step.

A good actuator needs

- Reliable tool use
- Long context for state
- Good recovery after an error

The weak point


We often use the same model as the comparator too.

Three kinds of comparator

Kind	Examples	Speed and cost	Use it for
Deterministic	tests, schema checks, linters, totals that must match	milliseconds, almost free	everything that code can measure
Fast typed model	Jev from TypeSafe AI	70–500 ms (vendor claim)	fuzzy checks at every step
Frontier judge	Opus 5.5 or Fable 5.1 as a reviewer	seconds, highest cost	checkpoints and hard cases

Use them in this order. Go to the next one only when the previous one cannot measure the error.

Two loops at two speeds



The inner loop is fast and cheap, so it runs at every step. The outer loop is slow and accurate, so it runs only when needed.

A simple escalation policy

Signal	Action
A deterministic check fails	Act again, with the error output as input
Jev: goal_met, p ≥ 0.9	Run the slow judge one time, then stop
Jev: p from 0.6 to 0.9	Run the slow judge now
Jev: p < 0.6, or failure = "spec"	Stop and ask a human
Step, token or time limit reached	Stop and report the status

The thresholds are examples. Calibrate them on your own tasks before you trust them.

APPENDIX · RULE 1 OF 4

Declare the setpoint as data

If the goal is only prose, no sensor can measure the error.

From Kubernetes: declarative spec

In practice

- Write acceptance criteria as checks.
- Keep the spec in a file. The loop reads it at each step.
- Say what you want, not how to do it.

Build sensors before actuators

An agent cannot fix what it cannot observe.

From Kubernetes: observed status

In practice

- Give the loop fresh reads: diffs, test output, API state.
- Read the state again at each step.
- Log each observation, so you can replay a run.

Make every action idempotent

Loops retry. A retry must not double the damage.

From Kubernetes: idempotent actions

In practice

- Use upserts and keys, not blind creates.
- Plan first, then apply, with a dry run.
- Put actions you cannot undo behind a human gate.

Add a governor: limits and back-off

A loop without a stop condition is a cost leak.

From Kubernetes: back-off and requeue

In practice

- Set a maximum for steps, tokens and time.
- If the same diff comes back two times, stop.
- On external errors, wait longer before each retry.

APPENDIX · THE DECIDER

The scheduler picks, the kubelet runs

Kubernetes scheduler

- filter: which nodes *can* run this pod?
- score: which one is best?
- pick: one node gets the pod

Same split for agents

- a small, fast model **decides**
- a big, slow model **does**
- the checks **judge**

```
# [decider] asks Jev two typed questions per round
move   ∈ {act, ask_human, stop}
target ∈ failing checks
# asked 3 times; confidence =
#   lowest p of the agreed move
```

Guardrails: the decider cannot judge pass or fail, and cannot pick a passing check. Under 60% confidence, or if the three answers disagree, a human decides. If the decider fails, loopctl uses the built-in rule.

The reference stack

SETPOINT	Goal spec and acceptance checks, kept as data
SENSORS	Tool results, diffs, logs, live API state
COMPARATOR	Code checks first, then Jev, then a frontier judge
ACTUATOR	Opus 5.5 or Fable 5.1, with idempotent tools
GOVERNOR	Budgets, back-off, repeat detection, human gates