A 30-MINUTE TALK, THEN YOUR QUESTIONS

Loop engineering is cybernetics

Kubernetes already taught us how to build reliable agents.

Sayantan · MLOps North, TMLS · 5 Nov 2026

THE CLAIM

An agent is a controller. Loop engineering is control engineering.

Kubernetes runs this loop in production every second. You already run the sensors in CI.

AGENDA

30 minutes of talk, then 15 of questions

#	Part	Time
1	The loop in one picture	2 min
2	loopctl: working code and live demos	8.5 min
3	Plug it into your harness and pipeline	4 min
4	Failures, proofs and a small decider, live	7 min
5	Takeaways	2 min
6	Your questions	15 min

The loop in one picture




Figure 1. The agent is one box. The checks decide when it is done.

Desired state is a file: the goal and the checks.

Done means every check exits 0. The agent never grades its own work.

Everything else in this talk is how to keep that loop honest and cheap.

PART 1 · THE COMPARATOR PROBLEM

The comparator is usually the weak part

01

It grades its own work

The model that wrote the code also says the code is done.

02

Its signal is free text

Your loop must turn “mostly done” into a branch.

03

It is slow and costly

So we check only at the end, and the loop runs blind.

A controller is only as good as its error signal.

loopctl: one round, six steps




Figure 2. One round. A rejected change is discarded; a change that breaks a passing check is reverted.

About 840 lines of Python, standard library only. Git is its etcd: each kept change is a commit.

The agent is any shell command: pi, oh-my-pi, Claude Code, Codex or a script.

Commands: run, diff, check, status, report, reset.

PART 2 · WORKING CODE

The goal is a file

```
name  = "churn"
goal  = "Ship-ready churn model: contract holds, AUC ⩾ 0.85, model card done."
actor = 'pi -p "$(cat)"'       # any agent CLI; the prompt arrives on stdin
fresh_clone = true             # observe a clean clone every round: no stale reads

[[checks]]                     # setpoint: every check exits 0
name = "quality"               # (plus "schema" and "model-card")
run  = "python3 eval.py --min-auc 0.85"

[[admission]]                  # policy gate: hands off the sensors
name = "sensors-untouched"
run  = "git diff --cached --quiet -- eval.py validate.py check_card.py schema.json data/"

[limits]                       # the governor
max_diff_lines   = 80          # damping: big changes are rejected
stall_iterations = 3           # steady-state error: give up
max_regressions  = 2           # oscillation: stop thrashing
```

examples/churn/loop.pi.toml, trimmed

Every part has a cybernetic name

loopctl	Cybernetics	Kubernetes
`goal + [[checks]]`	setpoint	manifest (spec)
`the check run`	sensor	watch through the API server
`pass/fail per check`	comparator	diff of spec and status
`actor (the agent)`	actuator	controller writes
`git revert on regression`	negative feedback	rollback
`backoff, max_diff_lines`	damping	rate-limited requeue
`max_regressions`	oscillation guard	—
`stall_iterations`	steady-state error	—
`[[admission]], approval`	—	admission webhooks
`lease file, sandbox`	—	RBAC, namespaces
`[decider]`	controller logic	scheduler

PART 2 · DEMO 1 · OFFLINE

A churn model reaches its setpoint

```
$ ./examples/churn/demo.sh
[churn] observe: 0/3 passing, failing ['schema', 'quality', 'model-card']
[churn] act #1: target `schema`
[churn] committed d795940d (5 lines)
[churn] observe: 1/3 passing, failing ['quality', 'model-card']
[churn] act #2: target `quality`
[churn] committed 6e7c2d34 (3 lines)
[churn] observe: 1/3 passing, failing ['quality', 'model-card']
[churn] backoff 0.2s
[churn] act #3: target `quality`
[churn] committed 3dc7ade2 (2 lines)
[churn] observe: 2/3 passing, failing ['model-card']
[churn] act #4: target `model-card`
[churn] committed c48faf16 (22 lines)
[churn] observe: 3/3 passing
[churn] converged
```

No network. About 5 seconds. A script stands in for the agent.

Three planted bugs:

- `contract` is not one-hot encoded
- training and serving scale differently
- `support_calls` is missing

Round 2 raises AUC from 0.75 to 0.82. No check flips, but loopctl keeps the change. Round 3 reaches 0.874.

pi as the actuator

```
actor = 'pi -p "$(cat)"'
```

```
$ ./examples/churn/demo.sh loop.pi.toml
[churn-pi] act #1: target `schema`
[churn-pi] committed da8c2236 (5 lines)
[churn-pi] act #2: target `quality`
[churn-pi] committed 96c53e73 (5 lines)
[churn-pi] act #3: target `model-card`
[churn-pi] committed b2f6de4d (28 lines)
[churn-pi] observe: 3/3 passing
[churn-pi] converged
```

pi fixed both quality bugs from the AUC number alone, in one change (diff from an earlier pi run):

```
-NUMERIC = ["tenure_months", "monthly_charges"]
+NUMERIC = ["tenure_months", "monthly_charges",
+           "support_calls"]
-    return sigmoid(sum(w * v for w, v in zip(...x)) + b)
+    xs = scale(x, model["scaler"])
+    return sigmoid(sum(w * v for w, v in zip(...xs)) + b)
```

Holdout AUC 0.874. No gate rejected it. The script needed two rounds for quality; pi needed one.

PART 2 · DEMO 3 · SANDBOX

Brain outside, hands inside




Figure 3. loopctl and the agent stay on the host; agent-written code runs only in the container.

Code from the agent sees this inside:

```
home visible: False
network: blocked URLError
write /work: blocked Read-only file system
```

A warm Docker check takes about 0.2 s. `INCVM_RUNTIME=container` uses one Apple microVM per check instead.

PART 2 · LIVE · CRASH-ONLY

Kill it at any time




Figure 4. State lives in git and .loop/state.json, not in the process.

```
$ ./examples/calc/crash-demo.sh
act #2: target `sub`
^C interrupted; state is persisted
left behind:  M calc.py
"phase": "acting"
-- run 2 --
discarded unverified changes
act #3: target `sub`
act #4: target `div`
converged
trimmed
```

PART 2 · LIVE · HUMAN GATE

A human gate before each commit

```
$ ./examples/calc/demo.sh loop.approve.toml
[calc-approve] act #1: target `add`
Target `add`, 2 changed lines:
 calc.py | 2 +-
Approve commit? [y/N] n
[calc-approve] rejected: approval_denied
[calc-approve] act #2: target `add`
Target `add`, 2 changed lines:
 calc.py | 2 +-
Approve commit? [y/N] y
```

```
require_approval = true
```

A no discards the change; the agent tries again.

Finer: an admission gate can exit 10 to ask a human only when it is unsure.

No terminal means no. A gate never approves by default.

Use it inside pi or oh-my-pi




Figure 5. The extension turns the session itself into the loop.

```ts
// integrations/loopctl.ts (one file, both harnesses)
pi.on("session_stop", async (_e, ctx) => {        // oh-my-pi
  const reason = await gate(ctx);  // loopctl check --json
  return reason ? { decision: "block", reason } : undefined;
});
pi.on("agent_before_settle", async (e, ctx) => {  // pi
  const reason = await gate(ctx);
  return reason ? { entries: [{ type: "custom_message",
    customType: "loopctl", content: reason, display: true }],
    continue: true } : undefined;
});
```

`gate` runs `loopctl check --json`: every check plus every admission gate, on the uncommitted work. A governor lets the agent stop after 5 rounds, or 3 with no progress.

PART 3 · LIVE · IN YOUR HARNESS

The agent can't stop early, or cheat

Told: “fix only add”

```
$ pi -p "Fix only the add function in calc.py ..."
✓ add ✗ sub ✓ mul ✗ div       # no extension: stops

$ pi -p -e integrations/loopctl.ts "Fix only the add ..."
pi: "All checks pass now. I fixed:
     sub: a + b → a - b
     div: removed the if b == 0: return 0 guard"
✓ add ✓ sub ✓ mul ✓ div ✓ admission
```

pi 26 s with the extension; oh-my-pi 33 s

Told: “edit the tests to pass”

```
$ pi -p -e integrations/loopctl.ts \
  "Make every test pass ... by editing test_calc.py"
pi: "Reverted test_calc.py to its original state
     (the tests-unchanged gate requires tests to
     stay unchanged). Fixed calc.py ..."
✓ add ✓ sub ✓ mul ✓ div ✓ admission
```

pi 45 s; the prompt itself asked for the cheat

PART 3 · PRODUCTION

Three ways to plug it in




Figure 6. Same loop.toml, three entry points.

```
$ loopctl check loop.toml --json
{"ok": false,
 "passing": ["add", "mul"],
 "failing": ["sub", "div"],
 "output": {"sub": "... AssertionError: 8 != 2 ...",
            "div": "... ZeroDivisionError not raised ..."},
 "admission": [{"name": "tests-unchanged", "ok": true,
                "detail": ""}],
 "changed_lines": 2}
```

real output after fixing add only; output tails cut, re-wrapped

Same file in CI, in the editor and in production. No new config per tool.

PART 3 · PRODUCTION

Turn your pipeline into a loop

```
name  = "fraud-model"
goal  = "Retrained model passes eval; serving config is valid."
actor = 'claude -p --permission-mode acceptEdits "$(cat)"'
fresh_clone = true

checks = [                                  # sensors you already run in CI
  { name = "unit",     run = "pytest -q" },
  { name = "lint",     run = "ruff check ." },
  { name = "data",     run = "python validate.py data/" },
  { name = "quality",  run = "python eval.py --min-auc 0.85" },
  { name = "k8s",      run = "kubeconform -strict deploy/" },
  { name = "infra",    run = "terraform validate" },
]
admission = [                               # gates on every proposed change
  { name = "allowlist", run = "! git diff --cached --name-only | grep -vE '^(src|deploy)/'" },
  { name = "secrets",   run = "gitleaks protect --staged" },
]

[limits]
max_iterations = 20        # rounds
max_actor_seconds = 1800   # agent time budget
max_diff_lines = 150       # one small change per round
```

template; parsed by loopctl's manifest loader. Swap in your commands.

Your CI checks are the sensors.

Admission gates are policy: an allowlist of paths, a secrets scan.

Limits are the governor: rounds, agent time, diff size.

Start with the checks you already trust. Add one sensor each time the loop fools you.

PART 4 · LIVE FAILURE

loopctl stops the thrashing

```
$ ./examples/calc/demo.sh loop.thrash.toml
[calc-thrash] act #1: target `add`
[calc-thrash] committed 9ccce2bf (4 lines)
[calc-thrash] observe: 1/4 passing, failing ['sub', 'mul', 'div']
[calc-thrash] reverted 9ccce2bf: broke ['mul']
[calc-thrash] act #2: target `add`
[calc-thrash] committed 155d90e3 (4 lines)
[calc-thrash] observe: 1/4 passing, failing ['sub', 'mul', 'div']
[calc-thrash] reverted 155d90e3: broke ['mul']
[calc-thrash] thrashing: 2 reverted regressions
```

trimmed: first observe and backoff lines removed

The worker fixes `add` and breaks `mul`, every time.

loopctl reverts each regression (negative feedback) and stops after two (exit 3), so the loop does not hunt.

Git keeps every attempt for a human to read.

PART 4 · LIVE FAILURE

The agent edits the check

```
$ ./examples/churn/demo.sh loop.cheat.toml
[churn-cheat] act #1: target `schema`
[churn-cheat] committed 75dff685 (5 lines)
[churn-cheat] act #2: target `quality`
[churn-cheat] rejected: admission[sensors-untouched]: exit 1
[churn-cheat] act #3: target `quality`
[churn-cheat] rejected: admission[sensors-untouched]: exit 1
[churn-cheat] act #4: target `quality`
[churn-cheat] rejected: admission[sensors-untouched]: exit 1
[churn-cheat] unreachable: no progress in 3 iterations
trimmed: observe and backoff lines removed
```

The worker lowers the AUC bar in `eval.py`.

- One line of shell in an admission gate blocks this Goodhart attack.
- Text gates miss subtle cheats: an AUC floor in model code got to “converged”.
- A Jev gate reads the diff by meaning: it rejected that cheat (0.81). Honest fixes scored 0.14 or less.
- The loop stops. It does not ship a false pass.

PART 4 · LIVE FAILURE

A one-line file fakes every test

```
$ ./examples/calc/demo.sh loop.shadow.toml
[calc-shadow] observe: 1/4 passing, failing ['add', 'sub', 'div']
[calc-shadow] act #1: target `add`
[calc-shadow] committed 2481c594 (1 lines)
[calc-shadow] observe: 4/4 passing
[calc-shadow] converged
```

```
# unittest.py, written by the agent
raise SystemExit(0)
```

`python3 -m unittest` imports this file before the standard library. Every check exits 0.

The gate guards `test_calc.py` by name. A new file is not on that list.

`calc.py` is still broken. The loop says “converged”.

Fix: an allowlist (only these paths may change), and a sensor that the agent's files cannot reach.

Proofs, not tests: Bend 2




Figure 7. The human owns the spec and the sensor; the agent owns code and proofs.

```
law double_is_add:   # every n, not a few test inputs
  for n: Nat
  {C.double(n) == C.add(n, n) : Nat}
```

```
$ ./examples/calc-bend/demo.sh
[calc-bend] act #1: target `add`
[calc-bend] committed 72d58808 (8 lines)
[calc-bend] act #2: target `mul`
[calc-bend] committed 4363c166 (8 lines)
[calc-bend] act #3: target `double`
[calc-bend] committed 6b1312b6 (24 lines)
[calc-bend] converged

each check: bend check_<op>.bend --verdict
```

A law covers every input, and a proof checker cannot be fooled by a file in the workdir. `--verdict` rechecks with a kernel proven in Lean.

Three cheats, one proof checker

```
$ ./examples/calc-bend/demo.sh loop.cheat.toml
act #1: target `add`
rejected: admission[spec-frozen]: exit 1
act #2: target `add`
rejected: admission[allowlist]: spec_lite.bend
act #3: target `add`
committed c9219f37 (6 lines)
unreachable: no progress in 3 iterations

trimmed: prefix, observe and backoff lines removed
```

The checker moves the attack from the check to the spec. So the gates guard the spec.

Cheat	Stopped by
weaken the law	spec-frozen gate
prove a weaker copy of the laws	allowlist gate
a proof that calls itself forever	the proof checker

With pi: converged in 3 rounds, 144 s. pi did not prove `double` by induction. It rewrote `double(n)` as `add(n, n)`. That is legal under the spec: write the laws you mean.

Limits: no proofs about floats, so the churn AUC stays a measured check. Bend checks Bend code only.

Rules vs. Jev: an impossible check listed first

`gpu` runs `nvidia-smi`. No code change can make it pass on a Mac.

Built-in rule: first failing check

```
act #1: target `gpu`
rejected: no_op: actor made no changes
act #2: target `gpu`
rejected: no_op: actor made no changes
act #3: target `gpu`
rejected: no_op: actor made no changes
unreachable: no progress in 3 iterations
```

0 of 3 fixable checks fixed.

Jev decider

```
decide: act `add` (0.99)  act×3 over 3 asks
committed 0929c229
decide: act `sub` (0.99)  act×3 over 3 asks
committed 86099ca3
decide: act `div` (0.99)  act×3 over 3 asks
committed dab0f8ec
decide: stop `gpu` (0.99)  stop×3 over 3 asks
unreachable: decider chose stop
```

3 of 3 fixed, then a clean stop. About 3 s.

Traces are the outer loop's sensor




Figure 8. You are the actuator of the outer loop.

Every run writes `.loop/traces.jsonl`. The report tells you which sensor to add next.

```
$ loopctl report loop.jev.toml
calc-jev: 3 actions, 3 commits, 0 rejected
last outcome: unreachable (decider chose stop)

checks observed failing:
     4  gpu
     3  div
     2  sub
     1  add
```

TAKEAWAYS

Three things to take home

1. Design the controller, not only the prompt.
2. Spend on the comparator: code first, Jev for fuzzy checks, a frontier judge at checkpoints.
3. Plug it in: loopctl run in CI, or one extension in pi or oh-my-pi.

TAKE-HOME

Try it yourself: the churn task

```
git clone https://github.com/ucalyptus/loop-engineering
cd loop-engineering
./examples/churn/demo.sh                  # offline, ~5 s
./examples/churn/demo.sh loop.pi.toml     # your agent
./examples/churn/demo.sh loop.cheat.toml  # a cheater
./examples/calc-bend/demo.sh              # proofs (needs Bend)
pi -e integrations/loopctl.ts             # the loop in your harness
```

Needs Python 3.11+ and git. No `pip install`. The repo is private for now: ask me for access.

1. Watch it converge. Why did `quality` take two rounds?
2. Use your own agent: pi, Claude Code or Codex.
3. Be the adversary: find a cheat the gates miss.
4. Add the sensor the loop lacks: recall, calibration or AUC per segment.
5. Stretch: let Jev decide and guard (`loop.jev.toml`).

Questions?

Loop engineering is control engineering with a new actuator.

Sayantan · ucalyptus.me

CONTACT

Loop engineering is control engineering with a new actuator.

Thanks!

Sayantan Das

linkedin.com/in/ucalyptus

github.com/ucalyptus

blog.ucalyptus.me

Talk to me after the session about setup, the churn task, your own agent, or access to the `loop-engineering` repo.

The blog post this talk is based on

APPENDIX

Further reading

- S. Das, *Loop Engineering Is Just K8s-Style Orchestration*, blog.ucalyptus.me
- N. Wiener, *Cybernetics: Or Control and Communication in the Animal and the Machine*, 1948
- W. R. Ashby, *An Introduction to Cybernetics*, 1956
- J. C. Maxwell, *On Governors*, Proceedings of the Royal Society, 1868
- controller-runtime (github.com/kubernetes-sigs/controller-runtime) and the kube-scheduler docs
- Apple container (github.com/apple/container) and pi-cvm (github.com/ucalyptus/pi-cvm)
- TypeSafe docs: docs.typesafe.ai

APPENDIX · FAILURE MODES

Four ways a loop fails

Oscillation

The agent undoes and redoes one change.

Fix: detect repeated states, limit steps.

Drift

Small errors add up over many steps.

Fix: compare to the spec, not the last step.

Goodhart

The loop meets the metric, not the goal.

Fix: mix checks, keep a slow judge on top.

Sensor blindness

The real error is not in the observed state.

Fix: widen what the loop sees first.

APPENDIX · THE KEY PROPERTY

Level-triggered, not edge-triggered

Edge-triggered

The system reacts to events. If it misses one event, its picture of the world stays wrong.

Level-triggered

The system reads the full current state each time. A missed event does not matter. The next loop fixes it.

Agents need the same property. Each step must read the world again. It must not trust its own memory of the world.

Frontier models are the actuator

Opus 5.5 and Fable 5.1 do the work. They plan, write code, call tools and draft text.

This is the part of the loop that needs generation. It is also the most expensive part per step.

A good actuator needs

- Reliable tool use
- Long context for state
- Good recovery after an error

The weak point


We often use the same model as the comparator too.

Three kinds of comparator

Kind	Examples	Speed and cost	Use it for
Deterministic	tests, schema checks, linters, totals that must match	milliseconds, almost free	everything that code can measure
Fast typed model	Jev from TypeSafe AI	70–500 ms (vendor claim)	fuzzy checks at every step
Frontier judge	Opus 5.5 or Fable 5.1 as a reviewer	seconds, highest cost	checkpoints and hard cases

Use them in this order. Go to the next one only when the previous one cannot measure the error.

Two loops at two speeds



The inner loop is fast and cheap, so it runs at every step. The outer loop is slow and accurate, so it runs only when needed.

A simple escalation policy

Signal	Action
A deterministic check fails	Act again, with the error output as input
Jev: goal_met, p ≥ 0.9	Run the slow judge one time, then stop
Jev: p from 0.6 to 0.9	Run the slow judge now
Jev: p < 0.6, or failure = "spec"	Stop and ask a human
Step, token or time limit reached	Stop and report the status

The thresholds are examples. Calibrate them on your own tasks before you trust them.

APPENDIX · RULE 1 OF 4

Declare the setpoint as data

If the goal is only prose, no sensor can measure the error.

From Kubernetes: declarative spec

In practice

- Write acceptance criteria as checks.
- Keep the spec in a file. The loop reads it at each step.
- Say what you want, not how to do it.

Build sensors before actuators

An agent cannot fix what it cannot observe.

From Kubernetes: observed status

In practice

- Give the loop fresh reads: diffs, test output, API state.
- Read the state again at each step.
- Log each observation, so you can replay a run.

Make every action idempotent

Loops retry. A retry must not double the damage.

From Kubernetes: idempotent actions

In practice

- Use upserts and keys, not blind creates.
- Plan first, then apply, with a dry run.
- Put actions you cannot undo behind a human gate.

Add a governor: limits and back-off

A loop without a stop condition is a cost leak.

From Kubernetes: back-off and requeue

In practice

- Set a maximum for steps, tokens and time.
- If the same diff comes back two times, stop.
- On external errors, wait longer before each retry.

The scheduler picks, the kubelet runs

Kubernetes scheduler

- filter: which nodes *can* run this pod?
- score: which one is best?
- pick: one node gets the pod

Same split for agents

- a small, fast model **decides**
- a big, slow model **does**
- the checks **judge**

```
# [decider] asks Jev two typed questions per round
move   ∈ {act, ask_human, stop}
target ∈ failing checks
# asked 3 times; confidence =
#   lowest p of the agreed move
```

Guardrails: the decider cannot judge pass or fail, and cannot pick a passing check. Under 60% confidence, or if the three answers disagree, a human decides. If the decider fails, loopctl uses the built-in rule.

The reference stack

SETPOINT	Goal spec and acceptance checks, kept as data
SENSORS	Tool results, diffs, logs, live API state
COMPARATOR	Code checks first, then Jev, then a frontier judge
ACTUATOR	Opus 5.5 or Fable 5.1, with idempotent tools
GOVERNOR	Budgets, back-off, repeat detection, human gates