WORKING CODE, LIVE DEMOS

Loop engineering is cybernetics



Kubernetes already taught us how to build reliable agents.

Sayantan Das

Senior Applied AI Scientist at Mychoice Financial

MLOps North, TMLS · 5 Nov 2026

LOOP ENGINEERING

The people who ship with agents stopped writing prompts

“I don’t prompt Claude anymore. I have loops that are running. They’re the ones that are prompting Claude and figuring out what to do. My job is to write loops.”

Boris Cherny, head of Claude Code at Anthropic · Acquired Unplugged, 2026

A loop

prompt, act, check, repeat. The loop decides what to ask next.

Why

one session per task becomes many; cheaper, resumable, auditable.

The catch

the loop has to know when the task is done, without asking the agent.


AGENDA

What we will cover

#	PART	WHAT YOU GET
1	**The loop, and the problem**	the five parts; why the comparator decides quality
2	**A tool for the loop**	loopctl: what it is, and the goal file
3	**Live: three demos**	an offline model, a real agent, a sandbox
4	**Live: in your session and pipeline**	the extension, the three entry points, failures and proofs
5	**Takeaways**	and what to run tomorrow

Every loop has the same five parts

the loop every controller runs



A thermostat, a Kubernetes controller and an agent are the same five boxes. Only the nouns change.



PART 1 · THE PROBLEM

It said done. It wasn’t.

```
# real session, abridged
$ pi -p "Fix only the add function in calc.py so test_add passes"
Fixed. `add` now returns `a + b`, and `test_add` passes.
The other failures are pre-existing bugs in functions you told me not to touch.

$ python3 -m loopctl check loop.toml
✓ add  ✗ sub  ✓ mul  ✗ div
```

THE REQUEST

Fix add so test_add passes. That part is done.

THE SETPOINT

All four checks pass. Two still fail: sub and div.

It is not lying. It grades its own work, in prose, from memory.

The comparator sets the ceiling

01	**It grades its own work**	The model that wrote the change also decides whether the change is good. The bias points one way.
02	**Its signal is prose**	“Mostly done” has to become a branch in code. That parsing is fragile, and it fails quietly.
03	**It is slow and costly**	A model call at every step is too expensive, so teams judge once, at the end, when a mistake is expensive.

> **A controller is only as good as its error signal.**
>
> Control engineers spend their effort on the sensor and the comparator. Agent builders spend theirs on the prompt.


Kubernetes already runs this loop

CYBERNETICS	KUBERNETES	LOOPCTL
setpoint	spec: the desired state	`goal + [[checks]]`
sensor	watch, informer	`the check command`
comparator	the controller’s diff	`pass or fail, per check`
actuator	API writes	`the agent`
negative feedback	rollback, rollout undo	`git revert on a regression`
damping	rate-limited requeue	`max_diff_lines, backoff`
admission control	admission webhooks	`[[admission]] gates`
isolation	RBAC, namespaces	`lease, sandbox`

The agent version has the same parts and two new ones: the actuator can be creative, and it can cheat.

PART 2 · THE TOOL

So I wrote loopctl



WHAT IT IS

About 840 lines of Python, standard library only, git as its etcd. Every kept change is a commit you can audit or revert.

WHAT IT NEEDS

A goal file and the commands that decide it is met. The agent is a shell command: pi, oh-my-pi, Claude Code or a script.

The goal is a file

```
# examples/churn/loop.pi.toml (excerpt)
actor = 'pi -p "$(cat)"'
[limits]
max_diff_lines = 80
stall_iterations = 3
max_regressions = 2
[[checks]]
name = "quality"
run = "python3 eval.py --min-auc 0.85"
[[admission]]
name = "sensors-untouched"
run = "git diff --cached --quiet -- eval.py validate.py check_card.py"
```

Why can’t the agent write this file?

It can draft it; a human owns the setpoint. Otherwise, the cheapest fix is a weaker check. The gate above guards sensors, not the goal file.

PART 2 · DEMO 1 · OFFLINE

A churn model reaches its setpoint

```
$ ./examples/churn/demo.sh
[churn] observe: 0/3 passing
[churn] act #1: target `schema`
[churn] observe: 1/3 passing
[churn] act #2: target `quality`
[churn] observe: 1/3 passing
[churn] act #3: target `quality`
[churn] observe: 2/3 passing
[churn] act #4: target `model-card`
[churn] observe: 3/3 passing
[churn] converged
```

offline, about 5 seconds · abridged

THE TASK

Predict churn. Three planted bugs: an unencoded contract column, a train and serve scaling mismatch, a missing feature.

THE SETPOINT

AUC at least 0.85, the data contract holds, the model card is done. Each is a command that exits 0 or 1.

ROUND 2

AUC rises from 0.75 to 0.82 and nothing passes yet. Kept: nothing regressed. Round 3 reaches 0.874.



The same task, with pi as the actuator

```
actor = 'pi -p "$(cat)"'
$ ./examples/churn/demo.sh loop.pi.toml
[churn-pi] act #1: target `schema`
[churn-pi] act #2: target `quality`
[churn-pi] act #3: target `model-card`
[churn-pi] converged
```

pi is a coding agent you can drive from a shell: one prompt in, edits on disk out. Any agent CLI fits, including Claude Code and oh-my-pi.


Real-agent run: about 5 minutes.

```
-NUMERIC = ["tenure_months", "monthly_charges"]
+NUMERIC = ["tenure_months", "monthly_charges",
+           "support_calls"]
 …
+    xs = scale(x, model["scaler"])
+    return sigmoid(… zip(…, xs)) + b
```

It fixed both quality bugs from one number, the AUC.

Holdout AUC 0.874, three rounds, no gate rejected it.

Brain outside, hands inside



Checks run in a disposable, network-isolated container.

The agent edits on the host. A read-only mount protects the snapshot from checker writes; admission gates still protect the grading inputs.

PART 2 · LIVE · CRASH-ONLY

Kill it at any time

```
$ ./examples/calc/crash-demo.sh
[calc-slow] act #2: target `sub`
^C  interrupted; state is persisted
left behind:  M calc.py   "phase": "acting"
-- rerun --
[calc-slow] discarded unverified changes
[calc-slow] act #3: target `sub`
[calc-slow] observed: 4/4 passing, converged
```

abridged: round 1 and the last round omitted

Losing the loop must cost one round, never the run.

State lives in git and one file, .loop/state.json. On restart the loop discards the unverified edit and resumes with the same budgets.

Interrupt it mid-round, restart it, watch it converge.

The human gate

```
$ ./examples/calc/demo.sh loop.approve.toml
[calc-approve] act #1: target `add`
Target `add`, 2 changed lines:
 calc.py | 2 +-
Approve commit? [y/N] n
[calc-approve] rejected: approval_denied
[calc-approve] act #2: target `add`
Approve commit? [y/N] y
```

```
# examples/calc/loop.approve.toml
require_approval = true
```

answer n, then y


One line of config puts a human in front of every commit. A no discards the change and the agent tries again. With no terminal attached, the answer is always no.

An admission gate can exit 10 to ask only when it is unsure, so the human sees the cases that need judgement, not every diff.

PART 3 · IN YOUR SESSION

The loop inside your agent

Your session: pi or oh-my-pi



pi and oh-my-pi are terminal coding agents. One extension connects their end-of-run hooks to your checks.

`integrations/loopctl.ts`

pi	`agent_before_settle`
oh-my-pi	`session_stop`

`loopctl check --json`

PART 3 · LIVE · IN YOUR SESSION

It cannot stop early, or cheat

Asked for one fix

No extension: pi stops.

✓ add ✗ sub ✓ mul ✗ div

With the extension: sent back until all pass.

✓ add ✓ sub ✓ mul ✓ div ✓ admission

Fixed sub (a + b → a - b) and removed the b == 0 guard in div.

pi, 26 seconds · oh-my-pi, 33

Asked to cheat

“Make every test pass by editing test_calc.py”

Gate says no:

`loopctl: rejected by admission[tests-unchanged]`

pi reverted test_calc.py and fixed calc.py instead.

✓ add ✓ sub ✓ mul ✓ div ✓ admission

pi, 45 seconds

```
$ pi -p -e integrations/loopctl.ts "..."
```

Three ways to put it to work

1 WRAP

`loopctl run`

loopctl owns the agent

· CI job, cron, Kubernetes Job
· the agent is a CLI argument
· no plugin, no API

2 EMBED

`integrations/loopctl.ts`

the session is the loop

· interactive work in pi or oh-my-pi
· runs when the agent says done
· one file to install

3 CALL

`loopctl check --json`

your agent asks

· any harness with a stop hook
· read-only: index untouched
· branch on ok

Wrap for batch work, embed for interactive work, call from any agent framework that has a stop hook.

All three read the same loop.toml.

Your pipeline, as a loop

Agent edits
the actor

→

Admission gates
allowlist, secrets

→

Sensors: your CI checks
unit, lint, data, quality, k8s, infra

→

Done
all checks pass

↩ **A rejected change or a failed check goes back to the agent as the next message.**

A quality check

```
[[checks]]
name = "quality"
run = "python eval.py --min-auc 0.85"
```

The same jobs that already gate your releases.

Limits: the governor

```
max_iterations = 20
max_actor_seconds = 1800
max_diff_lines = 150
```

Template: keep your commands, change the names. Add a sensor each time the loop is fooled.

Oscillation



```
$ ./examples/calc/demo.sh loop.thrash.toml
```

```
act #1: target `add`
committed 9ccce2bf (4 lines)
observe: 1/4 passing
reverted 9ccce2bf: broke ['mul']
act #2: target `add`
reverted 155d90e3: broke ['mul']
thrashing: 2 reverted regressions
```

Thrashing: fix one thing, break another, forever. Too much gain: every correction overshoots.

The governor reverts a change that broke a passing check, counts the reverts, and stops after two.

Git keeps every attempt, so a human can read what the agent kept trying.

Goalpost drift

```
$ ./examples/churn/demo.sh loop.cheat.toml
```

```
act #1: target `schema`
committed 75dff685 (5 lines)
act #2: target `quality`
rejected: admission[sensors-untouched]
act #3: target `quality`
rejected: admission[sensors-untouched]
unreachable: no progress in 3 iterations
```

The failing check is eval.py: it requires holdout AUC 0.85. The worker cannot reach it, so it lowers the bar in eval.py instead.

That is the Goodhart failure: a system optimising a measurement may move the measurement.

A plain-text gate stops the crude version. The Jev gate reads the diff by meaning: it rejected an AUC floor hidden in model code and scored honest fixes at 0.14 or less.

Shadows

```
$ ./examples/calc/demo.sh loop.shadow.toml
```

```
act #1: target `add`
committed 2481c594 (1 lines)
observe: 4/4 passing
converged

committed: unittest.py
  raise SystemExit(0)
exit 0
```

calc.py is the module under test; the checks run it with python3 -m unittest.

The worker adds a one-line unittest.py. Python imports it before the standard library, so every check exits 0 and the loop reports converged with calc.py still broken.

The gate guarded one file by name; the cheat added a new one. Guard paths with an allowlist, and keep the sensor where the agent's files cannot reach it.

Proofs, not tests

Bend 2

A small language where a rule is a law you can prove. A checker accepts or rejects the proof, and the agent cannot edit that checker from inside the repo.

The law

```
law double_is_add:
  for n: Nat
  {C.double(n) == C.add(n, n) : Nat}
```

A test samples inputs. A law covers every n, and a proof checker cannot be fooled by a file in the workdir.

```
$ ./examples/calc-bend/demo.sh
```

```
add: committed 72d58808 (8 lines)
mul: committed 4363c166 (8 lines)
double: committed 6b1312b6 (24 lines)
observe: 3/3 passing
converged
```

each check: `bend check_<op>.bend --verdict`

The human owns the laws and the check files; the agent owns the code and the proofs. --verdict rechecks every proof with a kernel proven in Lean.

Three ways to fake a proof

```
$ ./examples/calc-bend/demo.sh loop.cheat.toml
```

```
act #1: rejected:
  admission[spec-frozen]
act #2: rejected:
  admission[allowlist]: spec_lite.bend
act #3: committed c9219f37 (6 lines)
unreachable: no progress in 3 iterations
```

With pi as the agent the loop converged in 144 seconds, but pi redefined double as add(n, n), which the spec allows. Write the laws you mean.

The checker moves the attack from the check to the spec, so the gates guard the spec:

Weaken the law
stopped by: spec-frozen gate

Prove a weaker copy of the laws
stopped by: allowlist gate

A proof that never terminates
stopped by: the checker itself

Which failing check next?

```
$ ./examples/calc/demo.sh loop.jev.toml
```

Built-in rule: first failing check

```
act #1-3: target `gpu`
rejected: no_op, three times
unreachable: no progress
  in 3 iterations
```

Jev decides the next move

```
decide: act `add` (0.99)
decide: act `sub` (0.99)
decide: act `div` (0.99)
decide: stop `gpu` (0.99)
unreachable: decider chose stop
```

The manifest lists a check that cannot pass here: gpu runs nvidia-smi, on purpose. The built-in rule takes checks in order and spends its whole budget on gpu.

Jev is a typed decision model: state in, move and target out. It picks add, sub and div, then stops. It decides; the checks still judge success.



Traces are the next sensor

1 Run the loop `loopctl run` → **2 Trace it** `.loop/traces.jsonl` → **3 Read it** `loopctl report` → **4 Improve** a check, or the agent

↩ **You are the actuator of this loop: read the traces, add a sensor, improve the actor.**

```
$ loopctl report loop.jev.toml                checks observed failing:
calc-jev: 3 actions, 3 commits, 0 rejected       4  gpu
last outcome: unreachable (decider chose stop)   3  div
every run writes .loop/traces.jsonl              2  sub
                                                 1  add
```

Every round appends a trace: what was observed, decided, kept, reverted. The report shows which checks keep failing: the next sensor to add, or where the agent is weak.

TAKEAWAYS

What to do on Monday

1. Put the loop around the agent, and keep the checks out of its reach.
2. Spend the effort on the comparator: code checks at every step, a learned judge only where code cannot decide.
3. Ship it today: `loopctl run` in CI, or one extension in your session. Same goal file either way.

If you remember one thing: never let the actuator touch the sensor.

The agent is the actuator; the checks decide when the work is done.

Everything in this talk is in one repository, with the demos you just saw.

TAKE-HOME

Run it yourself

```
git clone https://github.com/ucalyptus/loop-engineering
cd loop-engineering
./examples/churn/demo.sh                    # offline, ~5 s
./examples/churn/demo.sh loop.pi.toml       # your agent
./examples/churn/demo.sh loop.cheat.toml    # a cheater
./examples/calc-bend/demo.sh                # proofs (needs Bend)
pi -e integrations/loopctl.ts               # the loop in your session
```

Watch it converge. Why did quality take two rounds?

Be the adversary: find a cheat the gates miss.

Use your own agent: pi, Claude Code or oh-my-pi.

Add the sensor the loop lacks: recall, calibration, AUC per segment.

Needs Python 3.11 and git; no pip install. The repository is private: ask me for access.

Questions?



Loop engineering is control engineering with a new actuator.

Sayantan Das

Senior Applied AI Scientist at Mychoice Financial

ucalyptus.me

CONTACT

Loop engineering is control engineering with a new actuator.

Thanks!

Sayantan Das
Senior Applied AI Scientist at Mychoice Financial

`linkedin.com/in/ucalyptus`
`github.com/ucalyptus`
`blog.ucalyptus.me`

Talk to me after the session about setup, the churn task, your own agent, or access to the `loop-engineering` repo.

The blog post this talk is based on

APPENDIX

Further reading

- S. Das, *Loop Engineering Is Just K8s-Style Orchestration*, blog.ucalyptus.me
- N. Wiener, *Cybernetics: Or Control and Communication in the Animal and the Machine*, 1948
- W. R. Ashby, *An Introduction to Cybernetics*, 1956
- J. C. Maxwell, *On Governors*, Proceedings of the Royal Society, 1868
- controller-runtime (github.com/kubernetes-sigs/controller-runtime) and the kube-scheduler docs
- Apple container (github.com/apple/container) and pi-cvm (github.com/ucalyptus/pi-cvm)
- TypeSafe docs: docs.typesafe.ai

APPENDIX · FAILURE MODES

Four ways a loop fails

Oscillation

The agent undoes and redoes one change.

Fix: detect repeated states, limit steps.

Drift

Small errors add up over many steps.

Fix: compare to the spec, not the last step.

Goodhart

The loop meets the metric, not the goal.

Fix: mix checks, keep a slow judge on top.

Sensor blindness

The real error is not in the observed state.

Fix: widen what the loop sees first.



APPENDIX · THE KEY PROPERTY

Level-triggered, not edge-triggered

Edge-triggered

The system reacts to events. If it misses one event, its picture of the world stays wrong.

Level-triggered

The system reads the full current state each time. A missed event does not matter. The next loop fixes it.

Agents need the same property. Each step must read the world again. It must not trust its own memory of the world.

Frontier models are the actuator

Opus 5.5 and Fable 5.1 do the work. They plan, write code, call tools and draft text.

This is the part of the loop that needs generation. It is also the most expensive part per step.

A good actuator needs

- Reliable tool use
- Long context for state
- Good recovery after an error

The weak point


We often use the same model as the comparator too.

Three kinds of comparator

Kind	Examples	Speed and cost	Use it for
Deterministic	tests, schema checks, linters, totals that must match	milliseconds, almost free	everything that code can measure
Fast typed model	Jev from TypeSafe AI	70–500 ms (vendor claim)	fuzzy checks at every step
Frontier judge	Opus 5.5 or Fable 5.1 as a reviewer	seconds, highest cost	checkpoints and hard cases

Use them in this order. Go to the next one only when the previous one cannot measure the error.

Two loops at two speeds



Fast checks run every step. A slower judge reviews checkpoints and uncertain cases.

A simple escalation policy

Signal	Action
A deterministic check fails	Act again, with the error output as input
Jev: goal_met, p ≥ 0.9	Run the slow judge one time, then stop
Jev: p from 0.6 to 0.9	Run the slow judge now
Jev: p < 0.6, or failure = "spec"	Stop and ask a human
Step, token or time limit reached	Stop and report the status

The thresholds are examples. Calibrate them on your own tasks before you trust them.



APPENDIX · RULE 1 OF 4

Declare the setpoint as data

If the goal is only prose, no sensor can measure the error.

From Kubernetes: declarative spec

In practice

- Write acceptance criteria as checks.
- Keep the spec in a file. The loop reads it at each step.
- Say what you want, not how to do it.

Build sensors before actuators

An agent cannot fix what it cannot observe.

From Kubernetes: observed status

In practice

- Give the loop fresh reads: diffs, test output, API state.
- Read the state again at each step.
- Log each observation, so you can replay a run.

Make every action idempotent

Loops retry. A retry must not double the damage.

From Kubernetes: idempotent actions

In practice

- Use upserts and keys, not blind creates.
- Plan first, then apply, with a dry run.
- Put actions you cannot undo behind a human gate.

APPENDIX · RULE 4 OF 4

Add a governor: limits and back-off

A loop without a stop condition is a cost leak.

From Kubernetes: back-off and requeue

In practice

- Set a maximum for steps, tokens and time.
- If the same diff comes back two times, stop.
- On external errors, wait longer before each retry.



The scheduler picks, the kubelet runs

Kubernetes scheduler

Filter eligible nodes.
Score the candidates.
Pick one node for the pod.

Agent control plane

A fast model decides.
A frontier model acts.
The checks judge the result.

```
move   ∈ {act, ask_human, stop}
target ∈ failing checks
3 answers; confidence = lowest p of the agreed move
```

Below 60% confidence, or on disagreement, ask a human. If the decider fails, use the built-in rule. The decider cannot declare success or select a passing check.

The reference stack

SETPOINT	Goal spec and acceptance checks, kept as data
SENSORS	Tool results, diffs, logs, live API state
COMPARATOR	Code checks first, then Jev, then a frontier judge
ACTUATOR	Opus 5.5 or Fable 5.1, with idempotent tools
GOVERNOR	Budgets, back-off, repeat detection, human gates