

Camera rate × cruise speed: courses completed, each arm at its measured cadence, latency and goal rate (course A, density 0.30, people 2.4 m, one flight per seed; grey = not flown)

XPU-RT · CP-SAT · 45 Hz camera	4/24	3/12	0/12	0/12	1/12
XPU-RT · CP-SAT · 90 Hz camera	3/12	0/12	1/12	2/12	1/12
XPU-RT · CP-SAT · 120 Hz camera	1/12	5/12	1/12	0/12	3/12
XPU-RT · greedy · 45 Hz camera	0/12	0/12	0/12	0/12	0/12
XPU-RT · greedy · 90 Hz camera	0/12	0/12	0/12	0/12	0/12
ROS 2 vanilla (4-hart YOLO) · 45 Hz camera	0/24	0/12	2/12	1/12	1/12
ROS 2 vanilla, control timer · 45 Hz camera	0/12	0/12	2/12	3/12	1/12
ROS 2 vanilla, control timer · 90 Hz camera	1/12	1/12	0/12	0/12	1/12
ROS 2 hand-tuned (pinned) · 45 Hz camera	2/12	3/12	1/12	1/12	3/12
ROS 2 hand-tuned (pinned) · 90 Hz camera	0/12	1/12	1/12	0/12	1/12
ROS 2 two YOLO nodes, 8 cores · 45 Hz camera	0/12	1/12	0/12	0/12	1/12
ROS 2 two YOLO nodes, 8 cores · 90 Hz camera	1/12	1/12	2/12	3/12	0/12
ROS 2 multi-threaded executor · 45 Hz camera	0/12	0/12	1/12	—	1/12
	1.0 m/s	1.2 m/s	1.4 m/s	1.6 m/s	1.8 m/s