

textNet: Directed, Multiplex, Multimodal Event Network Extraction from Textual Data

Elise Zufall¹ and Tyler Scott¹

¹ UC Davis Department of Environmental Science and Policy

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright
and release the work under a
Creative Commons Attribution 4.0
International License ([CC BY 4.0](#)).

Introduction

Network measurement in social science typically relies on data collected through surveys and interviews. Document-based measurement is automatable and scalable, providing opportunities for large scale or longitudinal research that are not possible through traditional methods. A number of tools exist to generate networks based on co-occurrence of words within documents (such as the [Nocodefunctions](#) app ([Levallois et al., 2012](#)), the “[textnets](#)” package ([Bail, 2024](#)), [InfraNodus](#) ([Paranyushkin, 2018](#)), and many more). But there is, to our knowledge, no open-source tool that generates network data based on the syntactic relationships between entities within a sentence. *textNet* allows a user to input one or more PDF documents and create arbitrarily complex directed, multiplex, and multimodal network graphs, enabling rich analysis of the relationships between verb attributes and tenses, entity types, structural motifs, and other network characteristics. For instance, [Zufall and Scott](#) demonstrate the use of *textNet* to identify which actors are involved in start-up versus ongoing or future management tasks, characterize patterns of information and funding flows, and compare the distribution of management tasks in networks from regions known to have contrasting characteristics ([2024](#)). *textNet* also works on arbitrarily long documents, making it well suited for research applications using long texts such as government planning documents, court proceedings, regulatory impact analyses, and environmental impact assessments.

textNet has applications in governance network scholarship, as demonstrated by [Zufall and Scott \(2024\)](#) and by ongoing work on groundwater governance at the UC Davis Center for Environmental Policy and Behavior. Additional potential applications include legal scholarship, social-ecological network analysis, government planning documents, court proceedings, archival research, communication and media research, and other fields interested in exploring events and entity relationships in textual data.

Statement of Need

Network extraction from documents has typically required manual coding. Furthermore, existing network extraction methods that use co-occurrence leave a vast amount of data on the table, namely, the rich edge attribute data and directionality of each verb phrase defining the particular relationship between two entities, and the respective roles of the entity nodes involved in that verb phrase. We present an R package, *textNet*, designed to enable directed, multiplex, multimodal network extraction from text documents through syntactic dependency parsing, in a replicable, automated fashion for collections of arbitrarily long documents. The *textNet* package facilitates the automated analysis and comparison of many documents, based on their respective network characteristics. Its flexibility allows for any desired entity categories, such as organizations, geopolitical entities, dates, or custom-defined categories, to be preserved.

40 Directed Graph Production

41 As a syntax-based network extractor, *textNet* identifies source and target nodes. This produces
42 directed graphs that contain information about network flow. Methods based on identifying
43 co-occurring nodes in a document, by contrast, produce undirected graphs. Co-occurrence
44 graphs also have the tendency to generate saturated subgraphs, since every co-occurring
45 collection of entities has every possible edge drawn amongst them. By contrast, *textNet* draws
46 connections not between every entity in the document or even the sentence, but specifically
47 between pairs of entities that are mediated by an event relationship.

48 Multiplex Graph Output

49 Syntax-based measurement encodes edges based on subject-verb-object relationships. *textNet*
50 stores verb information as edge attributes, which allows the user to preserve arbitrarily complex
51 topological layers (of different types of relationships) or customize groupings of edge types to
52 simplify representation.

53 Multimodal Graph Output

54 Multimodal networks, or networks where there are multiple categories of nodes, have common
55 use cases such as social-ecological network analysis of configurations of actors and environmental
56 features. Existing packages such as the *manynet* package (Hollway, 2024) provide analytical
57 functions for multimodal network statistics. *textNet* provides a structure for tagging and
58 organizing arbitrarily complex node labeling schemes that can then be fed into packages for
59 multi-node network statistical analysis. Node labels can be automated (e.g., the default entity
60 type tags for an NLP engine such as *spaCy* (Honnibal et al., 2021)), customized using a
61 dictionary, or based on a hybrid scheme of default and custom labels. Any node type is possible
62 (e.g., species, places, people, concepts, etc.) so this can be adapted to domain-specific research
63 applications by applying dictionaries or using a custom NER model.

64 Installation

65 The stable version of this package can be installed from Github, using the *devtools* package
66 (Wickham et al., 2022):

```
67 devtools::install_github("ucd-cepb/textnet")
```

68 The *textNet* package suggests several convenience wrappers of packages such as *spacyr* (Benoit
69 et al., 2023), *pdftools* (Ooms, 2024), *igraph* (Csárdi et al., 2024), and *network* (Butts et al.,
70 2023). To use the full functionality of *textNet*, such as pre-processing tools and post-processing
71 analysis tools, we recommend installing these packages, which for *spacyr* requires integration
72 with Python. However, the user may wish to preprocess and parse data using their own NLP
73 engine, and skip directly to the `textnet_extract()` function, which does not depend on *spacyr*
74 or Python integration.

75 Overview and Main Functions

76 The package architecture relies on four sets of functions around core tasks:

- 77 ■ [OPTIONAL] Pre-processing: `pdf_clean()`, a wrapper for the `pdftools::pdf_text()` func-
78 tion which includes a custom header/footer text removal feature; and `parse_text()`,
79 which is a wrapper for the *spacyr* package and uses the *spaCy* natural language pro-
80 cessing engine (Honnibal et al., 2021) to parse text and perform part of speech tagging,
81 dependency parsing, and named entity recognition (NER). Alternatively, the user can
82 skip this step and load parsed text directly into the package. Externally produced data
83 must be converted to standards outlined in the package manual.
- 84 ■ Network extraction: `textnet_extract()`, which generates a graph database from parsed text
85 based upon tags and dependency relations. The object returned from `textnet_extract()`

consists of a nodelist, an edgelist with a rich set of edge attributes, a verblist, and a list of potential coreferences for disambiguation.

- Disambiguation: tools for cleaning, recoding, and aggregating node and edge attributes, such as the `find_acronyms()` function, which can be paired with the `disambiguation()` function to identify acronyms in the text and replace them with the full entity name.
- Exploration: the `export_to_network()` function for exporting the graph database to `igraph` and network objects, `top_features()` for viewing node and edge attributes, and `combine_networks()` for aggregating multiple document-based graphs based on common nodes.

The figure below summarizes the functionality of *textNet* and the flow of function outputs. Optional data cleaning features are shown with dotted arrows.




Figure 1: Workflow of textNet Functions

Potential Further Analyses

textNet is compatible with standard network analysis tools in R. Functionality from *ggraph* (Pedersen & RStudio, 2024), *sna* (Butts, 2024), *igraph* (Csárdi et al., 2024), *network* (Butts et al., 2023), and other network visualization and analysis packages can be used to further explore the extracted networks.

The *ggraph* package has been used to create the network visualization seen here, using a weighted version of a *igraph* constructed using the “old_new_parsed” sample data in *textNet*.

New Network



Figure 2: Representation of the Event Network of the New Plan

The network-level attributes output from `export_to_network` can also be analyzed against exogenous metadata that has been collected separately by the researcher regarding the different documents and their real-world context. The extracted networks can also be analyzed through a variety of tools, such as an Exponential Random Graph Model or a Temporal Exponential Random Graph Model.

Vignette

More information about the entity network extraction algorithm and an example start-to-finish data processing and analysis workflow can be found in the vignette for this package. The vignette uses sample data that travels with the *textNet* package.

Acknowledgements

The authors gratefully acknowledge the support of the Sustainable Agricultural Systems program, project award no. 2021-68012-35914, from the U.S. Department of Agriculture's National Institute of Food and Agriculture and the National Science Foundation's Dynamics of Integrated Socio-Environmental Systems program, grant no. 2205239.

References

- Bail, C. (2024). *Cbail/textnets* (Version 0.1.1). <https://github.com/cbail/textnets>
- Benoit, K., Matsuo, A., Gruber, J., & Council (ERC-2011-StG 283794-QUANTESS), E. R. (2023). *Spacyr: Wrapper to the 'spaCy' 'NLP' library* (Version 1.3.0). <https://cran.r-project.org/web/packages/spacyr/index.html>
- Butts, C. T. (2024). *Sna: Tools for social network analysis* (Version 2.8). <https://cran.r-project.org/web/packages/sna/index.html>

- 125 Butts, C. T., Hunter, D., Handcock, M., Bender-deMoll, S., Horner, J., Wang, L., Krivitsky, P.
126 N., Knapp, B., Bojanowski, M., & Klumb, C. (2023). *Network: Classes for relational data*
127 (Version 1.18.2). <https://cran.r-project.org/web/packages/network/index.html>
- 128 Csárdi, G., Nepusz, T., Traag, V., Horvát, S., Zanini, F., Noom, D., Müller, K., Salmon, M.,
129 Antonov, M., & details, C. Z. I. igraph author. (2024). *Igraph: Network analysis and*
130 *visualization* (Version 2.1.1). <https://cran.r-project.org/web/packages/igraph/index.html>
- 131 Hollway, J. (2024). *Manynet: Many ways to make, modify, map, mark, and measure myriad*
132 *networks* (Version 1.2.6). <https://CRAN.R-project.org/package=manynet>
- 133 Honnibal, M., Montani, I., Van Landeghem, S., & Boyd, A. (2021). *spaCy: Industrial-strength*
134 *natural language processing in python* (Version 3.1.3). [https://github.com/explosion/](https://github.com/explosion/spaCy/tree/master)
135 [spaCy/tree/master](https://github.com/explosion/spaCy/tree/master)
- 136 Levallois, C., Clithero, J. A., Wouters, P., Smidts, A., & Huettel, S. A. (2012). Translating
137 upwards: Linking the neural and social sciences via neuroeconomics. *Nature Reviews*
138 *Neuroscience*, 13(11), 789–797. [https://nocodefunctions.com/cowo/semantic_networks_](https://nocodefunctions.com/cowo/semantic_networks_tool.html)
139 [tool.html](https://nocodefunctions.com/cowo/semantic_networks_tool.html)
- 140 Ooms, J. (2024). *Pdftools: Text extraction, rendering and converting of PDF documents*
141 (Version 3.4.1). <https://cran.r-project.org/web/packages/pdftools/index.html>
- 142 Paranyushkin, D. (2018). *InfraNodus*. Nodus Labs. <https://infranodus.com/>
- 143 Pedersen, T. L., & RStudio. (2024). *Ggraph: An implementation of grammar of graphics for*
144 *graphs and networks* (Version 2.2.1). [https://cran.r-project.org/web/packages/ggraph/](https://cran.r-project.org/web/packages/ggraph/index.html)
145 [index.html](https://cran.r-project.org/web/packages/ggraph/index.html)
- 146 Wickham, H., Hester, J., Chang, W., Bryan, J., & RStudio. (2022). *Devtools: Tools to make*
147 *developing r packages easier* (Version 2.4.5). [https://cran.r-project.org/web/packages/](https://cran.r-project.org/web/packages/devtools/index.html)
148 [devtools/index.html](https://cran.r-project.org/web/packages/devtools/index.html)
- 149 Zufall, E., & Scott, T. A. (2024). Syntactic measurement of governance networks from
150 textual data, with application to water management plans. *Policy Studies Journal*, n/a.
151 <https://doi.org/10.1111/psj.12556>