



← Depth in m to reference level ( )



Test according ASTM D5778-12

Project : **Site Investigations**

Location: **Wellington Town Hall**

Position: **1748823.1, 5427594.6 NZTM**


Date : **4/04/2017**

Cone no. : **C10CFIP.C13082**

Project no. : **04TT1**

CPT no. : **310a**

1/14



← Depth in m to reference level ( )

— Corrected cone resistance (qt) in MPa —→

2 4 6 8 10 12 14 16 18 20 22 24 26 28 30

G.L. : 1.96 m

34.9 ->

Tip

GWL Dipped Onsite

150 cm<sup>2</sup>  
10 cm<sup>2</sup>



Test according ASTM D5778-12

Project : **Site Investigations**

Location: **Wellington Town Hall**

Position: **1748823.1, 5427594.6 NZTM**


Date : **4/04/2017**

Cone no. : **C10CFIP.C13082**

Project no. : **04TT1**

CPT no. : **310a**

3/14



Test according ASTM D5778-12

Project : **Site Investigations**

Location: **Wellington Town Hall**

Position: **1748823.1, 5427594.6 NZTM**

Date : **4/04/2017**

Cone no. : **C10CFIP.C13082**

Project no. : **04TT1**

CPT no. : **310a**

**4/14**

← Depth in m to reference level ( )

— Effective cone resistance ( $q_e$ ) in MPa —→

2 4 6 8 10 12 14 16 18 20 22 24 26 28 30

G.L. : 1.96 m

35 ->

Tip

GWL Dipped Onsite

150 cm<sup>2</sup>  
10 cm<sup>2</sup>



Test according ASTM D5778-12

Project : **Site Investigations**

Location: **Wellington Town Hall**

Position: **1748823.1, 5427594.6 NZTM**

Date : **4/04/2017**

Cone no. : **C10CFIP.C13082**

Project no. : **04TT1**

CPT no. : **310a**

5/14

← Depth in m to reference level ( )

— Total vertical stress (rov,z) in kPa →

50 100 150 200 250 300 350 400 450 500 550 600 650 700 750

G.L. : 1.96 m

+2  
+1  
0  
-1  
-2  
-3  
-4  
-5  
-6  
-7  
-8  
-9  
-10  
-11  
-12  
-13  
-14  
-15  
-16  
-17  
-18  
-19  
-20  
-21  
-22



--- Effective vertical stress (rov,z') in kPa →

100

200

300

400

500

600

700

Tip

GWL Dipped Onsite



Test according ASTM D5778-12

Project : **Site Investigations**

Location: **Wellington Town Hall**

Position: **1748823.1, 5427594.6 NZTM**

Date : **4/04/2017**



Cone no. : **C10CFIP.C13082**

Project no. : **04TT1**



CPT no. : **310a**

6/14

← Depth in m to reference level ( )



Test according ASTM D5778-12		Date : 4/04/2017	
Project : Site Investigations		Cone no. : C10CFIP.C13082	
Location: Wellington Town Hall		Project no. : 04TT1	
Position: 1748823.1, 5427594.6 NZTM		CPT no. : 310a	7/14



Test according ASTM D5778-12		Date : 4/04/2017	
Project : Site Investigations		Cone no. : C10CFIP.C13082	
Location: Wellington Town Hall		Project no. : 04TT1	
Position: 1748823.1, 5427594.6 NZTM		CPT no. : 310a	8/14



← Depth in m to reference level ( )

— Soil behaviour type index (Ic) —→

0.5 1.0 1.5 2.0 2.5 3.0 3.5 4.0 4.5 5.0 5.5 6.0 6.5 7.0 7.5

G.L. : 1.96 m

+2  
+1  
0  
-1  
-2  
-3  
-4  
-5  
-6  
-7  
-8  
-9  
-10  
-11  
-12  
-13  
-14  
-15  
-16  
-17  
-18  
-19  
-20  
-21  
-22

(2) Organic soils  
(3) Clay  
(4) Silt mixtures  
(5) Sand mixtures  
(6) Sand clean to silty  
(7) Gravelly sand

150 cm<sup>2</sup>  
10 cm<sup>2</sup>

7

6

5

4

3

2



Test according ASTM D5778-12

Project : Site Investigations

Location: Wellington Town Hall

Position: 1748823.1, 5427594.6 NZTM

Date : 4/04/2017

Cone no. : C10CFIP.C13082

Project no. : 04TT1

CPT no. : 310a

9/14

← Depth in m to reference level ( )

— Undrained shear strength ( $S_u$ ) in kPa →

100 200 300 400 500 600 700 800 900 1000 1100 1200 1300 1400 1500

G.L. : 1.96 m

150 cm<sup>2</sup>  
10 cm<sup>2</sup>

Tip

GWL Dipped Onsite



Test according ASTM D5778-12

Project : **Site Investigations**

Location: **Wellington Town Hall**

Position: **1748823.1, 5427594.6 NZTM**

Date : **4/04/2017**

Cone no. : **C10CFIP.C13082**

Project no. : **04TT1**

CPT no. : **310a**

10/14

← Depth in m to reference level ( )

— Relative density (consolidated) in % —→

10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

G.L. : 1.96 m



--- Relative density (over-consolidated) in % —→

20

40

60

80

100

120

140



Test according ASTM D5778-12

Project : **Site Investigations**

Location: **Wellington Town Hall**

Position: **1748823.1, 5427594.6 NZTM**


Date : **4/04/2017**

Cone no. : **C10CFIP.C13082**

Project no. : **04TT1**

CPT no. : **310a**

11/14



Test according ASTM D5778-12

Project : **Site Investigations**

Location: **Wellington Town Hall**

Position: **1748823.1, 5427594.6 NZTM**


Date : **4/04/2017**

Cone no. : **C10CFIP.C13082**

Project no. : **04TT1**

CPT no. : **310a**

12/14



← Depth in m to reference level ( )

— Internal friction angle in degrees —→

5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

G.L. : 1.96 m

150 cm<sup>2</sup>  
10 cm<sup>2</sup>



Test according ASTM D5778-12

Project : **Site Investigations**

Location: **Wellington Town Hall**

Position: **1748823.1, 5427594.6 NZTM**


Date : **4/04/2017**


Cone no. : **C10CFIP.C13082**

Project no. : **04TT1**

CPT no. : **310a**

14/14







Test according ASTM D5778-12

Project : Site Investigations

Location : Wellington Town Hall

Date : 4/04/2017

Project no. : 04TT1

CPT no. : 310a

Test depth : 5.00 [m] - G.L.

Water level : -1.30 [m] - G.L.



