

IN4MATX 133: User Interface Software

Lecture 9:
Server-Side Development,
Authentication, & Authorization

Professor Daniel A. Epstein
TA Lucas de Melo Silva
TA Jong Ho Lee

Announcements

- A3 will be posted soon
 - Maybe tomorrow or over the weekend

Today's goals



By the end of today, you should be able to...

- Explain the advantages and disadvantages of different tools for server-side development
- Differentiate authentication from authorization
- Describe the utility of supporting authentication and authorization in interfaces
- Explain and implement the different stages to authenticating via OAuth
- Describe the advantages and disadvantages of OpenId

Client-side and server-side JavaScript



Edit what's being rendered
Trigger or react to events



Navigate file system programmatically
Dynamically generate pages or views
Transport, store, or interact with data

Client-side


- Runs in the browser
- Changes happen in real-time in the browser
- Cannot make HTTP requests to many APIs
- Examples: AJAX, Angular, React, Vue.js

Server-side

- Runs in the command line, etc. (but maybe can still be accessed from the browser)
- Changes happen in response to HTTP requests
- Can make HTTP requests to most APIs
- Examples: Node, ASP.NET

Servers on localhost


- Localhost: “this computer”



Live server: localhost:8080

Browser implements same-origin policy to protect the other data you have open in the browser



Same domain (localhost),
so they can communicate



Twitter proxy: localhost:7890

No same-origin policy restrictions, can communicate with Twitter

No communication restrictions



Server-side development: Node.js

- Event-driven, non-blocking I/O model makes it efficient
- Best for highly-interactive pages
 - When a lot of computation is required, other frameworks are better
 - Event-driven loops are inefficient
- Lower threshold for us: we're already learning JavaScript!



Other server-side environments

- Ruby, via Ruby on Rails
- Python, via Django or web2py
- These days, you can create a dynamic website in almost any language



django

WEB2PY

Node package manager (npm)

- Included in the download of Node
- Originally libraries specifically for Node
- Now includes many JavaScript packages



Node.js hello world

```
var http = require( 'http' );
```

 ← Require the http library

Node.js hello world

```
var http = require( 'http' );
```

← Require the http library

```
var server = http.createServer( function( req, res ) {
```

```
} );
```



Anonymous function with
request and response parameters

Node.js hello world

```
var http = require( 'http' );  
var server = http.createServer( function( req, res ) {  
  res.writeHead( 200 );  
  res.end( 'Hello World' );  
} );
```

← Require the http library

↑ Anonymous function with request and response parameters

↑ “Ok” status in the header,
write hello world text

Node.js hello world

```
var http = require( 'http' );  
var server = http.createServer( function( req, res ) {  
    res.writeHead( 200 );  
    res.end( 'Hello World' );  
} );  
server.listen( 8080 );
```

← Require the http library

↑ Anonymous function with request and response parameters


↑ “Ok” status in the header, write hello world text

↑ Listen on port 8080

Running Node.js

- `node file.js`

Node.js



**Remember,
Node.js is server-side JavaScript**

Where is the JavaScript running?

Server-side

node hello.js


hello.js:

```
var http = require('http');
var server = http.createServer(function(req, res) {
  res.writeHead(200);
  res.end('Hello World');
});
server.listen(8080);
console.log('Hello, console');
```

Node is listening on port 8080.
But the JavaScript is **not**
running in the browser.
It's running in the console.



A terminal window titled "l11_server_side_development — node hello.js — 96x15". It shows the command prompt "Daniels-MacBook-Pro:l11_server_side_development danielepstein\$ clear" followed by "Daniels-MacBook-Pro:l11_server_side_development danielepstein\$ node hello.js". The output "Hello, console" is displayed on the next line.



Where is the JavaScript running?

Client-side

live-server


hello.html:

```
<html>
  <head>
    <script src="./hello.js"></script>
  </head>
  <body>
    Hello, world
  </body>
</html>
```

Live-server is listening on port 8080. The JavaScript is running in the browser.

hello.js:

```
console.log('Hello, world');
```



What does Node.js add?

- OS-level functionality like reading and writing files
- Tools for importing and managing packages
- The ability to listen on a port as a web server
- But it's just JavaScript, and it's pretty basic as a web framework

What does a “good” server-side web framework need?

- To speak in HTTP
 - Accept connections, handle requests, send replies
- Routing
 - Map URLs to the webserver function for that URL
- Middleware support
 - Add data processing layers
 - Make it easy to add support for user sessions, security, compression, etc.
- Node.js has these, but they’re somewhat difficult to use

Switching topics: authentication & authorization

What is authentication?

- The process of establishing and verifying identity
- Identification: who are you? (username, account number, etc.)
- Authentication: prove it! (password, PIN, etc.)

What is authorization?

- Once we know a user's identity, we must decide what they are allowed to access or modify
- One way is the app defines permissions upfront based on a user's role
 - A student can access their own grades, but not modify them
 - A TA and a professor can access and modify everyone's grades
- Another way is for the app to request the user grant certain permissions
 - A Twitter app may ask, "can I Tweet on your behalf?"

Multi-factor authentication

- Should be a mix of things that you *have/possess* and things that you *know*
- ATM machine: 2-factor authentication
 - ATM card: something you *have*
 - PIN: something you *know*
- Password + code delivered via SMS: 2-factor authentication
 - Password: something you *know*
 - Code: validates that you *possess* your phone
- Two passwords != Two-factor authentication

Question

Which of these is an example of “good” two-factor authentication?

- ☐ A A government agency requiring a birth certificate and a passport
- ☐ B A store requiring a membership card and a PIN
- ☐ C A website requiring a password and a security question
- ☐ D Two of the above
- ☐ E All of the above


Question

Which of these is an example of “good” two-factor authentication?

- ☐ A A government agency requiring a birth certificate and a passport
- ☐ B A store requiring a membership card and a PIN
- ☐ C A website requiring a password and a security question
- ☐ D Two of the above
- ☐ E All of the above


Password protocol

- Send a login and a password to a server
- Server checks your credentials and okays you
- Need to trust that the server is storing your password securely




Password protocol: sending data

- Once you've logged in, the server can send you whatever data you're allowed to see



Sending data to a third party

- You want to send data that a server has to a third party
 - You could give them your username and password...
 - Why is this a bad idea?



Sending data to a third party

- Now you have to trust *another* service to manage your password
- What if you don't want them to have full access?
 - e.g., you want Mint to load your savings account but not your checking account
- What if you want to revoke access later?
 - Can change your password, but that's not a good solution

Oauth 2.0

- Open authentication
- Goal: support users in granting access to third-party applications
 - Do not require users to share their passwords with the third-party applications
 - Allow users to revoke access from the third parties at any time

OAuth 2.0 history

- There was a 1.0
 - It was complex (worse than 2.0)
 - It had security vulnerabilities
 - It shouldn't be used anymore
- Google, Twitter, & Yahoo! teamed up to propose 2.0
- 2.0 is not compatible with 1.0

https://en.wikipedia.org/wiki/OAuth#OAuth_2.0

Oauth 2.0 terminology

- Client
 - Third-party app who wants to access resources owned by the *resource owner* (e.g., app you develop)
- Resource owner (user)
 - Person whose data is being accessed, which is stored on the *resource server*
- Resource server
 - App that stores the resources (e.g., Spotify, Google, Facebook)
- Authorization and Token endpoints
 - URIs from where a resource owner authorizes requests


Oauth 2.0 terminology

- Authorization code
 - A string the client uses to request access tokens
- Access token
 - A string the client uses to access resources (e.g., songs on Spotify, Tweets, etc.)
 - Expires after some amount of time
- Refresh token
 - Once the access token expires, can be exchanged for a new access token

Oauth 2.0 steps


1. Request authorization
2. Get access token
3. Make API calls
4. Refresh access token

Oauth 2.0 steps



<https://developer.spotify.com/documentation/general/guides/authorization-guide/>


Oauth 2.0 and Spotify



Create a new ID

<https://developer.spotify.com/dashboard/>

Oauth 2.0 and Spotify




Need to specify what URI to return to
(redirect URI)

<https://developer.spotify.com/dashboard/>

Oauth 2.0 on server-side JavaScript


- This example will walk through the Oauth flow for server-side JavaScript (like Node.js/Express)
- There are browser-side ways of doing (some parts of) Oauth
- For A3, you'll send all browser-side requests to a Node.js/Express server

Step 1: request authorization to access data



Requesting authorization

- Make a page with links to Spotify's authorization endpoint (<https://accounts.spotify.com/authorize/>)
- Pass arguments in the query string
 - Client ID (public ID of your app)
 - Response type (string "code")
 - Redirect URI (where to return to)
 - Scope (what permissions to ask for)



<https://developer.spotify.com/documentation/general/guides/authorization-guide/>

Requesting authorization

- `https://accounts.spotify.com/authorize?` ← Endpoint
`response_type=code&` ← “code” response type
`client_id=6d81b7a55e894abdbf53143fb2901573&` ← Client id for app
`scope=user-read-private%20user-read-email&` ← Scope
`redirect_uri=http%3A%2F%2Flocalhost%3A8888%2Fcallback`
← URI to redirect to:
`http://localhost:8888/callback`
- Escaping characters: `encodeURIComponent()`

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/encodeURIComponent

<https://developer.spotify.com/documentation/general/guides/authorization-guide/>

Handling response

- User clicks “okay”, browser then redirects back to your server
- The response contains additional parameters in the URL
- `http://localhost:8888/callback?code=...`
- In Express, code can be accessed through `req.query`



Connect **The App** to your Spotify account.

The Description of The App

The App will be able to receive this Spotify account data.

You agree that The App is responsible for its use of your information in accordance with its privacy policy, and that your information may be transferred outside the EEA.


You are logged in as The User.
(Not you?)

CANCEL

OKAY

<https://developer.spotify.com/documentation/general/guides/authorization-guide/>

Step 2: request access and refresh tokens



Requesting an access token

- Our goal: trade `code` for an access token
 - An access token needs to be included in API requests
- Why do we need to do this?
 - The user has granted permission for the ID we created on Spotify to access resources
 - But any website could send a user to that URL: client IDs, etc. is all public information
 - How can we verify our app uses the client ID we created on Spotify?

<https://developer.spotify.com/documentation/general/guides/authorization-guide/>

Requesting an access token

- We make a `POST` request with our client's secret code and ask for an access token
 - Endpoint: <https://accounts.spotify.com/api/token>
- Why a `POST` request rather than a `GET`?
 - `POST` sends content in the body of an HTTP request (cannot be read by someone watching your web traffic)
 - `GET` sends content in the URI
 - `https://accounts.spotify.com/authorize?response_type=code&client_id=6d81b7a55e894abdbf53143fb2901573`

<https://security.stackexchange.com/questions/33837/get-vs-post-which-is-more-secure>

<https://developer.spotify.com/documentation/general/guides/authorization-guide/>

IN4MATX 133 example

IN4MATX 133 course

Client ID 6d81b7a55e894abdbf53143fb2901573

[SHOW CLIENT SECRET](#)

Requesting an access token

- Body of `POST` request requires 3 parameters
 - Grant type (string “authorization_code”)
 - Code (returned as a parameter in the response from the authorization request)
 - Redirect URI (must be the same as before)
- Header of `POST` request requires 2 parameters
 - Authorization (concatenation of client ID and client secret, as a Buffer)
 - Encoding (via Content-Type, as “*application/x-www-form-urlencoded*”)

<https://developer.spotify.com/documentation/general/guides/authorization-guide/>

Requesting an access token

- Making the body: URLSearchParams

- `params = new URLSearchParams();`
- `params.append('grant_type', 'authorization_code'); etc.`

- Header: a dictionary

- `'Content-Type': 'application/x-www-form-urlencoded'`
- `'Authorization': 'Basic ' + Buffer.from(my_client_id + ':' + my_client_secret).toString('base64')`

https://www.w3schools.com/nodejs/met_buffer_from.asp

<https://developer.mozilla.org/en-US/docs/Web/API/URLSearchParams>


<https://developer.spotify.com/documentation/general/guides/authorization-guide/>

Handling response

- In the response body, Spotify sends back:
 - Access Token (needed to make API calls)
 - Expires in (how long the access token is good for)
 - Refresh Token (once the Access Token expires, this can be used to get a new one)
- What would you do with these tokens?
 - Store them in a database for later access
 - In A3, we'll store them in a text file (bad form, but easier)

<https://developer.spotify.com/documentation/general/guides/authorization-guide/>

Step 3: use access token in requests to web API



Making an API request

- Pass the access token in the header
 - Much like the client id and secret, but no need to convert it
 - `'Authorization': 'Bearer ' + access_token`
- Make a GET request to one of the API endpoints
 - e.g., `https://api.spotify.com/v1/me`
 - Will return a JSON object with the requested resource
 - e.g., birthdate, email, a profile image


<https://developer.spotify.com/documentation/web-api/reference/users-profile/get-current-users-profile/>
<https://developer.spotify.com/documentation/general/guides/authorization-guide/>

Making an API request

- Spotify has endpoints for artists, albums, tracks, and more
- Often specify a subresource in the URI
 - e.g., <https://api.spotify.com/v1/albums/{id}> for a specific album

<https://developer.spotify.com/documentation/web-api/reference/>

Step 4: refresh access token



Refresh token

- Tokens typically expire after a fixed amount of time
 - One hour for Spotify tokens
 - After that time, all API requests will return with code 401 (Unauthorized)
- A user can use the refresh token to get a new token
- Why do tokens expire?
 - To allow a user to revoke their privileges

<https://developer.spotify.com/documentation/web-api/>


<https://developer.spotify.com/documentation/general/guides/authorization-guide/>

Refresh token

- Same endpoint as requesting an access token
 - Endpoint: <https://accounts.spotify.com/api/token>
- Similar parameters; header with encoding and authorization
 - `'Content-Type': 'application/x-www-form-urlencoded'`
 - `'Authorization': 'Basic ' + Buffer.from(my_client_id + ':' + my_client_secret).toString('base64')`
- Different body parameters
 - “refresh_token” as “grant_type”, the token itself as “refresh_token”

<https://developer.spotify.com/documentation/general/guides/authorization-guide/>

Oauth 2.0 steps




<https://developer.spotify.com/documentation/general/guides/authorization-guide/>

Authorizing from the browser


- Create a link to the authorization endpoint (<https://accounts.spotify.com/authorize/>)
 - Which will redirect to your server-side JavaScript
- Once tokens have been received, redirect back to client-side JavaScript

Authorizing from the browser



Making an API request from the browser


After authorizing



Making an API request from the browser

- How does the browser indicate that it wants the server to make an API request?
 - All web servers communicate in HTTP
 - Make an HTTP request to the server, asking it to make the API request
 - It returns the response

Assignment 3



Question

Which can make an HTTP request to the Spotify API?

(Assume the browser uses default settings)

A 4

B 1, 4

C 1, 2, 4

D 1, 3, 4

E 1, 2, 3, 4

(1) A browser open to spotify.com

(2) A browser with client-side JavaScript at localhost:8888

(3) A browser with server-side JavaScript at localhost:8888

(4) A server running in the Spotify domain

Question

Which can make an HTTP request to the Spotify API?

(Assume the browser uses default settings)

A 4

B 1, 4

C 1, 2, 4

D 1, 3, 4

E 1, 2, 3, 4

(1) A browser open to spotify.com


(2) A browser with client-side JavaScript at localhost:8888

(3) A browser with server-side JavaScript at localhost:8888

(4) A server running in the Spotify domain

OpenID Connect

- Ever seen a button with “sign in with Google”, etc.?
- Implemented with OpenID Connect
 - Added layer on top of OAuth



<https://openid.net/connect/>


OpenID Connect


- Benefits:
 - No need to get an ID for every service
 - Only one password to remember/store
- Drawbacks
 - Facebook/Google/etc.
gather (more) information about you
and and the websites you go to

[Browse Courses](#)

Get Started

Your courses will be available on all of your devices.

 Sign In

 Sign In

Sign up with your email

Already have an account?

Sign In



Question

Which of these topics would you prefer to have covered in Monday's discussion?

- ☐ A More on JavaScript, in support of A2
- ☐ B More on HTTP, server-side JavaScript, authentication & authorization
- ☐ C A preview of Angular, in support of A3
- ☐ D I will probably go regardless
- ☐ E I will probably not go regardless

Today's goals

By the end of today, you should be able to...

- Explain the advantages and disadvantages of different tools for server-side development
- Differentiate authentication from authorization
- Describe the utility of supporting authentication and authorization in interfaces
- Explain and implement the different stages to authenticating via OAuth
- Describe the advantages and disadvantages of OpenId

IN4MATX 133: User Interface Software

Lecture 9:
Server-Side Development,
Authentication, & Authorization

Professor Daniel A. Epstein
TA Lucas de Melo Silva
TA Jong Ho Lee

More on Node and Express

Node file system

`var fs = require('fs');` ← Require the file system library

`fs.readFile("/path/to/file", function(err, data) {
 console.log(data);`

`});` ↑


Read file, wait for
asynchronous response

Node file system

```
var http = require('http');
var fs = require('fs');
var server = http.createServer(function(req, res) {
  fs.readFile(__dirname + req.url, function(err, data) {
    if (err) {
      res.writeHead(404);
      res.end(JSON.stringify(err));
      return;
    }
    res.writeHead(200);
    res.end(data);
  });
});
server.listen(8080);
```

Node processing model

- Requests are handled in a single-threaded event loop
 - Every time someone loads a page node manages, it's added to this loop
- Requests are then processed asynchronously
 - When the work a request asks for is done, responses are returned to the client



Express.js

- A fairly minimal web framework that improves Node.js functionality
 - Can route HTTP requests, render HTML, and configure middleware

```
var expressApp = express();
```

```
expressApp.get('/', function (httpRequest, httpResponse)
{
  httpResponse.send('hello world');
});
expressApp.listen(3000);
```

Express installation

- `npm install express`
 - Will save it to your node_modules folder

Express routing

- By HTTP method

```
expressApp.get(urlPath, requestProcessFunction);  
expressApp.post(urlPath, requestProcessFunction);  
expressApp.put(urlPath, requestProcessFunction);  
expressApp.delete(urlPath, requestProcessFunction);  
expressApp.all(urlPath, requestProcessFunction);
```

- urlPath may contain parameters (e.g., ``/user/:user_id``)

HttpRequest object

```
expressApp.get('/user/:user_id', function (HttpRequest, httpResponse) ...
```

- Has a lot of properties
 - Middleware can add properties
 - `request.params`: object containing url route params (e.g., `user_id`)
 - `request.query`: object containing query params (e.g., `&foo=9 => {foo: '9'}`)
 - `request.body`: object containing the parsed body (e.g., if a JSON object was sent)

httpResponse object

`expressApp.get('/user/:user_id', function (httpRequest, httpResponse) ...`

- Has a lot of methods for setting HTTP response fields
 - `response.write(content)`: build up the response body with content
 - `response.status(code)`: set the HTTP status code for the reply
 - `response.end()`: end the request by responding to it (the only actual response!)
 - `response.send(content)`: write content and then end
- Methods should be chained

`response.status(code).write(content1).write(content2).end();`

Middleware

- Give other software the ability to manipulate requests
- ```
expressApp.all(urlPath, function (request, response,
next) {
 // Do whatever processing on request (or setting
response)
 next(); // pass control to the next handler
});
```

# Middleware

- Middleware examples:
  - Check to see if a user is logged in, otherwise send error response and don't call `next()`
  - Parse the request body as JSON and attach the object to `request.body` and call `next()`
  - Session and cookie management, compression, encryption, etc.

# Example Express server

```
var express = require('express');
var app = express(); // Creating an Express "App"
app.use(express.static(__dirname)); // Adding middleware
app.get('/', function (request, response) { // A simple request
 handler
 response.send('Simple web server of files from ' + __dirname);
});
app.listen(3000, function () { // Start Express on the requests
 console.log('Listening at http://localhost:3000 exporting the
 directory ' +
 __dirname);
});
```



# Example Express user list

```
app.get('/students/list', function (request, response) {
 response.status(200).send(in4matx133.enrolledStudents());
 return;
});
app.get('/students/:id', function (request, response) {
 var id = request.params.id;
 var user = in4matx133.isEnrolled(id);
 if (user === null) {
 console.log('Student with _id:' + id + ' not found. ');
 response.status(400).send('Not found');
 return;
 }
 response.status(200).send(user);
 return;
});
```

# Express generator



















- Express provides a tool that can create and initialize an application skeleton
  - Sets up a directory structure for isolating different components
  - Your app doesn't have to be built this way, but it's a useful starting point

<https://expressjs.com/en/starter/generator.html>

# Express generator



















- `npm install express-generator -g`
- Can be invoked on command line with `express`
- Adds some boilerplate code and commonly used dependencies
- Install dependencies with `npm install`
  - `cd` into project directory first
- Run with `npm start`

<https://expressjs.com/en/starter/generator.html>

| Name                                                                                                  |  |
|-------------------------------------------------------------------------------------------------------|--|
|  app.js            |  |
| ▼  bin             |  |
|  www               |  |
| ▶  node_modules    |  |
|  package-lock.json |  |
|  package.json      |  |
| ▼  public          |  |
| ▼  images         |  |
| ▼  javascripts   |  |
| ▼  stylesheets   |  |
|  style.css       |  |
| ▼  routes        |  |
|  index.js        |  |
|  users.js        |  |
| ▼  views         |  |
|  error.pug       |  |
|  index.pug       |  |
|  layout.pug      |  |

# Express generator

- `package.json`, `package-lock.json`,  
and `node_modules` folder: library management  
and installed libraries
- `public` folder: all public-facing images, stylesheets,  
and JavaScript files

| Name                                                                                                               |  |
|--------------------------------------------------------------------------------------------------------------------|--|
|  <code>app.js</code>            |  |
| ▼  <code>bin</code>             |  |
|  <code>www</code>               |  |
| ▶  <code>node_modules</code>    |  |
|  <code>package-lock.json</code> |  |
|  <code>package.json</code>      |  |
| ▼  <code>public</code>          |  |
| ▼  <code>images</code>         |  |
| ▼  <code>javascripts</code>   |  |
| ▼  <code>stylesheets</code>   |  |
|  <code>style.css</code>       |  |
| ▼  <code>routes</code>        |  |
|  <code>index.js</code>        |  |
|  <code>users.js</code>        |  |
| ▼  <code>views</code>         |  |
|  <code>error.pug</code>       |  |
|  <code>index.pug</code>       |  |
|  <code>layout.pug</code>      |  |

# Express generator

- Routes folder: files which handle your URL mappings



















```
var express = require('express');
var router = express.Router();
```

```
/* GET home page. */
router.get('/', function(req, res, next) {
 res.render('index', { title: 'Express' });
});
```

↑  
Variable passed to renderer



















```
module.exports = router;
```

↑  
So another page can import  
your router

| Name                                                                                                  |  |
|-------------------------------------------------------------------------------------------------------|--|
|  app.js            |  |
| ▼  bin             |  |
|  www               |  |
| ▶  node_modules    |  |
|  package-lock.json |  |
|  package.json      |  |
| ▼  public          |  |
| ▼  images         |  |
| ▼  javascripts   |  |
| ▼  stylesheets   |  |
|  style.css       |  |
| ▼  routes        |  |
|  index.js        |  |
|  users.js        |  |
| ▼  views         |  |
|  error.pug       |  |
|  index.pug       |  |
|  layout.pug      |  |

# Express generator

- Views folder: any webpages which need to be rendered
- Uses a *view engine*, Pug, which generates HTML

| Name                                                                                                  |  |
|-------------------------------------------------------------------------------------------------------|--|
|  app.js            |  |
| ▼  bin             |  |
|  www               |  |
| ▶  node_modules    |  |
|  package-lock.json |  |
|  package.json      |  |
| ▼  public          |  |
| ▼  images         |  |
| ▼  javascripts   |  |
| ▼  stylesheets   |  |
|  style.css       |  |
| ▼  routes        |  |
|  index.js        |  |
|  users.js        |  |
| ▼  views         |  |
|  error.pug       |  |
|  index.pug       |  |
|  layout.pug      |  |



# Pug view engine

- layout.pug

```
doctype html
html
 head
 title= title
 link(rel='stylesheet', href='/
stylesheets/style.css')
 body
 block content
```

- index.pug

extends layout ← Imports other file

```
block content
 h1= title
 p Welcome to #{title} ← Parses variable passed
```

```
<!DOCTYPE html>
<html>
 <head>
 <title>Express</title>
 <link rel="stylesheet" href="/
stylesheets/style.css">
 </head>
 <body>
 <h1>Express</h1>
 <p>Welcome to Express</p>
 </body>
</html>
```

<https://pugjs.org/api/getting-started.html>

# Express generator

- app.js: sets up middleware, routers, etc.

```
var indexRouter = require('./routes/index');
var usersRouter = require('./routes/users');
```

```
var app = express();
```

Import route files

```
app.use(express.json());
app.use(express.urlencoded({ extended: false }));
app.use(cookieParser());
app.use(express.static(path.join(__dirname, 'public')));
```

To parse content as json

To encode URLs



















To handle cookies (user state)

To treat the public folder  
as static content

```
app.use('/', indexRouter);
app.use('/users', usersRouter);
```

Use route files

Middleware

Name	
 app.js	
▼  bin	
 www	
▶  node_modules	
 package-lock.json	
 package.json	
▼  public	
▼  images	
▼  javascripts	
▼  stylesheets	
 style.css	
▼  routes	
 index.js	
 users.js	
▼  views	
 error.pug	
 index.pug	
 layout.pug	



# Express generator

- bin/www: set up what port to listen on
- File that is run with `npm start`

```
var app = require('..../app');
var http = require('http');

var port = normalizePort(process.env.PORT || '3000');
app.set('port', port);
var server = http.createServer(app);

server.listen(port);
server.on('error', onError);
server.on('listening', onListening);
```