# Vega-Lite

TAs Lucas and Jo

# Agenda

- Concepts Recap
  - Data, Mark, Transform, Encoding
- Live Demo
  - Distribution of different kinds of weather in Seattle
- Exercises
  - Exercise 1: Aggregate mean

- Data inline
  - JSON Array
  - Each row is an object in the array.

```
"data": {
 "values": [
    {"a": "C", "b": 2},
    {"a": "C", "b": 7},
    {"a": "C", "b": 4},
    {"a": "D", "b": 1},
    {"a": "D", "b": 2},
    {"a": "D", "b": 6},
    {"a": "E", "b": 8},
    {"a": "E", "b": 4},
    {"a": "E", "b": 7}
```

- Data from source
  - Can be imported through URL
  - Runtime datasource API (not addressed here)

```
"data": {"url": "https://vega.github.io/editor/data/seattle-weather.csv"},
```


- Marks
  - Shapes to visually encode data


```
"mark": {
    "type": ..., // mark Object
    ...
},
```


```
"mark": "..." ,// mark type
...
}
```

#### Marks


- Shapes to visually encode data
- Primitive types: area, bar, circle, line, point, rect, rule, square, text, tick, and geoshape








Open in Vega Editor



- Transform
  - Describe transformations on the data
  - Transform property or field transforms inside "encoding" (more on that later)
  - View-level are executed in order
- Some examples
  - Filter, Aggregate, Bin

```
"transform": [
  { ... : { ... }},
  { ... : { ... }}
```

- Transform example view level
  - data/cars.json
  - Aggregate mean of acceleration, group by number of cylinders




```
"chevrolet chevelle
Name:
Miles per Gallon:
Cylinders:
Displacement:
                    307
                    130
Horsepower:
Weight in lbs:
                    3504
Acceleration:
                    12
Year:
                    "1970-01-01"
Origin:
                    "USA"
```

- Encoding
  - Maps encoding channels to data fields or constant values
- Encoding channels
  - Position channels
    - x, y, x2, y2
  - Mark property channels
    - color, opacity, shape, size
  - Tooltip, Hyperlink channels
    - Text, tooltip, href (explained later)

- Channel definition
  - Either a field definition or a value definition
- Field definition
  - Encodes a particular field in the dataset with an encoding channel
  - "field": String defining the name of the field from which to pull data from
  - "type": Type of measurement
    - quantitative, ordinal, nominal, temporal

```
{ // Specification of a Single View
...,
"encoding": {
   "x": { // Constant value definition
        "value": ...
},
...
},
```

- Encoding types
  - Quantitative: for data that expresses
     some kind of quantity (e.g.,
     population number)
  - Temporal: for dates and times
  - Ordinal: for discrete ranked data that can be sorted
  - Nominal: for categorical data, doesn't determine magnitude or ordering




"x" is typed as quantitative in the class population demo

- Marks as clickable data points
  - Add properties:
    - Transform
    - Tooltip
    - href

```
"transform": [{
    "calculate": "'https://www.google.com/search?q=' +
datum.Name", "as": "url"
  } ],
  "encoding": {
    "tooltip": {"field": "Name", "type": "nominal"},
    "href": {"field": "url", "type": "nominal"}
```

# Vega-Lite Live Demo




# Vega-Lite Exercise 1

- Vega-Lite Docs: <a href="https://vega.github.io/vega-lite/docs/">https://vega.github.io/vega-lite/docs/</a>
- Using data from this URL:
   https://vega.github.io/editor/data/cars.json,
- Produce a bar chart that aggregates mean of Acceleration grouped by the number of cylinders using encoding field

definition
(No transform)

<u> </u>	
Name:	"buick skylark 320"
Miles_per_Gallon:	15
Cylinders:	8
Displacement:	350
Horsepower:	165
Weight_in_lbs:	3693
Acceleration:	11.5
Year:	"1970-01-01"
Origin:	"USA"



#### Vega-Lite Exercise 1 Solution

```
"data": {"url": "https://vega.github.io/editor/data/cars.json"},


"mark": "bar",

"encoding": {
    "x": {"field": "Cylinders", "type": "ordinal"},
    "y": {"aggregate": "mean", "field": "Acceleration", "type": "quantitative"}
}
```

#### Vega-Lite Exercise 1-1


- From the previous exercise 1,
  - Data: <a href="https://vega.github.io/editor/data/cars.json">https://vega.github.io/editor/data/cars.json</a>
- Produce a bar chart that aggregates mean of Acceleration grouped by the number of cylinders using encoding field definition only for cars produced in the USA

```
"buick skylark 320"
Name:
Miles per Gallon:
                    15
Cylinders:
                     8
Displacement:
                     350
Horsepower:
                    165
Weight in lbs:
                     3693
Acceleration:
                    11.5
Year:
                     "1970-01-01"
Origin:
                     "USA"
```



# Vega-Lite Exercise 1-2

- From the previous exercise 1,
- Produce a bar chart that aggregates mean of Acceleration grouped by the number of cylinders using encoding field definition only for cars produced at or after 1979



# Vega-Lite Exercise Solutions 1-1, 1-2

```
"data": {"url": "https://vega.github.io/editor/data/cars.json"},
"mark": "bar",
"transform": [
   //{"filter": {"field": "Origin", "equal": "USA"}} 1-1 Solution
    {"filter": {"timeUnit": "year", "field": "Year", "gte": "1979"}}
],
"encoding": {
  "x": {"field": "Cylinders", "type": "ordinal"},
  "y": {"aggregate": "mean", "field": "Acceleration", "type": "quantitative"}
```