

IN4MATX 133: User Interface Software

Lecture 7:
TypeScript &
Data Visualization Tools

Announcements

- There are some bonus/optional slides at the end of today's lecture on other TypeScript concepts
- Today covers the last of the material needed for A2
- Discussion on Friday will offer a more in-depth demo into Vega-Lite

Today's goals

By the end of today, you should be able to...

- Write code which follows object-oriented principles in TypeScript
- Explain the advantages and disadvantages of using TypeScript
- Describe the concepts of threshold and ceiling in software tools and what tool designers should be striving to create
- Explain the relative threshold and ceilings of visualization tools like Protovis, D3, and Vega-Lite
- Describe common visualization primitives like marks, axes, and scales
- Implement simple visualizations with Vega-Lite

Using npm to install TypeScript

- `npm install -g typescript`
- Installs `tsc`, the TypeScript transpiler
- Could also install via HomeBrew (mac) or Chocolatey (pc)

So what is TypeScript?

About TypeScript

- Released by Microsoft in 2012
- Originally only supported in Visual Studio
 - Now in Eclipse, Sublime, Webstorm, Atom, etc.
- Latest version is TypeScript 5.0, released in March 2023



About TypeScript

- Introduces static types, type checking, and objects
 - These are all optional!
- A strict superset of JavaScript
 - Syntactically-correct JavaScript will also run in TypeScript
 - Means TypeScript can use popular JavaScript libraries
- “Transcompiles” or “Transpiles” to JavaScript
 - Takes TypeScript code and converts it to equivalent JavaScript code



Typing

- hello.ts

```
var courseNumber:number = 133;
```

```
console.log('Hello, IN4MATX ' + courseNumber + '!');
```

- Transpiling: tsc hello.ts

- Generates hello.js

```
var courseNumber = 133;
```

```
console.log('Hello, IN4MATX ' + courseNumber + '!');
```


Typing

- Pre-defined types
 - Number
 - Boolean
 - String
 - Void (generally a function return type)
 - Null
 - Undefined
 - Any

Typing

- Typing is optional

```
var courseNumber:any = 133;
```

```
var courseNumber = 133;
```

```
console.log('Hello, IN4MATX ' + courseNumber + '!');
```

Typing

- Functions can specify argument types and return types

```
function area(shape: string, width: number, height: number)
{
    var area = width * height;
    return "I'm a " + shape + " of area " + area + " cm^2.";
}
```

// "better" function

```
function area(shape: string, width: number,
height: number):string {
    var area:number = width * height;
    return "I'm a " + shape + " of area " + area + " cm^2.";
}
```


Typing

- Types enable error checking

```
// "better" function
```

```
function area(shape: string, width: number, height:
number):string {
    var area:number = width * height;
    return "I'm a " + shape + " of area " + area + "
cm^2.";
}
```

```
document.body.innerHTML = area(15, 15, 'square');
```

```
error: Argument of type '15' is not assignable to parameter of type 'string'
```

Typescript demo



```
Elements Console Sources
top ▼ Filter
hello my name is theresa
hello my name is theresa
hello my name is theresa
in4matx-133
in4matx-133
two2too2to
two2too2to
two2too2to
two2too2to
> |
```

Question

Which TypeScript files would transpile to `function pythagorean(a, b) {
 var cSq = a * a + b * b;
 return Math.sqrt(cSq);
}` ?

A 1

B 2

C 3

D 1 and 2

E 1, 2, and 3

1 `function pythagorean(a:number, b:number):number {
 var cSq = a*a + b*b;
 return Math.sqrt(cSq);
}`

2 `function pythagorean(a:number, b:number) {
 var cSq = a*a + b*b;
 return Math.sqrt(cSq);
}`

3 `function pythagorean(a, b) {
 var cSq = a * a + b * b;
 return Math.sqrt(cSq);
}`

Which TypeScript files would transpile to `function pythagorean(a, b) {
 var cSq = a * a + b * b;
 return Math.sqrt(cSq);
}` ?

- ☐ A 1
- ☐ B 2
- ☐ C 3
- ☐ D 1 and 2
- ☐ E 1, 2, and 3

```
1 function pythagorean(a:number, b:number):number {  
  var cSq = a*a + b*b;  
  return Math.sqrt(cSq);  
}  
  
2 function pythagorean(a:number, b:number) {  
  var cSq = a*a + b*b;  
  return Math.sqrt(cSq);  
}  
  
3 function pythagorean(a, b) {  
  var cSq = a * a + b * b;  
  return Math.sqrt(cSq);  
}
```

A

0%

B

0%

C

0%

D

0%

E

0%

Question

Which TypeScript files would transpile to `function pythagorean(a, b) {
 var cSq = a * a + b * b;
 return Math.sqrt(cSq);
}` ?

- ☐ A 1
- ☐ B 2
- ☐ C 3
- ☐ D 1 and 2
- ☒ E 1, 2, and 3

1 `function pythagorean(a:number, b:number):number {
 var cSq = a*a + b*b;
 return Math.sqrt(cSq);
}`

2 `function pythagorean(a:number, b:number) {
 var cSq = a*a + b*b;
 return Math.sqrt(cSq);
}`

3 `function pythagorean(a, b) {
 var cSq = a * a + b * b;
 return Math.sqrt(cSq);
}`

Classes

- Also just like in Java, with a constructor and methods

```
class Shape {  
    area: number;  
    color: string;  
    name: string;  
  
    constructor (name: string, width: number, height: number ) {  
        this.name = name  
        this.area = width * height;  
        this.color = "pink";  
    };  
    shoutout() {  
        return "I'm " + this.color + " " + this.name + " with an area of " +  
this.area + " cm squared.";  
    }  
}  
  
var square = new Shape("square", 30, 30);
```

Classes

- Will make a function() with prototype methods when transpiled

//shape.js

```
var Shape = /** @class */ (function () {  
    function Shape(name, width, height) {  
        this.name = name;  
        this.area = width * height;  
        this.color = "pink";  
    }  
    ;  
    Shape.prototype.shoutout = function () {  
        return "I'm " + this.color + " " + this.name + " with an area of  
" + this.area + " cm squared.";  
    };  
    return Shape;  
})();  
var square = new Shape("square", 30, 30);
```

tsconfig.json

- Indicates a TypeScript project
 - Indicates what files or folders to transpile
 - Pick transpiler options, such as whether to remove comments
 - Specify what version of ECMAScript to transpile to
 - `tsc --project tsconfig.json`

Benefits of TypeScript

- Type checking
 - Transpiler can show warnings or errors *before* code is executed
 - Because your editor knows the types, it can autocomplete methods and API features
 - Easier to refactor code
- Object-oriented
 - Easier to manage/maintain large code bases
 - Simple enough to use; same principles as Java and other OO languages

Drawbacks of TypeScript

- Transpiling is occasionally a pain
 - Can be slow for large projects
- Might not work with new JavaScript libraries out of the gate
 - It took a little while for TypeScript to interface nicely with Angular and React, for example
 - Now it's the default for Angular

Other noteworthy JavaScript transpilers

- Dart

- Developed by Google
- Introduces typing and similar object-oriented practices
- Transpiles to JavaScript with dart2js



- Kotlin

- Developed by JetBrains, who develops a lot of IDEs
- Designed to be a “better language” than Java, but still be fully interoperable
- Can transpile to JavaScript with kotlin.js for use with React, etc.



Software Tools and Visualization

**Today is a *very* narrow slice
of visualization**

If you want more, take IN4MATX 143

Sequential programs (command line)

- Program takes control, prompts for input
- Person waits on the program
- Program says when it is ready for more input, which the person then provides



Sequential programs (command line)


```
while true {  
  print "Prompt for Input"  
  input = read_line_of_text()  
  output = do_work()  
  print output  
}
```

- Person is literally modeled as a file



Event-driven programming

- A program waits for a person to provide input
- All communication is done via events
 - Mouse down, item drag, key up
- All events go in a queue
 - Ensures events are handled in order
 - Hides specifics from applications



Basic interactive software loop

- All interactive software has this loop somewhere

```
do {  
    e = read_event();  
    dispatch_event(e);  
    if (damage_exists())  
        update_display();  
} while (e.type != WM_QUIT);
```

← Input
← Processing
← Output

Basic interactive software loop

- Maybe if you've made a game, you've built this loop
- But imagine you had to write this loop every time you wanted to write a webpage, desktop app, or mobile app
- Instead, we rely on tools to handle common operations

```
do {  
    e = read_event();  
    dispatch_event(e);  
    if (damage_exists())  
        update_display();  
} while (e.type != WM_QUIT);
```


Example: a button

- What's behind a button?
 - Set X and Y boundaries
 - Check if mouse down is within those boundaries
 - Check if mouse up is *also* within those boundaries
 - If so, then fire an event
- What if you had to program this sequence every time you wanted to add a button to your website?



Understanding tools

What is a user interface tool?

- Software or libraries which help you build a user interface
 - Bootstrap is a user interface tool, designed to help make interfaces responsive
 - Angular, React, etc. are all user interface tools

Understanding tools

We use tools because they...

- Identify common or important practices
- Package those practices in a framework
- Make it easy to follow those practices
- Make it easier to focus on the application we're building

Understanding tools

Tools enable...

- Faster and more iterative design
- Better implementation than without the tool
- Consistency across applications using the same tool

Understanding tools

Why is designing tools difficult?

- Need to understand the core practices and problems
- Those are often evolving with technology and design
- The tasks people are trying to solve change quickly, so tools struggle to keep up

Understanding tools

Key terms

- Threshold: How hard to get started
- Ceiling: How much can be achieved
- Path of least resistance: Tools influence what interfaces are created
- Moving targets: Changing needs make tools obsolete

Threshold

How hard to get started

- Some tools are harder to pick up
- Depends on what a person knows already
 - A new programming language adds to the threshold
 - If a tool borrows concepts from another popular tool, it will be easier for many people to pick up

Ceiling


How much can be achieved

- Tools restrict what's possible
 - Your program could do much more if it had direct access to the bits on your computing device

Path of least resistance

Tools influence what interfaces are created

- Remember the concern that all Bootstrap pages look similar?
- Sapir-Whorf Hypothesis
 - Roughly, some thoughts in one language cannot be expressed or understood in another language
- Our tools frame how we think about interaction and design





Brad Myers, Scott E. Hudson, and Randy Pausch. TOCHI, 2000. Past, present, and future of user interface software tools.
<https://doi.org/10.1145/344949.344959>

Moving targets

Changing needs make tools obsolete

- Codification eventually constrains design
 - Our understanding of how people interact with technology improves
 - New technology comes along to change the needs of tools
 - Example: Virtual reality has wildly different interactions and tool needs

Question



Relative to each other, what are the *threshold* and *ceiling* of Adobe Photoshop and Microsoft Paint?
(They're tools for making images, but the principles apply)

- (A) Photoshop: high ceiling, high threshold; Paint: low ceiling, low threshold
- (B) Photoshop: high ceiling, low threshold; Paint: low ceiling, high threshold
- (C) Photoshop: low ceiling, high threshold; Paint: high ceiling, low threshold
- (D) Photoshop: low ceiling, low threshold; Paint: high ceiling, high threshold
- (E) I'm confused, just clicking in to get participation credit

I7-Q2

Photoshop: high ceiling, high threshold; Paint: low ceiling, low threshold

0%

Photoshop: high ceiling, low threshold; Paint: low ceiling, high threshold

0%

Photoshop: low ceiling, high threshold; Paint: high ceiling, low threshold

0%



Photoshop: low ceiling, low threshold; Paint: high ceiling, high threshold

0%

I'm confused, just clicking in to get participation credit

0%

Question




Relative to each other, what are the *threshold* and *ceiling* of Adobe Photoshop and Microsoft Paint?
(They're tools for making images, but the principles apply)

- A** Photoshop: high ceiling, high threshold; Paint: low ceiling, low threshold
- B** Photoshop: high ceiling, low threshold; Paint: low ceiling, high threshold
- C** Photoshop: low ceiling, high threshold; Paint: high ceiling, low threshold
- D** Photoshop: low ceiling, low threshold; Paint: high ceiling, high threshold
- E** I'm confused, just clicking in to get participation credit

Threshold and ceiling

- It's all relative; no absolute measure
- Tools should be *low threshold*
 - Easy to pick up
- But tools should also be *high ceiling*
 - Can do a lot
- The best tools are both
 - Photoshop introduces tutorials, etc. to lower the threshold



**Ok, so what does any of this
have to do with visualization?**

Scaleable Vector Graphics (SVG)



- XML format for specifying graphics
 - Looks somewhat like HTML
 - Most browsers can render them
- Composed of lines, circles, rectangles, etc.

```
<svg width="100" height="100">  
  <circle cx="50" cy="50" r="40" stroke="green" stroke-  
width="4" fill="yellow" />  
</svg>
```



Visualization tools

- Are governed by the same principles
- Scalable vector graphics (svg)
 - High ceiling, but high threshold
- Microsoft excel
 - Low threshold, but low ceiling

Successive Loss of French Army During Napoleon's Russian Campaign



<https://www.edwardtufte.com/tufte/posters>



Declarative languages

- Programming by describing *what*, not *how*
- Separate specification (*what you want*) from execution (*how it should be computed*)
- Contrasts to **imperative** programming, where you must give explicit steps

Declarative languages

HTML



Markup
language

CSS



Styling
language

JS



Programming
language

Declarative languages

HTML



Declarative
language

CSS



Declarative
language

JS



Imperative
language

Declarative languages

HTML



```
<main class="container">
  <div class="row">
    <div class="col-3">A</div>
    <div class="col-6">B</div>
    <div class="col-4">C</div>
    <div class="col">D</div>
    <div class="col">E</div>
  </div>
</main>
```

What should be rendered, but not how

JS



```
var array = ['1', 'fish', 2, 'blue'];
array[5] = 'dog';
array.push('2');
array[2] = array[array.length - 1] - 4;
array[0] = typeof array[2];
array[4] = array.indexOf('blue');

console.log(array.join('*'));
```


Step-by-step

Why declarative languages?

- Faster iteration, less code
 - Easier to pick up; lower threshold
- Can be generated programmatically

Protovis


- Initial grammar for visualization
- A composition of data-representative marks
 - Self-contained JavaScript model (doesn't export to SVG or anything else)



Michael Bostock, Jeffrey Heer. IEEE Vis, 2009. Protovis: A Graphical Toolkit for Visualization.
<https://doi.org/10.1109/TVCG.2009.174>

Protovis


- Marks: graphical primitives
 - Marks specify how content should be rendered



Protovis


```
var vis = new pv.Panel();
vis.add(pv.Bar) ← Mark
  .data([1, 1.2, 1.7, 1.5, 0.7])
  .visible(true)
  .left((d) => this.index * 25)
  .bottom(0)
  .width(20)
  .height((d) => d * 80) ←
  .fillStyle("blue")
  .strokeStyle("black")
  .lineWidth(1.5);
vis.render();
```

Literally specifies
which pixel each bar
should start at and
how many pixels tall
it should be



D3

- Binds data directly to a web page's DOM by editing a SVG
- More expressive! Can make anything an SVG can make
- Enables interactivity, can access mouse & keyboard events through the same tools as a browser
- Much more complex...



Michael Bostock, Vadim Ogievetsky, Jeffrey Heer. IEEE Vis, 2011. D3: Data Driven Documents.
<http://doi.ieeecomputersociety.org/10.1109/TVCG.2011.185>

D3

```
var svg = d3.select(DOM.svg(width,  
height));
```




Find SVG in the DOM

```
svg.append("g")  
  .attr("fill", "steelblue")  
  .selectAll("rect").data(data).enter()  
  .append("rect") ← No more mention of marks!  
    .attr("x", d => x(d.name))  
    .attr("y", d => y(d.value))  
    .attr("height", d => y(0) -  
y(d.value))  
    .attr("width", x.bandwidth());
```

```
svg.append("g")  
  .call(xAxis);
```

```
svg.append("g")  
  .call(yAxis);
```



Michael Bostock, Vadim Ogievetsky, Jeffrey Heer. IEEE Vis, 2011. D3: Data Driven Documents.
<http://doi.ieeecomputersociety.org/10.1109/TVCG.2011.185>

D3

```
var svg = d3.select("body").append("svg")
    .attr("width", width + margin.left + margin.right)
    .attr("height", height + margin.top + margin.bottom)
    .append("g")
    .attr("transform", "translate(" + margin.left + "," + margin.top + ")");

d3.tsv("VotingInformation.tsv", function(error, data){
    // filter year
    var data = data.filter(function(d){return d.Year == '2012';});
    // Get every column value
    var elements = Object.keys(data[0])
        .filter(function(d){
            return ((d != "Year") & (d != "State"));
        });
    var selection = elements[0];
    var y = d3.scale.linear()
        .domain([0, d3.max(data, function(d){
            return +d[selection];
        })])
        .range([height, 0]);

    var x = d3.scale.ordinal()
        .domain(data.map(function(d){ return d.State;}))
        .rangeBands([0, width]);

    var xAxis = d3.svg.axis()
        .scale(x)
        .orient("bottom");
    var yAxis = d3.svg.axis()
        .scale(y)
        .orient("left");

    svg.append("g")
        .attr("class", "x axis")
        .attr("transform", "translate(0," + height + ")")
        .call(xAxis)
        .selectAll("text")
        .style("font-size", "8px")
        .style("text-anchor", "end")
        .attr("dx", "-.8em")
        .attr("dy", "-.55em")
        .attr("transform", "rotate(-90)");

    svg.append("g")
        .attr("class", "y axis")
        .call(yAxis);

    svg.selectAll("rectangle")
        .data(data)
        .enter()
        .append("rect")
        .attr("class", "rectangle")
        .attr("width", width/data.length)
        .attr("height", function(d){
            return height - y(+d[selection]);
        })
        .attr("x", function(d, i){
            return (width / data.length) * i;
        })
        .attr("y", function(d){
            return y(+d[selection]);
        })
        .append("title")
        .text(function(d){
            return d.State + " : " + d[selection];
        });

    var selector = d3.select("#drop")
        .append("select")
        .attr("id", "dropdown")
        .on("change", function(d){
            selection = document.getElementById("dropdown");

            y.domain([0, d3.max(data, function(d){
                return +d[selection.value];
            })]);

            yAxis.scale(y);


            d3.selectAll(".rectangle")
                .transition()
                .attr("height", function(d){
                    return height - y(+d[selection.value]);
                })
                .attr("x", function(d, i){
                    return (width / data.length) * i;
                })
                .attr("y", function(d){
                    return y(+d[selection.value]);
                })
                .ease("linear")
                .select("title")
                .text(function(d){
                    return d.State + " : " + d[selection.value];
                });

            d3.selectAll("g.y.axis")
                .transition()
                .call(yAxis);

        });


    selector.selectAll("option")
        .data(elements)
        .enter().append("option")
        .attr("value", function(d){
            return d;
        })
        .text(function(d){
            return d;
        })
    });
});
```

~118 lines of code,
plus data in a separate file




Michael Bostock, Vadim Ogievetsky, Jeffrey Heer. IEEE Vis, 2011. D3: Data Driven Documents.
<http://doi.ieeecomputersociety.org/10.1109/TVCG.2011.185>

Protovis & D3



Protovis
Low(er) ceiling



D3
High(er) ceiling

Compared to excel, etc., both have a high ceiling
But both have a pretty high threshold!


Vega-Lite: lowering the threshold

Lowering the threshold

- Goal: “create an *expressive* (high ceiling) yet *concise* (low threshold) declarative language for specifying visualizations”

Vega-Lite

- Grammar of graphics
 - Data: input data to visualize
 - Mark: Data-representative graphics
 - Transform: whether to filter, aggregate, bin, etc.
 - Encoding: mapping between data and mark properties
 - Scale: map between data values and visual values
 - Guides: axes & legends that visualize scales




JSON file

```
[
  {
    "date": "2015/01/01",
    "weather": "sun",
    "temperature": 1.1999999999999997
  },
  {
    "date": "2015/01/02",
    "weather": "fog",
    "temperature": 2.8
  },
  {
    "date": "2015/01/03",
    "weather": "fog",
    "temperature": 3.35
  },
  {
    "date": "2015/01/04",
    "weather": "fog",
    "temperature": 6.949999999999999
  },
  {
    "date": "2015/01/05",
    "weather": "fog",
    "temperature": 10.8
  },
  ...
]
```


Vega-lite


Making a histogram



Vega-lite

Histogram = (Bar with x=binned field, y=count)

- Bin records by their temperature
- Count how many records fall into each bin
- Render those bins as vertical bars



Vega-lite

Histogram = (Bar with x=binned field, y=count)


```
{  
  data: {url: "weather-seattle.json"},  
  mark: "tick",  
  encoding: {  
    x: {  
      field: "temperature",  
      type: "quantitative"  
    }  
  }  
}
```

← Set mark as a tick

Encode x according to the
"temperature" field




Four types:
quantitative (numerical)
temporal (time)
ordinal (ordered)
nominal (categorical)



Vega-lite

Histogram = (Bar with x=binned field, y=count)

```
{
  data: {url: "weather-seattle.json"},
  mark: "tick",
  encoding: {
    x: {
      bin: true, ← Bin values by x dimension
      field: "temperature",
      type: "quantitative"
    }
  }
}
```




Vega-lite

Histogram = (Bar with x=binned field, y=count)

```
{
  data: {url: "weather-seattle.json"},
  mark: "tick",
  encoding: {
    x: {
      bin: true,
      field: "temperature",
      type: "quantitative"
    },
    y: {
      aggregate: "count",
      type: "quantitative"
    }
  }
}
```

← y should aggregate the bins by counting how many values are in them




Vega-lite

Histogram = (Bar with x=binned field, y=count)

```
{
  data: {url: "weather-seattle.json"},
  mark: "bar",
  encoding: {
    x: {
      bin: true,
      field: "temperature",
      type: "quantitative"
    },
    y: {
      aggregate: "count",
      type: "quantitative"
    }
  }
}
```


← Change the mark to a bar



Vega-lite

Histogram + Color


```
{
  data: {url: "weather-seattle.json"},
  mark: "bar",
  encoding: {
    x: {
      bin: true,
      field: "temperature",
      type: "quantitative"
    },
    y: {
      aggregate: "count",
      type: "quantitative"
    },
    color: { ← Set the color to follow the weather
      field: "weather",
      type: "nominal"
    }
  }
}
```



Vega-lite

“Sensible defaults”

- The field chose reasonable defaults for presenting the data
 - We didn't specify what colors to use
 - Or how wide bins should be
 - Or how to label the axes
 - Or that the bars should be stacked
 - ...




Vega-lite

Overriding the sensible defaults

```
{
  data: {url: "weather-seattle.json"},
  mark: "bar",
  encoding: {
    x: {
      bin: true,
      field: "temperature",
      type: "quantitative"
    },
    y: {
      aggregate: "count",
      type: "quantitative"
    },
    color: {
      field: "weather",
      type: "nominal"
    },
    scale: {
      domain: ["sun", "fog", "drizzle", "rain", "snow"],
      range: ["#e7ba52", "#c7c7c7", "#aec7e8",
              "#1f77b4", "#9467bd"]
    }
  }
}
```

Set our own
color scale




Vega-lite

Monthly precipitation

```
{
  data: {url: "weather-seattle.json"},
  mark: "bar",
  encoding: {
    x: {
      timeUnit: "month", field: "date",
      type: "quantitative"
    },
    y: {
      aggregate: "mean",
      field: "precipitation",
      type: "quantitative"
    }
  }
}
```

Field is a date string ("2018-10-17"),
but display and bin it as a month


Aggregate by the mean



Vega-lite demo




U.S. age distribution in 2000



Question

How would this visualization be specified in Vega-Lite?
(Assume field names are correct)



A `mark: "point",
 encoding: {
 x: {field: "MPG", type: "ordinal"},
 y: {field: "Horsepower", type: "ordinal"},
 color: {field: "Origin", type: "nominal"}
 }`


B `mark: "point",
 encoding: {
 x: {field: "Horsepower", type: "quantitative"},
 y: {field: "MPG", type: "quantitative"},
 color: {field: "Origin", type: "nominal"}
 }`

D `mark: "point",
 encoding: {
 x: {field: "Horsepower", type: "quantitative"},
 y: {field: "MPG", type: "quantitative"},
 color: {field: "Origin", type: "ordinal"}
 }`

C `mark: "ticks",
 encoding: {
 x: {field: "Horsepower", type: "quantitative"},
 y: {field: "MPG", type: "quantitative"},
 color: {field: "Origin", type: "nominal"}
 }`

E `mark: "ticks",
 encoding: {
 x: {field: "MPT", type: "ordinal"},
 y: {field: "Horsepower", type: "ordinal"},
 color: {field: "Origin", type: "nominal"}
 }`

How would this visualization be specified in Vega-Lite? (Assume field names are correct)



A `mark: "point",
encoding: {
 x: {field: "MPG", type: "ordinal"},
 y: {field: "Horsepower", type: "ordinal"},
 color: {field: "Origin", type: "nominal"}
}`

B `mark: "point",
encoding: {
 x: {field: "Horsepower", type: "quantitative"},
 y: {field: "MPG", type: "quantitative"},
 color: {field: "Origin", type: "nominal"}
}`

D `mark: "point",
encoding: {
 x: {field: "Horsepower", type: "quantitative"},
 y: {field: "MPG", type: "quantitative"},
 color: {field: "Origin", type: "ordinal"}
}`

C `mark: "ticks",
encoding: {
 x: {field: "Horsepower", type: "quantitative"},
 y: {field: "MPG", type: "quantitative"},
 color: {field: "Origin", type: "nominal"}
}`

E `mark: "ticks",
encoding: {
 x: {field: "MPT", type: "ordinal"},
 y: {field: "Horsepower", type: "ordinal"},
 color: {field: "Origin", type: "nominal"}
}`

A

0%

B

0%

C

0%

D


0%

E

0%

Question

How would this visualization be specified in Vega-Lite?
(Assume field names are correct)



A `mark: "point",
 encoding: {
 x: {field: "MPG", type: "ordinal"},
 y: {field: "Horsepower", type: "ordinal"},
 color: {field: "Origin", type: "nominal"}
 }`

B `mark: "point",
 encoding: {
 x: {field: "Horsepower", type: "quantitative"},
 y: {field: "MPG", type: "quantitative"},
 color: {field: "Origin", type: "nominal"}
 }`

D `mark: "point",
 encoding: {
 x: {field: "Horsepower", type: "quantitative"},
 y: {field: "MPG", type: "quantitative"},
 color: {field: "Origin", type: "ordinal"}
 }`

C `mark: "ticks",
 encoding: {
 x: {field: "Horsepower", type: "quantitative"},
 y: {field: "MPG", type: "quantitative"},
 color: {field: "Origin", type: "nominal"}
 }`

E `mark: "ticks",
 encoding: {
 x: {field: "MPT", type: "ordinal"},
 y: {field: "Horsepower", type: "ordinal"},
 color: {field: "Origin", type: "nominal"}
 }`

Sensible defaults: Vega-lite's secret

- Threshold is lower
 - More concise definitions, less to understand up front
- Ceiling remains the same
 - The sensible defaults can be overridden
- A downside: visualizations made with Vega-Lite look similar
 - The path of least resistance Vega-Lite provides influences what visualizations people make and what they look like

Downside: path of least resistance

- The path of least resistance: tools influence what is created
- Sensible defaults make Vega-Lite visualizations look similar to one another
 - These defaults *can* be overwritten, but are they in practice?
- Similar concern to the widespread adoption of grid frameworks

Today's goals

By the end of today, you should be able to...

- Write code which follows object-oriented principles in TypeScript
- Explain the advantages and disadvantages of using TypeScript
- Describe the concepts of threshold and ceiling in software tools and what tool designers should be striving to create
- Explain the relative threshold and ceilings of visualization tools like Protovis, D3, and Vega-Lite
- Describe common visualization primitives like marks, axes, and scales
- Implement simple visualizations with Vega-Lite

IN4MATX 133: User Interface Software

Lecture 7:
TypeScript &
Data Visualization Tools

A few more TypeScript details

Type declaration files

- Because types get stripped out when transpiling, a “declaration file” (`.d.ts`) can be created
 - Important when someone else will use your code as a library
 - Declaration file helps their code check types in your library
 - `tsc --declaration test.ts`
- You can install typings declarations for many libraries from npm
 - `npm install --save @types/your-library-here`

Type declaration files

```
//test.ts
function area(shape: string, width: number, height: number):string {
    var area:number = width * height;
    return "I'm a " + shape + " of area " + area + " cm^2.";
}

document.body.innerHTML = area('square', 15, 15);
```

```
// transpiled test.js
function area(shape, width, height) {
    var area = width * height;
    return "I'm a " + shape + " of area " + area + " cm^2.";
}

document.body.innerHTML = area('square', 15, 15);
```

```
// generated test.d.ts
declare function area(shape: string, width: number, height: number): string;
```


Interfaces

- Just like in Java, describes the “inputs” and “outputs” of an object

```
interface Shape {  
    name: string;  
    width: number;  
    height: number;  
    color?: string; // ? Specifies an "optional" value  
}
```

```
function area(shape : Shape):string {  
    var area = shape.width * shape.height;  
    return "I'm " + shape.name + " with area " + area + " cm squared";  
}
```

```
console.log(area({name: "rectangle", width: 30, height: 15}));  
console.log(area({name: "square", width: 30, height: 30, color: "red"}));
```

Inheritance

- Like in Java, classes and interfaces can be extended

```
class Shape3D extends Shape {
    volume: number;

    constructor (name: string, width: number, height: number, length: number ) {
        super( name, width, height ); //calls base class constructor
        this.volume = length * this.area;
    };

    shoutout() { //overrides the base class
        return "I'm " + this.name + " with a volume of " + this.volume + " cm cube.";
    }

    superShout() { //calls base class shoutout method
        return super.shoutout();
    }
}

var cube = new Shape3D("cube", 30, 30, 30);
console.log( cube.shoutout() );
console.log( cube.superShout() );
```

Generics

- Also work the same as Java

```
function identity<T>(arg: T): T {  
    return arg;  
}
```

```
let output = identity<stringoutput will be 'string'  
let output = identity( "myString" );    // type of output  
will be 'string'
```

<https://www.typescriptlang.org/docs/handbook/generics.html>

Getter functions

- Also work the same a Java

```
const fullNameMaxLength = 10;
```

```
class Employee {  
    private _fullName: string = "";
```

```
    get fullName(): string {  
        return this._fullName;  
    }
```

```
    set fullName(newName: string) {  
        if (newName && newName.length > fullNameMaxLength) {  
            throw new Error("fullName has a max length of " + fullNameMaxLength);  
        }  
        this._fullName = newName;  
    }
```

```
}
```

<https://www.typescriptlang.org/docs/handbook/generics.html>

Multiple (union) types

- You can indicate multiple types that a variable could have with the “|” operator

Union Types

JavaScript functions may take a number of possible argument types. Up to now, we've supported this using function overloads. Starting with TypeScript 1.4, we've generalized this capability and now allow you to specify that a value is one of a number of different types using a union type:

```
function f(x: number | number[]) {  
  if (typeof x === "number") {  
    return x + 10;  
  }  
  else {  
    // return sum of numbers  
  }  
}
```

Copy

<https://devblogs.microsoft.com/typescript/announcing-typescript-1-4/>

Multiple types and optional methods

- You can specify optional arguments by labeling them with a “?”, or using an “=” to give a default

Optional Parameters

Functions in JavaScript often take a variable number of arguments. For example, the `toFixed` method of `number` takes an optional digit count:

```
function f(n: number) {  
  console.log(n.toFixed()); // 0 arguments  
  console.log(n.toFixed(3)); // 1 argument  
}
```

We can model this in TypeScript by marking the parameter as *optional* with `?`:

```
function f(x?: number) {  
  // ...  
}  
f(); // OK  
f(10); // OK
```

Although the parameter is specified as type `number`, the `x` parameter will actually have the type `number | undefined` because unspecified parameters in JavaScript get the value `undefined`.

You can also provide a parameter *default*:

```
function f(x = 10) {  
  // ...  
}
```

<https://www.typescriptlang.org/docs/handbook/2/functions.html#optional-parameters>