Surrogate Modelling of the Tritium Breeding Ratio

Petr Mánek Graham Van Goffrier

Centre for Doctoral Training in Data Intensive Science
University College London

22nd June 2020



UK Atomic
Energy
Authority

Project Background

Nuclear fusion – the energy of the future!

- Must produce and contain an extremely hot and dense plasma
  - Magnetic Confinement Fusion (MCF): toroidal circulation
  - Inertial Confinement Fusion (ICF): spherical compression

- Modern designs require enriched Hydrogen fuel of two varieties:
  - Deuterium (^{2}H) – abundant in naturally-sourced water
  - Tritium (^{3}H) – extremely rare, but can be produced *in-reactor*



Problem Description

Tritium breeding blankets convert neutron radiation from the fusion plasma into a steady supply of tritium fuel.

$$ {}^{1}_{0}n + {}^{6}_{3}Li \rightarrow {}^{3}_{1}H + {}^{4}_{2}He \qquad {}^{1}_{0}n + {}^{7}_{3}Li \rightarrow {}^{3}_{1}H + {}^{4}_{2}He + {}^{1}_{0}n $$

However, the tritium breeding ratio (TBR) depends on numerous geometric and material parameters.

TBR evaluation *Paramak* achieves very accurate results by OpenMC Monte Carlo neutronics simulation, but is computationally expensive.

Our Challenge:

Produce a fast TBR function which strongly approximates Paramak, making use of the latest in surrogate modelling techniques.

Data Generation

We designed the Approximate TBR Evaluator (ATE) package to generate training and test datasets from Paramak.

UCL's Hypatia cluster provided the multithreading power for us to produce one million TBR samples, representing 27 days of runtime.

These runs included full evaluations on the 18 continuous discrete parameters of Paramak, and "slice" evaluations with all discrete parameters frozen.

	Parameter name	Domain
Blanket	Breeder fraction†	$[0, 1]$
	Breeder ^{6}Li enrichment fraction	$[0, 1]$
	Breeder material	$\{Li_2TiO_3, Li_4SiO_4\}$
	Breeder packing fraction	$[0, 1]$
	Coolant fraction†	$[0, 1]$
	Coolant material	$\{D_2O, H_2O, He\}$
	Multiplier fraction†	$[0, 1]$
	Multiplier material	$\{Be, Be_{12}Ti\}$
	Multiplier packing fraction	$[0, 1]$
	Structural fraction†	$[0, 1]$
	Structural material	$\{SiC, eurofer\}$
	Thickness	$[0, 500]$
First wall	Armour fraction‡	$[0, 1]$
	Coolant fraction‡	$[0, 1]$
	Coolant material	$\{D_2O, H_2O, He\}$
	Structural fraction‡	$[0, 1]$
	Structural material	$\{SiC, eurofer\}$
	Thickness	$[0, 20]$

Methodology

Conventional regression task – search for a cheap surrogate $\hat{f}(x)$ that minimizes dissimilarity with an expensive function $f(x)$:

- Regression performance (capability to approximate)
  - Absolute: mean absolute error, σ of error
  - Relative: R^2, $R^2_{\text{adj.}}$
- Computational complexity: wall training & prediction time / sample.

2 approaches for surrogate training:

1. Decoupled – trains models from previously sampled $\mathcal{T} = \{(x, f(x))\}$.
2. Adaptive – repeats sampling & model training, increases sampling density in low-performance regions.

Outline

Experiments 1 & 2: Hyperparameter Tuning









- Experiment 1 (3x top), Experiment 2 (left).
- Showing the best 20 surrogates per family.
- Omitting discrete features yields only a negligible improvement in performance.
- Overall dominated by tree-based surrogates (GBTs, ERTs) and neural networks.

Experiment 3: Scaling Benchmark

Experiment 4: Model Comparison

The QASS Algorithm

Application on Toy Theory

Conclusion