


Surrogate Modelling of the Tritium Breeding Ratio

Petr Mánek Graham Van Goffrier

Centre for Doctoral Training in Data Intensive Science
University College London

22nd June 2020




UK Atomic
Energy
Authority

Project Background

Nuclear fusion – the energy of the future!

- Must produce and contain an extremely hot and dense plasma
 - Magnetic Confinement Fusion (MCF): toroidal circulation
 - Inertial Confinement Fusion (ICF): spherical compression
- Modern designs require enriched Hydrogen fuel of two varieties:
 - Deuterium (^2H) – abundant in naturally-sourced water
 - Tritium (^3H) – extremely rare, but can be produced *in-reactor*



Tritium breeding blankets convert neutron radiation from the fusion plasma into a steady supply of tritium fuel.



However, the tritium breeding ratio (TBR) depends on numerous geometric and material parameters.

TBR evaluation *Paramak* achieves very accurate results by OpenMC Monte Carlo neutronics simulation, but is computationally expensive.

Our Challenge:

Produce a fast TBR function which strongly approximates Paramak, making use of the latest in surrogate modelling techniques.

We designed the Approximate TBR Evaluator (ATE) package to generate training and test datasets from Paramak.

UCL's Hypatia cluster provided the multithreading power for us to produce one million TBR samples, representing 27 days of runtime.

These runs included full evaluations on the 18 continuous discrete parameters of Paramak, and "slice" evaluations with all discrete parameters frozen.

	Parameter name	Domain
Blanket	Breeder fraction [†]	[0, 1]
	Breeder ⁶ Li enrichment fraction	[0, 1]
	Breeder material	{Li ₂ TiO ₃ , Li ₄ SiO ₄ }
	Breeder packing fraction	[0, 1]
	Coolant fraction [†]	[0, 1]
	Coolant material	{D ₂ O, H ₂ O, He}
	Multiplier fraction [†]	[0, 1]
	Multiplier material	{Be, Be ₁₂ Ti}
	Multiplier packing fraction	[0, 1]
	Structural fraction [†]	[0, 1]
First wall	Structural material	{SiC, eurofer}
	Thickness	[0, 500]
	Armour fraction [†]	[0, 1]
	Coolant fraction [†]	[0, 1]
	Coolant material	{D ₂ O, H ₂ O, He}
	Structural fraction [†]	[0, 1]
	Structural material	{SiC, eurofer}
	Thickness	[0, 20]

Conventional regression task – search for a cheap surrogate $\hat{f}(x)$ that minimizes dissimilarity with an expensive function $f(x)$:

- Regression performance (capability to approximate)
 - Absolute: mean absolute error, σ of error
 - Relative: R^2 , R_{adj}^2 .
- Computational complexity: wall training & prediction time / sample.





2 approaches for surrogate training:

- 1 Decoupled – trains models from previously sampled $\mathcal{T} = \{(x, f(x))\}$.
- 2 Adaptive – repeats sampling & model training, increases sampling density in low-performance regions.

Outline






Experiments 1 & 2: Hyperparameter Tuning



- Experiment 1 (3× top), Experiment 2 (left).
- Showing the best 20 surrogates per family.
- Omitting discrete features yields only a negligible improvement in performance.
- Overall dominated by tree-based surrogates (GBTs, ERTs) and neural networks.

Experiment 3: Scaling Benchmark


- We observe a hierarchy.
 - Best-performing families from the previous experiments also scale the best in t_{pred} .
 - More samples: neural networks outperform tree-based models.
 - Instance-based surrogates offer train trivially but have complex lookup strategies.
 - Neural networks show inverse scaling due to parallelization.



Experiment 4: Model Comparison

- Plots show true vs. predicted TBR by Models 1-8, coloured by density.
- Best regression performance:
 - Model 1, ANN, 500K samples.
 - $R^2 = 0.998$, $\sigma = 0.013$,
 - $\bar{t}_{\text{pred.}} = 1.124 \mu\text{s}$, $6916416 \times$ faster.
- Fastest prediction:[†]
 - Model 2, ANN, 500K samples.
 - $R^2 = 0.985$, $\sigma = 0.033$,
 - $\bar{t}_{\text{pred.}} = 0.898 \mu\text{s}$, $8659251 \times$ faster.
- Smallest training set:[†]
 - Model 4, GBT, 10K samples.
 - $R^2 = 0.913$, $\sigma = 0.072$,
 - $\bar{t}_{\text{pred.}} = 6.125 \mu\text{s}$, $1269777 \times$ faster.

[†] with acceptable regression performance.



The QASS Algorithm



Application on Toy Theory



Conclusion

