

Stackschool

ACM Hack

Contents

Contents	ii
1 Introduction to Full Stack	1
2 Servers	2
2.1 Servers In General	2
2.2 Web API's: What's on the Menu?	5
2.3 Server Implementations	7
3 Databases	8
4 Backend Integration	9
5 Advanced Frontend	10

Introduction to Full Stack

1

Hello, here is some text without a meaning. This text should show what a printed text will look like at this place. If you read this text, you will get no information. Really? Is there no information? Is there a difference between this text and some nonsense like “Huardest gefburn”? Kjift – not at all! A blind text like this gives you information about the selected font, how the letters are written and an impression of the look. This text should contain all letters of the alphabet and it should be written in of the original language. There is no need for special content, but the length of words should match the language.

*"Simplicity, carried to an extreme,
becomes elegance."*

– Jon Franklin

Servers are probably one of the most misunderstood concepts for new developers. If you put ten new developers in a room, it's a pretty good bet that they've all *heard* of servers. Maybe they've been exposed to them through pop culture. They've seen movies or read books where the nerdy, basement dwelling side character is approached by the charismatic protagonist to "hack into the mainframe" to stop the evil corporation and save the world.¹ Or maybe they've come across the terminology at some point while learning about the fundamentals of programming, with their instructors glossing over it saying, "don't worry about this yet." Whatever the case may be, it's likely that a majority of the ten new developers you have confined to a room would not be able to tell you what exactly a server does, or why. Or even more fundamentally, what *is* a server?

In a way, this lack of understanding almost serves as a hint to what a server is: a blackbox² to process and retrieve information. We see this concept, **abstraction**, fairly frequently in programming and Computer Science. Through abstraction, we make it far simpler for others to interact with our programs. It's a very important concept, and we'll be digging into it in detail throughout this chapter.

This write-off of servers as blackboxes is great if we just want to use them to get some data. It makes our job much easier! In fact, you interact with servers (indirectly) every single day just by browsing the internet³. However, when it comes time to create our own, it's important to have a deeper understanding. And that's what we aim to accomplish here! By first instilling in you an idea of the *fundamental* concept of a server⁴, and later showing one possible implementation (among many), we'll break the blackbox open and expose the ideas within.

2.1 Servers In General

Put simply, a server is a computer like any other. What distinguishes a regular old computer and a server is that **servers are given the task of listening and responding to requests**. These tend to be requests for data or to perform some task and in general they come from other computers⁵. We call these "other" computers **clients**. You can think of the interaction between a server and a client in much the same way as the interaction between a customer at a restaurant and the restaurant's staff. Just as a customer can request a glass of water, new silverware, or a half serving of Tiramisú, a client can request some function to be performed or data to be processed and returned. This brings up an important question: how do the client and server communicate? A customer at a restaurant might use English or Portuguese, but unfortunately computers aren't

2.1 Servers In General 2

2.2 Web API's: What's on the Menu? 5

2.3 Server Implementations . . 7

1: Note that a mainframe is just a special name for a server that is capable of performing a large amount of concurrent operations. Whether or not "hacking" into one will save the world is another question.

2: A blackbox is a term for an object that takes some input and transforms it into some desired output, with the user not necessarily knowing the details of how it works.

3: Can you imagine if you had to be familiar with all the intricacies of servers just to watch a YouTube video?

4: Note that we won't go over all the low level implementation details. That's for your upper division CS classes to cover!

5: We will see that it's not always the case that requests originate from other computers. A single computer can be both the server and the client, and you'll see that this is actually very common, particularly during the development process of a full stack application.

quite there yet. They must have some standard, agreed upon language in order to do so.

The Language of Requests

In the context of clients and servers, the "language" that is typically used is **HTTP**, or Hypertext Transfer Protocol⁶. This protocol makes it easier for servers to parse through a client's request due to the fixed format. Take a look at the following example of a real HTTP request:

```
1 GET / HTTP/1.1
2 Host: www.example.com
3 User-Agent: Mozilla/5.0
4 Accept: text/html,application/xhtml+xml,application/xml;
5 q=0.9,image/avif,image/webp,*/*;q=0.8
6 Accept-Language: en-GB,en;q=0.5
7 Accept-Encoding: gzip, deflate, br
8 Connection: keep-alive
```

6: Note that there are other protocols that can be used, such as WebRTC, and each have their advantages. For now, let's not get into the weeds too much, but I recommend reading up on protocols if you're interested.

It may seem strange and hard to read as a human, but it is perfectly formatted for computers. We don't have to worry about the exact formatting as creating these requests is typically automated, but I do want to point out one key detail: the word **GET**. **GET** indicates to the server the particular action desired by the client, and it is one of several so called **HTTP request methods**. We'll discuss these in more detail and show several examples, so don't worry if you haven't quite grasped the concept yet. For now, here are a few essential methods to be aware of⁷:

- **GET**: indicates a request for some data
- **POST**: submits data to the server which often results in some side effect or change to the server's state
- **PUT**: submits data to the server in order to update an existing resource
- **DELETE**: removes some resource from the server

7: There are methods beyond these. Check out Mozilla's [article](#) on the subject if you're interested.

After receiving a well-formed request, the server will perform the specified action and create a **response** to send back to the client. The format of a response is also standardized by HTTP, and here is an example:

```
1 HTTP/1.1 200 OK
2 Date: Mon, 23 May 2005 22:38:34 GMT
3 Content-Type: text/html; charset=UTF-8
4 Content-Length: 155
5 Last-Modified: Wed, 08 Jan 2003 23:11:55 GMT
6 Server: Apache/1.3.3.7 (Unix) (Red-Hat/Linux)
7 ETag: "3f80f-1b6-3e1cb03b"
8 Accept-Ranges: bytes
9 Connection: close
10
11 <html>
12 <head>
13   <title>An Example Page</title>
14 </head>
15 <body>
16   <p>Hello World, this is a very simple HTML document.</p>
17 </body>
18 </html>
```

The first thing you might notice is that the response seems to have HTML embedded into it. Why might that be? Let's come back to that. Take a look at the first line of the response. As before, it indicates that it is following HTTP, but it also has the number 200 and the word OK. This is known as an **HTTP response code** and it represents the result of the server's attempt to address the client's request. In this case, 200 OK indicates that the request was successfully, received, understood, and accepted. There are many response codes but they all fall into the following categories:

- 1XX: informational; the request was received and is being processed
- 2XX: successful; the request was successfully, received, understood, and accepted
- 3XX: redirection; further action needs to be taken in order to complete the request
- 4XX: client error; the request contains bad syntax or cannot be fulfilled
- 5XX: server error; the server failed to fulfill an apparently valid request

You don't have to memorize these, but you'll find that after working with HTTP requests for a while they'll just come naturally. For example, you might be familiar with the infamous code 404, which indicates that a resource was not found. You'll come to recognize other codes just like this one.

About the HTML we saw before...

What was it doing there? It's known as the **body** of the response, and it's being sent back to the client, in essence, because that's what they asked for. Let's break things down. The client sent a GET request, asking the server to send some data back from a particular location (www.example.com). The data that was sent was this HTML code... Do you see where this is going yet?

We know that HTML is used by browsers in order to render web pages, so our client can now successfully render the web page stored on the server. In essence, the client uses this HTTP request in order to receive the data necessary to render a web page! This process happens billions of times per day, and it is the back bone of the whole internet. The internet is built upon servers which store HTML, CSS, and Javascript and your browser uses HTTP requests to request them to be sent to you! Obviously, there's more to the internet than just this, and we could fill many books talking about it, but it's outside the scope of this workshop series. If you're interested take CS 118!

HTML is not the only thing that can be placed in response bodies. In fact, just looking at the Accept section of our HTTP request we can see that images can be as well!

```
Accept: text/html,application/xhtml+xml,application/xml;
q=0.9,image/avif,image/webp,*/*;q=0.8
```

Another common data format used in HTTP bodies is known as **JSON**, or Javascript Object Notation. We'll discuss JSON more in detail once

we actually see it in action, but for now it suffices to understand that it is a way to encode objects in Javascript as strings. For example, the following code block shows an object called `heck` and its corresponding JSON string representation:

```

1 heck = {
2   studentOrgRanking: 1,
3   color: "#C960FF",
4   rizz: 100,
5   website: "https://hack.uclaacm.com"
6 }
7
8 {
9   "studentOrgRanking":1,
10  "color":"#C960FF",
11  "rizz":100,
12  "website":"https://hack.uclaacm.com"
13 }
```

2.2 Web API's: What's on the Menu?

Now that our server and client have a common language, it's time to take things a step further. Let's revisit the restaurant analogy. How does the customer know what they're allowed to order? They can't just demand to be served whatever they want, because the restaurant might not be able to accommodate their request⁸. That's why every restaurant has a menu! There needs to be a way to let customers know what they can order. Clients and servers are much the same. There needs to be an understanding between them about what the server can do for the client, and this is accomplished using the **API**, or Application Programming Interface. You may have heard this term before. It's another one of those nebulous phrases that gets thrown around a lot, but is rarely defined concretely.

In general, an API is just a way for two computer programs to interact with each other. Think of the customer at a restaurant as one program and the staff as another. The customer hasn't eaten in 16 hours and is craving a burrito with carnitas and guacamole⁹. Using the menu (the API), the customer is able to enjoy the result of the staff's work and they don't need to attend 4 years of culinary school in order to do it! Put another way, the API allows us to interact with a blackbox and receive meaningful results. API's can be found everywhere in software engineering, but we will be creating more specialized API's called **Web API's**¹⁰.

8: Yes, there are exceptions, secret menus, etc. But let's be real. If you order off the secret menu, the staff hates you.

9: I am so hungry right now.

10: As the name implies, these are API's that utilize the Web, allowing communication from client to server through HTTP requests.

Let's take a look at an example of a simple API.

API's can be expressed in several ways, either using code or English. Let's keep it simple and just use English. Consider a server with the sole purpose being to simulate a cat. The API defines several actions that you, as a pet owner, can take to interact with the cat, and in response the server will send a JSON string (recall that JSON is just a string representation of a Javascript object) with information about the cat and its actions.

The API is defined as follows:

```
FEED: You feed the cat.
WATER: You give the cat a drink.
PET: You pet the cat.
SCOLD: You scold the cat.
MEOW: You meow at the cat.
```

These 5 actions define how you can interact with the cat server. Some of the interactions may have side effects, or an effect on the state of the cat. Let's start by petting the cat. Note that these are not following HTTP.

```
REQUEST: PET
```

```
RESPONSE:
```

```
{
  "health": 100,
  "hunger": 10,
  "thirst": 10,
  "action": "Meows and sits down, ready
            for more pets."
}
```

He seems friendly! Let's give him some food.

```
REQUEST: FEED
```

```
RESPONSE:
```

```
{
  "health": 100,
  "hunger": 50,
  "thirst": 10,
  "action": "Meows gratefully,
            and attacks the food."
}
```

Okay, he seems to be enjoying that. Let's pet some more.

```
REQUEST: PET
```

```
RESPONSE:
```

```
{
  "health": 100,
  "hunger": 50,
  "thirst": 10,
  "action": "Bites your hand. He wasn't
            done eating yet!"
}
```

Ouch. How to respond?


```
REQUEST: MEOW
```

```
RESPONSE:
```

```
{  
  "health": 100,  
  "hunger": 50,  
  "thirst": 10,  
  "action": "Looks up from food, confused."  
}
```

Okay, that's enough playing with the cat! Hopefully, this toy example gave you a clearer idea of what an API is as well as its purpose. We'll be creating a real API later in this chapter using Javascript.

2.3 Server Implementations

Hello, here is some text without a meaning. This text should show what a printed text will look like at this place. If you read this text, you will get no information. Really? Is there no information? Is there a difference between this text and some nonsense like “Huardest gefburn”? Kjift – not at all! A blind text like this gives you information about the selected font, how the letters are written and an impression of the look. This text should contain all letters of the alphabet and it should be written in of the original language. There is no need for special content, but the length of words should match the language.

Hello, here is some text without a meaning. This text should show what a printed text will look like at this place. If you read this text, you will get no information. Really? Is there no information? Is there a difference between this text and some nonsense like “Huardest gefburn”? Kjift – not at all! A blind text like this gives you information about the selected font, how the letters are written and an impression of the look. This text should contain all letters of the alphabet and it should be written in of the original language. There is no need for special content, but the length of words should match the language.

Hello, here is some text without a meaning. This text should show what a printed text will look like at this place. If you read this text, you will get no information. Really? Is there no information? Is there a difference between this text and some nonsense like “Huardest gefburn”? Kjift – not at all! A blind text like this gives you information about the selected font, how the letters are written and an impression of the look. This text should contain all letters of the alphabet and it should be written in of the original language. There is no need for special content, but the length of words should match the language.